CNTTIDR, Counter-timer Timer ID Register

The CNTTIDR characteristics are:

Purpose

Indicates the implemented timers in the memory map, and their features. For each value of N from 0 to 7 it indicates whether:

- Frame CNTBaseN is a view of an implemented timer.
- Frame CNTBaseN has a second view, CNTEL0BaseN.
- Frame CNTBaseN has a virtual timer capability.

Configuration

It is implementation defined whether CNTTIDR is implemented in the Core power domain or in the Debug power domain.

For more information, see 'Power and reset domains for the system level implementation of the Generic Timer'.

Attributes

CNTTIDR is a 32-bit register.

Field descriptions

31 30 29 28	27 26 25 24	23 22 21 20	19 18 17 16	15 14 13 12	11 10 9 8	7 6 5 4	3 2 1 0
Frame7	Frame6	Frame5	Frame4	Frame3	Frame2	Frame1	Frame0

Frame<n>, bits [4n+3:4n], for n = 7 to 0

A 4-bit field indicating the features of frame CNTBase<n>.

Bit[3] of the field is res0.

Bit[2], the FEL0 subfield, indicates whether frame CNTBase<n> has a second view, CNTEL0Base<n>. The possible values of this bit are:

Bit[2]	Meaning
0b0	Frame<n> does not have a second view. The CNTEL0ACR register in the first view of the frame isres0
0b1	Frame<n> has a second view, CNTEL0Base<n>.

If bit[0] is 0, bit[2] is res0.

Bit[1], the FVI subfield, indicates whether both:

- Frame CNTBase<n> implements the virtual timer registers CNTV_CVAL, CNTV_TVAL, and CNTV_CTL.
- This CNTCTLBase frame implements the virtual timer offset register CNTVOFF<n>.

The possible values of bit[1] are:

Bit[1]	Meaning
0b0	Frame<n> does not have virtual capability. The virtual time and offset registers areres0.
0b1	Frame<n> has virtual capability. The virtual time and offset registers are implemented

If bit[0] is 0, bit[1] is res0.

Bit[0], the FI subfield, indicates whether frame CNTBase<n> is implemented. The possible values of this bit are:

Bit[0]	Meaning
0b0	Frame<n> is not implemented. All registers associated with the frame areres0.
0b1	Frame<n> is implemented

Accessing CNTTIDR

In a system that recognizes two Security states this register is accessible by both Secure and Non-secure accesses.

CNTTIDR can be accessed through the memory-mapped interfaces:

Component	Frame	Offset	Instance
Timer	CNTCTLBase	0x008	CNTTIDR

Accesses on this interface are **RO**.