TLBI ALLE1OS, TLBI ALLE1OSNXS, TLB Invalidate All, EL1, Outer Shareable

The TLBI ALLE1OS, TLBI ALLE1OSNXS characteristics are:

Purpose

Invalidates cached copies of translation table entries from TLBs that meet all the following requirements:

- The entry is a stage 1 or stage 2 translation table entry, from any level of the translation table walk.
- If FEAT RME is implemented, one of the following applies:
 - SCR_EL3.{NSE, NS} is {0, 0} and the entry would be required to translate an address using the Secure EL1&0 translation regime.
 - <u>SCR_EL3</u>.{NSE, NS} is {0, 1} and the entry would be required to translate an address using the Non-secure EL1&0 translation regime.
 - <u>SCR_EL3</u>.{NSE, NS} is {1, 1} and the entry would be required to translate an address using the Realm EL1&0 translation regime.
- If FEAT RME is not implemented, one of the following applies:
 - <u>SCR_EL3</u>.NS is 0 and the entry would be required to translate an address using the Secure EL1&0 translation regime.
 - <u>SCR_EL3</u>.NS is 1 and the entry would be required to translate an address using the Non-secure EL1&0 translation regime.

The invalidation applies to entries with any VMID.

The invalidation applies to all PEs in the same Outer Shareable shareability domain as the PE that executes this System instruction.

Note

For the EL1&0 translation regimes, the invalidation applies to both global entries and non-global entries with any ASID.

If FEAT_XS is implemented, the nXS variant of this System instruction is defined.

Both variants perform the same invalidation, but the TLBI System instruction without the nXS qualifier waits for all memory accesses using in-scope old translation information to complete before it is considered complete.

The TLBI System instruction with the nXS qualifier is considered complete when the subset of these memory accesses with XS attribute set to 0 are complete.

Configuration

This instruction is present only when FEAT_TLBIOS is implemented. Otherwise, direct accesses to TLBI ALLE1OS, TLBI ALLE1OSNXS are undefined.

Attributes

TLBI ALLE1OS, TLBI ALLE1OSNXS is a 64-bit System instruction.

Field descriptions

This instruction has no applicable fields.

The value in the register specified by <Xt> is ignored.

Executing TLBI ALLE1OS, TLBI ALLE1OSNXS

The Rt field should be set to 0b11111. If the Rt field is not set to 0b11111, it is constrained unpredictable whether:

- The instruction is undefined.
- The instruction behaves as if the Rt field is set to 0b11111.

Accesses to this instruction use the following encodings in the System instruction encoding space:

TLBI ALLE10S{, <Xt>}

| op0 | op1 | CRn | CRm | op2 |
|------|-------|--------|--------|-------|
| 0b01 | 0b100 | 0b1000 | 0b0001 | 0b100 |

```
if PSTATE.EL == EL0 then
     UNDEFINED;
elsif PSTATE.EL == EL1 then
```

TLBI ALLE10SNXS{, <Xt>}

| op0 | op1 | CRn | CRm | op2 |
|------|-------|--------|--------|-------|
| 0b01 | 0b100 | 0b1001 | 0b0001 | 0b100 |

```
if !IsFeatureImplemented(FEAT_XS) then
    UNDEFINED;
elsif PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if EL2Enabled() && HCR_EL2.NV == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    else
        UNDEFINED;
elsif PSTATE.EL == EL2 then
        AArch64.TLBI_ALL(SecurityStateAtEL(EL1),
Regime_EL10, Shareability_OSH, TLBI_ExcludeXS);
elsif PSTATE.EL == EL3 then
        AArch64.TLBI_ALL(SecurityStateAtEL(EL1),
Regime_EL10, Shareability_OSH, TLBI_ExcludeXS);
```

AArch32 AArch64 AArch32 AArch64 Index by
Registers Instructions Instructions Encoding

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94

External

Registers

Copyright © 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.