MPAMHCR_EL2, MPAM Hypervisor Control Register (EL2)

The MPAMHCR_EL2 characteristics are:

Purpose

Controls the PARTID virtualization features of MPAM. It controls the mapping of virtual PARTIDs into physical PARTIDs in MPAM0_EL1 when EL0_VPMEN == 1 and in MPAM1_EL1 when EL1_VPMEN == 1.

Configuration

This register is present only when FEAT_MPAM is implemented and MPAMIDR_EL1.HAS_HCR == 1. Otherwise, direct accesses to MPAMHCR_EL2 are undefined.

This register has no effect if EL2 is not enabled in the current Security state.

Attributes

MPAMHCR_EL2 is a 64-bit register.

Field descriptions

63	62	61	60	59	58	57	56	55	54	53	52	51	50	49	48	47	46	45	44	43	42	41	40	39	38	37	36	35	34	33
RES0																														
TRAP_MPAMIDR_EL1	RES0																												GSTAPP_PLK	RES0						EL1_VP
31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1

Bits [63:32]

Reserved, res0.

TRAP_MPAMIDR_EL1, bit [31]

Trap accesses from EL1 to MPAMIDR_EL1 to EL2.

TRAP_MPAMIDR_EL1	Meaning
0b0	This control does not cause any instructions to be trapped.

0b1	Direct accesses to MPAMIDR_EL1 from EL1 are trapped to EL2.

The reset behavior of this field is:

- On a Warm reset:
  - When EL3 is not implemented, this field resets to 1.
  - When EL3 is implemented, this field resets to an architecturally unknown value.

Bits [30:9]

Reserved, res0.

GSTAPP_PLK, bit [8]

Make the PARTIDs at EL0 the same as the PARTIDs at EL1. When executing at EL0, EL2 is enabled, HCR_EL2.TGE == 0 and GSTAPP_PLK = 1, MPAM1_EL1 is used instead of MPAM0_EL1 to generate MPAM labels for memory requests.

GSTAPP_PLK	Meaning
0b0	MPAM0_EL1 is used to generate MPAM labels when executing at EL0.
0b1	MPAM1_EL1 is used to generate MPAM labels when executing at EL0 with EL2 enabled and HCR_EL2.TGE == 0. Otherwise MPAM0_EL1 is used.

The reset behavior of this field is:

- On a Warm reset, this field resets to an architecturally unknown value.

Bits [7:2]

Reserved, res0.

EL1_VPMEN, bit [1]

Enable the virtual PARTID mapping of the PARTID fields in MPAM1_EL1 when executing at EL1. This bit also enables virtual PARTID mapping when MPAM1_EL1 is used to generate MPAM labels for memory requests at EL0 due to GSTAPP_PLK == 1.

EL1_VPMEN	Meaning
0b0	MPAM1_EL1.PARTID_I and MPAM1_EL1.PARTID_D are physical PARTIDs that are used to label memory system requests.
0b1	MPAM1_EL1.PARTID_I and MPAM1_EL1.PARTID_D are virtual PARTIDs that are used to index the PhyPARTID fields of MPAMVPM0_EL2 to MPAMVPM7_EL2 registers to map the virtual PARTID into a physical PARTID to label memory system requests.

The reset behavior of this field is:

- On a Warm reset, this field resets to an architecturally unknown value.

EL0_VPMEN, bit [0]

Enable the virtual PARTID mapping of the PARTID fields of MPAM0_EL1 unless HCR_EL2.E2H == 1 and HCR_EL2.TGE == 1.

When HCR_EL2.E2H == 1 and HCR_EL2.TGE == 1, EL0_VPMEN is ignored and MPAM0_EL1 PARTID fields are not mapped.

When MPAMHCR_EL2.GSTAPP_PLK == 1 and HCR_EL2.TGE == 0, MPAM1_EL1 is used as the source of PARTIDs and the virtual PARTID mapping of MPAM1_EL1 PARTIDs is controlled by MPAMHCR_EL2.EL1_VPMEN.

EL0_VPMEN	Meaning
0b0	MPAM0_EL1.PARTID_I and MPAM0_EL1.PARTID_D are physical PARTIDs that are used to label memory system requests.

0b1	MPAM0_EL1.PARTID_I and MPAM0_EL1.PARTID_D are virtual PARTIDs that are used to index the PhyPARTID fields of MPAMVPM0_EL2 to MPAMVPM7_EL2 registers to map the virtual PARTID into a physical PARTID to label memory system requests.

The reset behavior of this field is:

- On a Warm reset, this field resets to an architecturally unknown value.

Accessing MPAMHCR_EL2

Accesses to this register use the following encodings in the System register encoding space:

MRS <Xt>, MPAMHCR_EL2

op0	op1	CRn	CRm	op2
0b11	0b100	0b1010	0b0100	0b000

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if EL2Enabled() && HCR_EL2.<NV2,NV> == '11' then
        X[t, 64] = NVMem[0x930];
    elsif EL2Enabled() && HCR_EL2.NV == '1' then
        if HaveEL(EL3) && MPAM3_EL3.TRAPLOWER == '1'
then
            if Halted() && EDSCR.SDD == '1' then
                UNDEFINED;
            else
                AArch64.SystemAccessTrap(EL3, 0x18);
        else
            AArch64.SystemAccessTrap(EL2, 0x18);
    else
        UNDEFINED;
elsif PSTATE.EL == EL2 then
    if HaveEL(EL3) && MPAM3_EL3.TRAPLOWER == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        X[t, 64] = MPAMHCR_EL2;
```

```
elsif PSTATE.EL == EL3 then
    X[t, 64] = MPAMHCR_EL2;
```

MSR MPAMHCR_EL2, <Xt>

op0	op1	CRn	CRm	op2
0b11	0b100	0b1010	0b0100	0b000

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if EL2Enabled() && HCR_EL2.<NV2,NV> == '11' then
        NVMem[0x930] = X[t, 64];
    elsif EL2Enabled() && HCR_EL2.NV == '1' then
        if HaveEL(EL3) && MPAM3_EL3.TRAPLOWER == '1'
then
            if Halted() && EDSCR.SDD == '1' then
                UNDEFINED;
            else
                AArch64.SystemAccessTrap(EL3, 0x18);
        else
            AArch64.SystemAccessTrap(EL2, 0x18);
    else
        UNDEFINED;
elsif PSTATE.EL == EL2 then
    if HaveEL(EL3) && MPAM3_EL3.TRAPLOWER == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        MPAMHCR_EL2 = X[t, 64];
elsif PSTATE.EL == EL3 then
    MPAMHCR_EL2 = X[t, 64];
```


28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94