LDUR

Load Register (unscaled) calculates an address from a base register and an immediate offset, loads a 32-bit word or 64-bit doubleword from memory, zero-extends it, and writes it to a register. For information about memory accesses, see *Load/Store addressing modes*.



32-bit (size == 10)

```
LDUR <Wt>, [<Xn|SP>{, #<simm>}]
```

64-bit (size == 11)

```
LDUR <Xt>, [<Xn|SP>{, #<simm>}]
```

```
integer scale = UInt(size);
bits(64) offset = SignExtend(imm9, 64);
```

Assembler Symbols

<Wt>	Is the 32-bit name of the general-purpose register to be transferred, encoded in the "Rt" field.
<Xt>	Is the 64-bit name of the general-purpose register to be transferred, encoded in the "Rt" field.
<Xn|SP>	Is the 64-bit name of the general-purpose base register or stack pointer, encoded in the "Rn" field.
<simm>	Is the optional signed immediate byte offset, in the range -256 to 255, defaulting to 0 and encoded in the "imm9" field.

Shared Decode

```
integer n = UInt(Rn);
integer t = UInt(Rt);
integer regsize;

regsize = if size == '11' then 64 else 32;
constant integer datasize = 8 << scale;
boolean tagchecked = n != 31;
```

Operation

```
bits(64) address;
bits(datasize) data;

boolean privileged = PSTATE.EL != EL0;
AccessDescriptor accdesc = CreateAccDescGPR(MemOp_LOAD, FALSE, privileg

if n == 31 then
    CheckSPAlignment();
    address = SP[];
else
    address = X[n, 64];

address = address + offset;

data = Mem[address, datasize DIV 8, accdesc];
X[t, regsize] = ZeroExtend(data, regsize);
```

Operational information

If PSTATE.DIT is 1, the timing of this instruction is insensitive to the value of the data being loaded or stored.

Internal version only: isa v33.64, AdvSIMD v29.12, pseudocode no_diffs_2023_09_RC2, sve v2023-06_rel ; Build timestamp: 2023-09-18T17:56

Copyright Â© 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.