<u>Base</u>	SIMD&FP	<u>SVE</u>	<u>SME</u>	Index by
<u>Instructions</u>	<u>Instructions</u>	<u>Instructions</u>	<u>Instructions</u>	Encoding

Pseu

FCVTNT

Floating-point down convert and narrow (top, predicated)

Convert active floating-point elements from the source vector to the next lower precision, and place the results in the odd-numbered half-width elements of the destination vector, leaving the even-numbered elements unchanged. Inactive elements in the destination vector register remain unmodified.

It has encodings from 2 classes: <u>Single-precision to half-precision</u> and Double-precision to single-precision

Single-precision to half-precision

```
31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0 0 1 1 0 0 1 0 0 1 0 0 0 1 0 0 0 1 0 1 Pg Zn Zd
```

```
FCVTNT \langle Zd \rangle.H, \langle Pg \rangle /M, \langle Zn \rangle.S
```

```
if !HaveSVE2() && !HaveSME() then UNDEFINED;
constant integer esize = 32;
integer g = UInt(Pg);
integer n = UInt(Zn);
integer d = UInt(Zd);
```

Double-precision to single-precision

```
FCVTNT \langle Zd \rangle.S, \langle Pg \rangle /M, \langle Zn \rangle.D
```

```
if !HaveSVE2() && !HaveSME() then UNDEFINED;
constant integer esize = 64;
integer g = UInt(Pg);
integer n = UInt(Zn);
integer d = UInt(Zd);
```

Assembler Symbols

<zd></zd>	Is the name of the destination scalable vector register, encoded in the "Zd" field.
<pg></pg>	Is the name of the governing scalable predicate register P0-P7, encoded in the "Pg" field.
<zn></zn>	Is the name of the first source scalable vector register, encoded in the "Zn" field.

Operation

```
CheckSVEEnabled();
constant integer VL = CurrentVL;
constant integer PL = VL DIV 8;
constant integer elements = VL DIV esize;
bits(PL) mask = P[g, PL];
bits(VL) operand = if AnyActiveElement(mask, esize) then Z[n, VL] else
bits(VL) result = Z[d, VL];

for e = 0 to elements-1
   if ActivePredicateElement(mask, e, esize) then
        bits(esize) element = Elem[operand, e, esize];
        Elem[result, 2*e + 1, esize DIV 2] = FPConvertSVE(element, FPCF)
Z[d, VL] = result;
```

 $Internal\ version\ only: is a\ v33.64,\ AdvSIMD\ v29.12,\ pseudocode\ no_diffs_2023_09_RC2,\ sve\ v2023-06_rel\ ;\ Build\ timestamp:\ 2023-09-18T17:56$

Sh

Pseu

Copyright © 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.