Index by

Encoding

Base SIMD&FP Instructions Instructions

SVE Instructions SME Instructions

SQRDMULH (vector)

Signed saturating Rounding Doubling Multiply returning High half. This instruction multiplies the values of corresponding elements of the two source SIMD&FP registers, doubles the results, places the most significant half of the final results into a vector, and writes the vector to the destination SIMD&FP register.

The results are rounded. For truncated results, see *SQDMULH*.

If overflow occurs with any of the results, those results are saturated. If saturation occurs, the cumulative saturation bit *FPSR*.QC is set.

Depending on the settings in the *CPACR_EL1*, *CPTR_EL2*, and *CPTR_EL3* registers, and the current Security state and Exception level, an attempt to execute the instruction might be trapped.

It has encodings from 2 classes: Scalar and Vector

Scalar

```
31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0

0 1 1 1 1 1 1 0 size 1 Rm 1 0 1 1 0 1 Rn Rd

U
```

SQRDMULH <V><d>, <V><n>, <V><m>

```
integer d = UInt(Rd);
integer n = UInt(Rn);
integer m = UInt(Rm);
if size == '11' |  | size == '00' then UNDEFINED;
constant integer esize = 8 << UInt(size);
constant integer datasize = esize;
integer elements = 1;
boolean rounding = (U == '1');</pre>
```

Vector

```
31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0 0 Q 1 0 1 1 1 0 size 1 Rm 1 0 1 1 0 1 Rn Rd
```

SQRDMULH <Vd>.<T>, <Vn>.<T>, <Vm>.<T>

```
integer d = UInt(Rd);
integer n = UInt(Rn);
integer m = UInt(Rm);
if size == '11' |  | size == '00' then UNDEFINED;
constant integer esize = 8 << UInt(size);
constant integer datasize = 64 << UInt(Q);
integer elements = datasize DIV esize;
boolean rounding = (U == '1');</pre>
```

Assembler Symbols

<V>

Is a width specifier, encoded in "size":

size	<v></v>
0.0	RESERVED
01	Н
10	S
11	RESERVED

<d> Is the number of the SIMD&FP destination register, in the

"Rd" field.

<n> Is the number of the first SIMD&FP source register,

encoded in the "Rn" field.

<m> Is the number of the second SIMD&FP source register,

encoded in the "Rm" field.

<Vd> Is the name of the SIMD&FP destination register, encoded

in the "Rd" field.

<T> Is an arrangement specifier, encoded in "size:Q":

size	Q	<t></t>
0.0	Х	RESERVED
01	0	4H
01	1	8H
10	0	2S
10	1	4S
11	Х	RESERVED

<Vn> Is the name of the first SIMD&FP source register, encoded in the "Rn" field.

<Vm> Is the name of the second SIMD&FP source register, encoded in the "Rm" field.

Operation

```
CheckFPAdvSIMDEnabled64();
bits(datasize) operand1 = V[n, datasize];
bits(datasize) operand2 = V[m, datasize];
bits(datasize) result;
integer element1;
integer element2;
integer product;
boolean sat;

for e = 0 to elements-1
    element1 = SInt(Elem[operand1, e, esize]);
    element2 = SInt(Elem[operand2, e, esize]);
    product = 2 * element1 * element2;
```

```
product = RShr(product, esize, rounding);
  (Elem[result, e, esize], sat) = SignedSatQ(product, esize);
  if sat then FPSR.QC = '1';

V[d, datasize] = result;
```

Operational information

If PSTATE.DIT is 1:

- The execution time of this instruction is independent of:
 - The values of the data supplied in any of its registers.
 - The values of the NZCV flags.
- The response of this instruction to asynchronous exceptions does not vary based on:
 - The values of the data supplied in any of its registers.
 - The values of the NZCV flags.

BaseSIMD&FPSVESMEIndex byInstructionsInstructionsInstructionsInstructionsEncoding

Internal version only: isa v33.64, AdvSIMD v29.12, pseudocode no diffs 2023 09 RC2, sve v2023-06 rel ; Build timestamp: 2023-09-18T17:56

Copyright © 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.

Sh Pseu