

STSMIN, STSMINL

Atomic signed minimum on word or doubleword in memory, without return, atomically loads a 32-bit word or 64-bit doubleword from memory, compares it against the value held in a register, and stores the smaller value back to memory, treating the values as signed numbers.

- STSMIN does not have release semantics.
- STSMINL stores to memory with release semantics, as described in *Load-Acquire, Store-Release*.

For information about memory accesses, see *Load/Store addressing modes*.

This is an alias of [LDSDMIN, LDSDMINA, LDSDMINAL, LDSDMINL](#). This means:

- The encodings in this description are named to match the encodings of [LDSDMIN, LDSDMINA, LDSDMINAL, LDSDMINL](#).
- The description of [LDSDMIN, LDSDMINA, LDSDMINAL, LDSDMINL](#) gives the operational pseudocode, any constrained unpredictable behavior, and any operational information for this instruction.

Integer (FEAT_LSE)

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	x	1	1	1	0	0	0	0	R	1				Rs		0	1	0	1	0	0				Rn		1	1	1	1	1
size				A								opc								Rt											

32-bit LDSDMIN alias (size == 10 && R == 0)

STSMIN <Ws>, [[<Xn | SP>](#)]

is equivalent to

[LDSDMIN](#) <Ws>, WZR, [[<Xn | SP>](#)]

and is always the preferred disassembly.

32-bit LDSDMINL alias (size == 10 && R == 1)

STSDMINL <Ws>, [[<Xn | SP>](#)]

is equivalent to

[LDSDMINL](#) <Ws>, WZR, [[<Xn | SP>](#)]

and is always the preferred disassembly.

64-bit LDSMIN alias (size == 11 && R == 0)

```
STSMIN <Xs>, [<Xn|SP>]
```

is equivalent to

```
LDSMIN <Xs>, XZR, [<Xn|SP>]
```

and is always the preferred disassembly.

64-bit LDSMINL alias (size == 11 && R == 1)

```
STSMINL <Xs>, [<Xn|SP>]
```

is equivalent to

```
LDSMINL <Xs>, XZR, [<Xn|SP>]
```

and is always the preferred disassembly.

Assembler Symbols

- <Ws> Is the 32-bit name of the general-purpose register holding the data value to be operated on with the contents of the memory location, encoded in the "Rs" field.
- <Xs> Is the 64-bit name of the general-purpose register holding the data value to be operated on with the contents of the memory location, encoded in the "Rs" field.
- <Xn|SP> Is the 64-bit name of the general-purpose base register or stack pointer, encoded in the "Rn" field.

Operation

The description of [LDSMIN](#), [LDSMINA](#), [LDSMINAL](#), [LDSMINL](#) gives the operational pseudocode for this instruction.

Operational information

If PSTATE.DIT is 1, the timing of this instruction is insensitive to the value of the data being loaded or stored.