AT S1E1R, Address Translate Stage 1 EL1 Read

The AT S1E1R characteristics are:

Purpose

Performs stage 1 address translation, with permissions as if reading from the given virtual address from EL1, or from EL2 if the Effective value of HCR_EL2.{E2H, TGE} is {1, 1}, using the following translation regime:

- When EL2 is implemented and enabled in the Security state described by the current Effective value of SCR_EL3.{NSE, NS}:
    - If HCR_EL2.{E2H, TGE} is not {1, 1}, the EL1&0 translation regime, accessed from EL1.
    - If HCR_EL2.{E2H, TGE} is {1, 1}, the EL2&0 translation regime, accessed from EL2.
- Otherwise, the EL1&0 translation regime, accessed from EL1.

When FEAT_RME is implemented, if the Effective value of SCR_EL3.{NSE, NS} is a reserved value, this instruction is undefined at EL3.

Configuration

There are no configuration notes.

Attributes

AT S1E1R is a 64-bit System instruction.

Field descriptions

63	62	61	60	59	58	57	56	55	54	53	52	51	50	49	48	47	46	45	44	43	42	41	40	39	38	37	36	35	34	33	32
Input address for translation																															
Input address for translation																															
31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0

Bits [63:0]

Input address for translation. The resulting address can be read from the PAR_EL1.

If the address translation instructions are targeting a translation regime that is using AArch32, and so has a VA of only 32 bits, then VA[63:32] is res0.

Executing AT S1E1R

Accesses to this instruction use the following encodings in the System instruction encoding space:

AT S1E1R, <Xt>

op0	op1	CRn	CRm	op2
0b01	0b000	0b0111	0b1000	0b000

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if EL2Enabled() && HCR_EL2.AT == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() &&
IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
SCR_EL3.FGTEn == '1') && HFGITR_EL2.ATS1E1R == '1'
then
        AArch64.SystemAccessTrap(EL2, 0x18);
    else
        AArch64.AT(X[t, 64], TranslationStage_1,
EL1, ATAccess_Read);
elsif PSTATE.EL == EL2 then
    AArch64.AT(X[t, 64], TranslationStage_1, EL1,
ATAccess_Read);
elsif PSTATE.EL == EL3 then
    AArch64.AT(X[t, 64], TranslationStage_1, EL1,
ATAccess_Read);
```

28/03/2023 16:01; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94