TLBI RVALE3, TLBI RVALE3NXS, TLB Range Invalidate by VA, Last level, EL3

The TLBI RVALE3, TLBI RVALE3NXS characteristics are:

Purpose

If EL3 is implemented, invalidates cached copies of translation table entries from TLBs that meet all the following requirements:

- The entry is a 64-bit stage 1 translation table entry, from the final level of the translation table walk up to the level indicated in the TTL hint.

  Or, if FEAT_D128 is implemented, and the entry is a 128-bit stage 1 translation table entry, if TTL is `0b00`.

- The entry would be used to translate any of the VAs in the specified address range using the EL3 translation regime.

- The entry is within the address range determined by the formula [BaseADDR <= VA < BaseADDR + ((NUM +1)*$2^{(5*SCALE +1)}$ * Translation_Granule_Size)].

The invalidation applies to the PE that executes this System instruction.

For 64-bit translation table entry, the range of addresses invalidated is unpredictable when:

- For the 4K translation granule:
  - If TTL==01 and BaseADDR[29:12] is not equal to 000000000000000000.
  - If TTL==10 and BaseADDR[20:12] is not equal to 000000000.
- For the 16K translation granule:
  - If TTL==10 and BaseADDR[24:14] is not equal to 00000000000.
- For the 64K translation granule:
  - If TTL==01 and BaseADDR[41:16] is not equal to 00000000000000000000000000.

- If TTL==10 and BaseADDR[28:16] is not equal to 0000000000000.

If FEAT_XS is implemented, the nXS variant of this System instruction is defined.

Both variants perform the same invalidation, but the TLBI System instruction without the nXS qualifier waits for all memory accesses using in-scope old translation information to complete before it is considered complete.

The TLBI System instruction with the nXS qualifier is considered complete when the subset of these memory accesses with XS attribute set to 0 are complete.

Configuration

This instruction is present only when FEAT_TLBIRANGE is implemented. Otherwise, direct accesses to TLBI RVALE3, TLBI RVALE3NXS are undefined.

Attributes

TLBI RVALE3, TLBI RVALE3NXS is a 64-bit System instruction.

Field descriptions



Bits [63:48]

Reserved, res0.

TG, bits [47:46]

Translation granule size.

TG	Meaning
0b00	Reserved.
0b01	4K translation granule.
0b10	16K translation granule.
0b11	64K translation granule.

The instruction takes a translation granule size for the translations that are being invalidated. If the translations used a different translation granule size than the one being specified, then the architecture does not require that the instruction invalidates any entries.

SCALE, bits [45:44]

The exponent element of the calculation that is used to produce the upper range.

NUM, bits [43:39]

The base element of the calculation that is used to produce the upper range.

TTL, bits [38:37]

TTL Level hint. The TTL hint is only guaranteed to invalidate:

- Non-leaf-level entries in the range up to but not including the level described by the TTL hint.
- Leaf-level entries in the range that match the level described by the TTL hint.

TTL	Meaning
`0b00`	The entries in the range can be using any level for the translation table entries.
`0b01`	The TTL hint indicates level 1. If FEAT_LPA2 is not implemented, when using a 16KB translation granule, this value is reserved and hardware should treat this field as `0b00`.
`0b10`	The TTL hint indicates level 2.
`0b11`	The TTL hint indicates level 3.

BaseADDR, bits [36:0]
When FEAT_LPA2 is implemented and TCR_EL3.DS == 1:

The starting address for the range of the maintenance instructions. This field is BaseADDR[52:16] for all translation granules.

When using a 4KB translation granule, BaseADDR[15:12] is treated as `0b0000`.

When using a 16KB translation granule, BaseADDR[15:14] is treated as `0b00`.

Otherwise:

The starting address for the range of the maintenance instruction.

When using a 4KB translation granule, this field is BaseADDR[48:12].

When using a 16KB translation granule, this field is BaseADDR[50:14].

When using a 64KB translation granule, this field is BaseADDR[52:16].

Executing TLBI RVALE3, TLBI RVALE3NXS

Accesses to this instruction use the following encodings in the System instruction encoding space:

TLBI RVALE3{, <Xt>}

op0	op1	CRn	CRm	op2
0b01	0b110	0b1000	0b0110	0b101

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    UNDEFINED;
elsif PSTATE.EL == EL2 then
    UNDEFINED;
elsif PSTATE.EL == EL3 then
    AArch64.TLBI_RVA(SecurityStateAtEL(EL3),
Regime_EL3, VMID[], Shareability_NSH,
TLBILevel_Last, TLBI_AllAttr, X[t, 64]);
```

TLBI RVALE3NXS{, <Xt>}

op0	op1	CRn	CRm	op2
0b01	0b110	0b1001	0b0110	0b101

```
if !IsFeatureImplemented(FEAT_XS) then
    UNDEFINED;
elsif PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    UNDEFINED;
elsif PSTATE.EL == EL2 then
    UNDEFINED;
elsif PSTATE.EL == EL3 then
    AArch64.TLBI_RVA(SecurityStateAtEL(EL3),
```

```
Regime_EL3, VMID[], Shareability_NSH,
TLBILevel_Last, TLBI_ExcludeXS, X[t, 64]);
```

28/03/2023 16:01; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94