

TRCPIDR6, Peripheral Identification Register 6

The TRCPIDR6 characteristics are:

Purpose

Provides discovery information about the component.

For additional information, see the CoreSight Architecture Specification.

Configuration

This register is present only when FEAT_ETE is implemented and FEAT_TRC_EXT is implemented. Otherwise, direct accesses to TRCPIDR6 are res0.

Attributes

TRCPIDR6 is a 32-bit register.

Field descriptions

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
RES0																															

Bits [31:0]

Reserved, res0.

Accessing TRCPIDR6

External debugger accesses to this register are unaffected by the OS Lock.

TRCPIDR6 can be accessed through the external debug interface:

Component	Offset	Instance
ETE	0xFD8	TRCPIDR6

This interface is accessible as follows:

- When !IsTraceCorePowered(), accesses to this register generate an error response.

- Otherwise, accesses to this register are **RO**.

[AArch32
Registers](#)

[AArch64
Registers](#)

[AArch32
Instructions](#)

[AArch64
Instructions](#)

[Index by
Encoding](#)

[External
Registers](#)

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94

Copyright © 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.