

MOV (vector to array, four registers)

Move four vector registers to four ZA single-vector groups

The instruction operates on four ZA single-vector groups. The vector numbers forming the single-vector group within each quarter of the ZA array are selected by the sum of the vector select register and immediate offset, modulo quarter the number of ZA array vectors.

The vector group symbol VGx4 indicates that the instruction operates on four ZA single-vector groups.

The preferred disassembly syntax uses a 64-bit element size, but an assembler should accept any element size if it is used consistently for all operands. The vector group symbol is preferred for disassembly, but optional in assembler source code.

This instruction is unpredicated.

This is an alias of [MOVA \(vector to array, four registers\)](#). This means:

- The encodings in this description are named to match the encodings of [MOVA \(vector to array, four registers\)](#).
- The description of [MOVA \(vector to array, four registers\)](#) gives the operational pseudocode, any constrained unpredictable behavior, and any operational information for this instruction.

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	Rv	0	1	1	Zn	0	0	0	0	0	0	0	off3		

MOV ZA.D[<Wv>, <offs>{, VGx4}], { <Zn1>.D-<Zn4>.D }

is equivalent to

MOVA ZA.D[<Wv>, <offs>{, VGx4}], { <Zn1>.D-<Zn4>.D }

and is always the preferred disassembly.

Assembler Symbols

<Wv>	Is the 32-bit name of the vector select register W8-W11, encoded in the "Rv" field.
<offs>	Is the vector select offset, in the range 0 to 7, encoded in the "off3" field.
<Zn1>	Is the name of the first scalable vector register of a multi-vector sequence, encoded as "Zn" times 4.
<Zn4>	Is the name of the fourth scalable vector register of a multi-vector sequence, encoded as "Zn" times 4 plus 3.

Operation

The description of [MOVA \(vector to array, four registers\)](#) gives the operational pseudocode for this instruction.

Operational information

If FEAT_SVE2 is implemented or FEAT_SME is implemented, then if PSTATE.DIT is 1:

- The execution time of this instruction is independent of:
 - The values of the data supplied in any of its registers.
 - The values of the NZCV flags.
- The response of this instruction to asynchronous exceptions does not vary based on:
 - The values of the data supplied in any of its registers.
 - The values of the NZCV flags.

[Base
Instructions](#)

[SIMD&FP
Instructions](#)

[SVE
Instructions](#)

[SME
Instructions](#)

[Index by
Encoding](#)

[Sh
Pseu](#)

Internal version only: isa v33.64, AdvSIMD v29.12, pseudocode
no_diffs_2023_09_RC2, sve v2023-06_rel ; Build timestamp: 2023-09-18T17:56

Copyright Â© 2010-2023 Arm Limited or its affiliates. All rights reserved. This
document is Non-Confidential.