ID_AA64AFR0_EL1, AArch64 Auxiliary Feature Register 0

The ID_AA64AFR0_EL1 characteristics are:

Purpose

Provides information about the implementation defined features of the PE in AArch64 state.

For general information about the interpretation of the ID registers, see 'Principles of the ID scheme for fields in ID registers'.

Configuration

There are no configuration notes.

Attributes

ID_AA64AFR0_EL1 is a 64-bit register.

Field descriptions

63 62 61 60 59 58 57 56 55 54 53 52 51 50 49 48 47 46 45 44 43 42 41 40 39 38 37 36 35 34 33 32							
RES0							
IMPLEMENTATION DEFINED	IMPLEMENTATION DEFINED	IMPLEMENTATION DEFINED	IMPLEMENTATION DEFINED	IMPLEMENTATION DEFINED	IMPLEMENTATION DEFINED	IMPLEMENTATION DEFINED	IMPLEMENTATION DEFINED
31 30 29 28	27 26 25 24	23 22 21 20	19 18 17 16	15 14 13 12	11 10 9 8	7 6 5 4	3 2 1 0

Bits [63:32]

Reserved, res0.

IMPLEMENTATION DEFINED, bits [31:28]

implementation defined.

IMPLEMENTATION DEFINED, bits [27:24]

implementation defined.

IMPLEMENTATION DEFINED, bits [23:20]

implementation defined.

IMPLEMENTATION DEFINED, bits [19:16]

implementation defined.

IMPLEMENTATION DEFINED, bits [15:12]

implementation defined.

IMPLEMENTATION DEFINED, bits [11:8]

implementation defined.

IMPLEMENTATION DEFINED, bits [7:4]

implementation defined.

IMPLEMENTATION DEFINED, bits [3:0]

implementation defined.

Accessing ID_AA64AFR0_EL1

Accesses to this register use the following encodings in the System register encoding space:

MRS <Xt>, ID_AA64AFR0_EL1

op0	op1	CRn	CRm	op2
0b11	0b000	0b0000	0b0101	0b100

```
if PSTATE.EL == EL0 then
    if IsFeatureImplemented(FEAT_IDST) then
        if EL2Enabled() && HCR_EL2.TGE == '1' then
            AArch64.SystemAccessTrap(EL2, 0x18);
        else
            AArch64.SystemAccessTrap(EL1, 0x18);
    else
        UNDEFINED;
elsif PSTATE.EL == EL1 then
    if EL2Enabled() && HCR_EL2.TID3 == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    else
        X[t, 64] = ID_AA64AFR0_EL1;
elsif PSTATE.EL == EL2 then
    X[t, 64] = ID_AA64AFR0_EL1;
elsif PSTATE.EL == EL3 then
    X[t, 64] = ID_AA64AFR0_EL1;
```

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94