

STCLR, STCLRL

Atomic bit clear on word or doubleword in memory, without return, atomically loads a 32-bit word or 64-bit doubleword from memory, performs a bitwise AND with the complement of the value held in a register on it, and stores the result back to memory.

- STCLR does not have release semantics.
- STCLRL stores to memory with release semantics, as described in [Load-Acquire, Store-Release](#).

For information about memory accesses, see [Load/Store addressing modes](#).

This is an alias of [LDCLR, LDCLRA, LDCLRAL, LDCLRL](#). This means:

- The encodings in this description are named to match the encodings of [LDCLR, LDCLRA, LDCLRAL, LDCLRL](#).
- The description of [LDCLR, LDCLRA, LDCLRAL, LDCLRL](#) gives the operational pseudocode, any constrained unpredictable behavior, and any operational information for this instruction.

Integer (FEAT_LSE)

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0		
1	x	1	1	1	0	0	0	0	R	1					Rs		0	0	0	1	0	0					Rn		1	1	1	1	1
size										A						opc						Rt											

32-bit LDCLR alias (size == 10 && R == 0)

STCLR <Ws>, [[<Xn|SP>](#)]

is equivalent to

[LDCLR](#) <Ws>, WZR, [[<Xn|SP>](#)]

and is always the preferred disassembly.

32-bit LDCLRL alias (size == 10 && R == 1)

STCLRL <Ws>, [[<Xn|SP>](#)]

is equivalent to

[LDCLRL](#) <Ws>, WZR, [[<Xn|SP>](#)]

and is always the preferred disassembly.

64-bit LDCLR alias (size == 11 && R == 0)

STCLR <Xs>, [<Xn|SP>]

is equivalent to

LDCLR <Xs>, XZR, [<Xn|SP>]

and is always the preferred disassembly.

64-bit LDCLRL alias (size == 11 && R == 1)

STCLRL <Xs>, [<Xn|SP>]

is equivalent to

LDCLRL <Xs>, XZR, [<Xn|SP>]

and is always the preferred disassembly.

Assembler Symbols

- <Ws> Is the 32-bit name of the general-purpose register holding the data value to be operated on with the contents of the memory location, encoded in the "Rs" field.
- <Xs> Is the 64-bit name of the general-purpose register holding the data value to be operated on with the contents of the memory location, encoded in the "Rs" field.
- <Xn|SP> Is the 64-bit name of the general-purpose base register or stack pointer, encoded in the "Rn" field.

Operation

The description of [LDCLR](#), [LDCLRA](#), [LDCLRAL](#), [LDCLRL](#) gives the operational pseudocode for this instruction.

Operational information

If PSTATE.DIT is 1, the timing of this instruction is insensitive to the value of the data being loaded or stored.