

## GICC\_ABPR, CPU Interface Aliased Binary Point Register

The GICC\_ABPR characteristics are:

### Purpose

Defines the point at which the priority value fields split into two parts, the group priority field and the subpriority field. The group priority field determines Group 1 interrupt preemption.

### Configuration

This register is present only when FEAT\_GICv3\_LEGACY is implemented. Otherwise, direct accesses to GICC\_ABPR are res0.

In systems that support two Security states:

- This register is an alias of the Non-secure copy of [GICC\\_BPR](#).
- Non-secure accesses to this register return a shifted value of the binary point.
- If [ICC\\_CTLR\\_EL3.CBPR\\_EL1NS](#) == 1, Secure accesses to this register access [ICC\\_BPR0\\_EL1](#).

### Attributes

GICC\_ABPR is a 32-bit register.

### Field descriptions

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
RES0																															
Binary_Point																															

#### Bits [31:3]

Reserved, res0.

#### Binary\_Point, bits [2:0]

Controls how the 8-bit interrupt priority field is split into a group priority field, that determines interrupt preemption, and a subpriority field. The following list describes how this field

determines the interrupt priority bits assigned to the group priority field:

- 'Secure ICC\_BPR1\_EL1 Binary Point when CBPR == 0' in ARM® Generic Interrupt Controller Architecture Specification, GIC architecture version 3.0 and version 4.0 (ARM IHI 0069), for the processing of Group 1 interrupts in a GIC implementation that supports interrupt grouping, when [GICC\\_CTLR](#).CBPR == 0.
- 'Non-secure ICC\_BPR1\_EL1 Binary Point when CBPR == 0' in ARM® Generic Interrupt Controller Architecture Specification, GIC architecture version 3.0 and version 4.0 (ARM IHI 0069), for all other cases.

The reset behavior of this field is:

- On a Warm reset, this field resets to an architecturally unknown value.

### Accessing GICC\_ABPR

This register is used only when System register access is not enabled. When System register access is enabled, the System registers [ICC\\_BPR0\\_EL1](#) and [ICC\\_BPR1\\_EL1](#) provide equivalent functionality.

**GICC\_ABPR can be accessed through the memory-mapped interfaces:**

Component	Offset	Instance
GIC CPU interface	0x001C	GICC_ABPR

This interface is accessible as follows:

- When GICD\_CTLR.DS == 0, accesses to this register are **RW**.
- When an access is Secure, accesses to this register are **RW**.
- When an access is Non-secure, accesses to this register are **RW**.

[AArch32  
Registers](#)

[AArch64  
Registers](#)

[AArch32  
Instructions](#)

[AArch64  
Instructions](#)

[Index by  
Encoding](#)

[External  
Registers](#)

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94

Copyright © 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.