

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0	
1	1	0	0	0	0	0	1	0	sz	1	0		Zm		0	Rv	0	0	0		Zn		0	0	0	0	0	0	0	0	0	1
U S																																

For the four ZA quad-vectors and two ZA quad-vectors variant: is the vector select offset, pointing to last of four consecutive vectors, encoded as "o1" field times 4 plus 3.

<Zn> Is the name of the first source scalable vector register, encoded in the "Zn" field.

<Zn1> Is the name of the first scalable vector register of a multi-vector sequence, encoded as "Zn".

<Tb> Is the size specifier, encoded in "sz":

sz	<Tb>
0	B
1	H

<Zn4> Is the name of the fourth scalable vector register of a multi-vector sequence, encoded as "Zn" plus 3 modulo 32.

<Zn2> Is the name of the second scalable vector register of a multi-vector sequence, encoded as "Zn" plus 1 modulo 32.

<Zm> Is the name of the second source scalable vector register Z0-Z15, encoded in the "Zm" field.

Operation

```

CheckStreamingSVEAndZAEEnabled();
constant integer VL = CurrentVL;
constant integer elements = VL DIV esize;
integer vectors = VL DIV 8;
integer vstride = vectors DIV nreg;
bits(32) vbase = X[v, 32];
integer vec = (UInt(vbase) + offset) MOD vstride;
bits(VL) result;
vec = vec - (vec MOD 4);

for r = 0 to nreg-1
  bits(VL) operand1 = Z[(n+r) MOD 32, VL];
  bits(VL) operand2 = Z[m, VL];
  for i = 0 to 3
    bits(VL) operand3 = ZAvector[vec + i, VL];
    for e = 0 to elements-1
      integer element1 = SInt(Elem[operand1, 4 * e + i, esize DIV 4]);
      integer element2 = SInt(Elem[operand2, 4 * e + i, esize DIV 4]);
      bits(esize) product = (element1 * element2) < esize-1:0 >;
      Elem[result, e, esize] = Elem[operand3, e, esize] + product;
    ZAvector[vec + i, VL] = result;
  vec = vec + vstride;

```

Operational information

If PSTATE.DIT is 1:

- The execution time of this instruction is independent of:
 - The values of the data supplied in any of its registers.
 - The values of the NZCV flags.
- The response of this instruction to asynchronous exceptions does not vary based on:
 - The values of the data supplied in any of its registers.
 - The values of the NZCV flags.

Base Instructions	SIMD&FP Instructions	SVE Instructions	SME Instructions	Index by Encoding
-----------------------------------	--	----------------------------------	----------------------------------	-----------------------------------

[Sh](#)
[Pseu](#)

Internal version only: isa v33.64, AdvSIMD v29.12, pseudocode no_diffs_2023_09_RC2, sve v2023-06_rel ; Build timestamp: 2023-09-18T17:56

Copyright Â© 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.