LDFF1W (scalar plus scalar)

Contiguous load first-fault unsigned words to vector (scalar index)

Contiguous load with first-faulting behavior of unsigned words to elements of a vector register from the memory address generated by a 64-bit scalar base and scalar index which is multiplied by 4 and added to the base address. After each element access the index value is incremented, but the index register is not updated. Inactive elements will not cause a read from Device memory or signal a fault, and are set to zero in the destination vector.

This instruction is illegal when executed in Streaming SVE mode, unless FEAT_SME_FA64 is implemented and enabled.

It has encodings from 2 classes: [32-bit element](#) and [64-bit element](#)

32-bit element

31	30	29	28	27	26	25	24	23	22	21	20 19 18 17 16	15	14	13	12 11 10	9 8 7 6 5	4 3 2 1 0
1	0	1	0	0	1	0	1	0	1	0	Rm	0	1	1	Pg	Rn	Zt

dtype<1> dtype<0>

```
LDFF1W { <Zt>.S }, <Pg>/Z, [<Xn|SP>{, <Xm>, LSL #2}]
```

```
if !HaveSVE() then UNDEFINED;
integer t = UInt(Zt);
integer n = UInt(Rn);
integer m = UInt(Rm);
integer g = UInt(Pg);
constant integer esize = 32;
constant integer msize = 32;
boolean unsigned = TRUE;
```

64-bit element

31	30	29	28	27	26	25	24	23	22	21	20 19 18 17 16	15	14	13	12 11 10	9 8 7 6 5	4 3 2 1 0
1	0	1	0	0	1	0	1	0	1	1	Rm	0	1	1	Pg	Rn	Zt

dtype<1> dtype<0>

```
LDFF1W { <Zt>.D }, <Pg>/Z, [<Xn|SP>{, <Xm>, LSL #2}]
```

```
if !HaveSVE() then UNDEFINED;
integer t = UInt(Zt);
integer n = UInt(Rn);
integer m = UInt(Rm);
integer g = UInt(Pg);
constant integer esize = 64;
constant integer msize = 32;
boolean unsigned = TRUE;
```

Assembler Symbols

<Zt>   Is the name of the scalable vector register to be
             transferred, encoded in the "Zt" field.

<Pg>   Is the name of the governing scalable predicate register P0-
             P7, encoded in the "Pg" field.

<Xn|SP>   Is the 64-bit name of the general-purpose base register or
             stack pointer, encoded in the "Rn" field.

<Xm>   Is the optional 64-bit name of the general-purpose offset
             register, defaulting to XZR, encoded in the "Rm" field.

Operation

```
CheckNonStreamingSVEEnabled();
constant integer VL = CurrentVL;
constant integer PL = VL DIV 8;
constant integer elements = VL DIV esize;
bits(64) base;
bits(PL) mask = P[g, PL];
bits(VL) result;
bits(VL) orig = Z[t, VL];
bits(msize) data;
bits(64) offset;
constant integer mbytes = msize DIV 8;
boolean fault = FALSE;
boolean faulted = FALSE;
boolean unknown = FALSE;
boolean contiguous = TRUE;
boolean tagchecked = TRUE;
AccessDescriptor accdesc = CreateAccDescSVEFF(contiguous, tagchecked);

if !AnyActiveElement(mask, esize) then
    if n == 31 && ConstrainUnpredictableBool(Unpredictable_CHECKSPNONEA
        CheckSPAlignment();
else
    if n == 31 then CheckSPAlignment();
    base = if n == 31 then SP[] else X[n, 64];
    offset = X[m, 64];

assert accdesc.first;

for e = 0 to elements-1
    if ActivePredicateElement(mask, e, esize) then
        bits(64) addr = base + (UInt(offset) + e) * mbytes;
        if accdesc.first then
            // Mem[] will not return if a fault is detected for the firs
            data = Mem[addr, mbytes, accdesc];
            accdesc.first = FALSE;
        else
            // MemNF[] will return fault=TRUE if access is not performe
            (data, fault) = MemNF[addr, mbytes, accdesc];
    else
        (data, fault) = (Zeros(msize), FALSE);

    // FFR elements set to FALSE following a supressed access/fault
```

```
        faulted = faulted || fault;
        if faulted then
            ElemFFR[e, esize] = '0';

        // Value becomes CONSTRAINED UNPREDICTABLE after an FFR element is
        unknown = unknown || ElemFFR[e, esize] == '0';
        if unknown then
            if !fault && ConstrainUnpredictableBool(Unpredictable_SVELDNFDA
                Elem[result, e, esize] = Extend(data, esize, unsigned);
            elsif ConstrainUnpredictableBool(Unpredictable_SVELDNFZERO) the
                Elem[result, e, esize] = Zeros(esize);
            else  // merge
                Elem[result, e, esize] = Elem[orig, e, esize];
        else
            Elem[result, e, esize] = Extend(data, esize, unsigned);

    Z[t, VL] = result;
```

Base Instructions	SIMD&FP Instructions	SVE Instructions	SME Instructions	Index by Encoding	Sh Pseud

Internal version only: isa v33.64, AdvSIMD v29.12, pseudocode no_diffs_2023_09_RC2, sve v2023-06_rel ; Build timestamp: 2023-09-18T17:56