<u>Base</u>	SIMD&FP	<u>SVE</u>	<u>SME</u>	Index by
<u>Instructions</u>	<u>Instructions</u>	<u>Instructions</u>	<u>Instructions</u>	Encoding

Pseu

BIC (vectors, unpredicated)

Bitwise clear vectors (unpredicated)

Bitwise AND inverted all elements of the second source vector with corresponding elements of the first source vector and place the results in the corresponding elements of the destination vector. This instruction is unpredicated.

```
31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0 0 0 0 0 0 1 0 0 1 1 1 Zm 0 0 1 1 0 0 Zn Zd
```

```
BIC <Zd>.D, <Zn>.D, <Zm>.D

if !HaveSVE() && !HaveSME() then UNDEFINED;
integer n = UInt(Zn);
integer m = UInt(Zm);
integer d = UInt(Zd);
```

Assembler Symbols

```
<Zd> Is the name of the destination scalable vector register, encoded in the "Zd" field.
<Zn> Is the name of the first source scalable vector register, encoded in the "Zn" field.
<Zm> Is the name of the second source scalable vector register, encoded in the "Zm" field.
```

Operation

```
CheckSVEEnabled();
constant integer VL = CurrentVL;
bits(VL) operand1 = Z[n, VL];
bits(VL) operand2 = Z[m, VL];

Z[d, VL] = operand1 AND (NOT operand2);
```

Operational information

If FEAT_SVE2 is implemented or FEAT_SME is implemented, then if PSTATE.DIT is 1:

- The execution time of this instruction is independent of:
 - The values of the data supplied in any of its registers.
 - The values of the NZCV flags.
- The response of this instruction to asynchronous exceptions does not vary based on:
 - The values of the data supplied in any of its registers.
 - The values of the NZCV flags.

Internal version only: isa v33.64, AdvSIMD v29.12, pseudocode no_diffs_2023_09_RC2, sve v2023-06_rel ; Build timestamp: 2023-09-18T17:56

Sh

Pseu

Copyright \hat{A} © 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.