

## SRSHL (multiple and single vector)

Multi-vector signed rounding shift left by vector

Shift the signed elements of the two or four first source vectors by corresponding elements of the second source vector and destructively place the rounded results in the corresponding elements of the two or four first source vectors. A positive shift amount performs a left shift, otherwise a right shift by the negated shift amount is performed.

This instruction is unpredicated.

It has encodings from 2 classes: [Two registers](#) and [Four registers](#)

### Two registers (FEAT\_SME2)

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	0	0	0	0	0	1	size	1	0		Zm		1	0	1	0	0	0	1	0	0	0	1		Zdn		0			
U																															

SRSHL { <Zdn1>.<T>-<Zdn2>.<T> }, { <Zdn1>.<T>-<Zdn2>.<T> }, <Zm>.<T>

```
if !HaveSME2() then UNDEFINED;
constant integer esize = 8 << UInt(size);
integer dn = UInt(Zdn:'0');
integer m = UInt('0':Zm);
constant integer nreg = 2;
```

### Four registers (FEAT\_SME2)

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	0	0	0	0	0	1	size	1	0		Zm		1	0	1	0	1	0	1	0	1	0	0	0	1		Zdn		0	0
U																															

SRSHL { <Zdn1>.<T>-<Zdn4>.<T> }, { <Zdn1>.<T>-<Zdn4>.<T> }, <Zm>.<T>

```
if !HaveSME2() then UNDEFINED;
constant integer esize = 8 << UInt(size);
integer dn = UInt(Zdn:'00');
integer m = UInt('0':Zm);
constant integer nreg = 4;
```

## Assembler Symbols

<Zdn1> For the two registers variant: is the name of the first scalable vector register of a multi-vector sequence, encoded as "Zdn" times 2.

For the four registers variant: is the name of the first scalable vector register of a multi-vector sequence, encoded as "Zdn" times 4.

<T>

Is the size specifier, encoded in "size":

size	<T>
00	B
01	H
10	S
11	D

<Zdn4>

Is the name of the fourth scalable vector register of a multi-vector sequence, encoded as "Zdn" times 4 plus 3.

<Zdn2>

Is the name of the second scalable vector register of a multi-vector sequence, encoded as "Zdn" times 2 plus 1.

<Zm>

Is the name of the second source scalable vector register Z0-Z15, encoded in the "Zm" field.

## Operation

```

CheckStreamingSVEEnabled();
constant integer VL = CurrentVL;
constant integer elements = VL DIV esize;
array [0..3] of bits(VL) results;

for r = 0 to nreg-1
    bits(VL) operand1 = Z[dn+r, VL];
    bits(VL) operand2 = Z[m, VL];
    for e = 0 to elements-1
        integer element = SInt(Elem[operand1, e, esize]);
        integer shift = ShiftSat(SInt(Elem[operand2, e, esize]), esize);
        integer res;
        if shift >= 0 then
            res = element << shift;
        else
            shift = -shift;
            res = (element + (1 << (shift - 1))) >> shift;
        Elem[results[r], e, esize] = res<esize-1:0>;

for r = 0 to nreg-1
    Z[dn+r, VL] = results[r];

```

[Base  
Instructions](#)

[SIMD&FP  
Instructions](#)

[SVE  
Instructions](#)

[SME  
Instructions](#)

[Index by  
Encoding](#)

[Sh  
Pseudocode](#)

Internal version only: isa v33.64, AdvSIMD v29.12, pseudocode  
no\_diffs\_2023\_09\_RC2, sve v2023-06\_rel ; Build timestamp: 2023-09-18T17:56

Copyright Â© 2010-2023 Arm Limited or its affiliates. All rights reserved. This  
document is Non-Confidential.