TPIDR_EL2, EL2 Software Thread ID Register

The TPIDR_EL2 characteristics are:

Purpose

Provides a location where software executing at EL2 can store thread identifying information, for OS management purposes.

The PE makes no use of this register.

Configuration

AArch64 System register TPIDR_EL2 bits [31:0] are architecturally mapped to AArch32 System register HTPIDR[31:0].

If EL2 is not implemented, this register is res0 from EL3.

This register has no effect if EL2 is not enabled in the current Security state.

Attributes

TPIDR_EL2 is a 64-bit register.

Field descriptions

63	62	61	60	59	58	57	56	55	54	53	52	51	50	49	48	47	46	45	44	43	42	41	40	39	38	37	36	35	34	33	32
Thread ID																															
Thread ID																															
31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0

Bits [63:0]

Thread ID. Thread identifying information stored by software running at this Exception level.

The reset behavior of this field is:

- On a Warm reset, this field resets to an architecturally unknown value.

Accessing TPIDR_EL2

Accesses to this register use the following encodings in the System register encoding space:

MRS <Xt>, TPIDR_EL2

op0	op1	CRn	CRm	op2
0b11	0b100	0b1101	0b0000	0b010

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if EL2Enabled() && HCR_EL2.<NV2,NV> == '11' then
        X[t, 64] = NVMem[0x090];
    elsif EL2Enabled() && HCR_EL2.NV == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    else
        UNDEFINED;
elsif PSTATE.EL == EL2 then
    X[t, 64] = TPIDR_EL2;
elsif PSTATE.EL == EL3 then
    X[t, 64] = TPIDR_EL2;
```

MSR TPIDR_EL2, <Xt>

op0	op1	CRn	CRm	op2
0b11	0b100	0b1101	0b0000	0b010

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if EL2Enabled() && HCR_EL2.<NV2,NV> == '11' then
        NVMem[0x090] = X[t, 64];
    elsif EL2Enabled() && HCR_EL2.NV == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    else
        UNDEFINED;
elsif PSTATE.EL == EL2 then
    TPIDR_EL2 = X[t, 64];
elsif PSTATE.EL == EL3 then
    TPIDR_EL2 = X[t, 64];
```