STLRH

Store-Release Register Halfword stores a halfword from a 32-bit register to a memory location. The instruction also has memory ordering semantics as described in *Load-Acquire, Store-Release*. For information about memory accesses, see *Load/Store addressing modes*.

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
0	1	0	0	1	0	0	0	1	0	0	(1)	(1)	(1)	(1)	(1)	1	(1)	(1)	(1)	(1)	(1)			Rn					Rt		
size								L			Rs					o0		Rt2													

        STLRH <Wt>, [<Xn|SP>{,#0}]

```
integer n = UInt(Rn);
integer t = UInt(Rt);

boolean tagchecked = n != 31;
```

Assembler Symbols

<Wt>   Is the 32-bit name of the general-purpose register to be transferred, encoded in the "Rt" field.

<Xn|SP>   Is the 64-bit name of the general-purpose base register or stack pointer, encoded in the "Rn" field.

Operation

```
bits(64) address;
bits(16) data;

AccessDescriptor accdesc;
accdesc = CreateAccDescAcqRel(MemOp_STORE, tagchecked);

if n == 31 then
    CheckSPAlignment();
    address = SP[];
else
    address = X[n, 64];

address = address;
data = X[t, 16];
Mem[address, 2, accdesc] = data;
```

Operational information

If PSTATE.DIT is 1, the timing of this instruction is insensitive to the value of the data being loaded or stored.