Index by	Sh
Encoding	Pseud

SIMD&FP Base **SVE** Instructions **Instructions** Instructions

SME Instructions

LDNT1D (scalar plus immediate, consecutive registers)

Contiguous load non-temporal of doublewords to multiple consecutive vectors (immediate index)

Contiguous load non-temporal of doublewords to elements of two or four consecutive vector registers from the memory address generated by a 64-bit scalar base and immediate index which is multiplied by the vector's inmemory size, irrespective of predication, and added to the base address.

Inactive elements will not cause a read from Device memory or signal a fault, and are set to zero in the destination vector.

A non-temporal load is a hint to the system that this data is unlikely to be referenced again soon.

It has encodings from 2 classes: <u>Two registers</u> and <u>Four registers</u>

Two registers (FEAT_SVE2p1)

```
3130292827262524232221201918171615
                                   14
                                          13
                                              1211109876543210
1 0 1 0 0 0 0 0 0 1 0 0 imm4
                                               PNg
                                                       Rn
                                                              Ζt
                                                                  1
                                   1
                                msz<1>msz<0>
                                                                  N
```

```
LDNT1D { <Zt1>.D-<Zt2>.D }, <PNg>/Z, [<Xn | SP>{, #<imm>, MUL VL}]
```

```
if ! <a href="HaveSME2">HaveSWE2p1</a>() then UNDEFINED;
integer n = UInt(Rn);
integer g = <u>UInt('1':PNg);</u>
constant integer nreg = 2;
integer t = <u>UInt</u>(Zt:'0');
constant integer esize = 64;
integer offset = SInt(imm4);
```

Four registers (FEAT_SVE2p1)

```
3130292827262524232221201918171615
                                         13
                                              1211109876543210
1 0 1 0 0 0 0 0 0 1 0 0 imm4 | 1
                                          1
                                               PNg
                                                      Rn
                                                             Zt |0|1|
                                msz<1>msz<0>
```

```
LDNT1D { <Zt1>.D-<Zt4>.D }, <PNg>/Z, [<Xn | SP>{, #<imm>, MUL VL}]
```

```
if ! <a href="HaveSME2">HaveSWE2p1</a>() then UNDEFINED;
integer n = UInt(Rn);
integer g = <u>UInt</u>('1':PNg);
constant integer nreg = 4;
integer t = <u>UInt</u>(Zt:'00');
constant integer esize = 64;
integer offset = SInt(imm4);
```

Assembler Symbols

<Zt1> For the two registers variant: is the name of the first scalable vector register to be transferred, encoded as "Zt" times 2.

For the four registers variant: is the name of the first scalable vector register to be transferred, encoded as "Zt" times 4.

<Zt4> Is the name of the fourth scalable vector register to be transferred, encoded as "Zt" times 4 plus 3.

<Zt2> Is the name of the second scalable vector register to be transferred, encoded as "Zt" times 2 plus 1.

<PNg> Is the name of the governing scalable predicate register PN8-PN15, with predicate-as-counter encoding, encoded in the "PNg" field.

<Xn|SP> Is the 64-bit name of the general-purpose base register or stack pointer, encoded in the "Rn" field.

For the two registers variant: is the optional signed immediate vector offset, a multiple of 2 in the range -16 to 14, defaulting to 0, encoded in the "imm4" field.

For the four registers variant: is the optional signed immediate vector offset, a multiple of 4 in the range -32 to 28, defaulting to 0, encoded in the "imm4" field.

Operation

```
if <a href="HaveSVE2p1">HaveSVE2p1</a>() then <a href="CheckSVEEnabled">CheckSVEEnabled</a>(); else <a href="CheckStreamingSVEEnabled">CheckStreamingSVEEnabled</a>()
constant integer VL = CurrentVL;
constant integer PL = VL DIV 8;
constant integer elements = VL DIV esize;
constant integer mbytes = esize DIV 8;
bits(64) base;
bits(PL) pred = P[g, PL];
bits(PL * nreg) mask = CounterToPredicate(pred<15:0>, PL * nreg);
array [0..3] of bits(VL) values;
boolean contiguous = TRUE;
boolean nontemporal = TRUE;
boolean tagchecked = n != 31;
AccessDescriptor accdesc = CreateAccDescSVE (MemOp_LOAD, nontemporal, co
if !<u>AnyActiveElement</u>(mask, esize) then
     if n == 31 && ConstrainUnpredictableBool (Unpredictable CHECKSPNONEA
         CheckSPAlignment();
else
     if n == 31 then <a href="CheckSPAlignment">CheckSPAlignment</a>();
    base = if n == 31 then SP[] else X[n, 64];
for r = 0 to nreg-1
     for e = 0 to elements-1
```

if <u>ActivePredicateElement</u> (mask, r * elements + e, esize) then

Operational information

If PSTATE.DIT is 1, the timing of this instruction is insensitive to the value of the data being loaded or stored when its governing predicate register contains the same value for each execution.

<u>Base</u>	SIMD&FP	<u>SVE</u>	<u>SME</u>	Index by
<u>Instructions</u>	<u>Instructions</u>	<u>Instructions</u>	<u>Instructions</u>	Encoding

Internal version only: isa v33.64, AdvSIMD v29.12, pseudocode no diffs 2023 09 RC2, sve v2023-06 rel ; Build timestamp: 2023-09-18T17:56

Sh Pseu

Copyright © 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.