

---

## TLBIP RVAE1OS, TLBIP RVAE1OSNXS, TLB Range Invalidate by VA, EL1, Outer Shareable

The TLBIP RVAE1OS, TLBIP RVAE1OSNXS characteristics are:

### Purpose

Invalidates cached copies of translation table entries from TLBs that meet all the following requirements:

- The entry is a 128-bit stage 1 translation table entry, from any level of the translation table walk up to the level indicated in the TTL hint.

Or the entry is a 64-bit stage 1 translation table entry, if TTL is 0b00.

- The entry would be used to translate any of the VAs in the specified address range, and one of the following applies:
  - The entry is from a level of lookup above the final level and matches the specified ASID.
  - The entry is a global entry from the final level of lookup.
  - The entry is a non-global entry from the final level of lookup that matches the specified ASID.
- The entry is within the address range determined by the formula  $[\text{BaseADDR} \leq \text{VA} < \text{BaseADDR} + ((\text{NUM} + 1) * 2^{(5 * \text{SCALE} + 1)} * \text{Translation\_Granule\_Size})]$ .
- When EL2 is implemented and enabled in the current Security state:
  - If [HCR\\_EL2](#).{E2H, TGE} is not {1, 1}, the entry would be used with the current VMID and would be required to translate any of the VAs in the specified address range using the EL1&0 translation regime for the Security state.
  - If [HCR\\_EL2](#).{E2H, TGE} is {1, 1}, the entry would be required to translate any of the VAs in the specified address range using the EL2&0 translation regime for the Security state.
- When EL2 is not implemented or is disabled in the current Security state, the entry would be required to translate any of

the VAs in the specified address range using the EL1&0 translation regime for the Security state.

The Security state is indicated by the value of [SCR\\_EL3.NS](#) if FEAT\_RME is not implemented, or [SCR\\_EL3.{NSE, NS}](#) if FEAT\_RME is implemented.

The invalidation applies to all PEs in the same Outer Shareable shareability domain as the PE that executes this System instruction.

---

## Note

When a TLB maintenance instruction is generated to the Secure EL1&0 translation regime and is defined to pass a VMID argument, or would be defined to pass a VMID argument if [SCR\\_EL3.EEL2](#)==1, then:

- A PE with [SCR\\_EL3.EEL2](#)==1 is not architecturally required to invalidate any entries in the Secure EL1&0 translation of a PE in the same required shareability domain with [SCR\\_EL3.EEL2](#)==0.
- A PE with [SCR\\_EL3.EEL2](#)==0 is not architecturally required to invalidate any entries in the Secure EL1&0 translation of a PE in the same required shareability domain with [SCR\\_EL3.EEL2](#)==1.
- A PE is architecturally required to invalidate all relevant entries in the Secure EL1&0 translation of a System MMU in the same required shareability domain with a VMID of 0.

---

For 128-bit translation table entry, the range of addresses invalidated is unpredictable when Block or Page size corresponding to TTL and TG, for the translation system is not aligned.

## Configuration

This instruction is present only when FEAT\_D128 is implemented. Otherwise, direct accesses to TLBIP RVAE1OS, TLBIP RVAE1OSNXS are undefined.

## Attributes

TLBIP RVAE1OS, TLBIP RVAE1OSNXS is a 128-bit System instruction.

## Field descriptions

127	126	125	124	123	122	121	120	119	118	117	116	115	114	113	112	111	110	109	108	107	106	105	104	103	102	101	100	99	98	97	96
RES0																BaseADDR[55:12]															
95	94	93	92	91	90	89	88	87	86	85	84	83	82	81	80	79	78	77	76	75	74	73	72	71	70	69	68	67	66	65	64
BaseADDR[55:12]																															
63	62	61	60	59	58	57	56	55	54	53	52	51	50	49	48	47	46	45	44	43	42	41	40	39	38	37	36	35	34	33	32
ASID																TG	SCALE	NUM				TTL	RES0								
31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
RES0																															

### Bits [127:108]

Reserved, res0.

### BaseADDR[55:12], bits [107:64]

The starting address for the range of the maintenance instructions.  
This field is BaseADDR[55:12] for all translation granules.

### ASID, bits [63:48]

ASID value to match. Any TLB entries that match the ASID value and VA value will be affected by this System instruction.

Global TLB entries that match the VA value will be affected by this System instruction, regardless of the value of the ASID field.

If the implementation supports 16 bits of ASID, then the upper 8 bits of the ASID must be written to 0 by software when the context being invalidated only uses 8 bits.

### TG, bits [47:46]

Translation granule size.

TG	Meaning
0b00	Reserved.
0b01	4K translation granule.
0b10	16K translation granule.
0b11	64K translation granule.

The instruction takes a translation granule size for the translations that are being invalidated. If the translations used a different translation granule size than the one being specified, then the architecture does not require that the instruction invalidates any entries.

### SCALE, bits [45:44]

The exponent element of the calculation that is used to produce the upper range.

## NUM, bits [43:39]

The base element of the calculation that is used to produce the upper range.

## TTL, bits [38:37]

TTL Level hint. The TTL hint is only guaranteed to invalidate:

- Non-leaf-level entries in the range up to but not including the level described by the TTL hint.
- Leaf-level entries in the range that match the level described by the TTL hint.

TTL	Meaning
0b00	The entries in the range can be using any level for the translation table entries.
0b01	The TTL hint indicates level 1. If FEAT_LPA2 is not implemented, when using a 16KB translation granule, this value is reserved and hardware should treat this field as 0b00.
0b10	The TTL hint indicates level 2.
0b11	The TTL hint indicates level 3.

## Bits [36:0]

Reserved, res0.

## Executing TLBIP RVAE10S, TLBIP RVAE10SNXS

Accesses to this instruction use the following encodings in the System instruction encoding space:

TLBIP RVAE10S{, <Xt>, <Xt2>}

op0	op1	CRn	CRm	op2
0b01	0b000	0b1000	0b0101	0b001

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if EL2Enabled() && HCR_EL2.TTLB == '1' then
        AArch64.SystemAccessTrap(EL2, 0x14);
```

```

        elsif EL2Enabled() && HCR_EL2.TTLBOS == '1' then
            AArch64.SystemAccessTrap(EL2, 0x14);
        elsif EL2Enabled() &&
            IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
            SCR_EL3.FGTEn == '1') && HFGITR_EL2.TLBIRVAE1OS ==
            '1' then
            AArch64.SystemAccessTrap(EL2, 0x14);
        else
            if IsFeatureImplemented(FEAT_XS) &&
            IsFeatureImplemented(FEAT_HCX) && IsHCRXEL2Enabled()
            && HCRX_EL2.FnXS == '1' then

                AArch64.TLBIP_RVA(SecurityStateAtEL(EL1),
                Regime_EL10, VMID[], Shareability_OSH,
                TLBILevel_Any, TLBI_ExcludeXS, X[t2, 64]:X[t, 64]);
            else

                AArch64.TLBIP_RVA(SecurityStateAtEL(EL1),
                Regime_EL10, VMID[], Shareability_OSH,
                TLBILevel_Any, TLBI_AllAttr, X[t2, 64]:X[t, 64]);
            elsif PSTATE.EL == EL2 then
                if HCR_EL2.<E2H,TGE> == '11' then
                    AArch64.TLBIP_RVA(SecurityStateAtEL(EL2),
                    Regime_EL20, VMID_NONE, Shareability_OSH,
                    TLBILevel_Any, TLBI_AllAttr, X[t2, 64]:X[t, 64]);
                else
                    AArch64.TLBIP_RVA(SecurityStateAtEL(EL1),
                    Regime_EL10, VMID[], Shareability_OSH,
                    TLBILevel_Any, TLBI_AllAttr, X[t2, 64]:X[t, 64]);
            elsif PSTATE.EL == EL3 then
                if HCR_EL2.<E2H,TGE> == '11' then
                    AArch64.TLBIP_RVA(SecurityStateAtEL(EL2),
                    Regime_EL20, VMID_NONE, Shareability_OSH,
                    TLBILevel_Any, TLBI_AllAttr, X[t2, 64]:X[t, 64]);
                else
                    AArch64.TLBIP_RVA(SecurityStateAtEL(EL1),
                    Regime_EL10, VMID[], Shareability_OSH,
                    TLBILevel_Any, TLBI_AllAttr, X[t2, 64]:X[t, 64]);

```

**TLBIP RVAE1OSNXS{, <Xt>, <Xt2>}**

<b>op0</b>	<b>op1</b>	<b>CRn</b>	<b>CRm</b>	<b>op2</b>
0b01	0b000	0b1001	0b0101	0b001

```

if !IsFeatureImplemented(FEAT_XS) then
    UNDEFINED;
elsif PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if EL2Enabled() && HCR_EL2.TTLB == '1' then
        AArch64.SystemAccessTrap(EL2, 0x14);
    elsif EL2Enabled() && HCR_EL2.TTLBOS == '1' then
        AArch64.SystemAccessTrap(EL2, 0x14);

```

```

        elsif EL2Enabled() &&
        IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
        SCR_EL3.FGTEn == '1') &&
        IsFeatureImplemented(FEAT_HCX) && (!
        IsHCRXEL2Enabled() || HCRX_EL2.FGTnXS == '0') &&
        HFGITR_EL2.TLBIRVAE1OS == '1' then
            AArch64.SystemAccessTrap(EL2, 0x14);
        else
            AArch64.TLBIP_RVA(SecurityStateAtEL(EL1),
            Regime_EL10, VMID[], Shareability_OSH,
            TLBILevel_Any, TLBI_ExcludeXS, X[t2, 64]:X[t, 64]);
        elsif PSTATE.EL == EL2 then
            if HCR_EL2.<E2H,TGE> == '11' then
                AArch64.TLBIP_RVA(SecurityStateAtEL(EL2),
                Regime_EL20, VMID_NONE, Shareability_OSH,
                TLBILevel_Any, TLBI_ExcludeXS, X[t2, 64]:X[t, 64]);
            else
                AArch64.TLBIP_RVA(SecurityStateAtEL(EL1),
                Regime_EL10, VMID[], Shareability_OSH,
                TLBILevel_Any, TLBI_ExcludeXS, X[t2, 64]:X[t, 64]);
            elsif PSTATE.EL == EL3 then
                if HCR_EL2.<E2H,TGE> == '11' then
                    AArch64.TLBIP_RVA(SecurityStateAtEL(EL2),
                    Regime_EL20, VMID_NONE, Shareability_OSH,
                    TLBILevel_Any, TLBI_ExcludeXS, X[t2, 64]:X[t, 64]);
                else
                    AArch64.TLBIP_RVA(SecurityStateAtEL(EL1),
                    Regime_EL10, VMID[], Shareability_OSH,
                    TLBILevel_Any, TLBI_ExcludeXS, X[t2, 64]:X[t, 64]);

```

[AArch32  
Registers](#)

[AArch64  
Registers](#)

[AArch32  
Instructions](#)

[AArch64  
Instructions](#)

[Index by  
Encoding](#)

[External  
Registers](#)

28/03/2023 16:01; 72747e43966d6b97dcbdd230a1b3f0421d1ea3d94

Copyright © 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.