TLBI VALE1, TLBI VALE1NXS, TLB Invalidate by VA, Last level, EL1

The TLBI VALE1, TLBI VALE1NXS characteristics are:

Purpose

Invalidates cached copies of translation table entries from TLBs that meet all the following requirements:

- The entry is a 64-bit stage 1 translation table entry.

  Or if FEAT_D128 is implemented, and the entry is a 128-bit stage 1 translation table entry, if TTL[3:2] is 0b00.

- The entry would be used to translate the specified VA, and one of the following applies:

  - The entry is a global entry from the final level of lookup.

  - The entry is a non-global entry from the final level of lookup that matches the specified ASID.

- When EL2 is implemented and enabled in the current Security state:

  - If [HCR_EL2](#).{E2H, TGE} is not {1, 1}, the entry would be used with the current VMID and would be required to translate the specified VA using the EL1&0 translation regime for the Security state.
  - If [HCR_EL2](#).{E2H, TGE} is {1, 1}, the entry would be required to translate the specified VA using the EL2&0 translation regime for the Security state.

- When EL2 is not implemented or is disabled in the current Security state, the entry would be required to translate the specified VA using the EL1&0 translation regime for the Security state.

The Security state is indicated by the value of [SCR_EL3](#).NS if FEAT_RME is not implemented, or [SCR_EL3](#).{NSE, NS} if FEAT_RME is implemented.

The invalidation applies to the PE that executes this System instruction.

If FEAT_XS is implemented, the nXS variant of this System instruction is defined.

Both variants perform the same invalidation, but the TLBI System instruction without the nXS qualifier waits for all memory accesses using in-scope old translation information to complete before it is considered complete.

The TLBI System instruction with the nXS qualifier is considered complete when the subset of these memory accesses with XS attribute set to 0 are complete.

Configuration

There are no configuration notes.

Attributes

TLBI VALE1, TLBI VALE1NXS is a 64-bit System instruction.

Field descriptions

63 62 61 60 59 58 57 56 55 54 53 52 51 50 49 48 47 46 45 44 43 42 41 40 39 38 37 36 35 34 33 32

| ASID | | | | | | | | | | | | | | | | TTL | | | | VA[55:12] | | | | | | | | | | | |

| VA[55:12] | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0

ASID, bits [63:48]

ASID value to match. Any TLB entries that match the ASID value and VA value will be affected by this System instruction.

Global TLB entries that match the VA value will be affected by this System instruction, regardless of the value of the ASID field.

If the implementation supports 16 bits of ASID, then the upper 8 bits of the ASID must be written to 0 by software when the context being invalidated only uses 8 bits.

TTL, bits [47:44]
When FEAT_TTL is implemented:

Translation Table Level. Indicates the level of the translation table walk that holds the leaf entry for the address being invalidated.

TTL	Meaning
0b00xx	No information supplied as to the translation table level. Hardware must assume that the entry can be from any level. In this case, TTL<1:0> is res0.

0b01xx	The entry comes from a 4KB translation granule. The level of walk for the leaf level 0bxx is encoded as: 0b00 : If FEAT_LPA2 is implemented, level 0. Otherwise, treat as if TTL<3:2> is 0b00. 0b01 : Level 1. 0b10 : Level 2. 0b11 : Level 3.
0b10xx	The entry comes from a 16KB translation granule. The level of walk for the leaf level 0bxx is encoded as: 0b00 : Reserved. Treat as if TTL<3:2> is 0b00. 0b01 : If FEAT_LPA2 is implemented, level 1. Otherwise, treat as if TTL<3:2> is 0b00. 0b10 : Level 2. 0b11 : Level 3.
0b11xx	The entry comes from a 64KB translation granule. The level of walk for the leaf level 0bxx is encoded as: 0b00 : Reserved. Treat as if TTL<3:2> is 0b00. 0b01 : Level 1. 0b10 : Level 2. 0b11 : Level 3.

If an incorrect value of the TTL field is specified for the entry being invalidated by the instruction, then no entries are required by the architecture to be invalidated from the TLB.

Otherwise:

Reserved, res0.

VA[55:12], bits [43:0]

Bits[55:12] of the virtual address to match. Any appropriate TLB entries that match the ASID value (if appropriate) and VA will be affected by this System instruction.

If the TLB maintenance instructions are targeting a translation regime that is using AArch32, and so has a VA of only 32 bits, then the software must treat bits[55:32] as res0.

The treatment of the low-order bits of this field depends on the translation granule size, as follows:

- Where a 4KB translation granule is being used, all bits are valid and used for the invalidation.

- Where a 16KB translation granule is being used, bits [1:0] of this field are res0 and ignored when the instruction is executed, because VA[13:12] have no effect on the operation of the instruction.

- Where a 64KB translation granule is being used, bits [3:0] of this field are res0 and ignored when the instruction is executed, because VA[15:12] have no effect on the operation of the instruction.

Executing TLBI VALE1, TLBI VALE1NXS

Accesses to this instruction use the following encodings in the System instruction encoding space:

TLBI VALE1{, <Xt>}

op0	op1	CRn	CRm	op2
0b01	0b000	0b1000	0b0111	0b101

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if EL2Enabled() && HCR_EL2.TTLB == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() &&
IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
SCR_EL3.FGTEn == '1') && HFGITR_EL2.TLBIVALE1 == '1'
then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() && HCR_EL2.FB == '1' then
        if IsFeatureImplemented(FEAT_XS) &&
IsFeatureImplemented(FEAT_HCX) && IsHCRXEL2Enabled()
&& HCRX_EL2.FnXS == '1' then
            AArch64.TLBI_VA(SecurityStateAtEL(EL1),
Regime_EL10, VMID[], Shareability_ISH,
TLBILevel_Last, TLBI_ExcludeXS, X[t, 64]);
        else
            AArch64.TLBI_VA(SecurityStateAtEL(EL1),
Regime_EL10, VMID[], Shareability_ISH,
TLBILevel_Last, TLBI_AllAttr, X[t, 64]);
```

```
        else
            if IsFeatureImplemented(FEAT_XS) &&
IsFeatureImplemented(FEAT_HCX) && IsHCRXEL2Enabled()
&& HCRX_EL2.FnXS == '1' then
                AArch64.TLBI_VA(SecurityStateAtEL(EL1),
Regime_EL10, VMID[], Shareability_NSH,
TLBILevel_Last, TLBI_ExcludeXS, X[t, 64]);
            else
                AArch64.TLBI_VA(SecurityStateAtEL(EL1),
Regime_EL10, VMID[], Shareability_NSH,
TLBILevel_Last, TLBI_AllAttr, X[t, 64]);
elsif PSTATE.EL == EL2 then
    if HCR_EL2.<E2H,TGE> == '11' then
        AArch64.TLBI_VA(SecurityStateAtEL(EL2),
Regime_EL20, VMID_NONE, Shareability_NSH,
TLBILevel_Last, TLBI_AllAttr, X[t, 64]);
    else
        AArch64.TLBI_VA(SecurityStateAtEL(EL1),
Regime_EL10, VMID[], Shareability_NSH,
TLBILevel_Last, TLBI_AllAttr, X[t, 64]);
elsif PSTATE.EL == EL3 then
    if HCR_EL2.<E2H,TGE> == '11' then
        AArch64.TLBI_VA(SecurityStateAtEL(EL2),
Regime_EL20, VMID_NONE, Shareability_NSH,
TLBILevel_Last, TLBI_AllAttr, X[t, 64]);
    else
        AArch64.TLBI_VA(SecurityStateAtEL(EL1),
Regime_EL10, VMID[], Shareability_NSH,
TLBILevel_Last, TLBI_AllAttr, X[t, 64]);
```

TLBI VALE1NXS{, <Xt>}

op0	op1	CRn	CRm	op2
0b01	0b000	0b1001	0b0111	0b101

```
if !IsFeatureImplemented(FEAT_XS) then
    UNDEFINED;
elsif PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if EL2Enabled() && HCR_EL2.TTLB == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() &&
IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
SCR_EL3.FGTEn == '1') &&
IsFeatureImplemented(FEAT_HCX) && (!
IsHCRXEL2Enabled() || HCRX_EL2.FGTnXS == '0') &&
HFGITR_EL2.TLBIVALE1 == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() && HCR_EL2.FB == '1' then
        AArch64.TLBI_VA(SecurityStateAtEL(EL1),
Regime_EL10, VMID[], Shareability_ISH,
TLBILevel_Last, TLBI_ExcludeXS, X[t, 64]);
```

```
        else
            AArch64.TLBI_VA(SecurityStateAtEL(EL1),
Regime_EL10, VMID[], Shareability_NSH,
TLBILevel_Last, TLBI_ExcludeXS, X[t, 64]);
elsif PSTATE.EL == EL2 then
    if HCR_EL2.<E2H,TGE> == '11' then
        AArch64.TLBI_VA(SecurityStateAtEL(EL2),
Regime_EL20, VMID_NONE, Shareability_NSH,
TLBILevel_Last, TLBI_ExcludeXS, X[t, 64]);
    else
        AArch64.TLBI_VA(SecurityStateAtEL(EL1),
Regime_EL10, VMID[], Shareability_NSH,
TLBILevel_Last, TLBI_ExcludeXS, X[t, 64]);
elsif PSTATE.EL == EL3 then
    if HCR_EL2.<E2H,TGE> == '11' then
        AArch64.TLBI_VA(SecurityStateAtEL(EL2),
Regime_EL20, VMID_NONE, Shareability_NSH,
TLBILevel_Last, TLBI_ExcludeXS, X[t, 64]);
    else
        AArch64.TLBI_VA(SecurityStateAtEL(EL1),
Regime_EL10, VMID[], Shareability_NSH,
TLBILevel_Last, TLBI_ExcludeXS, X[t, 64]);
```

28/03/2023 16:01; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94