

# Azure Blob Storage Basic Operations

---

## What is Blob Storage?

Azure Blob (binary large object) Storage is Microsoft's cloud object storage solution. An 'object' describes images, text files, audio files, file backups, logs, etc. Azure Blob Storage is optimized for storing very large volumes of unstructured data that isn't constrained to a specific model or schema. Blob Storage is highly convenient and customizable to your needs. Users have many options to store and retrieve data from an instance of Azure Blob Storage.

Microsoft maintains client libraries for .Net, Java, Node.js, Python, Go, PHP, and Ruby. Additionally, you can also access objects using HTTP/HTTPS. Another selling point is that you also have security built-in through Microsoft's platform, as well as the additional benefit of high availability and disaster recovery.

## What is the structure of Blob Storage?

[Account](#) → [Container](#) → [Blob](#)

Blob Storage is relatively intuitive and similar to a traditional file structure: directory>subdirectory>file schema. Each Azure Blob Storage account can contain an unlimited number of containers, and each container can contain an unlimited number of blobs. People often think of the container as the directory in the above example, and try to create folders within the containers to replicate a traditional structure, producing a virtual file structure. However, it is better to think of the container as the subdirectory from above and the account itself as the directory. To avoid unnecessary complications, try to make the files as flat as possible without virtual subdirectories.

## What are the types of blobs?

- **Block Blobs:** Optimized for large 'blocks' of data and identified by a single block ID, a block blob can hold 50k blocks.
- **Page Blobs:** Collections of 512-byte pages optimized for read/write operations.
- **Append Blobs:** Composed of block blobs optimized for append operations, new blocks are added to the end of the blob. Updating/deleting are not supported.

## What are the storage tiers?

Azure also provides the option to customize storage options based on the purpose of the storage through different tiers. Currently, Microsoft offers three different storage tiers: Hot, Cool, and Archive.

### Hot Access Tier

This tier is used for storing objects that are actively and consistently read from and written to. The access costs for this tier are the lowest among the tiers, however the storage costs are the highest. Generally, once frequent access to the data is no longer necessary, the data should be migrated to a different tier.


## Cool Access Tier

Conversely, the cool access tier has higher access costs and lower storage costs than the hot access tier. This is meant for data that is no longer frequently used but users need immediate access should the need arise. Data in this tier should be expected to remain for at least 30 days.

## Archive Access Tier

This tier has the cheapest storage cost and the highest access cost of the tiers. Microsoft expects that data placed in this tier will persist for at least 180 days and the account will incur an early deletion charge if the data is removed prior to 180 days. Data in this tier is not immediately available: Microsoft takes these objects offline and you will not be able to read or modify them. In order to access objects in this tier, you must first 'rehydrate' them, which is basically Microsoft's terminology for moving the object back to an online tier such as cool or hot access.

Here is a quick graph to help picture how the access tiers are utilized:



The Y axis is how often the data needs to be accessed, while the X axis represents the length of time the data needs to be retained. The 'Hot' access tier is accessed often but is not required to be static very long, while the 'Cool' tier is not expected to be accessed often but is expected to remain available for 30-180 days, and finally the 'Archive' tier is not expected to be accessed outside of an anomaly.

## How do I create a storage account?

To create a storage account, you will have to log into your Azure account and navigate to 'Home' > 'Storage accounts'. From here, you will fill out all of the necessary information for the new account. If you already have a storage account, you can skip this step.

# Create a storage account ...

Basics Advanced Networking Data protection Tags Review + create

Azure Storage is a Microsoft-managed service providing cloud storage that is highly available, secure, durable, scalable, and redundant. Azure Storage includes Azure Blobs (objects), Azure Data Lake Storage Gen2, Azure Files, Azure Queues, and Azure Tables. The cost of your storage account depends on the usage and the options you choose below. [Learn more about Azure storage accounts](#)

## Project details

Select the subscription in which to create the new storage account. Choose a new or existing resource group to organize and manage your storage account together with other resources.

Subscription \*

Resource group \*

The value must not be empty.  
[Create new](#)

## Instance details

If you need to create a legacy storage account type, please click [here](#).

Storage account name ⓘ \*

Region ⓘ \*

Performance ⓘ \*

☒ Standard: Recommended for most scenarios (general-purpose v2 account)

☐ Premium: Recommended for scenarios that require low latency.

Redundancy ⓘ \*

☒ Make read access to data available in the event of regional unavailability.

Please note that once you have created the resource, you can see what the default access tier is for the account in the properties. This can be changed based on your needs, but be aware of what new objects will default to.

Properties Monitoring Capabilities (7) Recommen

## Blob service

Hierarchical namespace Disabled


Default access tier [Hot](#)

# How do I create a container?


Once you have a storage account, you will then be able to create a container.

## Storage Explorer

Simply navigate to the subscription and storage account then right-click 'Blob Containers' and select 'Create Blob Container' and name it.




You should now see an empty container.



# How do I create a blob?


## Storage Explorer

Uploading a blob using the storage explorer is fairly straightforward: Open the container, select 'Upload', select any file to upload, and press 'Upload'.




One thing to note here is that you are given the option to choose the Access Tier and the Blob Type. The Access Tier determines the access vs storage costs of the blob while the Blob Type determines how the blob is optimized. In practice, you will want to ensure that these options suit your purpose, however here I will leave it as defaulted.

Once the transfer is complete, your file is now stored as a blob.



## How do I change a blob's access tier?


Once a blob has been created and you find that your retention/access needs have changed for the data, you can update the blob's access tier to match these requirements and make more efficient use of your resources. One of the easiest ways to accomplish this is through the Storage Explorer. In Storage Explorer, navigate to the blob you want to update and right-click then select 'Change Access Tier' from the menu.



# How do I download a blob?

## Storage Explorer

In storage explorer this is generally a trivial process. The interface provides a clear download option that will prompt you for a path. Additionally, you can double-click the file to open it within temporary local storage.




## HTTP Request

You can also retrieve a blob using an HTTPS/HTTP request. One way to find the URL of the blob is by using the Azure portal by going to `Home > Storage Account > Container > Blob > Properties`.


Properties	
URL	<code>https://anchor.blob.cor...</code>
LAST MODIFIED	7/7/2021, 1:03:05 PM

However, probably the easiest way is to find the blob in the Storage Explorer, right-click, then select 'Copy URL'. This will copy the resource URL directly to the clipboard. To download the blob, you would navigate to the copied URL and your browser will initiate the download. First however, you will need to set up authentication for the resource, or set up public access. For this example, I'll set up public access to the container. To accomplish this, simply right-click the container in the storage explorer and select 'Set Public Access Level...' and fill out the form.

### Storage Explorer Copy URL



## Public Access




## How do I delete a blob?

### Storage Explorer

To delete a blob in Storage Explorer, simply right-click the target blob and select 'delete'.






## How do I delete a container?

### Storage Explorer

Deleting a container through Storage Explorer is almost identical to deleting a blob, except here you would right-click the container object itself and then select 'delete'.



## How to update Access Tier in Azure Storage Account Level?

When we create **Azure Storage Account**, we chose the **Storage Tier** (Available only for *gpV2* and *blob* account type). During the storage account creation, we can choose the tier between **Hot** or **Cool**.

Account kind ⓘ

StorageV2 (general purpose v2) ▼

\* Location

West Europe ▼

Replication ⓘ

Read-access geo-redundant storage (R... ▼

Performance ⓘ

Standard Premium

Access tier (default) ⓘ

Cool Hot

This access tier is the storage account level, which you can go and check from the **storage configuration** option.

Storage Explorer (preview)

SETTINGS

Access keys

Configuration

Performance ⓘ

Standard Premium

\* Secure transfer required ⓘ


Disabled Enabled

Access tier (default) ⓘ


Cool Hot

## How to update Access Tier at Blob Level using Portal?

You can easily change the access tier at blob level for storage accounts. If you want to perform this action from **Azure Portal**, open the respective **Azure Blob**. Then select the “**Blob Properties**”




From the **properties** window, you can change access tier for the blob to **Hot, Cool or Archive**.




## How to update Access Tier at Blob Level using Storage Explorer?

You can change the access tier from Azure Storage Explorer as well. Open the respective blob in the explorer and from the context menu select **"Change Access Tier"**




This will bring, “**Update Access Tier**” window from where you can select the access tier to update.



## What is Azure Blob Rehydration ?

With the different level of storage tiers, you can choose what types of tier needs for your data. We use hot storage tier for those data which are accessed very frequently. Cool tier intended to access less than hot tiers, in general for at least 30 days. Archive tier is intended for long-term data backup or archival purpose and will remain in the tier for at least 180 days. Hot tier has the highest storage cost and lowest access cost, whereas the archive tier has the lowest storage cost and highest access cost.

You can update the tier from Hot or Cool to Archive Tier as we saw in previous section



You can easily change the access tier at blob level for storage accounts. If you want to perform this action from **Azure Portal**, open the respective **Azure Blob**. Then select the **"Blob Properties"**. From the **properties** window, you can change access tier for the blob to **Hot, Cool or Archive**.

### Access Tier

Optimize storage costs by placing your data in the appropriate access tier. [Learn more](#)

Archive


Setting the access tier to Archive will make your blob inaccessible until it is rehydrated back to Hot or Cool, which may take several hours.

Once the Access Tier is moved to **Archive** tier, your Blob will be **inaccessible**. **Archive storage is offline**. At this time if you want to access the blob you will get **"This operation is not permitted on an archived blob"** error.

```
<?xml version='1.0' encoding='utf-8'>
<Error>
  <Code>BlobArchived</Code>
  <Message>
    This operation is not permitted on an archived blob.
  </Message>
</Error>
```

## How to Rehydrate Archived Blob from Azure Portal?

To access your archive data back, you need to rehydrate back your storage tier to either Hot or Cool. This process is called **Blob Rehydration**. The rehydration process may take several hrs. ( *up to 15 hrs. to complete* ) .





When the rehydration is in progress, the blob will be still inaccessible. You can start the rehydration process by just updating the tier for the blobs, and check the status of the rehydration.

### Access Tier

Optimize storage costs by placing your data in the appropriate access tier. [Learn more](#)



Cool

 Rehydrating a blob from Archive to Hot or Cool may take several hours to complete. 

### Access Tier

Optimize storage costs by placing your data in the appropriate access tier. [Learn more](#)

Archive


 This blob is currently rehydrating. This may take several hours to complete and during this time your blob is inaccessible. Archive status 'rehydrate-pending-to-cool'. 

Once the rehydration is complete, you can start access the data. This types of access tier ideal Long-term backup, and archival datasets where frequent data access is not required. Archive tier has the lowest storage cost and highest access cost.

## How to update the access tier of blobs automatically?

We can achieve automatic tier updates using **Storage Life Cycle Management**.

Navigate to the Azure Storage and Select **Life Cycle Management** available under “**Blob Service**”



learnazurestorageejcs Storage account

Search (Ctrl+/)

Properties  
Locks  
Export template

**Blob service**


Containers  
Custom domain  
Data protection  
Azure CDN  
Add Azure Search

**Lifecycle Management**

File service

File shares

Open in Explorer → Move Refresh Delete Feedback

 Classic alerts in Azure Monitor is announced to retire in 2021, it is recommended that you see Continue alerting with ARM storage accounts.

Resource group (change) : ICAJ


Status : Primary: Available, Secondary: Available


Location : West US, East US

Subscription (change) : Visual Studio Ultimate with MSDN

Subscription ID

Tags (change) : Click here to add tags

 **Containers**  
Scalable, cost-effective storage for unstructured data  
[Learn more](#)

 **File shares**  
Serverless SMB file share  
[Learn more](#)

In the **“Life Cycle Management”** section, select the **“Add Rule”** option to add a new rule. In the Add rule screen, you can define when you want to move blob storage from Hot to Cool and the Archive. Even you can configure when to delete blob storage.

## Add a rule

**Action set**   Filter set   Review + add

Each rule definition includes an action set and a filter set. The action set applies the tier or delete actions to the filtered set of objects. The filter set limits rule actions to a certain set of objects within a container or objects names.

**Rule name \***  ✓

**Status** ☐ Disabled ☒ Enabled

**Blobs**

☒ Move blob to cool storage  
Days after last modification  ✓

☒ Move blob to archive storage  
Days after last modification  ✓

☐ Delete blob  
Days after last modification

**Snapshots**

☐ Delete snapshot  
Days after blob is created

---

**Review + add**   < Previous   Next : Filter set >

You can also customize the rules for a specific set of Blob folder, which you can define as Filter set while defining the Rule.



# Add a rule

Action set   **Filter set**   Review + add

Each rule definition includes an action set and a filter set. The action set applies the tier or delete actions to the filtered set of objects. The filter set limits rule actions to a certain set of objects within a container or objects names.

Supported blob types   Block Blob

## Prefix match


Apply a rule to a container or a subset of virtual folders with the use of up to 10 prefixes as filters. By default, a rule will apply to the entire storage account.

 Browse    Delete

☒ Path

Container/virtual folder

Once rules is created, you can see them under Lifecycle Management screen and status as enabled if it was set to enabled during the creation.

 **learnazurestorageejcs** | Lifecycle Management

Storage account

[+ Add rule](#)   [✓ Enable](#)   [□ Disable](#)   [↻ Refresh](#)   [🗑 Delete](#)

☰ Properties

🔒 Locks

📄 Export template

**Blob service**

📁 Containers

🌐 Custom domain

🛡 Data protection

☁ Azure CDN

➕ Add Azure Search


**🕒 Lifecycle Management**

List view   Code view

Lifecycle management offers a rich, rule-based policy for general purpose v2 and blob storage accounts. Use the policy to transition your [more](#)

<input type="checkbox"/> Name	Status
<input type="checkbox"/> CustomStorageRules	Enabled


The Lifecycle management windows show both list view and the code view the rules that bring a JSON format of custom rules setup for the blob storage account.



Using this you can easily update blob storage tiers automatically.

## How to Enable / Disable Automated Access Tier Change Rules in Azure Blob Storage

When we create any rules for the blob storage account, We can choose the status as **Enabled** or **Disabled**. However, at a later point in time, if you want to enable or disable the rule sets, you can select the particular rules from **List View**, and Choose **Enable / Disable** option from the toolbar.




Lifecycle management view supports two windows, **List View** and **Code View**. You can update the status of the rules from the **Code View** as well.

Microsoft Azure

Search resources, services, and docs (G+ /)

Home >

 learnazurestorageajcs | Lifecycle Management

Storage account

Search (Ctrl+ /)

2

Save Discard Download Refresh Delete

Events

Storage Explorer (preview)

Settings

Access keys

Geo-replication

CORS

Configuration

Encryption

Shared access signature

Firewalls and virtual networks

Private endpoint connections

List view

Code view

```
1 {
2   "rules": [
3     {
4       "enabled": false,
5       "name": "Custom",
6       "type": "Lifecycle",
7       "definition": {
8         "actions": {
9           "baseBlob": {
10            "tierToCool": {
11              "daysAfterModificationGreaterThan": 40
12            },
13            "tierToArchive": {
14              "daysAfterModificationGreaterThan": 100
15            }
16          }
17        }
18      }
19    }
20  ]
21 }
```