## Reverse Level Order

```
#include <stdio.h>
#include <stdlib.h>
#define MAX 500
struct node
{
       int data;
       struct node *left;
       struct node *right;
};
struct node *newNode(int data)
       struct node *temp = (struct node *)malloc(sizeof(struct node));
       temp->data = data;
       temp->left = temp->right = NULL;
       return temp;
}
struct node **createQueue(int *front, int *rear)
       struct node **queue = (struct node **)malloc(sizeof(struct node *)*MAX);
       *front = *rear = 0;
       return queue;
}
void enqueue(struct node **queue, int *rear, struct node *newNode)
       queue[(*rear)++] = newNode;
}
struct node *dequeue(struct node **queue, int *front)
{
       return queue[(*front)++];
}
int isQueueEmpty(int *rear, int *front)
{
       return ((*rear) == (*front));
struct node **createStack(int *top)
       struct node **stack = (struct node **)malloc(sizeof(struct node *)*MAX);
       *top = -1;
       return stack;
}
void push(struct node **stack, struct node *node, int *top)
       stack[++(*top)] = node;
```

```
}
struct node *pop(struct node **stack, int *top)
       return stack[(*top)--];
}
int isStackEmpty(int *top)
{
       return (*top == -1);
}
void printReverseLevelOrder(struct node *root)
       int front, rear, top;
       if(root)
              struct node **queue = createQueue(&front, &rear);
              struct node **stack = createStack(&top);
              struct node *temp;
              enqueue(queue, &rear, root);
              while(!isQueueEmpty(&rear, &front))
                      temp = dequeue(queue, &front);
                     push(stack, temp, &top);
                     if(temp->right)
                             enqueue(queue, &rear, temp->right);
                     if(temp->left)
                             enqueue(queue, &rear, temp->left);
              while(!isStackEmpty(&top))
              {
                      temp = pop(stack, &top);
                      printf("%d\t", temp->data);
              }
       }
}
int main()
{
       struct node *root=NULL;
       root = newNode(10);
       root->left = newNode(20);
       root->right = newNode(30);
       root->left->left = newNode(40);
       root->right->left = newNode(50);
       root->right->right = newNode(60);
       printReverseLevelOrder(root);
       return 0;
}
Time complexity: O(n)
```

Space complexity is O(n)