--Summary of Numeric Functions:

- **ABS(): Absolute value of a number.**
- **CEIL(): Round up.**
- **FLOOR(): Round down.**
- **ROUND(): Round to a specific number of digits.**
- **MOD(): Modulo operation.**
- **POW()/POWER(): Exponentiation.**
- **SQRT(): Square root.**
- **LN(): Natural logarithm.**
- **LOG(): Logarithm to a specific base.**
- **EXP(): Exponential function.**
- **RADIANS(): Convert degrees to radians.**
- **DEGREES(): Convert radians to degrees.**
- **SIGN(): Returns the sign of a number.**
- **RAND(): Generate a random number.**
- **GREATEST(): Find the maximum value.**
- **LEAST(): Find the minimum value.**
- **PI(): Return the value of Pi.**
- **TRUNCATE() Truncate decimal places (no rounding)**
- **ROUND(x, d, mode) Round with control over mode**
- **LOG2() Log base 2**
- **LOG10() Log base 10**
- **BIT_COUNT() Count set bits in binary**
- **CONV() Convert between number bases**
- **HEX() Convert to hexadecimal**
- **OCT() Convert to octal**
- **BIN() Convert to binary**

1. ABS() - Absolute Value

Description: Returns the absolute value of a number (removes the sign).

```
SELECT ABS(-100) AS absolute_value;
```

Output:

```
+----------------+
| absolute_value |
+----------------+
| 100            |
+----------------+
```

---

2. CEIL() or CEILING() - Round Up

Description: Rounds a number up to the nearest integer.

```
SELECT CEIL(12.34) AS rounded_up;
```

Output:

```
+------------+
| rounded_up |
+------------+
| 13         |
+------------+
```

---

3. FLOOR() - Round Down

Description: Rounds a number down to the nearest integer.

```
SELECT FLOOR(12.34) AS rounded_down;
```

Output:

```
+--------------+
| rounded_down |
+--------------+
| 12           |
+--------------+
```

---

4. ROUND() - Round to a Specific Number of Digits

Description: Rounds a number to a specified number of decimal places.

```
SELECT ROUND(12.3456, 2) AS rounded_value;
```

Output:

```
+--------------+
| rounded_value|
+--------------+
| 12.35        |
+--------------+
```

---

5. MOD() - Modulo (Remainder of Division)

Description: Returns the remainder of the division of two numbers.

```
SELECT MOD(17, 5) AS remainder;
```

Output:

+-----------+

| remainder |

+-----------+

| 2 |

+-----------+

---

6. POW() or POWER() - Exponentiation

Description: Returns the value of a number raised to the power of another number.

```
SELECT POW(2, 3) AS power_value;
```

Output:

+-------------+

| power_value |

+-------------+

| 8 |

+-------------+

---

7. SQRT() - Square Root

Description: Returns the square root of a number.

```
SELECT SQRT(16) AS square_root;
```

Output:

+-------------+

| square_root |

+-------------+

| 4 |

+-------------+

---

8. LN() - Natural Logarithm

Description: Returns the natural logarithm (base e) of a number.

```
SELECT LN(10) AS natural_log;
```

Output:

```
+-------------+
| natural_log |
+-------------+
| 2.302585    |
+-------------+
```

---

9. LOG() - Logarithm

Description: Returns the logarithm of a number to a specified base.

```
SELECT LOG(10, 100) AS log_value;
```

Output:

```
+-----------+
| log_value |
+-----------+
| 2         |
+-----------+
```

---

10. EXP() - Exponential

Description: Returns the value of e (Euler's number) raised to the power of the specified number.

```
SELECT EXP(1) AS exponential_value;
```

Output:

```
+------------------+
| exponential_value |
+------------------+
| 2.718282         |
+------------------+
```

---

11. RADIANS() - Convert Degrees to Radians

Description: Converts degrees to radians.

```
SELECT RADIANS(180) AS radians_value;
```

Output:

```
+---------------+
| radians_value |
+---------------+
| 3.141593      |
+---------------+
```

---

12. DEGREES() - Convert Radians to Degrees

Description: Converts radians to degrees.

SELECT DEGREES(PI()) AS degrees_value;

Output:

```
+---------------+
| degrees_value |
+---------------+
| 180           |
+---------------+
```

---

13. SIGN() - Sign of a Number

Description: Returns the sign of a number:

- **1 for positive numbers**
- **0 for zero**
- **-1 for negative numbers**

SELECT SIGN(-25) AS sign_value;

Output:

```
+------------+
| sign_value |
+------------+
| -1         |
+------------+
```

---

14. RAND() - Generate a Random Number

Description: Returns a random floating-point number between 0 and 1.

```
SELECT RAND() AS random_value;
```

Output:

```
+--------------+
| random_value |
+--------------+
| 0.538953     |
+--------------+
```

To generate a random number within a specific range:

```
SELECT FLOOR(RAND() * (100 - 1 + 1) + 1) AS random_in_range;
```

Output:

```
+------------------+
| random_in_range  |
+------------------+
| 47               |
+------------------+
```

---

15. GREATEST() - Find the Maximum Value

Description: Returns the largest value from a list of expressions.

```
SELECT GREATEST(5, 10, 15, 20) AS GREATEST_value;
```

Output:

```
+----------------+
```

| greatest_value |

+----------------+

| 20 |

+----------------+

---

16. LEAST() - Find the Minimum Value

Description: Returns the smallest value from a list of expressions.

```
SELECT LEAST(5, 10, 15, 20) AS least_value;
```

Output:

+--------------+

| least_value |

+--------------+

| 5 |

+--------------+

---

17. PI() - Returns the Value of Pi

Description: Returns the constant value of π (pi).

```
SELECT PI() AS pi_value;
```

Output:

+-----------+

| pi_value |

+-----------+

| 3.141593 |

+-----------+

18. TRUNCATE() – Truncate Decimal Places

Description: Truncates a number to a specified number of decimal places without rounding.

SELECT TRUNCATE(12.3456, 2) AS truncated_value;

Output:

+----------------+

| truncated_value|

+----------------+

| 12.34 |

+----------------+

19. ROUND(X, D [, mode]) – Round with Optional Mode

Description: Rounds a number X to D decimal places. If mode is set to 1, it truncates away from zero instead of rounding.

Output:

+----------------+

| rounded_custom |

+----------------+

| -1.5 |

+----------------+

20. LOG2() – Logarithm Base 2

Description: Returns the base-2 logarithm of a number.

SELECT LOG2(8) AS log2_value;

Output:

```
+-------------+
| log2_value  |
+-------------+
| 3           |
+-------------+
```

21. LOG10() – Logarithm Base 10

Description: Returns the base-10 logarithm of a number.

```
SELECT LOG10(1000) AS log10_value;
```

Output:

```
+--------------+
| log10_value  |
+--------------+
| 3            |
+--------------+
```

22. BIT_COUNT() – Count of Set Bits

Description: Returns the number of bits that are set (i.e., 1s) in the binary representation of a number.

```
SELECT BIT_COUNT(7) AS set_bits_count;
```

Output:

```
+-----------------+
| set_bits_count  |
+-----------------+
```

| 3 |

+-----------------+

Because 7 in binary is 111 → 3 bits are set.

23. CONV(N, from_base, to_base) – Convert Number Between Bases

Description: Converts a number N from one base to another (between 2 and 36).

SELECT CONV('A', 16, 10) AS base10_value;

Output:

+--------------+

| base10_value |

+--------------+

| 10 |

+--------------+

24. HEX() – Convert to Hexadecimal

Description: Returns the hexadecimal value of a decimal number.

SELECT HEX(255) AS hex_value;

Output:

+-----------+

| hex_value |

+-----------+

| FF |

+-----------+

25. OCT() – Convert to Octal

Description: Returns the octal (base 8) representation of a number.

```
SELECT OCT(64) AS octal_value;
```

Output:

```
+-------------+
| octal_value |
+-------------+
| 100         |
+-------------+
```

26. BIN() – Convert to Binary

Description: Converts a decimal number to its binary representation.

```
SELECT BIN(10) AS binary_value;
```

Output:

```
+--------------+
| binary_value |
+--------------+
| 1010         |
+--------------+
```

```
CREATE TABLE employee(
        emp_id INT PRIMARY KEY,
        emp_name VARCHAR(50),
        age INT,
        department VARCHAR(30),
```

```
    salary DECIMAL(10,2),
    bonus DECIMAL(10,2),
    experience DECIMAL(5,2),
    performance_score DECIMAL(6,2)
);

INSERT INTO employee VALUES
(101,'Rahul',25,'IT',35000.75,2500.50,2.5,85.45),
(102,'Anjali',30,'HR',42000.80,3200.75,5.8,91.65),
(103,'Ramesh',27,'Sales',38000.60,2100.90,3.2,74.55),
(104,'Priya',35,'Finance',55000.90,5000.25,8.7,95.80),
(105,'Arjun',29,'IT',46000.50,3500.60,4.6,82.45),
(106,'Sneha',24,'HR',32000.20,1800.40,1.8,69.85),
(107,'Kiran',32,'Sales',50000.90,4200.30,6.5,88.90),
(108,'Deepika',28,'Finance',41000.75,3000.50,4.2,79.65),
(109,'Mahesh',40,'IT',68000.40,6500.75,12.5,97.20),
(110,'Divya',26,'HR',36000.85,2400.25,2.9,76.40);
```

SQL STRING FUNCTIONS

MySQL String Functions with Description

Function	Description
CONCAT()	**Concatenates (joins) two or more strings into a single string without any separator unless specified.**
CONCAT_WS()	**Concatenates multiple strings using a specified separator (WS = With Separator).**

UPPER()	**Converts all characters in a string to uppercase. (UCASE() is an alias.)**
LOWER()	**Converts all characters in a string to lowercase. (LCASE() is an alias.)**
SUBSTRING()	**Extracts a specified number of characters from a string starting at a given position. (SUBSTR() is an alias.)**
LEFT()	**Returns the specified number of characters from the beginning (left side) of a string.**
RIGHT()	**Returns the specified number of characters from the end (right side) of a string.**
LENGTH()	**Returns the length of a string in bytes. For multi-byte characters, the byte count may be greater than the character count.**
CHAR_LENGTH()	**Returns the number of characters in a string, regardless of how many bytes each character occupies.**
REPLACE()	**Replaces all occurrences of a specified substring within a string with another substring.**
TRIM()	**Removes leading and trailing spaces (or specified characters) from a string.**
POSITION()	**Returns the position of the first occurrence of a substring within a string. Returns 0 if the substring is not found.**
INSTR()	**Returns the position of the first occurrence of a substring within a string. Similar to POSITION(), but uses a different syntax.**
REVERSE()	**Reverses the order of characters in a string.**
LPAD()	**Pads the left side of a string with a specified character until the string reaches the desired length.**
RPAD()	**Pads the right side of a string with a specified character until the string reaches the desired length.**

ASCII() **Returns the ASCII value of the first character in a string.**

Table Setup

A single employees table is reused for every question in this workbook — from basic single-function calls through advanced multi-function reports.

```
CREATE TABLE employees (
        emp_id INT PRIMARY KEY,
        first_name VARCHAR(30),
        last_name VARCHAR(30),
        email VARCHAR(60),
        phone_number VARCHAR(20),
        department VARCHAR(30),
        city VARCHAR(30),
        salary DECIMAL(10,2)
);
```

Sample Data

```
INSERT INTO employees VALUES
(101,'Rahul','Kumar','rahul.kumar@gmail.com','987-654-3210','IT','Hyderabad',45000),
(102,'Anita','Sharma','anita.sharma@yahoo.com','912-345-6789','HR','Bangalore',38000),
(103,'Suresh','Verma','suresh.verma@gmail.com','998-123-4567','Sales','Chennai',52000),
(104,'Priya','Singh','priya.singh@outlook.com','900-456-7890','Finance','Pune',47000),
(105,'Rahul','Joshi','rahul.joshi@gmail.com','955-888-1111','Testing','Delhi',41000),
(106,'Kiran','Reddy','kiran.reddy@gmail.com','901-222-3333','IT','Hyderabad',56000),
(107,'Deepika','Naidu','deepika.naidu@yahoo.com','944-111-2222','HR','Vizag',39000),
```

```
(108,'Mahesh','Patel','mahesh.patel@gmail.com','933-444-
5555','Sales','Mumbai',62000),

(109,'Divya','Gupta','divya.gupta@gmail.com','955-777-8888','Finance','Delhi',49000),

(110,'Arjun','Rao','arjun.rao@gmail.com','988-999-
7777','Developer','Hyderabad',68000);
```

Basic Level

20 Questions — one string function at a time

Q1. Display full name by concatenating first_name and last_name.

```
SELECT CONCAT(first_name, ' ', last_name) AS full_name
FROM employees;
```

Q2. Convert first_name to uppercase.

```
SELECT first_name, UPPER(first_name) AS upper_name
FROM employees;
```

Q3. Convert last_name to lowercase.

```
SELECT last_name, LOWER(last_name) AS lower_name
FROM employees;
```

Q4. Extract the first 10 characters of email.

```
SELECT email, SUBSTRING(email, 1, 10) AS email_prefix
FROM employees;
```

Q5. Find the length of first_name.

```
SELECT first_name, LENGTH(first_name) AS name_length
FROM employees;
```

Q6. Remove dashes from phone_number.

```
SELECT phone_number, REPLACE(phone_number, '-', '') AS clean_phone
FROM employees;
```

Q7. Remove leading and trailing spaces from first_name.

```
SELECT TRIM(first_name) AS trimmed_name
FROM employees;
```

Q8. Concatenate first_name, last_name and email separated by a comma.SELECT CONCAT_WS(‘)

```
SELECT CONCAT_WS(', ', first_name, last_name, email) AS employee_info
FROM employees;
```

Q9. Find the position of the letter 'a' in first_name using POSITION().

```
SELECT first_name, POSITION('a' IN first_name) AS position_of_a
FROM employeeSELECT FIRST_NAME,INSTR
```

Q10. Find the position of the letter 'a' in first_name using INSTR().

```
SELECT first_name, INSTR(first_name, 'a') AS position_of_a
FROM employees;
```

Q11. Display the first 3 characters of first_name.

```
SELECT first_name, LEFT(first_name, 3) AS short_name
FROM employees;
```

Q12. Display the last 3 characters of last_name.

```
SELECT last_name, RIGHT(last_name, 3) AS end_letters
FROM employees;
```

Q13. Reverse the first_name.

```
SELECT first_name, REVERSE(first_name) AS reversed_name
FROM employees;
```

Q14. Pad first_name on the left with '*' to make it 10 characters.

```
SELECT first_name, LPAD(first_name, 10, '*') AS padded_name
FROM employees;
```

Q15. Pad first_name on the right with '-' to make it 10 characters.

```
SELECT first_name, RPAD(first_name, 10, '-') AS padded_name
FROM employees;
```

Q16. Find the ASCII value of the first character of first_name.

```
SELECT first_name, ASCII(first_name) AS ascii_value
FROM employees;
```

Q17. Find the character length of first_name.

```
SELECT first_name, CHAR_LENGTH(first_name) AS char_len
FROM employees;
```

Q18. Convert email addresses to lowercase.

```
SELECT email, LOWER(email) AS lower_email
FROM employees;
```

Q19. Convert department names to uppercase.

```
SELECT department, UPPER(department) AS upper_department
FROM employees;
```

Q20. Remove leading spaces and trailing spaces from city using LTRIM() and RTRIM().

```
SELECT city, LTRIM(city) AS left_trimmed, RTRIM(city) AS right_trimmed
FROM employees;
```

SQL DATE & TIME FUNCTIONS

CURDATE(): Current date.

CURTIME(): Current time.

NOW(): Current date and time.

DATE(): Extract date part.

TIME(): Extract time part.

YEAR(): Extract year.

MONTH(): Extract month.

DAY()/DAYOFMONTH(): Extract day of the month.

WEEK(): Extract week number.

DAYOFWEEK(): Extract day of the week.

DATE_ADD(): Add time to a date.

DATE_SUB(): Subtract time from a date.

DATEDIFF(): Difference between two dates.

TIMESTAMPDIFF(): Difference between two DATETIME values.

STR_TO_DATE(): Convert string to date.

DATE_FORMAT(): Format a date.

FROM_UNIXTIME(): Convert Unix timestamp to date.

UNIX_TIMESTAMP(): Convert date to Unix timestamp.

1. CURDATE() - Current Date

Description: Returns the current date in YYYY-MM-DD format (no time).

```
SELECT CURDATE() AS current__date;
```

Output:

```
+-------------+
| current_date|
+-------------+
```

| 2024-11-28 |

+------------+

---

2. CURTIME() - Current Time

Description: Returns the current time in HH:MM:SS format (no date).

SELECT CURTIME() AS current_time;

Output:

+--------------+

| current_time |

+--------------+

| 14:32:45 |

+--------------+

---

3. NOW() - Current Date and Time

Description: Returns the current date and time in YYYY-MM-DD HH:MM:SS format.

SELECT NOW() AS current_datetime;

Output:

+---------------------+

| current_datetime |

+---------------------+

| 2024-11-28 14:32:45 |

+---------------------+

---

4. DATE() - Extract Date Part

Description: Extracts the date part from a DATETIME or TIMESTAMP value.

```
SELECT DATE('2024-11-28 14:32:45') AS extracted_date;
```

Output:

```
+----------------+
| extracted_date |
+----------------+
| 2024-11-28     |
+----------------+
```

---

5. TIME() - Extract Time Part

Description: Extracts the time part from a DATETIME or TIMESTAMP value.

```
SELECT TIME('2024-11-28 14:32:45') AS extracted_time;
```

Output:

```
+-----------------+
| extracted_time  |
+-----------------+
| 14:32:45        |
+-----------------+
```

---

6. YEAR() - Extract Year

Description: Returns the year part from a DATE, DATETIME, or TIMESTAMP value.

```
SELECT YEAR('2024-11-28') AS year_part;
```

Output:

```
+-----------+
| year_part |
+-----------+
| 2024      |
+-----------+
```

---

7. MONTH() - Extract Month

Description: Returns the month part (1–12) from a DATE, DATETIME, or TIMESTAMP value.

```
SELECT MONTH('2024-11-28') AS month_part;
```

Output:

```
+------------+
| month_part |
+------------+
| 11         |
+------------+
```

---

8. DAY() or DAYOFMONTH() - Extract Day of the Month

Description: Returns the day of the month (1–31) from a DATE, DATETIME, or TIMESTAMP value.

```
SELECT DAY('2024-11-28') AS day_part;
```

Output:

```
+-----------+
| day_part  |
+-----------+
| 28        |
+-----------+
```

DAY

---

9. WEEK() - Extract Week Number

Description: Returns the week number of the year (1–53) from a DATE, DATETIME, or TIMESTAMP value.

```
SELECT WEEK('2024-11-28') AS week_number;
```

Output:

```
+--------------+
| week_number  |
+--------------+
| 48           |
+--------------+
```

---

10. DAYOFWEEK() - Day of the Week

Description: Returns the day of the week as an integer (1 for Sunday, 2 for Monday, ..., 7 for Saturday).

```
SELECT DAYOFWEEK('2024-11-28') AS day_of_week;
```

Output:

+-------------+

| day_of_week |

+-------------+

| 5 |

+-------------+

---

11. DATE_ADD() - Add Time to a Date

Description: Adds a specified time interval to a date or time.

```
SELECT DATE_ADD('2024-11-28', INTERVAL 10 DAY) AS new_date;
```

Output:

diff

Copy code

+------------+

| new_date |

+------------+

| 2024-12-08 |

+------------+

---

12. DATE_SUB() - Subtract Time from a Date

Description: Subtracts a specified time interval from a date or time.

```
SELECT DATE_SUB('2024-11-28', INTERVAL 10 DAY) AS new_date;
```

Output:

+------------+

| new_date |

+------------+

| 2024-11-18 |

+------------+

---

13. DATEDIFF() - Difference Between Two Dates

Description: Returns the number of days between two dates.

```
SELECT DATEDIFF('2024-11-28', '2024-11-18') AS days_diff;
```

Output:

+-----------+

| days_diff |

+-----------+

| 10 |

+-----------+

---

14. TIMESTAMPDIFF() - Difference Between Two Date/Time Values

Description: Returns the difference between two date or time values in the specified unit (e.g., seconds, minutes, hours, etc.).

```
SELECT TIMESTAMPDIFF(DAY, '2024-11-18', '2024-11-28') AS days_difference;
```

Output:

+------------------+

| days_difference |

+------------------+

| 10 |

+------------------+

---

15. STR_TO_DATE() - Convert String to Date

Description: Converts a string to a DATE, DATETIME, or TIMESTAMP using a specified format.

```
SELECT STR_TO_DATE('2024-11-28', '%Y-%m-%d') AS formatted_date;
```

Output:

```
+----------------+
| formatted_date |
+----------------+
| 2024-11-28     |
+----------------+
```

---

16. DATE_FORMAT() - Format a Date

Description: Formats a DATE, DATETIME, or TIMESTAMP value into a string according to a specified format.

```
SELECT DATE_FORMAT('2024-11-28', '%W, %M %d, %Y') AS formatted_date;
```

Output:

```
+------------------------+
| formatted_date         |
+------------------------+
| Thursday, November 28, 2024 |
+------------------------+
```

---

17. FROM_UNIXTIME() - Convert Unix Timestamp to Date

Description: Converts a Unix timestamp to a DATETIME value.

SELECT FROM_UNIXTIME(1609459200) AS datetime_value;

Output:

+---------------------+

| datetime_value |

+---------------------+

| 2021-01-01 00:00:00 |

+---------------------+

---

18. UNIX_TIMESTAMP() - Convert Date to Unix Timestamp

Description: Converts a DATETIME or DATE value to a Unix timestamp.

SELECT UNIX_TIMESTAMP('2024-11-28 14:32:45') AS unix_timestamp;

Output:

+------------------+

| unix_timestamp |

+------------------+

| 1638111165 |

+------------------+

—----------

----

19. LAST_DAY() – Last Day of the Month

Description: Returns the last day of the month for a given date.

SELECT LAST_DAY('2024-11-28') AS last_day_of_month;

Output:

+------------------+

| last_day_of_month |

+------------------+

| 2024-11-30 |

+------------------+

---

20. MAKEDATE() – Create a Date from Year and Day Number

Description: Returns a date from a given year and day number (1–366).

SELECT MAKEDATE(2024, 60) AS result_date;

Output:

+-------------+

| result_date |

+-------------+

| 2024-02-29 |

+-------------+

---

21. MAKETIME() – Create Time from Hour, Minute, Second

Description: Returns a time value from hour, minute, and second.

SELECT MAKETIME(14, 30, 15) AS result_time;

Output:

+-------------+

| result_time |

+-------------+

| 14:30:15 |

+-------------+

---

22. MONTHNAME() – Full Name of the Month

Description: Returns the name of the month from a date.

SELECT MONTHNAME('2024-11-28') AS month_name;

Output:

+-------------+

| month_name |

+-------------+

| November |

+-------------+

---

23. DAYNAME() – Name of the Day

Description: Returns the name of the weekday.

SELECT DAYNAME('2024-11-28') AS day_name;

Output:

+-----------+

| day_name |

+-----------+

| Thursday |

+-----------+

---

24. QUARTER() – Quarter of the Year

Description: Returns the quarter (1 to 4) of the year for a date.

SELECT QUARTER('2024-11-28') AS quarter_value;

Output:

```
+---------------+
| quarter_value |
+---------------+
| 4             |
+---------------+
```

---

25. EXTRACT() – Extract Specific Part of Date

Description: Returns part of a date (e.g., YEAR, MONTH, DAY, etc.).

SELECT EXTRACT(WEEK FROM '2024-11-28') AS week_value;

Output:

```
+-------------+
| week_value  |
+-------------+
| 48          |
+-------------+
```

You can extract:

- YEAR

- MONTH
- DAY
- WEEK
- HOUR
- MINUTE
- SECOND
- QUARTER
- etc.

---

26. ADDDATE() – Same as DATE_ADD()

Description: Synonym for DATE_ADD(). Adds days or intervals.

SELECT ADDDATE('2024-11-28', INTERVAL 5 DAY) AS new_date;

Output:

+------------+

| new_date |

+------------+

| 2024-12-03 |

+------------+

---

27. SUBDATE() – Same as DATE_SUB()

Description: Synonym for DATE_SUB(). Subtracts days or intervals.

SELECT SUBDATE('2024-11-28', INTERVAL 5 DAY) AS new_date;

Output:

+------------+

| new_date |

+------------+

| 2024-11-23 |

+------------+

---

28. SEC_TO_TIME() – Convert Seconds to Time

Description: Converts an integer number of seconds to HH:MM:SS format.

SELECT SEC_TO_TIME(3661) AS time_value;

Output:

+-------------+

| time_value |

+-------------+

| 01:01:01 |

+-------------+

---

29. TIME_TO_SEC() – Convert Time to Seconds

Description: Converts a time value into seconds.

```
SELECT TIME_TO_SEC('01:01:01') AS total_seconds;
```

Output:

```
+----------------+
| total_seconds  |
+----------------+
| 3661           |
+----------------+
```

---

30. SYSDATE() – Current Date and Time (Execution Time)

Description: Returns the exact time at the moment the query executes (unlike NOW() which may be cached).

```
SELECT SYSDATE() AS system_time;
```

Output:

```
+---------------------+
| system_time         |
+---------------------+
| 2024-11-28 14:35:50 |
+---------------------+
```