Paired Exact-Reset Evaluation of a Prediction-Derived Medium-to-Full World-Model Cascade

Malo de Pastor
Télécom SudParis, Institut Polytechnique de Paris, France
depastorm@gmail.com ORCID: 0009-0009-1913-0052

arXiv:submit/7880342 [cs.LG] 30 Jul 2026

Abstract

Existing adaptive-inference methods and recent world-action-model systems already use cheap-stage outputs, intermediate states, or predicted futures to allocate additional computation. We study a narrower evaluation question: under paired exact-reset physical outcomes, can a Medium-derived interface predict when switching to a separately frozen Full predictor improves task-specific decision loss enough to offset sequential overhead? Our contribution is a paired evaluation and audit protocol, rather than a new generic routing rule: every candidate action is executed from the same reset state, Medium and Full induce decisions over the same candidate set and downstream task, and their paired physical-loss difference supplies the post-hoc routing target. On an initial fresh PushT audit bank (V106; 1,600 states, 39 tasks, three frozen checkpoint pairs), a frozen prediction-interface router lowers overhead-inclusive decision cost relative to standalone Medium by 0.00431, standalone Full by 0.00258, and a latency-advantaged task-only router by 0.00262. We then use V106 only for development and prospectively seal a second 1,600-state PushT confirmation (V107) against a stronger current-state alternative: an input router using the task and a dimension-matched projection of current DINO features plus all five candidate actions, with no DINO encoder latency charged. The prediction interface lowers priced physical decision cost by 0.002549 (state-clustered 95% interval $[-0.002867, -0.002238]$; one-sided 95% upper bound -0.002286), and all three fixed checkpoint-pair effects are negative. A controlled-PyBullet audit (12,000 states, 81 tasks, six regimes, three checkpoint pairs) independently supports a composite task–prediction–regime router against fixed, margin, and matched-random policies; a post-audit repair preserves shared-state pairing without changing point estimates. The sequential router remains slower than fixed policies, and its fixed-policy advantage is restricted to low compute prices. The evidence supports incremental routing information in the tested aligned prediction interface beyond one deliberately favoured current-DINO control; it does not establish imagined-future causal sufficiency, compute saving, a new adaptive-routing theory, closed-loop value, or cross-family generality.

1 Introduction

Predictive models are useful because their outputs mediate decisions. World models make this relationship unusually concrete: for a current observation and candidate action, the model exposes an imagined consequence that a controller may score before acting. A natural response to difficult queries is to spend more computation—use a larger predictor, draw more rollouts, or run more denoising or planning steps. Yet "more predictive compute" is not an ordered intervention. A higher-capacity model can improve average predictive error while changing the ordering of the few actions that matter, and the benefit can reverse across states and tasks.

Several concurrent systems already establish prediction- or intermediate-state-conditioned world-model computation. Gated geometric Best-of-N uses an initial action and predicted visual future to decide whether to draw additional rollouts; SANTS learns where to stop video denoising from intermediate video states; adaptive action execution uses prediction–reality consistency to determine when another world-action-model pass is required; and adaptive-depth latent world models route predictor depth during planning [13, 14, 17, 22]. Generic adaptive neural cascades, post-hoc deferral, and paid second-stage acquisition likewise learn whether the conditional improvement of later computation exceeds its cost [3, 5, 8, 10]. Accordingly, our novelty claim does not concern the use of predicted futures for adaptive computation; it concerns the paired physical estimand and frozen evaluation protocol used to compare separately trained predictive capacities. We ask:

> *Under paired exact-reset physical outcomes, can a Medium-derived interface predict when switching to a separately frozen Full predictor improves task-specific decision loss enough to offset sequential overhead?*

We isolate this question through information interfaces. A prediction-interface router observes the downstream loss specification and Medium's predicted consequence, but no true future, oracle regret, Full prediction, or privileged




Figure 1: The deployed policy sees only the task and Medium's predicted consequence. Exact physical outcomes supervise and evaluate the router offline, but are unavailable at routing time.

simulator state. Exact resets let us evaluate Medium, Full, and all candidate actions on the same physical queries, making the realized escalation benefit observable offline. At test time the policy is sequential: evaluate Medium, form its downstream action, and decide whether to pay for Full. A task-only control is allowed to route before Medium is run, so it is latency-advantaged rather than an artificially weakened sequential baseline. Because that V106 control routes to Full on 99.1% of audit rows, we subsequently conduct a stronger prospective test. V107 freezes the prediction router and a dimension-matched input router that receives the task, the current DINO representation, and every candidate action. The current-DINO control is deliberately favoured: its representation is treated as already available, its routing decision precedes Medium, and no encoder latency is charged. Only after the comparison, thresholds, projection, bootstrap, and fresh-state manifest are sealed do we generate a second 1,600-state exact-reset bank.

The distinction between *decision value* and *compute saving* is central. We account for Medium, Full, task evaluation, and router overhead in the objective. The learned router reduces physical regret enough to beat both fixed policies after pricing these latencies, but it remains slower in raw milliseconds. This result is useful—it identifies a learnable selective benefit—while ruling out a stronger deployment claim.

Our contributions are:

1. A candidate-complete paired exact-reset protocol for measuring task-specific physical decision losses of separately frozen Medium and Full predictors on identical state–task–action queries.
2. A deployment-cost ledger that instantiates standard adaptive-cascade and value-of-information theory while explicitly comparing the Medium-first sequence with standalone Full.
3. Frozen PushT and controlled-PyBullet audits, including a prospectively sealed second PushT bank against a latency-favoured, action-conditioned current-DINO control, state-clustered inference, compute-price sensitivity, and released paper-facing records.

2 Decision ledger for Medium-to-Full escalation

2.1 Queries and observable decision loss

Work on a probability space supporting a physical query $Q = (X, T, \mathcal{A})$: current observation X, downstream task T, and finite candidate action set $\mathcal{A}$. All population statements below are conditional on a known frozen Medium/Full checkpoint pair r, with its associated router, threshold, and latency constants; we suppress r in the notation. Equivalently, when averaging the finite three-checkpoint design, the checkpoint-pair index is included in every compared information field, and the reported risk is the prespecified equally weighted average of the three checkpoint-specific risks. A frozen model $m \in \{M, F\}$ predicts $\widehat{Y}_m(Q, a)$ and selects

$$A_m(Q) \in \arg\min_{a \in \mathcal{A}} \ell_T(\widehat{Y}_m(Q, a)),$$

using a fixed tie rule. Exact reset exposes $Y(Q, a)$ for every candidate. We use candidate-set physical regret

$$L_m(Q) = \ell_T(Y(Q, A_m)) - \min_{a \in \mathcal{A}} \ell_T(Y(Q, a)).$$

Thus L_M and L_F are observed on the same query; no claim is made about actions outside $\mathcal{A}$ or real-robot causal effects. Pairing is source-enforced for every candidate: PushT resets to the recorded seeded base state before each

rollout, and PyBullet restores a saved simulator state. Deterministic duplicate replay is additionally checked on three states per PushT shard and one candidate per checked state; this is sampled validation, not an exhaustive replay test over all states and actions. Model action ties use the frozen deterministic tie rule. V106 router scores are replayed as NumPy float32 and escalate only under the strict comparison score > threshold; the V104D/V104E audit environment pins the serialization runtime and records archived escalation-mask checksums.

2.2 Sequential and standalone costs

Let $s_{\mathcal{G}}(Q)$ be the always-paid latency for running Medium and exposing interface $\mathcal{G}$, and let $d_F(Q)$ be the additional latency of evaluating and scoring Full after Medium. The general notation also permits query-dependent standalone latencies $c_M(Q)$ and $c_F(Q)$. In the executed analyses these latencies are frozen constants within checkpoint pair and latency summary, so expectations average them only across the prespecified checkpoint weights. Assume the relevant losses and costs are integrable. At compute price $\lambda \geq 0$, define realized net escalation benefit

$$B = L_M - L_F - \lambda d_F. \tag{1}$$

Positive B means escalation reduces the priced decision objective.

A sequential interface $\mathcal{G}$ is the sigma-field available after Medium. For example,

$$\mathcal{G}_0 = \sigma(T, R), \qquad \mathcal{G}_1 = \sigma(T, R, S_M),$$

where T is the downstream task, R denotes any information held fixed between the interfaces (such as a prespecified regime descriptor), and S_M is Medium's predicted physical consequence. A $\mathcal{G}$-measurable binary policy π has sequential cost

$$C_{\mathcal{G}}(\pi) = L_M + \lambda s_{\mathcal{G}} - \pi B. \tag{2}$$

Define $b_{\mathcal{G}} = \mathbb{E}[B \mid \mathcal{G}]$.

Proposition 1 (Standard Bayes escalation rule and available value)**.** *An optimal $\mathcal{G}$-measurable rule is*

$$\pi^\star_{\mathcal{G}} = \mathbf{1}\{b_{\mathcal{G}} > 0\},$$

up to ties. Its expected cost is

$$\mathbb{E}[C_{\mathcal{G}}(\pi^\star_{\mathcal{G}})] = \mathbb{E}[L_M + \lambda s_{\mathcal{G}}] - V(\mathcal{G}), \qquad V(\mathcal{G}) := \mathbb{E}[(b_{\mathcal{G}})_+].$$

Thus $V(\mathcal{G})$ is the improvement available from conditional escalation after the incremental Full cost has been priced, but before comparing the always-paid sequential latency to a standalone policy.

Proposition 2 (Sequential-to-standalone accounting identity)**.** *Let c_M and c_F be the measured standalone latencies of Fixed Medium and Fixed Full, and define the signed sequential-to-standalone Full latency gap $\kappa_{\mathcal{G}} = s_{\mathcal{G}} + d_F - c_F$. In the evaluated protocols this gap is positive, so it is a duplication penalty; the identity itself does not require nonnegativity. The Bayes sequential router's expected gains over the standalone policies are*

$$\mathbb{E}[C^{\text{fix}}_M - C_{\mathcal{G}}(\pi^\star_{\mathcal{G}})] = V(\mathcal{G}) - \lambda \mathbb{E}[s_{\mathcal{G}} - c_M], \tag{3}$$

$$\mathbb{E}[C^{\text{fix}}_F - C_{\mathcal{G}}(\pi^\star_{\mathcal{G}})] = \mathbb{E}[(-b_{\mathcal{G}})_+] - \lambda \mathbb{E}[\kappa_{\mathcal{G}}], \tag{4}$$

where $C^{\text{fix}}_m = L_m + \lambda c_m$.

Equation (4) prevents a common accounting error. The negative-part term is the value of not escalating on unfavorable queries, but standalone Full avoids the Medium pass entirely. A sequential router beats Fixed Full only when its optionality exceeds the priced signed latency gap. In both evaluated protocols $\kappa_{\mathcal{G}} > 0$, so the gap is a duplication penalty; our routers overcome it at the frozen price despite higher raw latency.

2.3 Value of the predicted consequence

Suppose $\mathcal{G}_0 = \sigma(T, R) \subseteq \mathcal{G}_1 = \sigma(T, R, S_M)$, so that the only added source is Medium's predicted consequence.

Theorem 1 (Nested-interface Jensen identity)**.** *Define*

$$\mathrm{PIV}(\mathcal{G}_1;\mathcal{G}_0) := V(\mathcal{G}_1) - V(\mathcal{G}_0).$$

Then

$$\mathrm{PIV}(\mathcal{G}_1;\mathcal{G}_0) = \mathbb{E}\big[(\mathbb{E}[B \mid \mathcal{G}_1])_+ - (\mathbb{E}[B \mid \mathcal{G}_0])_+\big] \geq 0. \tag{5}$$

Writing $U = \mathbb{E}[B \mid \mathcal{G}_1]$, the gap is strictly positive exactly when a positive-probability set of coarse outcomes has both $\mathbb{E}[U_+ \mid \mathcal{G}_0] > 0$ and $\mathbb{E}[(-U)_+ \mid \mathcal{G}_0] > 0$. For a common incremental Full cost, the net deployment value of replacing $\mathcal{G}_0$ by $\mathcal{G}_1$ is

$$\mathrm{PIV}(\mathcal{G}_1;\mathcal{G}_0) - \lambda\mathbb{E}[s_{\mathcal{G}_1} - s_{\mathcal{G}_0}].$$

The theorem is a population information statement, not a guarantee that an arbitrary finite-sample learner will exploit the interface. Moreover, our sealed PushT task-only control routes before Medium and is therefore latency-advantaged. It is a strict deployment comparator under frozen function classes and data, not a plug-in estimator of Eq. (5).

2.4 Finite-sample selection

Conditional on all development data, validation choices, fitted parameters, and algorithmic randomness, let $\widehat{b}$ be a $\mathcal{G}$-measurable score and let $\widehat{\pi} = \mathbf{1}\{\widehat{b} > 0\}$. Any executed strict threshold rule $\mathbf{1}\{s > \tau\}$ has this form by taking $\widehat{b} = s - \tau$. Assume $\mathbb{E}|b_{\mathcal{G}}| < \infty$; for the finite upper bound below also assume $\mathbb{E}|\widehat{b} - b_{\mathcal{G}}| < \infty$.

Proposition 3 (Standard plug-in sign-regret identity)**.** *For a fixed interface,*

$$\mathbb{E}[C_{\mathcal{G}}(\widehat{\pi})] - \mathbb{E}[C_{\mathcal{G}}(\pi^\star_{\mathcal{G}})] = \mathbb{E}\big[|b_{\mathcal{G}}|\,\mathbf{1}\{\widehat{\pi} \neq \pi^\star_{\mathcal{G}}\}\big] \leq \mathbb{E}[|\widehat{b} - b_{\mathcal{G}}|]. \tag{6}$$

This weighted sign identity explains why noisy individual benefit prediction can still improve aggregate decisions: errors matter only when they cross zero, and their decision penalty is the true conditional margin.

Corollary 1 (Learned-policy deployment decomposition)**.** *Let*

$$\mathcal{R}_{\mathcal{G}}(\widehat{\pi}) := \mathbb{E}\big[|b_{\mathcal{G}}|\mathbf{1}\{\widehat{\pi} \neq \pi^\star_{\mathcal{G}}\}\big]\,.$$

The learned router's gains over standalone Medium and Full equal, respectively,

$$V(\mathcal{G}) - \lambda\mathbb{E}[s_{\mathcal{G}} - c_M] - \mathcal{R}_{\mathcal{G}}(\widehat{\pi}), \tag{7}$$

$$\mathbb{E}[(-b_{\mathcal{G}})_+] - \lambda\mathbb{E}[\kappa_{\mathcal{G}}] - \mathcal{R}_{\mathcal{G}}(\widehat{\pi}). \tag{8}$$

Equations (7)–(8) separate the three ways a sequential method can fail: insufficient conditional optionality, excess acquisition/duplication cost, or imperfect selection from the available interface.

Corollary 2 (Margin corollary)**.** *If $A < \infty$, $\alpha \geq 0$, $\varepsilon \geq 0$, $\mathbb{P}(|b_{\mathcal{G}}| \leq t) \leq At^\alpha$ for all $t > 0$, and $|\widehat{b} - b_{\mathcal{G}}| \leq \varepsilon$ almost surely, then the excess cost in Eq. (6) is at most $A\varepsilon^{\alpha+1}$.*

Proposition 4 (Scalar-ordering obstruction)**.** *Let Z be a real-valued $\mathcal{G}$-measurable score and let the high-score threshold policy be $\pi_\tau = \mathbf{1}\{Z > \tau\}$. Suppose there are $\mathcal{G}$-measurable sets A_+ and A_- with positive probability and a $\gamma > 0$ such that*

$$b_{\mathcal{G}} \geq \gamma \text{ on } A_+, \qquad b_{\mathcal{G}} \leq -\gamma \text{ on } A_-,$$

while

$$\operatorname*{ess\,sup}_{A_+} Z < \operatorname*{ess\,inf}_{A_-} Z.$$

Then every high-score threshold has Bayes excess cost at least

$$\gamma \min\{\mathbb{P}(A_+), \mathbb{P}(A_-)\}.$$

Thus "escalate when difficulty is high" requires a single-crossing relationship between the score and conditional benefit. A score that ranks a negative-benefit region above a positive-benefit region has irreducible threshold regret. The matched Medium-margin baseline probes this issue empirically, but its failure alone does not verify the proposition's setwise assumptions.

Table 1: Theory-to-evidence map. The algebra organizes the experiment; the new evidence lies in paired protocols and frozen audit comparisons.

Object	Status	Empirical role
Bayes escalation/value	Standard, adapted	Defines the priced escalation target and oracle.
Nested-interface Jensen gap	Standard value of information	Defines population prediction-interface value.
Standalone-Full decomposition	Protocol-specific identity	Separates optionality from the signed sequential-to-standalone Full latency gap.
Plug-in sign regret	Standard, adapted	Explains why noisy benefit scores can still select usefully.
Finite-audit observability	Protocol-specific formalization	A complete executed record makes candidate-level costs computable; the compact release recomputes paper-facing statistics.
Frozen audit policy gains	New empirical evidence	Tested in V104E, V106, and the prospective V107 current-DINO/action confirmation.

Proposition 5 (Fixed-rate rearrangement lemma)**.** *Fix $q \in [0,1]$ and allow a $\mathcal{G}$-measurable routing propensity $g : \Omega \to [0,1]$ with $\mathbb{E}[g] = q$. On an enlarged probability space carrying an independent $U \sim \mathrm{Unif}(0,1)$, the realized binary action $\pi = \mathbf{1}\{U \le g\}$ is measurable with respect to $\mathcal{G} \vee \sigma(U)$ and satisfies $\mathbb{E}[\pi \mid \mathcal{G}] = g$. Among these propensities, an optimizer is*

$$g^\star = \mathbf{1}\{b_{\mathcal{G}} > t\} + \rho\, \mathbf{1}\{b_{\mathcal{G}} = t\},$$

where t and $\rho \in [0,1]$ are chosen so that $\mathbb{E}[g^\star] = q$; the endpoint cases $q = 0$ and $q = 1$ are constant propensities. This upper-tail rule maximizes $\mathbb{E}[b_{\mathcal{G}} g]$. Its advantage over independent rate-q routing is

$$\mathbb{E}[b_{\mathcal{G}} g^\star] - q\mathbb{E}[B] \ge 0.$$

For $0 < q < 1$, the inequality is strict if and only if $b_{\mathcal{G}}$ is not almost surely constant.

This isolates selection from escalation count. Our random controls are input-routing controls and hence avoid Medium on Full-routed queries; their lower latency makes the empirical comparison conservative rather than an exact evaluation of Proposition 5.

3 Paired physical routing

3.1 Common protocol

For every current physical state, we construct the same candidate action set for Medium and Full. Exact resets provide a paired record

$$\big\{S_M(Q,a), S_F(Q,a), Y(Q,a)\big\}_{a \in \mathcal{A}},$$

where S_m is a predicted consequence and Y the realized physical consequence. Each downstream task maps predicted consequences to candidate scores, selects an action, and evaluates its physical regret using Y. Because Medium and Full are observed on the same query and action set, their realized loss difference is paired rather than confounded by state sampling.

Proposition 6 (Finite-record recomputability and target-law observation)**.** *Suppose a complete executed audit record contains every candidate physical outcome, all frozen model decisions and policy inputs, and all randomness needed to replay stochastic components. Then the realized cost of any frozen policy and every paired candidate-minus-reference difference are measurable functions of that record; their finite-audit empirical means are exactly computable. The public compact release provides the weaker property needed for the reported audit: it contains policy-facing per-state/per-task arrays sufficient to recompute every paper-facing statistic, but not every candidate physical outcome or upstream prediction from first principles.*

A target-population claim requires a separate sampling model. Let physical-state clusters be sampled from a declared law or known sampling design, and let task, bank, and checkpoint-pair weights be fixed in advance. The resulting target mean is a functional of the observable cluster law. Primary confidence statements are model-based over physical-state clusters: conditional on the fixed tasks, bank weights, and three frozen checkpoint pairs, generated states within each declared simulator-state generator or bank are treated as iid draws from that law. The fixed audit

mean is exactly known without this assumption; its confidence interpretation depends on it, and the chosen reset seeds are not a randomized-treatment design. Under iid cluster sampling, or a design-valid analogue, and finite second moments, the sample mean is consistent and admits standard mean asymptotics. Bootstrap confidence statements require additional validity conditions and a resampling scheme that preserves every clustered and crossed factor. Treating checkpoint pairs as random additionally requires a declared checkpoint-generating population; three fixed checkpoints alone define only a finite equally weighted checkpoint estimand.

This separates deterministic recomputability from population inference. Neither property turns the finite candidate-set simulator intervention into an unrestricted robotics or real-world causal-generalization result.

For checkpoint pair r, the executed V106 router regresses the paired gross regret difference $\Delta_r = L_{M,r} - L_{F,r}$. Because measured incremental Full latency is constant across queries within that checkpoint pair, $d_{F,r}(Q) = d_{F,r}$, the Bayes net-benefit score satisfies $\mathbb{E}[B_r \mid \mathcal{G}_r] = \mathbb{E}[\Delta_r \mid \mathcal{G}_r] - \lambda d_{F,r}$. Thus an exactly calibrated gross conditional-mean score could be converted to the Bayes net rule by thresholding at $\lambda d_{F,r}$. The executed fitted score is not assumed perfectly calibrated: for each checkpoint pair, interface, and compute price, a strict threshold is selected from a validation grid consisting of the two constant endpoints and 101 empirical score quantiles. This is a frozen threshold-policy implementation, not an estimate of the Bayes net-benefit function. If incremental Full latency varies by query, the Bayes rule depends on $\mathbb{E}[\Delta_r - \lambda d_{F,r} \mid \mathcal{G}_r] = \mathbb{E}[\Delta_r \mid \mathcal{G}_r] - \lambda \mathbb{E}[d_{F,r} \mid \mathcal{G}_r]$. A constant threshold on a gross-benefit score is Bayes-equivalent only when $\mathbb{E}[d_{F,r} \mid \mathcal{G}_r]$ is constant within the deployed checkpoint pair, or when its conditional variation is already absorbed into the score. Observing realized latency at routing time is sufficient but not necessary. The recovered V104D source uses the same gross target, fits routers only on training rows, and selects strict thresholds only on validation rows. V104E applies the frozen V104D router and thresholds without refitting on confirmation outcomes. Both routers use a two-hidden-layer MLP (128 and 64 ReLU units). The PushT candidate uses the task description and Medium's calibrated predicted consequence. The PyBullet candidate additionally uses a prespecified regime descriptor. Neither uses the explicit simulator state, true future, realized losses, oracle action, Full prediction, or correctness labels.

At audit time, Medium is always evaluated. The router observes its frozen interface and either retains Medium's action or evaluates Full and uses Full's action. The reported objective is

$$\text{decision regret} + \lambda \times \text{measured latency (ms)},$$

with $\lambda = 0.002$. Candidate-minus-reference differences are negative when the candidate is better. Sequential latency follows $s_{\mathcal{G}} + \pi d_F$: a Full escalation adds a complete Full prediction/decision pass to the already-paid Medium interface.

3.2 Prospective prediction-versus-current-DINO confirmation

The initial V106 audit is development data for the stronger V107 control; none of its rows are reused as confirmatory evidence. Before any V107 physical outcome is generated, we seal one primary comparison:

$$C_{\text{prediction}} - C_{\text{DINO+actions}}.$$

Both interfaces use the same checkpoint-pair-specific `StandardScaler+MLPRegressor` family and regress the paired gross Medium-minus-Full physical regret difference. The prediction interface has 22 task features plus the complete 43-dimensional Medium-derived consequence interface. The control has the same 22 task features plus a 43-dimensional projection of the current 64-D DINO representation concatenated with the five candidate actions. Its scaler and PCA are fit only on V106 training states. Thus both have 65 input dimensions, while the control receives direct action information and routes before Medium. We treat its current DINO representation as already available and charge no DINO encoder latency.

The six serialized direct-gross routers, checkpoint-specific thresholds, float32 score semantics, latency ledger, projection, 39 tasks, five actions, three checkpoint pairs, 1,600 fresh reset seeds, and audit code are hashed in the confirmation manifest before generation. Thresholds are selected only on V106 validation states. V107 uses two new 800-state shards and no fitting, threshold selection, debugging, or scientific design change may use their outcomes. The single primary gate averages tasks and the three fixed checkpoint-pair effects within physical state, resamples 1,600 states for 20,000 bootstrap repetitions, and passes only if the aggregate point and one-sided 95% upper bound are negative and every checkpoint-pair point is negative. Secondary price and fixed-policy displays cannot rescue or redefine this gate.

Table 2: The frozen audits share the routing question. V107 is a second prospective PushT bank against a stronger current-DINO/action control; PyBullet covers a different physical mechanism. The predictors remain related DINO-style families rather than distinct world-model paradigms.

Evaluation	States	Tasks	Model seeds	Primary references
PushT V106 (initial fresh bank)	1,600	39	3	5
PushT V107 (prospective control)	1,600	39	3	1
PyBullet V104E (6 regimes)	12,000	81	3	4

3.3 References and inference

The primary references are:

- **Fixed Medium** and **Fixed Full**;
- a **task-only input router** in PushT, with the same MLP family but no state- or prediction-dependent signal;
- a cheaper **Medium-margin sequential router** at the candidate's escalation rate;
- **matched random input routing**, preserving the candidate rate (and exact seedwise counts in PushT).

We cluster paired inference at physical state and average tasks within state. V107 has one primary comparison and uses the prospective gate in Section 3.2; its ordinary 95% interval and one-sided 95% upper bound are conditional on the fixed tasks and checkpoint pairs. V106 averages the three fixed seed effects for each shared state before resampling 1,600 states. Its post-audit crossed seed sensitivity resamples three seed positions and one common physical-state index vector shared across all sampled seed positions; it remains secondary and does not establish population coverage over training randomness. The originally executed V104E bootstrap resampled different state-index vectors inside sampled seed–bank cells and therefore failed to preserve the crossed physical-state pairing. After external audit, we repaired only the uncertainty calculation: the primary analysis averages the three frozen seed effects within each of 12,000 physical states, resamples states within each of six fixed equally weighted banks, and uses 10,000 percentile replicates. A crossed sensitivity resamples model seeds and one common state-index vector per bank, shared across sampled seeds. Point estimates, policies, outcomes, and the four-reference family are unchanged. Bonferroni-adjusted percentile-bootstrap upper quantiles are 0.99 for V106 and 0.9875 for V104E; every corrected primary and crossed-sensitivity upper bound remains below zero. These are approximate bootstrap statements conditional on the fixed tasks, banks, checkpoints, and cluster-sampling interpretation, not exact finite-sample family-wise guarantees. Random input policies and the PushT task-only policy avoid duplicated Medium computation, so the candidate must overcome their latency advantage.

4 Frozen audit evaluations

PushT. We generate ten exact-reset shards from the public PushT simulator. Shards 0–7 supply 5,200 training and 1,200 validation states; shards 8–9 are a sealed audit set of 1,600 fresh states and are never opened during router or threshold selection. Each query has five candidate actions and horizon 30. The task family crosses 13 block-displacement targets with balanced, position-weighted, and orientation-weighted losses (39 tasks). Medium and Full are frozen residual MLP predictors over a 64-D PCA of pooled DINOv2 ViT-S/14 features. Medium has two 256-wide GELU layers (99,392 parameters); Full has three 512-wide layers (592,448 parameters). Both were trained with AdamW on 4,950 action-conditioned rows, selected on 900 validation rows, and then passed through capacity-specific ridge physical calibrators fit on 180 states (900 action rows). The 65-D router interface is task plus Medium's calibrated block-pose consequence. It is trained on $5{,}200 \times 39$ query–task rows; the threshold is selected only from the $1{,}200 \times 39$ validation rows. The primary family contains five comparisons and 20,000 state-clustered bootstrap repetitions. An additional 5,000-draw exact-count random-input benchmark preserves every seed's realized escalation count; it is descriptive and is not part of the inferential family.

V107 is a second, non-overlapping PushT confirmation generated only after its fresh-state manifest and primary comparison are sealed. It contains two new 800-state shards, with the same 39 tasks, five candidates, horizon, and three frozen checkpoint pairs. The prediction and current-DINO/action routers are the six direct-gross MLPs selected during development, then copied and hashed before V107 generation. The primary family contains exactly one comparison and 20,000 state-clustered bootstrap repetitions.

Controlled PyBullet. The frozen confirmation contains six 2,000-state banks: an ID replication and prespecified changes in horizon, velocity, obstacle count, and their composition. The 81-task family crosses nine spatial targets

Table 3: Frozen predictive computations and router interfaces. Parameter/MAC counts are available for the PushT MLPs; the archived PyBullet protocol records its Transformer dimensions.

Evaluation / capacity	Architecture	Parameters	MACs/candidate	Interface dim.
PushT Medium	MLP 256×2	99,392	98,816	65
PushT Full	MLP 512×3	592,448	590,848	—
PyBullet Medium	Transformer 192/4/2	—	—	59
PyBullet Full	Transformer 384/6/3	—	—	—




Figure 2: Empirical capacity reversals in the finite audits after averaging downstream tasks and the three frozen checkpoint effects within each unique physical state. Medium has lower decision cost on 51.9% of controlled PyBullet states and 45.1% of PushT states; Full wins on the complements. These realized reversals do not establish Blackwell incomparability or, by themselves, value available to the deployed interface.

with nine loss geometries, including anisotropic, diagonal, movement-regularized, and safety-penalized losses. Three frozen model seeds yield 36,000 crossed state–seed rows representing 12,000 unique physical states after tasks are averaged. The selected 59-dimensional task–prediction–regime interface and all thresholds were frozen from a prespecified development ablation and readiness audit before any confirmation outcome was opened. The primary estimand weights banks and model seeds equally; four comparisons and 10,000 bootstrap repetitions form the primary family. The predictors are residual token Transformers over pooled DINOv2 features: Medium uses width 192, four heads, and two layers; Full uses width 384, six heads, and three layers. Training uses AdamW for 100 epochs on 5,000 states, followed by frozen physical calibration on 1,000 states.

Latency protocol. All costs use one physical state, one downstream task, and five candidate actions as the decision unit. World-model forwards were measured on NVIDIA H100 GPUs. Task and router components were measured single-threaded on the associated HPC CPU nodes. PushT uses 200 warmups, seven rounds of 1,000 repeats, 512 sampled queries, and the median of round medians; p90 accounting is a sealed sensitivity. PyBullet freezes end-to-end component medians from its pre-confirmation readiness audit. Absolute latency portability is limited because the compact archive does not record the CPU SKU.

5 Results

5.1 Additional capacity has conditional decision value

Figure 2 shows that neither fixed capacity is a statewise oracle. After averaging the three frozen seed effects per unique state, Full wins on 48.1% of controlled-PyBullet states and 54.9% of PushT states. These reversals establish substantial realized state-level heterogeneity in the finite audit and a clairvoyant state-conditioned selection opportunity. They do not by themselves establish positive value for the declared routing interface; exploitability is assessed by the frozen router comparisons below.

5.2 A fresh current-DINO control confirms incremental prediction-interface value




Figure 3: Prospectively sealed V107 prediction-minus-current-DINO/action decision-cost effects at $\lambda = 0.002$. The aggregate first averages 39 tasks and three fixed checkpoint-pair effects within each of 1,600 fresh states; bars are state-clustered 95% bootstrap intervals. Checkpoint-pair rows are fixed-design diagnostics, not a population interval over training randomness. Negative values favour the prediction interface.

The V107 primary gate passes. On the second fresh exact-reset PushT bank, the prediction interface lowers priced physical decision cost relative to the dimension-matched current-DINO/action control by 0.002549, with state-clustered 95% interval $[-0.002867, -0.002238]$ and one-sided 95% upper bound -0.002286. The fixed checkpoint-pair effects are -0.002680, -0.002428, and -0.002540 for seeds 92002, 2026, and 314159; every checkpoint-specific 95% interval is also below zero. This is the one primary comparison declared before V107 outcomes, so no exploratory control or learner can replace the gate.

Table 4: V107 aggregate operating point at $\lambda = 0.002$, equally weighting the three fixed checkpoint pairs after averaging 39 tasks within each fresh state. The control is faster and receives current DINO for free, but the prediction interface reduces physical regret enough to lower priced cost by 7.9% relative to the control.

Policy	Regret	Latency (ms)	Decision cost	Escalation
Prediction interface	0.02849	0.664	0.02981	47.2%
Current-DINO + actions	0.03110	0.630	0.03236	66.2%
Prediction − control	-0.00262	+0.034	-0.00255	-19.0 pp

Table 4 isolates the mechanism of the priced gain. Prediction routing has mean regret 0.02849 versus 0.03110 for the control, while its mean latency is 0.664 ms versus 0.630 ms. The 0.002617 regret improvement therefore exceeds the 0.000068 priced latency disadvantage. Prediction routing also escalates less often, 47.2% versus 66.2%. Because the control receives the task, current DINO, and all candidate actions with matched dimension and favourable accounting, this result rules out the narrow explanation that the V106 gain is obtainable from this current-state/action interface alone. It does not prove that imagined futures are causally sufficient or superior to every possible current-state representation.

Earlier V106 prediction-withheld comparison. The initial fresh PushT interface test uses the task-only input router. At $\lambda = 0.002$, that comparator routes to Full on 100% of audit query–task rows for checkpoint pairs 2026 and 314159 and 97.4359% for checkpoint pair 92002, or 99.1453% under equal checkpoint weighting. It is therefore latency-advantaged but nearly a standalone-Full policy rather than a rich task-conditioned selector. Despite paying Medium before routing, the prediction interface lowers decision cost by 0.002620, with state-clustered 95% interval $[-0.003037, -0.002213]$. It also improves over the matched-rate margin policy by 0.003294 and expected matched random by 0.003591. Among 5,000 independently generated uniform matched-count input-routing policies per seed, none attained aggregate cost no larger than the candidate; the plus-one Monte Carlo benchmark tail fraction is




Figure 4: Priced decision-cost improvement at the prespecified $\lambda = 0.002$ for the nine original V106/PushT and V104E/PyBullet comparisons. The separate V107 primary comparison appears in Figure 3. PushT retains its frozen state-clustered intervals; PyBullet uses the repaired fixed-checkpoint state-clustered bootstrap. Negative values favor the router, and all environment-specific Bonferroni-adjusted percentile-bootstrap upper bounds are below zero.

$1/5001 \approx 0.00020$. Because the learned assignment was not randomized and no row-exchangeability null is assumed, this is descriptive rather than a hypothesis-test p-value.

Controlled PyBullet. Controlled PyBullet supports selective routing for the frozen prediction–task–regime interface, but does not independently isolate the prediction from the regime descriptor. Under repaired fixed-seed state-clustered inference, candidate-minus-margin is -0.002800 (95% interval $[-0.002902, -0.002698]$), and candidate-minus-random is -0.003668 ($[-0.003773, -0.003565]$). The paired crossed-seed robustness display gives wider 2.5%–97.5% empirical sensitivity quantiles $[-0.002953, -0.002642]$ and $[-0.004090, -0.003352]$, respectively; these are not confidence coverage for a broader checkpoint-generating population.

5.3 The original V106 and PyBullet primary families pass

Figure 4 summarizes all primary comparisons. On PushT, the candidate improves over Fixed Medium by 0.004308 ($[-0.004759, -0.003857]$) and Fixed Full by 0.002577 ($[-0.003001, -0.002159]$). On controlled PyBullet, the corresponding unchanged point improvements are 0.003677 and 0.003746, with repaired 95% intervals $[-0.003805, -0.003553]$ and $[-0.003880, -0.003613]$.

All three model seeds have favorable point estimates against Fixed Medium and matched random in each environment. Every PyBullet bank has a favorable point estimate against those two references, and no individual unadjusted 95% bankwise interval lies entirely above zero against either reference. Every PushT weight profile is favorable against both fixed references, with no profile interval entirely above zero. Under resampling from the empirical three-checkpoint distribution, the global PyBullet crossed-seed sensitivity has all four adjusted upper quantiles below zero. The corrected PushT crossed sensitivity likewise remains favorable for all five references, with 2.5%–97.5% empirical quantiles ranging from $[-0.004870, -0.003750]$ against Fixed Medium to $[-0.003218, -0.001891]$




Figure 5: The router is slower than both fixed policies. It buys a physical regret reduction, but its Medium-first interface overhead prevents raw latency dominance. The plotted "clairvoyant lower bound" uses realized audit outcomes and zero router overhead; it is not the Bayes interface oracle.

Table 5: Primary operating point at $\lambda = 0.002$. The router lowers regret and priced decision cost while increasing latency. Environment and seed weights follow the frozen estimands.

Evaluation	Policy	Regret	Latency (ms)	Decision cost	Escalation
PyBullet	Router	0.02309	1.320	0.02573	17.8%
PyBullet	Fixed Medium	0.02759	0.909	0.02941	0.0%
PyBullet	Fixed Full	0.02727	1.103	0.02948	100.0%
PushT	Router	0.02907	0.651	0.03037	42.0%
PushT	Fixed Medium	0.03411	0.281	0.03468	0.0%
PushT	Fixed Full	0.03222	0.364	0.03295	100.0%

against Fixed Full. These are robustness displays, not confidence intervals for a broader checkpoint-generating population.

5.4 Decision improvement is not compute saving

On PushT, the router's mean regret is 0.02907 versus 0.03411 for Medium and 0.03222 for Full, but latency is 0.651 ms versus 0.281 and 0.364 ms. It escalates 42.0% of query–task pairs. Its decision cost 0.03037 beats both fixed policies after pricing latency, yet a cheaper clairvoyant empirical lower bound that selects from realized audit outcomes reaches 0.02031. The difference mixes unavailable realized information, policy estimation error, and protocol-overhead differences; it is not an estimate of Bayes interface regret.

Controlled PyBullet shows the same boundary. Mean router regret is 0.02309 versus 0.02759 and 0.02727, while latency is 1.320 ms versus 0.909 and 1.103 ms; the escalation rate is 17.8%. These numbers rule out "compute saving," "latency dominance," and "near oracle" as interpretations of our results. The measured signed latency gaps relative to standalone Full are $\mathbb{E}[\kappa_{\mathcal{G}}] = 0.49785$ ms in PushT and 1.12352 ms in PyBullet, priced as 0.000996 and 0.002247 at $\lambda = 0.002$.




Figure 6: Declared PushT compute-price sensitivity, not a deployment Pareto frontier. Negative router-minus-reference values favor routing. Thresholds are selected on validation separately for each declared price. The router wins at $\lambda \leq 0.01$ but loses to every listed reference at 0.025 and 0.05.

Table 6: PushT candidate-minus-reference decision cost across the full declared compute-price grid. The primary frozen point is $\lambda = 0.002$; positive values at larger prices delimit rather than invalidate that operating-point result.

λ	vs. Medium	vs. Full	vs. task-only	vs. margin	vs. random
0.000	-0.0051	-0.0032	-0.0032	-0.0036	-0.0042
0.002	-0.0043	-0.0026	-0.0026	-0.0033	-0.0036
0.005	-0.0032	-0.0017	-0.0018	-0.0027	-0.0026
0.010	-0.0015	-0.0004	-0.0006	-0.0016	-0.0011
0.025	+0.0031	+0.0030	+0.0025	+0.0018	+0.0031
0.050	+0.0097	+0.0074	+0.0084	+0.0079	+0.0095

Figure 6 and Table 6 show that the result is not a continuous Pareto improvement. The candidate remains favorable through $\lambda = 0.01$, with a narrow -0.000385 difference versus Fixed Full at that price, but becomes worse than all fixed and routing references at $\lambda \in \{0.025, 0.05\}$. In the separate V107 fixed-threshold sensitivity, prediction remains below the current-DINO/action router throughout $\lambda \in \{0, 0.002, 0.005, 0.01, 0.025, 0.05\}$, but this does not imply high-price deployment value: both routing policies can be dominated by fixed policies as latency becomes expensive. Scientific replay uses the exact serialized threshold strings cast to NumPy float32 and a strict score $>$ threshold comparison. Across the task-only grid there are 17,600 score–threshold equalities. A non-scientific replay that reads those thresholds through the default pandas float parser and promotes scores to float64 changes 6,400 high-price decisions; the released all-grid audit, mask hashes, and regression test lock the scientific convention.

6 Related work

World models and predictive planning. DINO-WM predicts future DINOv2 patch features and plans zero-shot across navigation, manipulation, and multi-particle tasks [9, 23]. Our experiments likewise use frozen semantic visual features, but ask how the predicted consequence should inform selection between frozen computations rather than how to learn a planner. Decision-focused learning instead trains predictions for downstream optimization loss [18]; prediction-interface routing leaves the world models frozen and learns the conditional value of switching between them. ACID modifies the planning score with inverse-dynamics action consistency across several latent and video world models [12]; we instead leave each downstream scorer frozen and ask which predictive computation to evaluate.

Adaptive WAM inference. Several concurrent systems already establish prediction- or intermediate-state-conditioned computation. Gated geometric Best-of-N uses an initial action and predicted visual future to decide whether to draw additional world-action-model rollouts, includes a same-trigger-rate random diagnostic, and evaluates closed-loop task success across multiple backbones [22]. SANTS learns state-dependent stopping along a video denoising trajectory and reports closed-loop latency reductions [14]; adaptive action execution invokes another model pass when prediction and reality diverge [17]; and adaptive-depth latent world models expose help, hurt, and flat depth regimes during planning [13]. Fast-WAM questions whether explicit future generation is needed at inference, while AHA-WAM routes and reuses long-horizon world context asynchronously [4, 19]. These works establish the broad adaptive-compute premise. Our difference is not that premise but the combination of separate frozen capacities, paired exact-reset downstream losses, task-dependent decision evaluation, and duplication-aware comparison with standalone Full.

Adaptive cascades, deferral, and information value. Adaptive neural networks already learn continuation from a cheap stage signal using per-example cheap-versus-expensive losses and runtime [3]. Learning to defer and post-hoc deferral select between fixed experts from conditional risk differences [7, 8]; confidence-based cascade analysis characterizes when a cheap model's confidence is insufficient [5]; and consistent two-stage acquisition studies whether paid additional information is worth its cost [10]. Rational metareasoning studies computational actions [11], while conditional-risk calibration treats the required regression problem directly [16]. Our Bayes sign rule, positive-part value, weighted sign regret, and fixed-rate upper-tail result are standard or adapted specializations. We use them as an estimand and cost ledger; the distinctive evidence is the paired physical protocol and frozen audit comparison.

Calibration and statistical experiments. Decision calibration evaluates predictions through their induced decision losses [20, 21]. Blackwell comparison, Le Cam deficiency, and deficiency-based representation analysis provide general languages for informativeness [1, 2, 6, 15]. Our current experiments do not estimate a garbling kernel, deficiency, or a separating class of all decision problems; rescue and reversal events therefore motivate but do not establish statistical-experiment incomparability.

7 Limitations and conclusion

The action sets and downstream loss families are controlled, and none of the evaluations is a closed-loop robotics deployment. The predictors remain related DINO-style calibrated interfaces rather than genuinely different world-model families, and only three fixed checkpoint pairs are available. V107 answers one important alternative explanation prospectively: under its tested 65-dimensional interfaces, the aligned Medium prediction contains routing information not recovered by a task-, current-DINO-, and action-conditioned input router that is deliberately favoured

in latency. This does not establish prediction causality, sufficiency, or superiority to all current-state encodings, architectures, or compute-matched ensembles.

Full is not uniformly better, benefit prediction is imperfect, and the clairvoyant lower-bound gap remains substantial. Timing combines measured components on a specified H100-based stack but is not synchronized end-to-end deployment evidence; the sequential prediction router is slower than fixed policies. The original PushT fixed-policy sensitivity supports only a low-price operating region, not a continuous frontier. PyBullet validates a composite task–prediction–regime interface and does not independently isolate prediction from regime.

Within those boundaries, the evidence supports a sharper interface claim than the initial audit alone. Under paired exact-reset outcomes, the tested Medium-derived prediction interface supports useful post-hoc selection between two frozen predictors. It beats fixed and prediction-withheld references on the first fresh PushT bank, and on a second prospectively sealed bank it beats a dimension-matched, action-conditioned current-DINO router with no encoder latency charged. All three fixed checkpoint-pair effects are favourable, and the primary state-clustered gate passes. Controlled PyBullet supplies a second physical mechanism, with its conclusions surviving a transparent repair of the crossed-state bootstrap.

The contribution remains a paired physical evaluation and audit protocol, not a new generic routing theory. The study does not establish compute saving, closed-loop value, or generality across world-model families. The highest-value main-track extension is now a genuinely different stochastic or iterative world-model family with nested additional computation, closed-loop evaluation, and synchronized end-to-end timing.

A Proofs

A.1 Proof of the standard Bayes escalation result (Proposition 1)

Conditioning Eq. (2) on $\mathcal{G}$ gives

$$\mathbb{E}[C_{\mathcal{G}}(\pi) \mid \mathcal{G}] = \mathbb{E}[L_M + \lambda s_{\mathcal{G}} \mid \mathcal{G}] - \pi b_{\mathcal{G}}.$$

Since $\pi \in \{0, 1\}$, the pointwise minimizer escalates exactly when $b_{\mathcal{G}} > 0$. Substitution yields

$$\mathbb{E}[C_{\mathcal{G}}(\pi^\star_{\mathcal{G}}) \mid \mathcal{G}] = \mathbb{E}[L_M + \lambda s_{\mathcal{G}} \mid \mathcal{G}] - (b_{\mathcal{G}})_+ .$$

Taking expectations proves the claim.

A.2 Proof of the accounting identity (Proposition 2)

For Fixed Medium, subtract Proposition 1's cost:

$$\mathbb{E}[C^{\text{fix}}_M - C_{\mathcal{G}}(\pi^\star_{\mathcal{G}})] = \mathbb{E}[L_M + \lambda c_M - L_M - \lambda s_{\mathcal{G}}] + V(\mathcal{G}),$$

which is Eq. (3). Always escalating under the sequential protocol costs $L_F + \lambda(s_{\mathcal{G}} + d_F)$. Its excess over the Bayes router is

$$-\mathbb{E}[B] + V(\mathcal{G}) = -\mathbb{E}[b_{\mathcal{G}}] + \mathbb{E}[(b_{\mathcal{G}})_+] = \mathbb{E}[(-b_{\mathcal{G}})_+].$$

Standalone Full removes $\lambda\kappa_{\mathcal{G}}$ from that always-escalate cost, which gives Eq. (4).

A.3 Proof of the nested-interface Jensen identity (Theorem 1)

Nested conditioning gives

$$\mathbb{E}[b_{\mathcal{G}_1} \mid \mathcal{G}_0] = b_{\mathcal{G}_0}.$$

The positive-part map $z \mapsto z_+$ is convex, so conditional Jensen implies

$$(b_{\mathcal{G}_0})_+ \le \mathbb{E}[(b_{\mathcal{G}_1})_+ \mid \mathcal{G}_0].$$

Taking expectations proves nonnegativity. Let $U = b_{\mathcal{G}_1}$ and define $P_0 = \mathbb{E}[U_+ \mid \mathcal{G}_0]$ and $N_0 = \mathbb{E}[(-U)_+ \mid \mathcal{G}_0]$. Since $\mathbb{E}[U \mid \mathcal{G}_0] = P_0 - N_0$, the conditional Jensen gap is $P_0 - (P_0 - N_0)_+ = \min(P_0, N_0)$. Its expectation is positive exactly when a positive-probability set has both $P_0 > 0$ and $N_0 > 0$. Subtracting the interface-overhead terms gives the deployment comparison.

A.4 Proof of the standard sign-regret identity (Proposition 3)

Condition on $\mathcal{G}$. A correct sign choice matches the Bayes action and has zero excess cost. A sign mismatch forfeits exactly $|b_{\mathcal{G}}|$. Therefore the conditional excess is $|b_{\mathcal{G}}|\mathbf{1}\{\widehat{\pi} \neq \pi^\star_{\mathcal{G}}\}$. On a sign mismatch, zero lies between $\widehat{b}$ and $b_{\mathcal{G}}$, implying $|b_{\mathcal{G}}| \le |\widehat{b} - b_{\mathcal{G}}|$. Take expectations.

A.5 Proof of Corollary 1

Proposition 3 shows that replacing $\pi^\star_{\mathcal{G}}$ by $\widehat{\pi}$ increases expected sequential cost by exactly $\mathcal{R}_{\mathcal{G}}(\widehat{\pi})$. Subtracting this amount from each Bayes gain in Proposition 2 gives Eqs. (7)–(8).

A.6 Proof of Corollary 2

If $\varepsilon = 0$, sign disagreement can occur only where $b_{\mathcal{G}} = 0$, so the weighted excess cost is zero. Assume henceforth that $\varepsilon > 0$. A sign error implies $|b_{\mathcal{G}}| \le \varepsilon$. Hence the exact identity is at most

$$\mathbb{E}[|b_{\mathcal{G}}|\mathbf{1}\{|b_{\mathcal{G}}| \le \varepsilon\}] \le \varepsilon\mathbb{P}(|b_{\mathcal{G}}| \le \varepsilon) \le A\varepsilon^{\alpha+1}.$$

A.7 Proof of the scalar-ordering obstruction (Proposition 4)

Let $z_+ = \operatorname{ess\,sup}_{A_+} Z$ and $z_- = \operatorname{ess\,inf}_{A_-} Z$, so $z_+ < z_-$. If $\tau < z_-$, the threshold escalates almost surely on A_- and therefore disagrees with the Bayes rule there. If $\tau \ge z_-$, then $\tau > z_+$, so it does not escalate almost surely on A_+ and disagrees there. The exact identity in Proposition 3 therefore lower bounds the excess cost by $\gamma\mathbb{P}(A_-)$ in the first case and by $\gamma\mathbb{P}(A_+)$ in the second. Taking the smaller bound proves the claim.

A.8 Proof of the fixed-rate rearrangement lemma (Proposition 5)

The endpoint cases use $g^\star \equiv 0$ or $g^\star \equiv 1$. For $0 < q < 1$, choose t such that $\mathbb{P}(b_{\mathcal{G}} > t) \le q \le \mathbb{P}(b_{\mathcal{G}} \ge t)$ and choose $\rho \in [0,1]$ so that $g^\star = \mathbf{1}\{b_{\mathcal{G}} > t\} + \rho \mathbf{1}\{b_{\mathcal{G}} = t\}$ has $\mathbb{E}[g^\star] = q$. Conditional expectation gives $\mathbb{E}[gB] = \mathbb{E}[gb_{\mathcal{G}}]$. For any feasible g with $\mathbb{E}[g] = q$, we have $\mathbb{E}[g^\star - g] = 0$, and therefore

$$\mathbb{E}[b_{\mathcal{G}}(g^\star - g)] = \mathbb{E}[(b_{\mathcal{G}} - t)(g^\star - g)] \ge 0.$$

The integrand is nonnegative on $\{b_{\mathcal{G}} > t\}$ and $\{b_{\mathcal{G}} < t\}$, and zero on $\{b_{\mathcal{G}} = t\}$. Hence $g^\star$ maximizes $\mathbb{E}[b_{\mathcal{G}} g]$. Its advantage over independent rate-q routing is $\mathrm{Cov}(b_{\mathcal{G}}, g^\star) \ge 0$, with strict inequality for $0 < q < 1$ exactly when $b_{\mathcal{G}}$ is not almost surely constant. Independent uniform randomization realizes the propensity as a binary action on $\mathcal{G} \vee \sigma(U)$ without changing its conditional expectation.

A.9 Proof of the finite-record observation (Proposition 6)

Every frozen model decision and policy action is replayable from a complete executed record. Because every $Y(Q, a)$ is present there, both $L_M(Q)$ and $L_F(Q)$, hence $B(Q)$ and each realized policy cost, are deterministic functions of that record. Finite-audit means are therefore exactly computable. The public compact package does not claim to be this complete candidate-level record; it releases the policy-facing arrays needed to recompute the reported statistics. A declared target law and weighting rule separately define a population estimand; when the required costs are observable functionals of the cluster law, that law identifies the expectation. Sampling assumptions then justify consistency and asymptotics, while bootstrap coverage requires its own regularity conditions and a resampling scheme that preserves all clustered and crossed factors.

B Why latent distance is not a common currency

Proposition 7 (Measurable recoding observation)**.** *Let Z take values in a finite discrete subset $\{z_1, \dots, z_n\}$ of a standard-Borel space. For any distinct Euclidean target vectors $w_1, \dots, w_n$, define $T(z_i) = w_i$. Then T and its inverse on the image are measurable, $\sigma(T(Z)) = \sigma(Z)$, and every Bayes risk over unrestricted measurable decision rules is unchanged. Coordinate-dependent geometric statistics need not be preserved. The conclusion does not preserve a restricted neural class, sample complexity, regularization, optimization, continuity, or computational cost.*

Proof. The assignment $T(z_i) = w_i$ is one-to-one because the target vectors are distinct. On finite supports both T and its inverse are measurable, and each is a deterministic garbling of the other. They therefore generate the same sigma-field. Any decision rule based on one signal can be composed with the inverse to obtain a rule with identical loss under the other, so all Bayes risks agree. □

Applying model-specific recodings shows why a universal comparison across independently parameterized latent spaces cannot rest only on Euclidean norm, pairwise distance, cosine, or a similarly coordinate-dependent geometry. The statement is exact for finite supports and extends to bimeasurably equivalent signals. It is a representation caution, not a claim that our two models are Blackwell- or Le-Cam-incomparable: the proposition compares two recodings of one signal, whereas the experiments compare distinct predictive computations.

C Protocol details

C.1 Information restrictions

The PushT prediction candidate feature groups are the task and Medium's calibrated prediction. Explicit state, future state, current or future raw DINO latent, true loss, oracle action, Medium/Full realized regret, oracle benefit, Full prediction, correctness, coverage, and goal pose are forbidden to that candidate.

V107 adds one prespecified input-routing control. It receives the same task, the current 64-D DINO representation, and all five candidate actions, then compresses the non-task block to 43 dimensions using a scaler and PCA fit only on V106 training states. It receives no predicted future, Full prediction, true future, or realized loss. Treating current DINO as already available and routing before Medium deliberately favours the control.

The controlled-PyBullet candidate feature groups are task, predicted physical consequence, and prespecified regime. Its upstream ablation removed explicit simulator state. The PushT prediction candidate and PyBullet candidate route only after mandatory Medium computation; the V107 current-DINO/action control is the declared input-routing exception.

C.2 Sealing and statistical gates

V107 is sealed after the V106 audit has been used only as development data. Its protocol, two-shard fresh-state manifest, six router hashes, PCA projection, thresholds, latency components, float32 scoring implementation, single primary comparison, and bootstrap seed are fixed before any V107 physical outcome. Generation and inference verify the seal before execution; audit writes to a staging directory, verifies all lineage hashes, moves atomically, and repeats the postcheck. The primary gate requires a negative aggregate point, a negative one-sided 95% upper bound, and negative points for all three fixed checkpoint pairs.

V106 uses development shards 0–7 and audit-only shards 8–9. The router, thresholds, latency components, comparison family, bootstrap scheme, and matched-count benchmark generator were sealed before audit generation. Its global gate requires all five Bonferroni-adjusted percentile-bootstrap one-sided upper bounds below zero. Seed replication and weight-profile robustness are separate frozen criteria. The matched-count random-input benchmark is also reported as a prespecified descriptive criterion, but is not an inferential gate or part of the five-comparison family.

V104E is a fresh confirmation after the V104D interface ablation and V104D2 readiness audit. The frozen candidate may not use V104E labels for training, threshold, feature, or hyperparameter selection. Its global four-reference gate, seed replication, and six-bank robustness are jointly required.

C.3 Executed estimands and inference

For a candidate/reference pair, let D_{rit} denote candidate-minus-reference cost for model seed r, physical state i, and task t. V107 uses this statistic for prediction minus current-DINO/action with $(n, R, T) = (1600, 3, 39)$. It first averages tasks and the three fixed checkpoint effects within state, then resamples the 1,600 state effects for 20,000 bootstrap repetitions with seed 107031. Its one-sided upper quantile is 0.95 because there is one primary comparison. The two-sided interval is reported descriptively, and checkpoint-specific intervals are fixed-design diagnostics.

The original V106 PushT primary statistic is

$$\widehat{\Delta}_{\mathrm{PT}} = \frac{1}{n}\sum_{i=1}^{n}\frac{1}{R}\sum_{r=1}^{R}\frac{1}{T}\sum_{t=1}^{T} D_{rit}, \qquad (n, R, T) = (1600, 3, 39).$$

The primary bootstrap first forms the checkpoint- and task-averaged state effect and resamples its n physical states with replacement. Thus tasks sharing a state are never treated as independent, and the three checkpoint effects are fixed design replicates in this primary interval. The ordinary interval uses the 0.025 and 0.975 bootstrap quantiles; the one-sided five-comparison Bonferroni-adjusted percentile-bootstrap upper bound uses quantile $1 - 0.05/5 = 0.99$, with approximate simultaneous interpretation under the stated cluster-sampling model. A separate crossed sensitivity resamples checkpoint positions and one common physical-state index vector shared across all sampled positions; its 2.5%–97.5% values are empirical sensitivity quantiles for the observed three-checkpoint distribution, not population confidence intervals.

For PyBullet, write D_{brit} for bank b. Its unchanged point estimand is

$$\widehat{\Delta}_{\mathrm{PB}} = \frac{1}{BR}\sum_{b=1}^{B}\sum_{r=1}^{R}\frac{1}{n_b}\sum_{i=1}^{n_b}\frac{1}{T}\sum_{t=1}^{T} D_{brit}, \qquad (B, R, n_b, T) = (6, 3, 2000, 81).$$

The repaired primary first averages tasks and the three fixed checkpoint effects for each physical state, resamples the $n_b = 2000$ state clusters within each fixed bank, and then averages the six bank means. A crossed sensitivity resamples three checkpoint positions and, within each bank, one common state-index vector shared across all sampled positions. Both use 10,000 replicates; the four-comparison primary analysis uses a Bonferroni-adjusted one-sided percentile-bootstrap upper bound at quantile $1 - 0.05/4 = 0.9875$, with approximate simultaneous interpretation under the cluster-sampling model. Crossed outputs are labelled empirical sensitivity quantiles. The originally executed cellwise bootstrap is released for provenance but is not used for paper-facing uncertainty.

The PushT matched-count random-input benchmark samples, independently for each model seed, exactly as many query–task rows as the candidate escalated. With $R_{\mathrm{perm}} = 5000$ draws, the plus-one benchmark tail fraction is

$$\widehat{p}_{\mathrm{bench}} = \frac{1 + \#\{\text{random matched-count cost} \le \text{candidate cost}\}}{R_{\mathrm{perm}} + 1}.$$

This addresses selection beyond escalation count relative to the specified random-policy generator. It is descriptive rather than a design-based hypothesis-test p-value, and it is not the source of the state-clustered confidence intervals.

D Complete primary comparisons

D.1 Prospective V107 confirmation

Fixed design	$\widehat{\Delta C}$	95% interval	One-sided 95% upper
Aggregate	-0.002549	[-0.002867, -0.002238]	-0.002286
92002	-0.002680	[-0.003113, -0.002248]	-0.002313
2026	-0.002428	[-0.002962, -0.001896]	-0.001986
314159	-0.002540	[-0.003054, -0.002027]	-0.002110

D.2 Original V106 and V104E families

Intervals are state-clustered for both environments; PyBullet uses the repaired fixed-seed, bank-stratified physical-state bootstrap.

Environment	Reference	$\widehat{\Delta}C$	95% CI	Gate
PushT V107	Current-DINO + actions	-0.0025	[-0.0029, -0.0022]	Pass
PyBullet	Fixed Medium	-0.0037	[-0.0038, -0.0036]	Pass
PyBullet	Fixed Full	-0.0037	[-0.0039, -0.0036]	Pass
PyBullet	Margin sequential matched-rate	-0.0028	[-0.0029, -0.0027]	Pass
PyBullet	Random input matched-rate	-0.0037	[-0.0038, -0.0036]	Pass
PushT	Fixed Medium	-0.0043	[-0.0048, -0.0039]	Pass
PushT	Fixed Full	-0.0026	[-0.0030, -0.0022]	Pass
PushT	Task-only input router	-0.0026	[-0.0030, -0.0022]	Pass
PushT	Margin sequential matched-rate	-0.0033	[-0.0037, -0.0029]	Pass
PushT	Expected random input matched-rate	-0.0036	[-0.0039, -0.0033]	Pass

E V107 fixed-threshold price sensitivity

The V107 routers and thresholds remain frozen at their $\lambda = 0.002$ values. Negative values favour prediction over the current-DINO/action control; this comparison does not assert dominance over fixed policies.

λ	Prediction − control	95% interval
0.000	-0.002617	[-0.002934, -0.002306]
0.002	-0.002549	[-0.002867, -0.002238]
0.005	-0.002448	[-0.002765, -0.002136]
0.010	-0.002279	[-0.002598, -0.001967]
0.025	-0.001772	[-0.002094, -0.001456]
0.050	-0.000927	[-0.001258, -0.000601]

F Claim guardrails

Unsupported wording	Supported replacement
The router saves compute.	The router lowers a priced decision objective but is slower than both fixed policies.
Full is the better expert.	The value of Full is state- and task-dependent; both fixed capacities win on substantial subsets.
The models are Blackwell-incomparable.	Capacity ordering reverses empirically for the evaluated decision families.
The router is near oracle.	A substantial gap remains to the realized-loss clairvoyant lower bound, which uses unavailable audit outcomes and zero router overhead.
Prediction is universally superior to current state.	On one prospectively sealed PushT bank, the tested aligned prediction interface beats one dimension-matched current-DINO/action router.
The method generalizes to arbitrary world models.	Two controlled physical mechanisms and two fresh PushT banks support the claim under related calibrated DINO-style interfaces.
We establish a continuous frontier.	We report a frozen primary compute price and separately declared sensitivity points.

G Reproducibility and archival note

The public release candidate separates three layers:

1. exact hash-verified frozen sources used by the sealed runs;
2. compact sealed protocols, manifests, comparisons, and policy summaries;
3. a new reusable implementation of decision value, interface value, routing cost, clustered bootstrap, and lineage checks.

The reusable implementation was not retroactively substituted for the executed code. The release now includes the executed V104D and V104D2 scripts, reports, router checkpoints, thresholds, manifests, the V104E and V106 sealed result tars in their respective provenance directories, and the compact per-state arrays required to reconstruct all paper-facing statistics. A release-mode postcheck maps historical absolute source paths to their hash-matched package copies while preserving the original frozen postcheck for provenance.

The archive still does not include the heavy raw observations, all-candidate physical outcome tensors, DINO feature banks, upstream world-model checkpoints, or the original HPC environment needed to regenerate every rollout from first principles. Consequently, the statistics, frozen router lineage, and source semantics are independently auditable from the package, whereas full physical outcome regeneration remains an external-asset task. Hashes and self-authored seal records establish released-record consistency, not external timestamped certification of chronology. Candidate-action ties use NumPy's deterministic first-minimum `argmin` convention; the legacy V106 `tie_tolerance` configuration field is not used in action selection. These are archival disclosures, not scientific reruns.

References

[1] Pradeep Kr. Banerjee and Guido Montúfar. The variational deficiency bottleneck. *arXiv preprint arXiv:1810.11677*, 2018. URL https://arxiv.org/abs/1810.11677.

[2] David Blackwell. Equivalent comparisons of experiments. *The Annals of Mathematical Statistics*, 24(2):265–272, 1953.

[3] Tolga Bolukbasi, Joseph Wang, Ofer Dekel, and Venkatesh Saligrama. Adaptive neural networks for efficient inference. In *Proceedings of the 34th International Conference on Machine Learning*, volume 70, pages 527–536, 2017. URL https://proceedings.mlr.press/v70/bolukbasi17a.html.

[4] Jisong Cai, Long Ling, Shiwei Chu, Zhongshan Liu, Jiayue Kang, Zhixuan Liang, Wenjie Xu, Yinan Mao, Weinan Zhang, Xiaokang Yang, Ru Ying, Ran Zheng, and Yao Mu. AHA-WAM: Asynchronous horizon-adaptive world-action modeling with observation-guided context routing. *arXiv preprint arXiv:2606.09811*, 2026. URL https://arxiv.org/abs/2606.09811.

[5] Wittawat Jitkrittum, Neha Gupta, Aditya K. Menon, Harikrishna Narasimhan, Ankit Rawat, and Sanjiv Kumar. When does confidence-based cascade deferral suffice? In *Advances in Neural Information Processing Systems*, volume 36, 2023.

[6] Lucien Le Cam and Grace Lo Yang. *Asymptotics in Statistics: Some Basic Concepts*. Springer, 2 edition, 2000.

[7] Hussein Mozannar and David Sontag. Consistent estimators for learning to defer to an expert. In *Proceedings of the 37th International Conference on Machine Learning*, 2020.

[8] Harikrishna Narasimhan et al. Post-hoc estimators for learning to defer to an expert. In *Advances in Neural Information Processing Systems*, 2022.

[9] Maxime Oquab, Timothée Darcet, Théo Moutakanni, Huy Vo, Marc Szafraniec, Vasil Khalidov, Pierre Fernandez, Daniel Haziza, Francisco Massa, Alaa El-Nouby, et al. DINOv2: Learning robust visual features without supervision. *Transactions on Machine Learning Research*, 2024.

[10] Florence Regol, Joseph Cotnareanu, Theodore Glavas, and Mark Coates. Is the acquisition worth the cost? surrogate losses for consistent two-stage classifiers. In *Advances in Neural Information Processing Systems*, volume 38, 2025.

[11] Stuart Russell and Eric Wefald. *Do the Right Thing: Studies in Limited Rationality*. MIT Press, 1991.

[12] Gawon Seo, Dongwon Kim, and Suha Kwak. ACID: Action consistency via inverse dynamics for planning with world models. *arXiv preprint arXiv:2607.02403*, 2026. URL https://arxiv.org/abs/2607.02403.

[13] Achyuthan Sivasankar. Adaptive compute in latent world models: When depth helps, hurts, or doesn't matter. *arXiv preprint arXiv:2607.10203*, 2026. URL https://arxiv.org/abs/2607.10203.

[14] Yirui Sun, Guangyu Zhuge, Keliang Liu, Jie Gu, Xinyu Bing, Zhongxue Gan, and Chunxu Tian. SANTS: A state-adaptive scheduler for world action models. *arXiv preprint arXiv:2605.27947*, 2026. URL https://arxiv.org/abs/2605.27947.

[15] Brendan van Rooyen and Robert C. Williamson. Le cam meets lecun: Deficiency and generic feature learning. *arXiv preprint arXiv:1402.4884*, 2014. URL https://arxiv.org/abs/1402.4884.

[16] Andrey Vasilyev, Yikai Wang, Xiaocheng Li, and Guanting Chen. Calibrating conditional risk. *arXiv preprint arXiv:2604.20409*, 2026. URL https://arxiv.org/abs/2604.20409.

[17] Rui Wang, Yue Zhang, Jiehong Lin, Kuncheng Luo, Jianan Wang, Zhongrui Wang, and Xiaojuan Qi. When to trust imagination: Adaptive action execution for world action models. *arXiv preprint arXiv:2605.06222*, 2026. URL https://arxiv.org/abs/2605.06222.

[18] Bryan Wilder, Bistra Dilkina, and Milind Tambe. Melding the data-decisions pipeline: Decision-focused learning for combinatorial optimization. In *Proceedings of the AAAI Conference on Artificial Intelligence*, 2019.

[19] Tianyuan Yuan, Zibin Dong, Yicheng Liu, and Hang Zhao. Fast-WAM: Do world action models need test-time future imagination? *arXiv preprint arXiv:2603.16666*, 2026. URL https://arxiv.org/abs/2603.16666.

[20] Shengjia Zhao and Stefano Ermon. Right decisions from wrong predictions: A mechanism design alternative to individual calibration. In *Proceedings of the 24th International Conference on Artificial Intelligence and Statistics*, volume 130, pages 2683–2691, 2021.

[21] Shengjia Zhao, Michael Kim, Roshni Sahoo, Tengyu Ma, and Stefano Ermon. Calibrating predictions to decisions: A novel approach to multi-class calibration. In *Advances in Neural Information Processing Systems*, 2021.

[22] Zesen Zhao, Minkyoung Cho, Hui Shen, Boyuan Zheng, Kunxiao Gao, Yulong Cao, and Z. Morley Mao. Test-time scaling for world action models via zero-shot geometric verification. *arXiv preprint arXiv:2607.17454*, 2026. URL https://arxiv.org/abs/2607.17454.

[23] Gaoyue Zhou, Hengkai Pan, Yann LeCun, and Lerrel Pinto. DINO-WM: World models on pre-trained visual features enable zero-shot planning. In *Proceedings of the 42nd International Conference on Machine Learning*, volume 267 of *Proceedings of Machine Learning Research*, pages 79115–79135, 2025. URL https://proceedings.mlr.press/v267/zhou25t.html.