

## KEN washer disinfector IQ6

# Intelligent Quality

- The Future of Efficient Disinfection

- **Easy to use**
- **Easy to trust**
- **Easy to service**
- **Easy to choose**

KEN A/S has developed a new range of washer disinfectors that will facilitate the usage, liability and service of washer disinfectors for the CSSDs, utility rooms in hospitals and private clinics.

The IQ series is a modular built range that meets all relevant standards such as ISO 15883, UL to name a few.

The elegant design provides a smooth surface in tempered glass that is easy to clean. The IQ5 has downward sliding doors that allows for manual loading, or the use of a unique automatic loading that provides high flexibility and uses very little space.

The IQ is easy to operate by touch panel with swipe function, showing all relevant information of the program needed by the operators.

IQ5, the first washer in the series, has the lowest energy and water consumption in the market, this keeps operating costs at a minimum and contribute to a clean environment. The IQ6 is equally low in operating costs.

IQ6 comes with a 5 or 6 level trolley and can hold up to 18 DIN baskets.

All data from the IQ6 are fully exchangeable with common computer systems.



#### Advantages:

- Intuitive smart display PCTP
- Very low water consumption
- RFID technology
- Maintenance free sliding doors
- Robotic loading / unloading
- Service access from the front

#### Hygiene safety

- EN 62366 tested
- EN ISO 15883-1-2-5
- Glass surfaces easy to clean

#### Validation of all processes

- Open programs structure
- Full process validation
- Exchange of data
- Printer

#### Environment

- Low energy costs
- Low noise level
- Low chemical usage

Outer dimensions	H: 1985 x W: 820 x D: 1010 mm
Outer dimensions with condensor/turbo	H: 2370 x W: 820 x D: 1010 mm
Total chamber volume	443 L
Capacity on DIN baskets (480x250mm)	15 - 18 Pcs
Detergent and rinse aid dosage	2 pcs. standard + 2 optional
Water consumption per filling (5lev.)	22 liter
Programs	10 Standard + 30 optional
Proces times	Standard 30-40 min. Turbo 25-30 min.
Water connection	2 pcs. 3/4" RG (3x3/4" RG optional)
Cold water Pressure	200-800kPa, ≥15L/min, 5-30°, 0-30° dH
Hot water	200-800kPa, ≥15L/min, 30-70°, 0-3° dH
Demineralised water	200-800kPa, 15L/min 5-70° cond. 0-200µS
Steam heating	200-400 kPa
Power	Max 28kW, 63A
Ventilation	Ø100mm, 410m3 per hour



### Contact a **KEN** partner

KEN will gladly help you find the right solution.



Tel.: +45 62 63 10 91  
E-mail: ken@ken.dk  
Web: www.ken.dk

Malones Hospital Services Pty Ltd.  
24 Tathra Street West Gosford, 2250, NSW  
Phone: +61 (02) 4323 9731  
sales@malones.com.au - www.malones.com.au



**We make a difference - locally and globally**

KEN HYGIENE SYSTEMS A/S • Bøgebjergvej 60 • DK-5672 Broby •

Tel. +45 62 63 10 91 • Fax +45 62 63 16 07 • www.ken.dk