Product Description

VERTICAL
STEAM STERILIZER

UNICLAVE 99



Standard Version **Special Version**

Available Models

Model	***Usable Volume of Chamber*** *(l)*	***Usable Chamber dimensions*** *(cm)* *(diam. x depth)*	***Equipment dimensions*** *(cm)* *(width x height x depth)*
AJC 80	80	Ø40 x 63	69 x 105 x 74
AJC 120	120	Ø50 x 62	80 x 105 x 85
AJC 160	160	Ø50 x 82	80 x 125 x 85

The steam sterilizer **Uniclave 99**, manufactured by **A.J. Costa (Irmãos), Lda** is a vertical steam sterilizer specially directed for laboratory requirements, ideal to process small loads that demand a precise and strict control of different sterilization cycle parameters. Versatile, with fixed sterilization cycles and also enables the operator to choose the sterilization cycle parameters.

Applications

The steam sterilizer **Uniclave 99** sterilizes instruments, glassware, metallic utensils, liquids, rubbers and other thermo sensitive materials, filters, culture media, etc.

The steam sterilizer **Uniclave 99**, in order to fully correspond to laboratory or any other organization requirements can be equipped with an additional product temperature control probe, and with a printer.

General features

- The autoclave is controlled by a microprocessor. The entire operation is made on a touchscreen control panel;
- Simple operation interface;
- 4 pre-programmed cycles, with automatic operation and selection and introduction of parameters of the sterilization cycle
- Control panel
  - 3,5” colour touchscreen
  - On/Off button;
  - Emergency/Stop pushbutton
  - Steam manometer
- Sound alarm for fault and cycle end;
- Vertical load of the sterilization chamber;
- Easy maintenance;
- Chamber in mechanically polished stainless steel AISI 316L;
- Cabinet enclosed stainless steel AISI 304 construction;
- Thermal protected locking mechanism and door handle(s);
- Automatic door locking;
- Steam generation by stainless steel electrical resistance;
- Vacuum system by temperature shock cooling coil, which enables to do final vacuum in the chamber and drying;
- Equipped with exhaustion steam condenser;
- Double security system against overpressure with high-pressure valve;
- Sterilization chamber temperature limiter;
- Heating elements with automatic security cut off for water level failure;
- Permanent degassing during sterilization, with air/steam trap;
- Equipped with bacteriological filter for intake air;

Special Option

- Special option is required for Printer and Liquids *;
  - * Special option includes an automatic water level control system and automatic water operation
  - * 9 pre-programmed cycles with automatic operation and programmable cycle parameters
- Thermal printer for registration and documentation of each sterilization cycle (Printer option);
- Incorporated temperature sensor to control the temperature inside product being sterilized PT100 (Liquids option);
  - Water overflow with air ballast support - Rapid cooling and control by F0, so that the UNICLAVE 99 can quickly cool the material to be processed, which will imply that this cooling is carried out by flooding the chamber and controlling the pressure in it using injection of compressed air (option requiring Product Probe);
    - Air compressor (required for air ballast support option)
- Keep warm function (culture media) (Liquids option);

Accessories & Options

- Half-Loading stainless steel wire baskets;
- Closed bottom for half-Loading stainless steel wire baskets
- Water Treatment System:
  - Prefiltration
  - Water Softener System
  - Demineraliser with conductivity meter
- AJC Vision Map - Documentation Software to collect via PLC complete documentation of each sterilization cycle. The information can be collected via USB or Ethernet connection.
- Built-in PC

- 2 cycles P3, 121ºC
- UPS
- Remote Module System
- Drainage cooling with PT100 sensor control
- Wheels for easy movement

External network connections

- Electricity

Uniclave Model	Power Supply
Uniclave 99 AJC 80	1 ~ + N + G 230V 50/60Hz 3 kW
Uniclave 99 AJC 120	3 ~ + N + G 400V 50/60Hz 6 kW
Uniclave 99 AJC 160	3 ~ + N + G 400V 50/60Hz 6 kW

*Other electrical connections are available upon request.

- Drainage
- Water (depending on model)

Certifications / Compliance with directives and standards

- The steam sterilizer **Uniclave 99**, conforms with the following directives and standards:
  - Pressure Equipment Directive 2014/68/UE.
  - Electromagnetic Compatibility Directive 89/336/CE.
  - EN 61326 - Electrical Equipment for measurement, control and laboratory use.
  - Electromagnetic Compatibility EN 61000.

- **A. J. Costa (Irmãos), Lda,** is certified ISO EN 9001

  Certificates are issued by SGS-UKAS and assure that **A.J.Costa (Irmãos), Lda**, fulfils the requirements of quality management systems, which covers design, project, manufacture, maintenance, delivery and installation.