

Technical drawing of a vertical assembly. The drawing shows a central vertical shaft with various components and dimensions. At the top, there is a dimension of 3 3. Below this, there is a dimension of 40 40. The shaft has a diameter of 10 10 at a certain point. There are two main components labeled: BLE2P150, S355J2-N and BLE2P140, S355J2-N. A dimension of 5 5 is shown for a small component. The bottom part of the drawing shows a dimension of 30 70. There are also two labels in boxes: A1 and A26/1001 HEA120, and S2 and A/1006 RSK1007.

3 3

40 40

10 10

5 5

30 70

BLE2P150, S355J2-N

BLE2P140, S355J2-N

A1

A26/1001 HEA120

S2

A/1006 RSK1007

[illegible]

Isometrie Primärkonstruktion Typ A - 2026

Technical drawing of a mechanical part, likely a bracket or plate, showing dimensions and feature callouts. The part has a central rectangular hole and several mounting holes. Dimensions are given in inches. Callouts include A6/1001, A26/1001, A1005, and A1006, along with part numbers like 4-x 6-KI, 933 M20x70, 8.8 and 4-x 6-KI, 933 M20x70, 8.8. Surface finish symbols like Rk130/100, Rk130/50, and Rk130/20 are also present.

The diagram illustrates a cross-section of a window frame assembly. Key components and their specifications are as follows:

- Top Sill Profile:** Labeled A1/A26/1001. Dimensions include a total width of 200mm and individual segments of 100mm.
- Side Profiles:** Labeled RND120, S125/SR. They feature a 4x6-KL 933 M12738-8,8 profile with a 5° slope and a 40mm dimension.
- Bottom Profile:** Labeled BLR20*210, S156,12-N. It includes a 4x6-KL 933 M12707-7,8 profile with a 5° slope and a 20mm dimension.
- Internal Components:**
 - A central panel labeled QR A/1001 with a 20mm thickness.
 - An internal reinforcement or insulation layer labeled RK180*100's, S156,12-N.
- Dimensions and Slopes:** Various dimensions are provided throughout the assembly, including 100mm, 40mm, 20mm, and 120mm. Slopes of 5° are indicated at several points.
- Material Codes:** The drawing uses codes like A1, A26/1001, RND120, S125/SR, BLR20*210, S156,12-N, and QR A/1001 to identify specific parts and materials.

Technical drawing of a square plate with the following dimensions and annotations:

- Overall width: 280
- Overall height: 280
- Inner square dimensions: 160 (width) x 160 (height)
- Distances from edges to inner square corners: 30 (top), 30 (bottom), 30 (left), 30 (right)
- Distances from inner square corners to outer square corners: 220 (top), 220 (bottom), 220 (left), 220 (right)
- Material: 4 x 6-Kt. 933 M20*70..B
- Surface treatment: BLEU20*280..S305.12-N
- Surface finish: 6.3
- Material grade: R9K160*6..0..S355J2H
- Inner square hole dimensions: 4 x Ø 30
- Inner square hole position: 11,0/90

S2
A/1006

RKX1009-0, S355J2H

BLE20*200, S355J2+N
BLE20*200, S355J2+N

6x6-Kt K23 M20*70_8.8

Technical drawing A/1007 shows a perspective view of a rectangular plate. The plate has two long edges labeled "BLE20*200, S355J2+N". It features four mounting holes arranged in a rectangle, with dimensions 75 mm between the center-to-center of the top and bottom holes, and 120 mm between the center-to-center of the left and right holes. The distance from each corner to the nearest hole center is 61 mm. Two bolts are shown passing through the plate, labeled "6x6-Kt K23 M20*70_8.8". The drawing includes dimension lines and arrows indicating measurements.

Technical drawing of a square plate with the following dimensions and specifications:

- Overall width: 200
- Overall height: 200
- Inner square dimensions: 150 (width) x 150 (height)
- Distance from outer edge to inner square edge: 25
- Distance from center of inner square to center of outer square: 100
- Four mounting holes: 4 x $\phi 25$
- Four mounting holes: 4 x $\phi 40$
- Material: 4 x 6-K1, 933 M20*70, 8.8
- Surface treatment: BLE20*200, S355J2+H

Achse Micropfahl = 7394

Micropfahl Bauelemente

4 x EN-14399-4 HV M20*75, 10.9

A26/1004

BLE20*300... S355J2+N

90 90

90 90

Micropfahl Bauelemente

4 x EN-14399-4 HV M20*75, 10.9

A26/1003

BLE20*300... S355J2+N

90 90

90 90

Micropfahl Bauelemente

4 x EN-14399-4 HV M20*75, 10.9

A26/1004

BLE20*300... S355J2+N

90 90

90 90

Micropfahl Bauelemente

4 x EN-14399-4 HV M20*75, 10.9

A26/1003

BLE20*300... S355J2+N

Technical drawing of a roof connection detail (A26/1003) showing a cross-section of a roof assembly. The drawing includes dimensions for the roof structure, insulation, and the connection of the two roof types. Key components include the roof structure (A26/1003), insulation (BLE20°/30°, Bausteine), and the connection of the two roof types (BLE20°/30°, BLE20°/30°). The drawing is labeled with 'A26/1003' and 'BLE20°/30°'.

S1
A1/1005

RRK180°/0... S35J2H

50 90
20

8

BLE20°100, S35J2H+N

1 x 6-KM 533 M24*75, 8.8

S1

A26/1003

BLE20°300... S35J2H+N

4 x EM 14399-4 HV M20*75, 10.9
Langloch in Platte 22*75

BLE20°100, Baugteile

80 80
20

60 180 60

300

Mikroprofil Baugteile

[illegible][illegible]

Gesamte Konstruktion ist Roh

MAUCHLE
Stahlbau

Auftragsnr.	24027	BAUHERR Axpo Solutions AG
Zeichner	P.Koch	

interne Kontrolle		BAUSTELLE NalpSolar
ABTEILUNG	UNTERSCHRIFT	

		Primärkonstruktion Typ A
		Typ 2026
PL	J. Mäder	Ansicht, Schnitte & Details

MAßSTAB	1:10	1:20	1:55	ZEICHNUNGSNUMMER					
ANSICHT	 			24027	S	0	M	008	D
				PROJEKT	ABTEILUNG	LOS	TITELBLATT	FORTLAUFENDE NR.	REVISION