

Technical drawing of a vertical assembly. The drawing shows a central vertical shaft with various components and dimensions. At the top, there is a dimension of 3 3. Below this, there is a dimension of 40 40. The shaft has a diameter of 10 10 at a certain point. Below this, there is a dimension of 5 5. The shaft has a diameter of 10 10 at another point. Below this, there is a dimension of 5 5. The shaft has a diameter of 10 10 at a third point. Below this, there is a dimension of 30 70. The drawing includes several part numbers and dimensions: BLE2P30, S355,12-N; BLE2P150, S355,12-N; BLE2P140, S355,12-N; A26/1001 HEA120; A1006 RSK1007; 3 x 6 x 6, 9,33 M12 x 25, 8,8 mit Korkmutter; 1 x 6,8, 9,33 M14 x 100, 8,8 mit Korkmutter; S2 A/1006.

A1
A26/1001
HEAL20, S305

A2
A/1006
RRK100P/S, S355, D2

[illegible]

60

40

40

40

A

4 x 6-KI 933 M12*35, 8.8
mit Kontermutter

A1
A26/1001
HEA120, 5355x12

40

40

40

4 x 6-KI 933 M12*35, 8.8
mit Kontermutter

40

40

4 x 6-KI 933 M12*35, 8.8
mit Kontermutter

4 x 6-KI 933 M20*70, 8.8

4 x 6-KI 933 M20*70, 8.8

4 x 6-KI 933 M20*70, 8.8

4 x 6-KI 933 M20*70, 8.8

20

3192

A1 A1005
HEA100x10, 5355x10

A26/1003
BL530*300, 5355x10

1 x 6-KI 933 M24*75, 8.8

4 x EN-14399-4 HV_M20*75_10.9

Technical drawing of a cable assembly. The drawing shows a vertical cable with two components, A26/1004 and A26/1003, connected to it. Component A26/1004 is a rectangular block with four circular ports on its side, labeled "4 x EN-14399-4 HV M20*75 10 9". It is connected to the cable via a "Mikrofilhl Bauseits" (microfilament base). Component A26/1003 is a similar rectangular block, also labeled "4 x EN-14399-4 HV M20*75 10 9", and is connected to the cable via another "Mikrofilhl Bauseits". The drawing includes dimension lines indicating a 90-degree angle for the cable's path. The cable is labeled "BL20*300... S3952-4".

Microphall Bauseits

4 x EN-14399-4 HV M20*75 10.9

A26/1004

BLE20*900 , 5355J2-N

90 90

4 x EN-14399-4 HV M20*75 10.9

Microphall Bauseits

A26/1003

BLE20*900 , 5355J2-N

The diagram shows a two-link manipulator. The first link is labeled $Q1$ and is connected to a fixed base at a revolute joint. The second link is labeled $Q2$ and is connected to the first link at a revolute joint. The end effector is a prismatic joint, labeled $S1$, which moves along a vertical guide. The diagram also shows the joint labels $A1$ and $A2$ at the base and end effector respectively, and the joint labels $S1$ and $S2$ at the base and end effector respectively.

[illegible][illegible][illegible]

4 x EN-14399-4 HV M20-75 10.9

Length in Plate 22°75

300

60 180 60

300

60 180 60

80 ± 80
20

75

BLE20°190, S355J2+N

5

1 x 6-Kt. 933 M24x75

[illegible]

Technical drawing of the front view of a square plate. The overall dimensions are 200 mm by 200 mm. The plate features four mounting holes, each with a diameter of 25 mm. The center-to-center distance between the holes is 100 mm. The distance from the center of each hole to the nearest edge is 25 mm. The plate is made of 4 x 6-K1 933 M20*70_8.8 and is coated with BLE20*200, S355J2+H. The plate is also marked with 1* Ø40.

[illegible][illegible]

Gesamte Konstruktion ist Roh

NACH	DATUM		ANZEIGUNG-BESTELLUNG		NAMEN
MAUCHLE Stahlbau					
Industriestrasse 9 · CH-6210 Sutz · T +41 41 925 12 51 - info@mauchlestahlbau.ch					
Auftragnr.	24027		BAUHERR		
Zeichner	P.Koch		Xppo Solutions AG		
Interne Kennzahl			BAUSTELLE		
ARTBELEG			NalpSolar		
PL J. Mäder			BESCHNANG Primärkonstruktion Typ A Typ 2026 - für 8er Modulstich Ansicht, Schnitte & Details		
MASSSTAB 1:10 1:20 1:55			ZEICHNUNGSNUMMER		
ANSICHT			24027 S 0 M 013 STRICHZEICHEN ANSCHLÜSSE FÜR VERBINDEN KABEL-KABELKANNEN		
			VERFUGEN		