



Metallurgica Bresciana S.P.A. Viale G. Marconi n.31 Dello		DICHIARAZIONE DI CONFORMITA' DECLARATION OF CONFORMITY		No 5170004081 DATA 18.06.2026 Date PAGINA 1 of 1 Page	
DESTINATARIO PURCHASER SIRAIL S.A.S. Parc trans Avenir Crespin 59154 132418			COMMESSA N CDA260508480 13.05.2026 CONTRACT N		
			ORDINE INTERNO N 4620002024 WORK ORDER		
			DESTINAZIONE MATERIALE SHIPPED TO SIRAIL S.A.S. Parc trans Avenir Crespin 59154 France		
DOC. INVIATI A: ASSICURAZ. QUALITA' DOCUMENT SENT: INSURANCE QUALITY			NUMERO COLLI 00001 PACKAGE N		
DOCUMENTO DI TRASPORTO N SHIPPING NOTICE N					
POSIZ ITEM	CODICE PART NUMBER	DESCRIZIONE DESCRIPTION	QUANTITY (Qty)	LOTTO - LOT ODP - P.O.	
000030	F580F71187 71801810	4x20 AWG LAN CABLE EN50200 matr. FS30885 2909220001	269,000	90022559	
Questa Societa dichiara, sotto la propria ed esclusiva responsabilit�, che la fornitura in oggetto, se non altrimenti dichiarato, � stata fabbricata, provata e ispezionata in accordo con i termini di contratto/ordine ad essa relativi e completamente conforme alle Norme o Specifiche in descrizione. Dichiara inoltre che le procedure adottate sono in accordo alle prescrizioni dello standard UNI EN ISO 9001, con certificazione CSQ n 9125 MET7. In accordo con la norma ISO/IEC 17050-1 This company declares under his own responsibility, that the above mentioned supply, unless otherwise stated, has been manufactured, tested and inspected in accordance with the terms of the contract/order applicable thereto and fully compliant to the standards/specifications in description. Declares also that the adopted procedures are in accordance with the conditions of UNI EN ISO 9001 - registration CSQ N. 9125 MET7 in accordance with ISO/IEC 17050-1					
Dello,		DATA 18.06.2026 Date	IL RESPONSABILE ASSICURAZIONE QUALITA' Ing. Adigraz Antonio 		



CERTIFICATO DI COLLAUDO / Test Certificate

data 18-06-2026

90022559

SIRAIL S.A.S.

Customer

FRANCE

Delivery Point

Oggetto:

"LAN" CABLE 100 OHM 4x20 AWG S-FTP cat 5e FIRE RESISTANT

Normative/

Object

Specifiche:

Specification

TIPOLOGIA Control Type	CARATTERISTICA Test	UdM Um	RICHIESTO MIN Required Min	RICHIESTO MAX Required Max	RILEVATO Measurement	NOTE Remarks
Prove dimensionali - Dimensional test						
	CONDUTTORE / CONDUCTOR		OK	OK	OK	CORDINA RAME SN. - STRANDED ANNEALED TINNED COPPER
	DIAMETRO CONDUTTORE / CONDUCTOR DIAMETER	mm	0	n.a.	0.941	
	COLORE ISOLANTE / INSULATION COLOUR		OK	OK	OK	BIANCO, GIALLO, BLU E ARANCIO - WHITE, YELLOW, BLUE, ORANGE
	NASTRO 1 / TAPE 1		OK	OK	OK	VETRO-MICA - MICA-GLASS
	CORDATURA / STRANDING		OK	OK	OK	- 4 CORES TWISTED TOGETHER
	NASTRO 3 / TAPE 3		OK	OK	OK	- MICA-GLASS
	NASTRO 4 / TAPE 4		OK	OK	OK	ALL/POL/ALL 0.062 - ALUMINIUM/POLYESTER TAPE UNDER BRAID
	SCHERMO TRECCIA / WIRES BRAID SHIELD		OK	OK	OK	TRECCIA RAME SN 0.10 - BRAID ANNEALED TINNED COPPER
	COPERTURA SCHERMO / SCREEN COVERAGE	%	OK	OK	OK	
	GUAINA / OUTER SHEATH		OK	OK	OK	EM104 - EM104 IN ACCORDING TO EN50264
	DIAMETRO GUAINA MEDIO / EXTERNAL DIAMETER	mm	0	n.a.	7.889	
	SPessore GUAINA MEDIO / OUTER SHEATH AVERAGE THICKNESS	mm	0	n.a.	0.832	
	COLORE GUAINA / SHEATH COLOUR		OK	OK	OK	BLUE
	MARCATURA / CABLE SURFACE MARKING		OK	OK	OK	"METALLURGICA BRESCIANAsettimanalanno - 4X20 AWG SF/UTP - 100 OHM - CAT. 5e - EN50200 PH30" - WEEK/YEAR
Prove elettriche - Electrical test						
	CONTINUITÀ ELETTRICA / CONTINUITY TEST		OK	OK	OK	
	TENSIONE CONDUTTORE/CONDUTTORE / VOLTAGE TEST COND/COND	kV	2 AC	2 AC	OK	- x 1 MIN
	TENSIONE CONDUTTORE/SCHERMO / VOLTAGE TEST COND/SCREEN	kV	2 AC	2 AC	OK	- x 1 MIN
	RESISTENZA ELETTRICA a 20°C / CONDUCTOR RESISTANCE AT 20°C	ohm/km	0	34.3	32.57	
	RESISTENZA ISOLAMENTO / INSULATION RESISTANCE	Mohm*km	1000	n.a.	14500	
	SQUILIBRIO CAPACITÀ (COND/SCHE) / CAPACITANCE UNBALANCE (COND/SCREEN)	pF/m	0	1.5	1.087	
	IMPEDENZA (1 MHz) / IMPEDANCE (1 MHz)	ohm	0	n.a.	101.39	
	IMPEDENZA (10 MHz) / IMPEDANCE (10 MHz)	ohm	85	115	101.54	
	IMPEDENZA (100 MHz) / IMPEDANCE (100 MHz)	ohm	85	115	97.55	

MB

Nº: 90022559

TIPOLOGIA Control Type	CARATTERISTICA Test	UdM Um	RICHIESTO MIN Required Min	RICHIESTO MAX Required Max	RILEVATO Measurement	NOTE Remarks
	ATTENUAZIONE (1 MHz) / ATTENUATION (1 MHz)	dB/km	0	20	14.7	
	ATTENUAZIONE (10 MHz) / ATTENUATION (10 MHz)	dB/km	0	65	54.9	
	ATTENUAZIONE (100 MHz) / ATTENUATION (100 MHz)	dB/km	0	220	183.25	
	PARADIAFONIA (1 MHz) / NEAR-END CROSSTALK (1 MHz)	dB	65.3	n.a.	83.05	
	PARADIAFONIA (10 MHz) / NEAR-END CROSSTALK (10 MHz)	dB	50.3	n.a.	74.52	
	PARADIAFONIA (100 MHz) / NEAR-END CROSSTALK (100 MHz)	dB	35.3	n.a.	52.1	
	SCARTO DI TELEDIAFONIA (1 MHz) / ELFEKT (1 MHz)	dB	64	n.a.	84.93	
	SCARTO DI TELEDIAFONIA (10 MHz) / ELFEKT (10 MHz)	dB	44	n.a.	63.41	
	SCARTO DI TELEDIAFONIA (100 MHz) / ELFEKT (100 MHz)	dB	24	n.a.	37.21	
	RESISTENZA AL FUOCO EN 50200 / FIRE RESISTANCE EN 50200	kV	OK	OK	OK	- PH 30
Prove fisiche - Physical test						
	DUREVOLEZZA MARCATURA / DURABILITY OF IDENTIFICATION		OK	OK	OK	
	ALLUNGAMENTO GUAINA / OUTER SHEATH ELONGATION AT BREAK	%	125	n.a.	223	
	CARICO DI ROTTURA GUAINA / OUTER SHEATH TENSILE STRENGTH	N/mm2	10	n.a.	12.85	
	ALLUNGAMENTO A CALDO GUAINA / SHEATH HOT SET TEST ELONGATION	%	0	100	30	- 15 MIN at 200°C 20N/cm²
	ALLUNGAMENTO A CALDO GUAINA RESIDUO / SHEATH HOT SET TEST ELONG. AFTER COOLING	%	0	25	0	
	NON PROPAGAZIONE DELLA FIAMMA / VERTICAL BURNING TEST (SINGLE CABLE)	mm	OK	OK	OK	- EN 60332-1-2
	EMISSIONE HCL / AMOUNT OF HALOGEN ACID GAS DURING COMB. HCl	%	0	0.5	0.1	- <=0.1 - EN 50267-2-1
	ASSENZA DI ALOGENI CONDUTTIVITA' / ABSENCE OF HALOGENS CONDUCTIVITY	µS/mm	0	10	2	- <=2 - EN 50267-2-2
	ASSENZA DI ALOGENI PH / ABSENCE OF HALOGENS PH	pH	4.3	n.a.	5	- >=5 - EN 50267-2-2

SIDA S.p.A. **TECNOLOGICA BRESCIANA S.p.A.**
CONTROLLO QUALITA'
"Ritrovabile"

N°: 90022559

MB

Metallurgica Bresciana S.p.A.

PACKING LIST N. 4620002024/2

LISTA DEI COLLI

CONSIGNEE
DELIVERY ADDRESS

: SIRAIL SAS
: Parc trans Avenir
59154 Crespin - FRANCIA

METALLURGICA BRESCIANA S.p.A.
CONTROLLO QUALITA'
11. Remontabilio

P. ORDER N. : CDA260508480
COUNTRY OF ORIGIN : ITALY
PACKAGE N. : 1/1
GROSS WEIGHT KG. : 46
NET WEIGHT KG. : 26
DIMENSIONS CM. : 80X80X55

N.	PACKAGE REEL	SIZE CM.	Q.TY MT.	CABLE TYPE	WEIGHT KG GROSS	NET
1	PALLET	80X80X55		CONTAINING:	15	
	FS30885	50X40X50	269	4x20 AWG LAN CABLE EN50200	71801810	31
						26
	1 PALLET	m3 =0,352			46	26