


1. Install the metamask in browser. Setup the metamask digital cryptocurrency wallet. Create multiple accounts in metamask and connect with one of the etherum blockchain test network. Perform the task buy ethers and send ethers from one account to another. Take the screenshots of created accounts, account assets and account transactions which showing the details of transaction.









Practical No:04

Roll No:16







 Write a solidity smart contract to transfer funds (ethers) from user account to contract account using remixIDE and JavaScriptVM environment.

Code:

```
pragma solidity ^0.5.2;
contract Financialcontract2{
  address owner;
  constructor() public{
     owner=msg.sender;
  }
  modifier ifOwner(){
    if(owner!=msg.sender){
       revert();
     else{
  function receiveDeposit() payable public{
  function getBalance() public view returns(uint)
     return address(this).balance;
  function withdraw(uint funds)public ifOwner{
     msg.sender.transfer(funds);
  }
Output:
```

VALUE


4563

Wei

CONTRACT (Compiled by Remix)


Financialcontract2 - contracts/Finar


Deploy




3. Write a solidity smart contract to withdraw funds (ethers) from contract account to user account using remixIDE and JavaScriptVM environment. Program:

```
pragma solidity ^0.5.2;
contract Financialcontract2{
  address owner;
  constructor() public{
     owner=msg.sender;
  modifier ifOwner(){
     if(owner!=msg.sender){
       revert();
     else{
  function receiveDeposit() payable public{
  function getBalance() public view returns(uint)
     return address(this).balance;
  }
  function withdraw(uint funds)public ifOwner{
     msg.sender.transfer(funds);
  function getMoney(){
}
```







4. Write a solidity smart contract to apply restriction that only owner of the contract can withdraw funds (ethers) from contract account to his/her user account using remixIDE and JavaScriptVM environment.

Program:

```
pragma solidity ^0.5.2;
contract Financialcontract2{
  address owner;
  constructor() public{
     owner=msg.sender;
  modifier ifOwner(){
     if(owner!=msg.sender){
       revert();
     }
     else{
  function receiveDeposit() payable public{
  }
  function getBalance() public view returns(uint)
     return address(this).balance;
  }
  function withdraw(uint funds)public ifOwner{
     msg.sender.transfer(funds);
  function getMoney(){
  }
}
```

5. Create Ethereum node using Geth and create genesis block and create your personal private Ethereum blockchain. And use IPC to interact with Geth node to perform following task: create account, transfer funds using send transaction, mine the block, show the account balance before and after the mining the block, show the specific block details and access chain details.

Program:

Create Account

```
C:\Users\HP>geth attach ipc:\\.\pipe\geth.ipc
Welcome to the Geth JavaScript console!
instance: Geth/v1.10.26-stable-e5eb32ac/windows-amd64/go1.18.5
at block: 0 (Thu Jan 01 1970 05:30:00 GMT+0530 (IST))
datadir: D:\MCA\sem3\Blockchain\Private_Chain\chaindata
modules: admin:1.0 debug:1.0 engine:1.0 eth:1.0 ethash:1.0 miner:1.0 ne t:1.0 personal:1.0 rpc:1.0 txpool:1.0 web3:1.0
To exit, press ctrl-d or type exit
  personal.newAccount()
Passphrase:
Repeat passphrase:
"0x2c2cacffc74a77b000461838042125db1203e487"
> eth.accounts
["0x2c2cacffc74a77b000461838042125db1203e487"]
> eth.coinbase
"0x2c2cacffc74a77b000461838042125db1203e487"
> eth.getBalance(eth.accounts[0])
> miner.start()
null > miner.stop()
> eth.getBalance(eth.accounts[0])
> personal.newAccount()
Passphrase:
Repeat passphrase:
"0x6680bf98a5b24a5f56cfd77c10fcd8d7a299bd88"
```

Transfer funds, mine block and account balance before and after the mining of block

```
> personal.unlockAccount(eth.accounts[0])
Unlock account 0x2c2cacffc74a77b000461838042125db1203e487
Passphrase:
true
> eth.sendTransaction({from:eth.coinbase,to:eth.accounts[1],value:web3
> eth.sendTransaction({from:eth.coinbase,to:eth.accounts[1],value:web3
oWei(10, "ether")})
"0xdb1638c9911dd2899a6b0f1dad5e83841f33719178717977e5c7469f25523674"
> eth.getBalance(eth.accounts[1])
> miner.start()
null
> miner.stop()
null
> eth.getBalance(eth.accounts[1])
100000000000000000000
> eth.getBalance(eth.accounts[0])
4600000000000000000000
> web3.fromWei(eth.getBalance(eth.accounts[1]),"ether")
```

Specific block details

```
> eth.getBlock("latest")
 difficulty: 135519,
 extraData: "0xda83010a1a846765746888676f312e31382e358777696e646f7773", gasLimit: 3443331,
 gasUsed: 0.
 hash: "0x995c47f334df9523073e0b5bde93759c7054300e9106ddae909242888ef8b8a4",
 miner: "0x2c2cacffc74a77b000461838042125db1203e487",
 mixHash: "0x07dd647a1e0cc4111f04894fd68c4b2bbbd3174268aeff27184550279204279e",
 nonce: "0x130bf96d66b38274",
 number: 94,
 parentHash: "0x1f7b1e919a2702f68e3bf03758ee74cc45bc5d476bf494f324aa1359a7480fa8"
 receiptsRoot: "0x56e81f171bcc55a6ff8345e692c0f86e5b48e01b996cadc001622fb5e363b421",
 sha3Uncles: "0x1dcc4de8dec75d7aab85b567b6ccd41ad312451b948a7413f0a142fd40d49347",
 stateRoot: "0x7a1dadb4ff0380d5727775ce1ce53712e86fdc22d8c4d40bcbd5a6815e93a993".
 timestamp: 1669783124,
 totalDifficulty: 12658148,
 transactions: [],
 transactionsRoot: "0x56e81f171bcc55a6ff8345e692c0f86e5b48e01b996cadc001622fb5e363b421",
}
```

6. Create Ethereum node using Geth and create genesis block and create your personal private Ethereum blockchain. And use IPC to interact with Geth node to perform following task: create account, transfer funds using send transaction, mine the block, show the account balance before and after the mining the block, show the specific block details and access chain details.

Create Account

```
C:\Users\HP>geth attach ipc:\\.\pipe\geth.ipc
Welcome to the Geth JavaScript console
instance: Geth/v1.10.26-stable-e5eb32ac/windows-amd64/go1.18.5
   block: 0 (Thu Jan 01 1970 05:30:00 GMT+0530 (IST))
datadir: D:\MCA\sem3\Blockchain\Private_Chain\chaindata
 modules: admin:1.0 debug:1.0 engine:1.0 eth:1.0 ethash:1.0 miner:1.0 ne
t:1.0 personal:1.0 rpc:1.0 txpool:1.0 web3:1.0
To exit, press ctrl-d or type exit
 personal.newAccount()
Passphrase:
Repeat passphrase:
 0x2c2cacffc74a77b000461838042125db1203e487"
> eth.accounts
["0x2c2cacffc74a77b000461838042125db1203e487"]
> eth.coinbase
"0x2c2cacffc74a77b000461838042125db1203e487"
> eth.getBalance(eth.accounts[0])
> miner.start()
> miner.stop()
> eth.getBalance(eth.accounts[0])
> personal.newAccount()
Passphrase
Repeat passphrase:
"0x6680bf98a5b24a5f56cfd77c10fcd8d7a299bd88"
```

Transfer funds, mine block and account balance before and after the mining of block


```
> personal.unlockAccount(eth.accounts[0])
Unlock account 0x2c2cacffc74a77b000461838042125db1203e487
Passphrase:
> eth.sendTransaction({from:eth.coinbase,to:eth.accounts[1],value:web3
> eth.sendTransaction({from:eth.coinbase,to:eth.accounts[1],value:web3
oWei(10, "ether")})
"0xdb1638c9911dd2899a6b0f1dad5e83841f33719178717977e5c7469f25523674"
> eth.getBalance(eth.accounts[1])
> miner.start()
null
> miner.stop()
null
> eth.getBalance(eth.accounts[1])
100000000000000000000
> eth.getBalance(eth.accounts[0])
4600000000000000000000
> web3.fromWei(eth.getBalance(eth.accounts[1]),"ether")
10
```


Specific block details


```
> eth.getBlock("latest")
 difficulty: 135519,
 extraData: "0xda83010a1a846765746888676f312e31382e358777696e646f7773", gasLimit: 3443331,
 gasUsed: 0,
 hash: "0x995c47f334df9523073e0b5bde93759c7054300e9106ddae909242888ef8b8a4",
 miner: "0x2c2cacffc74a77b000461838042125db1203e487",
 mixHash: "0x07dd647a1e0cc4111f04894fd68c4b2bbbd3174268aeff27184550279204279e",
 nonce: "0x130bf96d66b38274".
 number: 94,
 parentHash: "0x1f7b1e919a2702f68e3bf03758ee74cc45bc5d476bf494f324aa1359a7480fa8",
 receiptsRoot: "0x56e81f171bcc55a6ff8345e692c0f86e5b48e01b996cadc001622fb5e363b421".
 sha3Uncles: "0x1dcc4de8dec75d7aab85b567b6ccd41ad312451b948a7413f0a142fd40d49347",
 stateRoot: "0x7a1dadb4ff0380d5727775ce1ce53712e86fdc22d8c4d40bcbd5a6815e93a993",
 timestamp: 1669783124,
 totalDifficulty: 12658148,
 transactions: [],
 transactionsRoot: "0x56e81f171bcc55a6ff8345e692c0f86e5b48e01b996cadc001622fb5e363b421",
 uncles: []
```


7. Create new truffle project with migration script, smart contract and configuration file. First compile it using truffle suite. Then connect it with personal private blockchain i.e. Ganache and deploy (migrate) smart contract on Ganache. Open truffle console and create instance of deployed (migrated) contract of Ganache. Then interact with smart contract using created instance. Take screenshots of all transaction's details and block details from Ganache














8. Create new truffle project with migration script, smart contract and configuration file. First compile it using truffle suite. Then connect it with personal private blockchain i.e. Ganache and deploy (migrate) smart contract on Ganache. Open truffle console and create instance of deployed (migrated) contract of Ganache. Then interact with smart contract using created instance. Take screenshots of all transaction's details and block details from Ganache.

