Decorative Paints

Product / Application	BIS	ISO	ASTM	DIN	Other Standards(SSPC,AMPP, REACH, FDA)
Interior Emulsion Paint	IS 15489 (Interior Emulsion Paint); IS 427; IS 5410	ISO 2813 (Gloss Measurement); ISO 2808 (Dry Film Thickness); ISO 2409 (Cross-Cut Adhesion); ISO 11998 (Wet Scrub Resistance); ISO 4628 Series (Coating Degradation Evaluation),ISO 4618; ISO 6504	ASTM D2486 (Scrub Resistance of Wall Paints); ASTM D3359 (Adhesion by Tape Test); ASTM D523 (Gloss Measurement); ASTM D2805 (Hiding Power of Paints); ASTM D2244 (Colour Difference); ASTM D2369 (Volatile Content/VOC); ASTM D5895 (Drying Time); ASTM D4060 (Abrasion Resistance),ASTM D1200; ASTM D1210; ASTM D3273; ASTM D522; ASTM D56	DIN EN ISO 11998 (Wet Scrub Resistance and Cleanability of Coatings); DIN EN ISO 2409 (Cross-Cut Adhesion Test); DIN EN ISO 2813 (Gloss Measurement); DIN EN ISO 2808 (Dry Film Thickness); DIN EN ISO 15184 (Pencil Hardness); DIN EN ISO 16000-9 (Emission Testing of VOCs from Building Products where low emission claims apply)	DIN EN ISO 527 (Tensile Properties of Plastics); DIN EN ISO 4593 (Thickness Measurement of Plastic Film and Sheeting); DIN EN ISO 7765-1 (Impact Resistance of Plastic Film by Free-Falling Dart Method)
Exterior Emulsion Paint	IS 15489:2024; IS 427; IS 5410	ISO 11507 (Artificial Weathering); ISO 4628 Series (Coating Degradation); ISO 11998 (Wet Scrub Resistance); ISO 2808 (Film Thickness),ISO 4618; ISO 6504	ASTM D4587 (UV-Condensation Weathering); ASTM G154 (Fluorescent UV Exposure); ASTM G155 (Xenon Arc Weathering); ASTM D523 (Gloss); ASTM D2244 (Colour Change); ASTM D610 (Rust Evaluation); ASTM D714 (Blistering Evaluation); ASTM D3359 (Adhesion),ASTM D1200; ASTM D1210; ASTM D2486; ASTM D3273; ASTM D522; ASTM D56	DIN EN ISO 2409 (Adhesion); DIN EN ISO 2813 (Gloss); DIN EN ISO 4628 series (Evaluation of Coating Degradation); DIN EN ISO 16474-3 (UV Fluorescent Weathering); DIN EN ISO 16474-2 (Xenon Arc Weathering); DIN EN ISO 7783 (Water Vapour Transmission); DIN EN ISO 1062 series (Coatings for Masonry and Concrete)	REACH: Regulation (EC) No. 1907/2006 (VOC, biocides, pigments, additives); AMPP: SP 13/NACE No.6 only when applied as protective coating on concrete/masonry substrates
Acrylic Emulsion Paint	IS 15489:2024; IS 427; IS 5410	ISO 2813 (Gloss); ISO 2808 (Film Thickness); ISO 2409 (Adhesion); ISO 4624 (Pull-Off Adhesion),ISO 4618; ISO 6504	ASTM D6083 (Liquid Applied Acrylic Coating for Roof Applications where applicable); ASTM D2486 (Scrub Resistance); ASTM D3359 (Adhesion); ASTM D2369 (VOC Content); ASTM D4587 (Accelerated Weathering),ASTM D1200; ASTM D1210; ASTM D3273; ASTM D522; ASTM D523; ASTM D56	DIN EN ISO 11998 (Wet Scrub Resistance); DIN EN ISO 2409 (Adhesion); DIN EN ISO 2813 (Gloss); DIN EN ISO 7783 (Water Vapour Transmission); DIN EN ISO 16474 (Artificial Weathering)	REACH: Regulation (EC) No. 1907/2006 (acrylate polymers, VOC, preservatives, additives)
Plastic Emulsion Paint	IS 15489:2024; IS 427; IS 5410	ISO 11998 (Wet Scrub Resistance); ISO 2813 (Gloss); ISO 2409 (Adhesion); ISO 2808 (Film Thickness),ISO 4618; ISO 6504	ASTM D2486 (Scrub Resistance of Wall Paints); ASTM D2805 (Hiding Power); ASTM D523 (Gloss); ASTM D3359 (Adhesion); ASTM D4060 (Abrasion Resistance),ASTM D1200; ASTM D1210; ASTM D3273; ASTM D522; ASTM D56	DIN EN ISO 11998 (Washability/Scrub Resistance); DIN EN ISO 2409 (Adhesion); DIN EN ISO 2813 (Gloss); DIN EN ISO 2808 (Thickness Measurement)	REACH: Regulation (EC) No. 1907/2006 (polymer binders, VOC, pigments, additives)
Luxury Emulsion Paint	IS 15489:2024; IS 427; IS 5410	ISO 11998 (Wet Scrub Resistance); ISO 2813 (Gloss); ISO 11507 (Weathering Resistance); ISO 2409 (Adhesion),ISO 4618; ISO 6504	ASTM D2486 (Scrub Resistance); ASTM D4446 (Water Repellency where applicable); ASTM D523 (Gloss); ASTM D2244 (Colour Difference); ASTM D3359 (Adhesion),ASTM D1200; ASTM D1210; ASTM D3273; ASTM D522; ASTM D56	DIN EN ISO 11998 (Wet Abrasion Resistance); DIN EN ISO 2813 (Gloss); DIN EN ISO 2409 (Adhesion); DIN EN ISO 1062-3 (Water Permeability of Coatings)	REACH: Regulation (EC) No. 1907/2006 (VOC, pigments, additives, preservatives)
Economy Emulsion Paint	IS 15489:2024; IS 427; IS 5410	ISO 11998 (Wet Scrub Resistance); ISO 2409 (Adhesion); ISO 2808 (Film Thickness),ISO 4618; ISO 6504	ASTM D2486 (Scrub Resistance); ASTM D2805 (Hiding Power); ASTM D523 (Gloss); ASTM D2369 (VOC Content); ASTM D5895 (Drying Time),ASTM D1200; ASTM D1210; ASTM D3273; ASTM D3359; ASTM	DIN EN ISO 11998 (Wet Scrub Resistance); DIN EN ISO 2409 (Adhesion); DIN EN ISO 2808 (Film Thickness); DIN EN ISO 2813 (Gloss)	REACH: Regulation (EC) No. 1907/2006 (VOC, pigments, fillers, additives)

Product / Application	BIS	ISO	ASTM	DIN	Other Standards(SSPC,AMPP, REACH, FDA)
			D522; ASTM D56		
Distemper	Depends on type,IS 15489; IS 427; IS 5410	ISO 2808 (Film Thickness); ISO 2409 (Adhesion); ISO 11998 (Scrub Resistance),ISO 4618; ISO 6504	ASTM D2486 (Scrub Resistance); ASTM D2805 (Hiding Power); ASTM D3359 (Adhesion); ASTM D523 (Gloss Measurement); ASTM D5895 (Drying Time),ASTM D1200; ASTM D1210; ASTM D3273; ASTM D522; ASTM D56	DIN EN ISO 11998 (Wet Scrub Resistance where applicable); DIN EN ISO 2409 (Adhesion); DIN EN ISO 2813 (Gloss); DIN EN ISO 2808 (Thickness)	REACH: Regulation (EC) No. 1907/2006 (pigments, fillers, additives)
Acrylic Distemper	IS 15489; IS 427; IS 5410	ISO 11998 (Wet Scrub Resistance); ISO 2813 (Gloss); ISO 2409 (Adhesion),ISO 4618; ISO 6504	ASTM D2486 (Scrub Resistance); ASTM D3359 (Adhesion); ASTM D2244 (Colour Difference); ASTM D2369 (VOC Content),ASTM D1200; ASTM D1210; ASTM D3273; ASTM D522; ASTM D523; ASTM D56	DIN EN ISO 11998 (Wet Scrub Resistance); DIN EN ISO 2409 (Adhesion); DIN EN ISO 16474 (Weathering); DIN EN ISO 2813 (Gloss)	REACH: Regulation (EC) No. 1907/2006 (acrylic binder, VOC, preservatives)
Cement Paint	IS 5410:2013; IS 15489; IS 427	ISO 4628 Series (Coating Degradation); ISO 6270 (Humidity Resistance); ISO 2808 (Film Thickness),ISO 4618; ISO 6504	ASTM D4541 (Pull-Off Adhesion); ASTM D610 (Rust Evaluation where applied on metal); ASTM D2247 (Humidity Resistance); ASTM D1308 (Chemical Resistance),ASTM D1200; ASTM D1210; ASTM D2486; ASTM D3273; ASTM D3359; ASTM D522; ASTM D523; ASTM D56	DIN EN 1062 series (Coating Materials for Mineral Substrates); DIN EN ISO 2409 (Adhesion); DIN EN ISO 4628 series (Coating Defects); DIN EN ISO 7783 (Water Vapour Transmission)	REACH: Regulation (EC) No. 1907/2006 (cement additives, pigments, chromium compounds where applicable)
Lime Wash	IS 15489; IS 427; IS 5410	ISO 2808 (Film Thickness); ISO 2409 (Adhesion),ISO 4618; ISO 6504	ASTM C926 (Application of Portland Cement-Based Plaster where applicable); ASTM D2805 (Hiding Power); ASTM D3359 (Adhesion),ASTM D1200; ASTM D1210; ASTM D2486; ASTM D3273; ASTM D522; ASTM D523; ASTM D56	DIN EN 1062 series (Coatings for Mineral Substrates); DIN EN ISO 2409 (Adhesion); DIN EN ISO 7783 (Water Vapour Transmission)	REACH: Regulation (EC) No. 1907/2006 (lime chemistry, additives, pigments)
White Wash	IS 15489; IS 427; IS 5410	ISO 2808 (Film Thickness); ISO 2409 (Adhesion),ISO 4618; ISO 6504	ASTM D2805 (Hiding Power); ASTM D523 (Gloss); ASTM D3359 (Adhesion),ASTM D1200; ASTM D1210; ASTM D2486; ASTM D3273; ASTM D522; ASTM D56	DIN EN 1062 series (Mineral Coatings); DIN EN ISO 2808 (Thickness); DIN EN ISO 2409 (Adhesion)	REACH: Regulation (EC) No. 1907/2006 (pigments, additives)
Texture Paint	IS 15489; IS 427; IS 5410	ISO 2409 (Adhesion); ISO 2808 (Film Thickness); ISO 2813 (Gloss Measurement),ISO 4618; ISO 6504	ASTM D2486 (Scrub Resistance); ASTM D4060 (Abrasion Resistance); ASTM D3359 (Adhesion); ASTM D523 (Gloss); ASTM D4541 (Pull-Off Strength),ASTM D1200; ASTM D1210; ASTM D3273; ASTM D522; ASTM D56	DIN EN ISO 2409 (Adhesion); DIN EN ISO 11998 (Wet Scrub Resistance); DIN EN ISO 4624 (Pull-Off Adhesion); DIN EN ISO 2813 (Gloss)	REACH: Regulation (EC) No. 1907/2006 (polymer binders, fillers, pigments, additives)
Elastomeric Paint	IS 15489; IS 427; IS 5410	ISO 12944 (Protective Paint Systems); ISO 4628 Series (Coating Degradation); ISO 11507 (Artificial Weathering); ISO 2808 (Film Thickness),ISO 4618; ISO 6504	ASTM D6083 (Liquid Applied Acrylic Coating for Roof Applications); ASTM D2370 (Tensile Properties of Organic Coatings); ASTM D412 (Rubber Tensile Properties where elastomeric properties apply); ASTM D1200; ASTM D1210; ASTM D2486; ASTM D3273; ASTM D3359; ASTM D522; ASTM D523; ASTM D56	DIN EN ISO 1062 series (Coating Materials for Mineral Substrates); DIN EN ISO 527 (Tensile Properties where elastomeric films apply); DIN EN ISO 2409 (Adhesion); DIN EN ISO 16474 (Weathering Resistance)	REACH: Regulation (EC) No. 1907/2006 (elastomeric polymers, plasticisers, additives); AMPP: SP 13/NACE No.6 when used for concrete protection
Weatherproof Paint	IS 15489; IS 427; IS 5410	ISO 11507 (Artificial Weathering); ISO 16474 (Exposure to Artificial Radiation); ISO 4628 Series (Coating Degradation),ISO 4618; ISO 6504	ASTM D4587 (UV Condensation Weathering); ASTM G154 (UV Exposure); ASTM G155 (Xenon Arc Exposure); ASTM D2244 (Colour Change); ASTM D523 (Gloss Retention),ASTM D1200; ASTM D1210;	DIN EN ISO 16474 series (Artificial Weathering); DIN EN ISO 4628 series (Coating Degradation); DIN EN ISO 2813 (Gloss Retention); DIN EN ISO 1062 (Exterior Coatings)	REACH: Regulation (EC) No. 1907/2006 (UV stabilisers, pigments, additives); AMPP: SP 13/NACE No.6 for concrete/masonry protective applications

Product / Application	BIS	ISO	ASTM	DIN	Other Standards(SSPC,AMPP, REACH, FDA)
			ASTM D2486; ASTM D3273; ASTM D3359; ASTM D522; ASTM D56		
Anti-Fungal Paint	IS 15489; IS 427; IS 5410	ISO 846 (Evaluation of Microbial Action on Plastics/Coatings); ISO 22196 (Antibacterial Activity on Non-Porous Surfaces),ISO 4618; ISO 6504	ASTM D3273 (Resistance to Growth of Mold on Interior Coatings); ASTM D3274 (Evaluation of Degree of Surface Disfigurement); ASTM D5590 (Fungal Growth Resistance),ASTM D1200; ASTM D1210; ASTM D2486; ASTM D3359; ASTM D522; ASTM D523; ASTM D56	DIN EN ISO 846 (Evaluation of Antimicrobial Activity of Plastics/Polymeric Materials); DIN EN ISO 16869 (Fungal Protection of Plastics); DIN EN ISO 11998 (Scrub Resistance)	REACH: Regulation (EC) No. 1907/2006 (biocides, preservatives, SVHC); EU Biocidal Products Regulation (EU) No. 528/2012 for biocidal claims
Anti-Bacterial Paint	IS 15489; IS 427; IS 5410	ISO 22196 (Antibacterial Activity); ISO 21702 (Antiviral Activity on Plastic and Non-Porous Surfaces); ISO 846 (Microbial Resistance),ISO 4618; ISO 6504	ASTM D5590 (Fungal Growth Resistance); ASTM E2180 (Antimicrobial Activity in Polymer/Coating Materials); ASTM E2149 (Antimicrobial Activity of Immobilized Agents under Dynamic Contact Conditions),ASTM D1200; ASTM D1210; ASTM D2486; ASTM D3273; ASTM D3359; ASTM D522; ASTM D523; ASTM D56	DIN EN ISO 22196 (Measurement of Antibacterial Activity on Plastics and Non-Porous Surfaces); DIN EN ISO 846 (Antimicrobial Activity); DIN EN ISO 2409 (Adhesion)	REACH: Regulation (EC) No. 1907/2006 (antimicrobial substances); EU Biocidal Products Regulation (EU) No. 528/2012
Low VOC Paint	IS 15489; IS 427; IS 5410	ISO 11890-1 / ISO 11890-2 (Determination of VOC Content),ISO 4618; ISO 6504	ASTM D2369 (Volatile Content); ASTM D3960 (VOC Content Determination); ASTM D6886 (VOC Emissions from Waterborne Air-Dry Coatings),ASTM D1200; ASTM D1210; ASTM D2486; ASTM D3273; ASTM D3359; ASTM D522; ASTM D523; ASTM D56	DIN EN ISO 11890-1 / 11890-2 (Determination of VOC Content); DIN EN 16516 (Emission Assessment of Construction Products); DIN EN ISO 16000 series (Indoor Air Emissions)	REACH: Regulation (EC) No. 1907/2006; EU Directive 2004/42/EC (VOC limits for paints and varnishes)
Washable Wall Paint	IS 15489:2024; IS 427; IS 5410	ISO 11998 (Wet Scrub Resistance); ISO 2409 (Adhesion); ISO 2813 (Gloss),ISO 4618; ISO 6504	ASTM D2486 (Scrub Resistance); ASTM D3450 (Washability Properties of Interior Architectural Coatings); ASTM D4828 (Practical Washability of Organic Coatings),ASTM D1200; ASTM D1210; ASTM D3273; ASTM D3359; ASTM D522; ASTM D523; ASTM D56	DIN EN ISO 11998 (Wet Scrub Resistance); DIN EN ISO 2409 (Adhesion); DIN EN ISO 2813 (Gloss); DIN EN ISO 4628 (Defect Evaluation)	REACH: Regulation (EC) No. 1907/2006 (VOC, pigments, preservatives, additives)
Ceiling Paint	IS 15489:2024; IS 427; IS 5410	ISO 2813 (Gloss); ISO 11998 (Scrub Resistance); ISO 2409 (Adhesion),ISO 4618; ISO 6504	ASTM D2486 (Scrub Resistance); ASTM D2805 (Hiding Power); ASTM D523 (Gloss); ASTM D3359 (Adhesion),ASTM D1200; ASTM D1210; ASTM D3273; ASTM D522; ASTM D56	DIN EN ISO 11998 (Scrub Resistance); DIN EN ISO 2813 (Gloss); DIN EN ISO 2409 (Adhesion)	REACH: Regulation (EC) No. 1907/2006 (VOC, pigments, additives)
Masonry Paint	IS 15489:2024 – Paint, Plastic Emulsion — SpecificationIS 427; IS 5410	ISO 12944 (Protective Coating Systems); ISO 6270 (Humidity Resistance); ISO 4628 Series,ISO 4618; ISO 6504	ASTM D6083 (Acrylic Coating Applications where applicable); ASTM D4541 (Pull-Off Adhesion); ASTM D4446 (Water Repellency); ASTM D1308 (Chemical Resistance),ASTM D1200; ASTM D1210; ASTM D2486; ASTM D3273; ASTM D3359; ASTM D522; ASTM D523; ASTM D56	DIN EN 1062 series (Paints and Coating Materials for Exterior Masonry); DIN EN ISO 7783 (Water Vapour Transmission); DIN EN ISO 1062-3 (Liquid Water Permeability); DIN EN ISO 2409 (Adhesion)	REACH: Regulation (EC) No. 1907/2006; AMPP: SP 13/NACE No.6 when used for concrete/masonry protection
Brick Paint	IS 15489; IS 427; IS 5410	ISO 12944 (Protective Paint Systems); ISO 4628 Series; ISO 6270 (Moisture Resistance),ISO 4618; ISO 6504	ASTM D4541 (Pull-Off Adhesion); ASTM D4446 (Water Repellency); ASTM D6083 (Acrylic Coatings where applicable); ASTM D4587 (Weathering),ASTM D1200; ASTM D1210; ASTM D2486; ASTM D3273;	DIN EN 1062 series (Masonry Coatings); DIN EN ISO 7783 (Water Vapour Transmission); DIN EN ISO 4628 series (Weathering Defects); DIN EN ISO 2409 (Adhesion)	REACH: Regulation (EC) No. 1907/2006; AMPP: SP 13/NACE No.6 where substrate preparation follows concrete/masonry coating practice

Product / Application	BIS	ISO	ASTM	DIN	Other Standards(SSPC,AMPP, REACH, FDA)
			ASTM D3359; ASTM D522; ASTM D523; ASTM D56		
Concrete Paint	IS 15489; IS 427; IS 5410	ISO 4624 (Pull-Off Adhesion); ISO 12944 (Protective Coating Systems); ISO 6270 (Humidity Resistance),ISO 4618; ISO 6504	ASTM D4541 (Pull-Off Adhesion); ASTM C1583 (Tensile Strength of Concrete Surfaces); ASTM D7234 (Pull-Off Adhesion Strength of Coatings on Concrete); ASTM D1308 (Chemical Resistance),ASTM D1200; ASTM D1210; ASTM D2486; ASTM D3273; ASTM D3359; ASTM D522; ASTM D523; ASTM D56	DIN EN 1504-2 (Surface Protection Systems for Concrete); DIN EN ISO 4624 (Pull-Off Adhesion); DIN EN ISO 7783 (Water Vapour Transmission); DIN EN ISO 1062 (Coating Performance)	AMPP: SP 13/NACE No.6 (Surface Preparation of Concrete); REACH: Regulation (EC) No. 1907/2006 (binders, additives, VOC)
Wood Finish Paint	IS 15489; IS 427; IS 5410	ISO 2409 (Adhesion); ISO 2813 (Gloss); ISO 11507 (Weathering Resistance),ISO 4618; ISO 6504	ASTM D3023 (Evaluation of Coatings Applied to Wood Products); ASTM D4446 (Water Repellency of Wood); ASTM D3359 (Adhesion); ASTM D523 (Gloss),ASTM D1200; ASTM D1210; ASTM D2486; ASTM D3273; ASTM D522; ASTM D56	DIN EN 927 series (Coating Materials and Coating Systems for Exterior Wood); DIN EN ISO 2409 (Adhesion); DIN EN ISO 2813 (Gloss); DIN EN ISO 4628 (Coating Defects)	REACH: Regulation (EC) No. 1907/2006 (solvents, preservatives, pigments, biocides)
Metal Finish Paint	IS 15489; IS 427; IS 5410	ISO 12944 (Corrosion Protection); ISO 8501 (Surface Preparation); ISO 2409 (Adhesion),ISO 4618; ISO 6504	ASTM D3359 (Adhesion); ASTM D4541 (Pull-Off Strength); ASTM B117 (Salt Spray Corrosion Testing); ASTM D610 (Rust Evaluation); ASTM D714 (Blistering),ASTM D1200; ASTM D1210; ASTM D2486; ASTM D3273; ASTM D522; ASTM D523; ASTM D56	DIN EN ISO 12944 series (Corrosion Protection of Steel Structures); DIN EN ISO 2409 (Adhesion); DIN EN ISO 4628 series (Rust/Blister Evaluation); DIN EN ISO 9227 (Salt Spray Testing)	AMPP: SP 1 (Solvent Cleaning); AMPP: SP 2 (Hand Tool Cleaning); AMPP: SP 3 (Power Tool Cleaning); AMPP: SP 6/NACE No.3 (Commercial Blast Cleaning); REACH: Regulation (EC) No. 1907/2006
Chalkboard Paint	IS 15489; IS 427; IS 5410	ISO 2813 (Gloss); ISO 2409 (Adhesion); ISO 2808 (Film Thickness),ISO 4618; ISO 6504	ASTM D3363 (Pencil Hardness); ASTM D3359 (Adhesion); ASTM D4060 (Abrasion Resistance); ASTM D523 (Gloss),ASTM D1200; ASTM D1210; ASTM D2486; ASTM D3273; ASTM D522; ASTM D56	DIN EN ISO 2409 (Adhesion); DIN EN ISO 15184 (Pencil Hardness); DIN EN ISO 11998 (Wet Scrub Resistance); DIN EN ISO 2813 (Gloss)	REACH: Regulation (EC) No. 1907/2006 (pigments, binders, VOC, additives)
Magnetic Paint	IS 15489; IS 427; IS 5410	ISO 2808 (Film Thickness); ISO 2409 (Adhesion); ISO 2813 (Surface Finish),ISO 4618; ISO 6504	ASTM D3359 (Adhesion); ASTM D4060 (Abrasion Resistance); ASTM D3363 (Hardness); ASTM D523 (Gloss),ASTM D1200; ASTM D1210; ASTM D2486; ASTM D3273; ASTM D522; ASTM D56	DIN EN ISO 2409 (Adhesion); DIN EN ISO 2808 (Thickness); DIN EN ISO 15184 (Hardness); DIN EN ISO 2813 (Gloss)	REACH: Regulation (EC) No. 1907/2006 (iron fillers, binders, additives)
Heat Reflective Paint	IS 15489; IS 427; IS 5410	ISO 11507 (Weathering Resistance); ISO 12944 (Protective Coating Systems); ISO 2808 (Film Thickness),ISO 4618; ISO 6504	ASTM C1549 (Solar Reflectance); ASTM E903 (Solar Absorptance); ASTM G173 (Solar Spectrum Reference); ASTM D4587 (Weathering Resistance),ASTM D1200; ASTM D1210; ASTM D2486; ASTM D3273; ASTM D3359; ASTM D522; ASTM D523; ASTM D56	DIN EN ISO 6946 (Thermal Properties of Building Components); DIN EN ISO 9050 (Light Transmittance and Solar Properties of Glass where applicable); DIN EN ISO 16474 (Weathering); DIN EN ISO 2813 (Gloss)	REACH: Regulation (EC) No. 1907/2006 (reflective pigments, fillers, binders); AMPP where used for industrial protective thermal coatings
Fire Retardant Decorative Paint	IS 15489; IS 427; IS 5410	ISO 1182 (Non-Combustibility Testing); ISO 1716 (Heat Release); ISO 834 (Fire Resistance Testing),ISO 4618; ISO 6504	ASTM E84 (Surface Burning Characteristics); ASTM E119 (Fire Resistance Testing); ASTM E162 (Surface Flammability); ASTM E662 (Smoke Generation),ASTM D1200; ASTM D1210; ASTM D2486; ASTM D3273; ASTM D3359; ASTM D522; ASTM D523; ASTM D56	DIN 4102 series (Fire Behaviour of Building Materials); DIN EN 13501-1 (Reaction to Fire Classification); DIN EN ISO 11925-2 (Ignitability Test); DIN EN 13823 (Single Burning Item Test)	REACH: Regulation (EC) No. 1907/2006 (flame retardants, additives, SVHC substances)

Source field: Dyes and Pigments