Enamels

Product / Application	BIS	ISO	ASTM	DIN	Other Standards(SSPC,AMPP, REACH, FDA)
Synthetic Enamel Paint	IS 2932 (current edition); IS 2933	ISO 2813 (Gloss Measurement); ISO 2409 (Cross-Cut Adhesion); ISO 2808 (Film Thickness); ISO 4628 Series (Coating Degradation),ISO 1518; ISO 2812	ASTM D523 (Gloss Measurement); ASTM D3359 (Adhesion by Tape Test); ASTM D3363 (Pencil Hardness); ASTM D4060 (Abrasion Resistance); ASTM D5895 (Drying/Curing Time); ASTM D2244 (Colour Difference),ASTM D1475; ASTM D522	DIN EN ISO 2409 (Adhesion); DIN EN ISO 2813 (Gloss); DIN EN ISO 15184 (Hardness); DIN EN ISO 6272 (Impact Resistance); DIN EN ISO 16474 (Weathering); DIN EN ISO 9227 (Corrosion Resistance)	AMPP: SP 1; AMPP: SP 6/NACE No.3 where applied on metal; REACH: Regulation (EC) No. 1907/2006 (alkyd resins, solvents, pigments)
Premium Enamel Paint	IS 2932,IS 2933	ISO 2813 (Gloss); ISO 2409 (Adhesion); ISO 4624 (Pull-Off Adhesion); ISO 11998 (Wet Scrub Resistance),ISO 1518; ISO 2812	ASTM D523 (Gloss); ASTM D3359 (Adhesion); ASTM D3363 (Hardness); ASTM D4060 (Abrasion Resistance); ASTM D2486 (Scrub Resistance),ASTM D1475; ASTM D522	DIN EN ISO 2409; DIN EN ISO 2813; DIN EN ISO 15184; DIN EN ISO 11998 (Wet Scrub Resistance); DIN EN ISO 4628	REACH: Regulation (EC) No. 1907/2006 (VOC, pigments, additives)
Quick Dry Enamel	IS 2932; IS 2933	ISO 9117 Series (Drying Time of Paints and Varnishes); ISO 2808 (Film Thickness); ISO 2813 (Gloss),ISO 1518; ISO 2812	ASTM D5895 (Drying Time of Paints and Coatings); ASTM D1640 (Drying, Curing, or Film Formation); ASTM D3359 (Adhesion); ASTM D3363 (Hardness),ASTM D1475; ASTM D4060; ASTM D522; ASTM D523	DIN EN ISO 9117 series (Drying Time); DIN EN ISO 2409 (Adhesion); DIN EN ISO 15184 (Hardness); DIN EN ISO 2813 (Gloss)	REACH: Regulation (EC) No. 1907/2006 (solvents, drying agents, VOC, pigments)
High Gloss Enamel	IS 2932,IS 2933	ISO 2813 (Gloss Measurement); ISO 2409 (Adhesion); ISO 2808 (Film Thickness),ISO 1518; ISO 2812	ASTM D523 (Gloss Measurement); ASTM D3359 (Adhesion); ASTM D3363 (Pencil Hardness); ASTM D4060 (Abrasion Resistance),ASTM D1475; ASTM D522	DIN EN ISO 2813 (Gloss); DIN EN ISO 2409 (Adhesion); DIN EN ISO 15184 (Hardness); DIN EN ISO 6272 (Impact Resistance)	REACH: Regulation (EC) No. 1907/2006 (resins, pigments, VOC)
Semi Gloss Enamel	IS 2932,IS 2933	ISO 2813 (Gloss Measurement); ISO 2409 (Adhesion); ISO 4628 Series (Coating Defects Evaluation),ISO 1518; ISO 2812	ASTM D523 (Gloss Measurement); ASTM D2244 (Colour Difference); ASTM D3359 (Adhesion); ASTM D4060 (Abrasion Resistance),ASTM D1475; ASTM D522	DIN EN ISO 2813 (Gloss); DIN EN ISO 2409 (Adhesion); DIN EN ISO 15184 (Hardness); DIN EN ISO 11998 (Scrub Resistance)	REACH: Regulation (EC) No. 1907/2006 (binders, pigments, solvents)
Matt Enamel	IS 2932,IS 2933	ISO 2813 (Gloss Measurement); ISO 2409 (Adhesion); ISO 2808 (Film Thickness),ISO 1518; ISO 2812	ASTM D523 (Gloss Measurement); ASTM D3363 (Hardness); ASTM D3359 (Adhesion); ASTM D4060 (Abrasion Resistance),ASTM D1475; ASTM D522	DIN EN ISO 2813 (Low Gloss Measurement); DIN EN ISO 2409 (Adhesion); DIN EN ISO 15184 (Hardness); DIN EN ISO 11998 (Cleaning Resistance)	REACH: Regulation (EC) No. 1907/2006 (matting agents, pigments, additives)
Stoving Enamel	IS 2932; IS 2933	ISO 9117 Series (Drying and Baking Characteristics); ISO 2808 (Film Thickness); ISO 2409 (Adhesion),ISO 1518; ISO 2812	ASTM D5895 (Drying/Curing Time); ASTM D3363 (Hardness); ASTM D3359 (Adhesion); ASTM D523 (Gloss),ASTM D1475; ASTM D4060; ASTM D522	DIN EN ISO 9117 (Drying/Curing); DIN EN ISO 2409 (Adhesion); DIN EN ISO 15184 (Hardness); DIN EN ISO 2813 (Gloss)	REACH: Regulation (EC) No. 1907/2006 (melamine/alkyd resins, curing agents, solvents)
Heat Resistant Enamel	IS 2932; IS 2933	ISO 12944 (Protective Coating Systems); ISO 4628 Series (Coating Degradation); ISO 2813 (Gloss),ISO 1518; ISO 2812	ASTM D2485 (Resistance to Heat of Coatings); ASTM D3359 (Adhesion); ASTM D4060 (Abrasion Resistance); ASTM D1308 (Chemical Resistance),ASTM D1475; ASTM D522; ASTM D523	DIN EN ISO 3248 (Heat Resistance); DIN EN ISO 2409 (Adhesion); DIN EN ISO 15184 (Hardness); DIN EN ISO 2812 (Chemical Resistance)	AMPP: SP 1; AMPP: SP 6/NACE No.3 where metal protection is required; REACH: Regulation (EC) No. 1907/2006
Machinery Enamel	IS 2932; IS 2933	ISO 12944 (Corrosion Protection); ISO 9227 (Salt Spray Testing); ISO 2409 (Adhesion); ISO 2808 (Film Thickness),ISO 1518; ISO 2812	ASTM B117 (Salt Spray Corrosion Testing); ASTM D610 (Rust Evaluation); ASTM D714 (Blistering); ASTM D3359 (Adhesion); ASTM D4060 (Abrasion Resistance),ASTM D1475; ASTM D522; ASTM D523	DIN EN ISO 12944 series (Corrosion Protection); DIN EN ISO 9227 (Salt Spray); DIN EN ISO 2409 (Adhesion); DIN EN ISO 4628 (Coating Defects); DIN EN ISO 2808 (Thickness)	AMPP: SP 1; AMPP: SP 2; AMPP: SP 3; AMPP: SP 6/NACE No.3; REACH: Regulation (EC) No. 1907/2006
Automotive Enamel	IS 2932; IS 2933	ISO 2409 (Adhesion); ISO 2813 (Gloss); ISO 11507 (Weathering Resistance); ISO 16750 (Road	ASTM D523 (Gloss); ASTM D3359 (Adhesion); ASTM D3363 (Hardness); ASTM G154 (UV Weathering); ASTM	DIN EN ISO 2409 (Adhesion); DIN EN ISO 2813 (Gloss); DIN EN ISO 15184 (Hardness); DIN EN ISO	REACH: Regulation (EC) No. 1907/2006 (VOC, pigments, solvents, restricted substances)

Product / Application	BIS	ISO	ASTM	DIN	Other Standards(SSPC,AMPP, REACH, FDA)
		Vehicle Environmental Testing where applicable),ISO 1518; ISO 2812	B117 (Corrosion Resistance),ASTM D1475; ASTM D4060; ASTM D522	16474 (Weathering); DIN EN ISO 9227 (Corrosion Testing)	
Metal Enamel	IS 2932 (if synthetic metal enamel); IS 2933	ISO 12944 (Corrosion Protection); ISO 8501 (Surface Preparation); ISO 2409 (Adhesion),ISO 1518; ISO 2812	ASTM B117 (Salt Spray); ASTM D610 (Rust Evaluation); ASTM D3359 (Adhesion); ASTM D4541 (Pull-Off Adhesion Strength); ASTM D7091 (Dry Film Thickness),ASTM D1475; ASTM D4060; ASTM D522; ASTM D523	DIN EN ISO 12944 series; DIN EN ISO 9227; DIN EN ISO 2409; DIN EN ISO 4628; DIN EN ISO 2808	AMPP: SP 1; AMPP: SP 6/NACE No.3; REACH: Regulation (EC) No. 1907/2006
Wood Enamel	IS 2932 (if synthetic enamel); IS 2933	ISO 2409 (Adhesion); ISO 2813 (Gloss); ISO 11507 (Weathering Resistance),ISO 1518; ISO 2812	ASTM D3023 (Evaluation of Coatings Applied to Wood Products); ASTM D4446 (Water Repellency of Wood); ASTM D3359 (Adhesion); ASTM D523 (Gloss),ASTM D1475; ASTM D4060; ASTM D522	DIN EN 927 series (Wood Coating Systems); DIN EN ISO 2409; DIN EN ISO 2813; DIN EN ISO 4628; DIN EN ISO 7783	REACH: Regulation (EC) No. 1907/2006 (solvents, pigments, preservatives)
Anti-Corrosive Enamel	IS 2932; IS 2933	ISO 12944 (Corrosion Protection); ISO 9227 (Salt Spray); ISO 8501 (Surface Preparation); ISO 4628 Series,ISO 1518; ISO 2812	ASTM B117 (Salt Spray); ASTM D1654 (Evaluation of Painted Specimens Subjected to Corrosive Environments); ASTM D610 (Rust Evaluation); ASTM D714 (Blister Evaluation); ASTM D7091 (Thickness Measurement),ASTM D1475; ASTM D3359; ASTM D4060; ASTM D522; ASTM D523	DIN EN ISO 12944 series; DIN EN ISO 9227 (Salt Spray); DIN EN ISO 4628 series; DIN EN ISO 2409; DIN EN ISO 8501-1 (Surface Preparation)	AMPP: SP 1; AMPP: SP 6/NACE No.3; AMPP: SP 10/NACE No.2 where required; REACH: Regulation (EC) No. 1907/2006
Industrial Enamel	IS 2932; IS 2933	ISO 12944 (Protective Coating Systems); ISO 2808 (Film Thickness); ISO 2409 (Adhesion); ISO 4624 (Pull-Off Adhesion),ISO 1518; ISO 2812	ASTM B117 (Corrosion Resistance); ASTM D3359 (Adhesion); ASTM D4541 (Pull-Off Strength); ASTM D4060 (Abrasion Resistance); ASTM D1308 (Chemical Resistance),ASTM D1475; ASTM D522; ASTM D523	DIN EN ISO 12944 series; DIN EN ISO 2409; DIN EN ISO 4624; DIN EN ISO 2812; DIN EN ISO 9227	AMPP: SP 1; AMPP: SP 6/NACE No.3; AMPP: SP 10/NACE No.2 for protective systems; REACH: Regulation (EC) No. 1907/2006

Source field: Dyes and Pigments