Hot Melt Adhesives

Product / Application	BIS	ISO	ASTM	DIN	Other Standards(SSPC,AMPP, REACH, FDA)
EVA Hot Melt Adhesive	IS 13360; IS 13575	ISO 4587 (Tensile Shear Strength); ISO 11339 (Peel Strength); ISO 10365 (Failure Classification),ISO 1133; ISO 2555	ASTM D1002 (Lap Shear Strength); ASTM D1876 (T-Peel Resistance); ASTM D903 (Peel Strength); ASTM D3165 (Shear Strength of Adhesives); ASTM D2979 (Tack of Pressure Sensitive Adhesives where applicable),ASTM D1557; ASTM D1993; ASTM D3236; ASTM D4498; ASTM D4499	DIN EN 1465 (Adhesives — Tensile Lap-Shear Strength); DIN EN ISO 11339 (Adhesives — T-Peel Test); DIN EN ISO 9142 (Adhesive Bond Durability); DIN EN ISO 10365 (Designation of Main Failure Patterns); DIN EN ISO 527 (Mechanical Properties of Polymer Materials where applicable)	REACH: Regulation (EC) No. 1907/2006 (EVA polymer additives, tackifiers, residual monomers); FDA: 21 CFR 175.105 where used in food packaging
Polyolefin Hot Melt Adhesive	IS 13360; IS 13575	ISO 4587 (Adhesive Bond Strength); ISO 10365 (Failure Classification); ISO 527 (Mechanical Properties where applicable),ISO 1133; ISO 2555	ASTM D1002 (Lap Shear Strength); ASTM D903 (Peel Strength); ASTM D1876 (T-Peel Strength); ASTM D3165 (Adhesive Shear Strength); ASTM D3359 (Adhesion),ASTM D1557; ASTM D1993; ASTM D3236; ASTM D4498; ASTM D4499	DIN EN 1465 (Lap Shear Strength); DIN EN ISO 11339 (Peel Strength); DIN EN ISO 9142 (Durability); DIN EN ISO 10365 (Failure Classification); DIN EN ISO 527 (Mechanical Properties)	REACH: Regulation (EC) No. 1907/2006 (polyolefin polymers, additives); FDA: 21 CFR 175.105 where food-contact adhesive applications apply
Polyamide Hot Melt Adhesive	IS 13360; IS 13575	ISO 4587 (Tensile Shear Strength); ISO 11339 (Peel Strength); ISO 10365,ISO 1133; ISO 2555	ASTM D1002 (Lap Shear Strength); ASTM D1876 (T-Peel Strength); ASTM D903 (Peel Strength); ASTM D3165 (Shear Strength); ASTM D2240 (Hardness where applicable),ASTM D1557; ASTM D1993; ASTM D3236; ASTM D4498; ASTM D4499	DIN EN 1465 (Shear Strength); DIN EN ISO 11339 (Peel Strength); DIN EN ISO 9142 (Durability); DIN EN ISO 10365 (Failure Modes); DIN EN ISO 527 (Mechanical Properties)	REACH: Regulation (EC) No. 1907/2006 (polyamide resins, additives); FDA: 21 CFR 175.105 where food-contact applications exist
Polyurethane Reactive (PUR) Hot Melt Adhesive	IS 13360; IS 13575	ISO 4587 (Tensile Shear Strength); ISO 11339 (Peel Strength); ISO 10365,ISO 1133; ISO 2555	ASTM D1002 (Lap Shear Strength); ASTM D1876 (T-Peel Strength); ASTM D903 (Peel Strength); ASTM D3165 (Shear Strength); ASTM D905 (Wood Adhesive Strength where applicable),ASTM D1557; ASTM D1993; ASTM D3236; ASTM D4498; ASTM D4499	DIN EN 1465 (Lap Shear Strength); DIN EN ISO 11339 (T-Peel Strength); DIN EN ISO 9142 (Durability of Adhesive Bonds); DIN EN ISO 10365 (Failure Pattern Classification); DIN EN 14257 (WATT 91 Heat Resistance for Wood Applications)	REACH: Regulation (EC) No. 1907/2006 (isocyanates, reactive polymers); REACH Annex XVII (diisocyanates); FDA: 21 CFR 175.105 where food-contact compliant systems are used
Pressure Sensitive Hot Melt Adhesive	IS 13360; IS 13575	ISO 29862 (Peel Adhesion); ISO 29863 (Shear Adhesion); ISO 29864 (Tensile Strength),ISO 1133; ISO 2555	ASTM D3330 (Peel Adhesion of Pressure Sensitive Tape); ASTM D3654 (Shear Adhesion); ASTM D2979 (Tack); ASTM D6252 (Peel Adhesion of Pressure Sensitive Labels); ASTM D1002 (Shear Strength),ASTM D1557; ASTM D1993; ASTM D3236; ASTM D4498; ASTM D4499	DIN EN ISO 29862 (Peel Adhesion Properties of Pressure-Sensitive Adhesive Tape); DIN EN ISO 29863 (Shear Adhesion); DIN EN ISO 29864 (Breaking Strength and Elongation); DIN EN 1939 (Adhesion Properties of Tape and Labels); DIN EN ISO 29861 (Tack Measurement)	REACH: Regulation (EC) No. 1907/2006 (tackifiers, polymers, additives); FDA: 21 CFR 175.105 for food-contact labels/tapes
Packaging Hot Melt Adhesive	IS 13360; IS 13575	ISO 4587 (Bond Strength); ISO 10365 (Failure Classification); ISO 11339 (Peel Strength),ISO 1133; ISO 2555	ASTM D903 (Peel Strength); ASTM D1002 (Lap Shear Strength); ASTM F88 (Seal Strength of Flexible Barrier Materials where packaging application applies); ASTM D1876 (T-Peel Strength),ASTM D1557; ASTM D1993; ASTM D3236; ASTM D4498; ASTM D4499	DIN EN 1465 (Lap Shear Strength); DIN EN ISO 11339 (Peel Strength); DIN EN ISO 9142 (Durability); DIN EN ISO 10365 (Failure Classification); DIN EN ISO 527 (Mechanical Properties for Laminates)	FDA: 21 CFR 175.105 (Adhesives); FDA 21 CFR 176.170/176.180 where used in food-contact paper structures; REACH: Regulation (EC) No. 1907/2006
Bookbinding Hot Melt	IS 13360; IS	ISO 4587 (Bond Strength); ISO	ASTM D903 (Peel Strength); ASTM	DIN EN ISO 1465 (Adhesive Bond	REACH: Regulation (EC) No.

Product / Application	BIS	ISO	ASTM	DIN	Other Standards(SSPC,AMPP, REACH, FDA)
Adhesive	13575	10365 (Failure Classification); ISO 12647 (Printing/Publishing Applications where applicable),ISO 1133; ISO 2555	D1002 (Lap Shear Strength); ASTM D1876 (T-Peel Strength); ASTM D3330 (Peel Adhesion where pressure-sensitive applications apply),ASTM D1557; ASTM D1993; ASTM D3236; ASTM D4498; ASTM D4499	Strength); DIN EN ISO 11339 (Peel Strength); DIN EN ISO 9142 (Durability); DIN EN ISO 10365 (Failure Mode); DIN EN 204 (Wood Adhesive Classification where applicable)	1907/2006 (polymers, additives); FDA: 21 CFR 175.105 only for food-contact applications
Woodworking Hot Melt Adhesive	IS 13360; IS 13575	ISO 12465 (Wood Adhesive Applications where applicable); ISO 4587 (Bond Strength); ISO 11339 (Peel Strength),ISO 1133; ISO 2555	ASTM D905 (Strength Properties of Adhesive Bonds in Shear by Compression Loading); ASTM D1002 (Shear Strength); ASTM D1876 (T-Peel Strength),ASTM D1557; ASTM D1993; ASTM D3236; ASTM D4498; ASTM D4499	DIN EN 204 (Classification of Thermoplastic Wood Adhesives); DIN EN 205 (Determination of Tensile Shear Strength of Wood Adhesives); DIN EN 14257 (WATT 91 Heat Resistance); DIN EN 14256 (Open Assembly Time)	REACH: Regulation (EC) No. 1907/2006 (polymers, additives, VOC); FDA: only food-contact wood applications
Edge Banding Hot Melt Adhesive	IS 13360; IS 13575	ISO 4587 (Bond Strength); ISO 10365 (Failure Classification); ISO 11339 (Peel Strength),ISO 1133; ISO 2555	ASTM D905 (Wood Adhesive Bond Strength); ASTM D1002 (Lap Shear Strength); ASTM D903 (Peel Strength); ASTM D1876 (T-Peel Strength),ASTM D1557; ASTM D1993; ASTM D3236; ASTM D4498; ASTM D4499	DIN EN 204 (Wood Adhesive Classification); DIN EN 205 (Shear Strength); DIN EN ISO 11339 (Peel Strength); DIN EN ISO 9142 (Durability); DIN EN 14257 (Heat Resistance)	REACH: Regulation (EC) No. 1907/2006 (EVA/PUR polymers, additives); FDA: only food-contact furniture applications
Textile Hot Melt Adhesive	IS 13360; IS 13575	ISO 105 Series (Textile Applications where applicable); ISO 4587 (Bond Strength); ISO 11339 (Peel Strength),ISO 1133; ISO 2555	ASTM D5034 (Breaking Strength of Textile Fabrics); ASTM D751 (Coated Fabric Testing); ASTM D1002 (Adhesive Shear Strength); ASTM D903 (Peel Strength),ASTM D1557; ASTM D1993; ASTM D3236; ASTM D4498; ASTM D4499	DIN EN ISO 13934 series (Textile Tensile Properties); DIN EN ISO 105 series (Colour Fastness where adhesive affects textile); DIN EN ISO 1465 (Shear Strength); DIN EN ISO 11339 (Peel Strength)	REACH: Regulation (EC) No. 1907/2006 (restricted chemicals, residual monomers, additives)
Automotive Hot Melt Adhesive	IS 13360; IS 13575	ISO 16750 (Road Vehicle Environmental Testing where applicable); ISO 4587 (Bond Strength); ISO 11343 (Impact Peel Test),ISO 1133; ISO 2555	ASTM D1002 (Lap Shear Strength); ASTM D3165 (Shear Strength); ASTM D1876 (T-Peel Strength); ASTM D3762 (Adhesive Bond Strength of Aluminium); ASTM D1183 (Adhesive Environmental Durability),ASTM D1557; ASTM D1993; ASTM D3236; ASTM D4498; ASTM D4499	DIN EN ISO 9142 (Environmental Durability); DIN EN 1465 (Lap Shear Strength); DIN EN ISO 11339 (Peel Strength); DIN EN ISO 10365 (Failure Classification); DIN EN ISO 16701 (Corrosion Control where applicable)	REACH: Regulation (EC) No. 1907/2006 (restricted substances, VOC, additives); REACH Annex XVII where applicable
Electronics Assembly Hot Melt Adhesive	IS 13360; IS 13575	ISO 4587 (Bond Strength); ISO 527 (Mechanical Properties where applicable); ISO 14644 (Cleanroom Applications where applicable),ISO 1133; ISO 2555	ASTM D1002 (Lap Shear Strength); ASTM D3165 (Shear Strength); ASTM D257 (Electrical Resistance where conductive applications apply); ASTM D149 (Dielectric Breakdown Voltage where insulating applications apply),ASTM D1557; ASTM D1993; ASTM D3236; ASTM D4498; ASTM D4499	DIN EN IEC 60093 (Volume Resistivity); DIN EN IEC 62631 series (Dielectric Properties); DIN EN IEC 60243 series (Electric Strength); DIN EN 1465 (Mechanical Bond Strength); DIN EN ISO 9142 (Durability)	REACH: Regulation (EC) No. 1907/2006 (SVHC substances, halogens, additives); RoHS Directive 2011/65/EU (where electronic assemblies are involved)
Hygiene Product Hot Melt Adhesive	IS 13360; IS 13575	ISO 4587 (Bond Strength); ISO 10993 Series (Biological Evaluation where skin-contact application applies); ISO 10365,ISO 1133; ISO 2555	ASTM D1002 (Shear Strength); ASTM D903 (Peel Strength); ASTM D1876 (T-Peel Strength); ASTM D3330 (Peel Adhesion); ASTM D2979 (Tack),ASTM D1557; ASTM D1993; ASTM D3236; ASTM D4498; ASTM D4499	DIN EN ISO 29862 (Peel Adhesion); DIN EN ISO 29863 (Shear Adhesion); DIN EN ISO 29861 (Tack); DIN EN 1465 (Shear Strength); DIN EN ISO 9142 (Durability)	REACH: Regulation (EC) No. 1907/2006 (skin-contact related substances, SVHC); FDA: applicable only for regulated medical/hygiene products requiring FDA compliance
Labeling Hot Melt Adhesive	IS 13360; IS 13575	ISO 29862 (Peel Adhesion); ISO 29863 (Shear Adhesion); ISO 29864	ASTM D3330 (Peel Adhesion); ASTM D3654 (Shear Adhesion); ASTM	DIN EN ISO 29862 (Peel Adhesion); DIN EN ISO 29863 (Shear Adhesion); DIN EN	REACH: Regulation (EC) No. 1907/2006; FDA: 21 CFR 175.105 for

Product / Application	BIS	ISO	ASTM	DIN	Other Standards(SSPC,AMPP, REACH, FDA)
		(Tensile Strength),ISO 1133; ISO 2555	D2979 (Tack); ASTM D6252 (Pressure Sensitive Label Peel Adhesion),ASTM D1557; ASTM D1993; ASTM D3236; ASTM D4498; ASTM D4499	ISO 29861 (Tack); DIN EN 1939 (Bond Strength); DIN EN ISO 9142 (Durability)	food-contact labels
Carton Sealing Hot Melt Adhesive	IS 13360; IS 13575	ISO 4587 (Tensile Shear Strength of Adhesive Bonds); ISO 11339 (T-Peel Strength); ISO 10365 (Adhesive Failure Classification),ISO 1133; ISO 2555	ASTM D903 (Peel Strength); ASTM D1002 (Lap Shear Strength); ASTM D1876 (T-Peel Strength); ASTM D3165 (Shear Strength),ASTM D1557; ASTM D1993; ASTM D3236; ASTM D4498; ASTM D4499	DIN EN ISO 1465 (Lap Shear Strength); DIN EN ISO 11339 (Peel Strength); DIN EN ISO 9142 (Durability); DIN EN ISO 10365 (Failure Classification)	REACH: Regulation (EC) No. 1907/2006; FDA: 21 CFR 175.105 where cartons are food-contact packaging
Case & Carton Closing Adhesive	IS 13360; IS 13575	ISO 4587 (Bond Strength); ISO 10365 (Failure Classification); ISO 11339 (Peel Strength),ISO 1133; ISO 2555	ASTM D1002 (Lap Shear Strength); ASTM D903 (Peel Strength); ASTM D1876 (T-Peel Strength),ASTM D1557; ASTM D1993; ASTM D3236; ASTM D4498; ASTM D4499	DIN EN ISO 1465 (Shear Strength); DIN EN ISO 11339 (Peel Strength); DIN EN ISO 9142 (Durability); DIN EN ISO 10365 (Failure Pattern)	REACH: Regulation (EC) No. 1907/2006; FDA: 21 CFR 175.105 where used for food packaging
Assembly Hot Melt Adhesive	IS 13360; IS 13575	ISO 4587 (Tensile Shear Strength); ISO 10365 (Failure Classification),ISO 1133; ISO 2555	ASTM D1002 (Lap Shear Strength); ASTM D3165 (Shear Strength); ASTM D903 (Peel Strength),ASTM D1557; ASTM D1993; ASTM D3236; ASTM D4498; ASTM D4499	DIN EN ISO 1465 (Lap Shear Strength); DIN EN ISO 11339 (Peel Strength); DIN EN ISO 9142 (Durability); DIN EN ISO 10365 (Failure Classification)	REACH: Regulation (EC) No. 1907/2006 (polymers, additives, VOC); FDA: application dependent
Hot Melt Glue Stick	IS 13360; IS 13575	ISO 4587 (Bond Strength); ISO 10365 (Failure Classification),ISO 1133; ISO 2555	ASTM D1002 (Lap Shear Strength); ASTM D903 (Peel Strength); ASTM D1876 (T-Peel Strength); ASTM D2240 (Hardness where applicable),ASTM D1557; ASTM D1993; ASTM D3236; ASTM D4498; ASTM D4499	DIN EN ISO 1465 (Bond Strength); DIN EN ISO 11339 (Peel Strength); DIN EN ISO 527 (Mechanical Properties); DIN EN ISO 9142 (Durability)	REACH: Regulation (EC) No. 1907/2006 (polymers, additives); FDA: only where intended for food-contact applications
Low Temperature Hot Melt Adhesive	IS 13360; IS 13575	ISO 4587 (Bond Strength); ISO 11339 (Peel Strength); ISO 10365,ISO 1133; ISO 2555	ASTM D1002 (Shear Strength); ASTM D903 (Peel Strength); ASTM D1876 (T-Peel Strength); ASTM D3359 (Adhesion),ASTM D1557; ASTM D1993; ASTM D3236; ASTM D4498; ASTM D4499	DIN EN ISO 1465 (Shear Strength); DIN EN ISO 11339 (Peel Strength); DIN EN ISO 9142 (Durability); DIN EN ISO 10365 (Failure Mode)	REACH: Regulation (EC) No. 1907/2006 (polymer additives, tackifiers); FDA: where food-contact compliant formulation is used
High Temperature Hot Melt Adhesive	IS 13360; IS 13575	ISO 4587 (Bond Strength); ISO 527 (Mechanical Properties); ISO 10365,ISO 1133; ISO 2555	ASTM D1002 (Lap Shear Strength); ASTM D3165 (Shear Strength); ASTM D2294 (Adhesive Bond Strength after Heat Exposure); ASTM D1876 (T-Peel Strength),ASTM D1557; ASTM D1993; ASTM D3236; ASTM D4498; ASTM D4499	DIN EN ISO 1465 (Lap Shear Strength); DIN EN ISO 11339 (Peel Strength); DIN EN ISO 9142 (Temperature/Environmental Durability); DIN EN 14257 (Heat Resistance); DIN EN ISO 10365 (Failure Classification)	REACH: Regulation (EC) No. 1907/2006 (high-temperature polymers, additives); FDA: where food-contact applications exist

Source field: Dyes and Pigments