# Industrial Paints

| Product / Application | BIS | ISO | ASTM | DIN | Other Standards(SSPC,AMPP, REACH, FDA) |
|---|---|---|---|---|---|
| Alkyd Industrial Paint | IS 101; IS 2074 | ISO 12944 (Corrosion Protection); ISO 2409 (Adhesion); ISO 2808 (Film Thickness); ISO 9227 (Salt Spray Testing), | ASTM D522 (Flexibility); ASTM D3359 (Adhesion); ASTM D523 (Gloss); ASTM D4060 (Abrasion Resistance); ASTM B117 (Corrosion Resistance),ASTM D1640; ASTM D4541; ASTM D7091; ASTM G154; ASTM G155 | DIN EN ISO 12944 series (Corrosion Protection Systems); DIN EN ISO 2409 (Adhesion); DIN EN ISO 2813 (Gloss); DIN EN ISO 4628 series (Coating Degradation); DIN EN ISO 9227 (Salt Spray) | AMPP: SP 1; AMPP: SP 6/NACE No.3; AMPP: SP 10/NACE No.2; REACH: Regulation (EC) No. 1907/2006 (solvents, pigments, driers, VOC) |
| Epoxy Industrial Paint | IS 101; IS 2074 | ISO 12944 (Corrosion Protection); ISO 9227 (Salt Spray Resistance); ISO 4624 (Pull-Off Adhesion); ISO 2409 (Adhesion),ISO 2808 | ASTM D4541 (Pull-Off Adhesion); ASTM B117 (Salt Spray); ASTM D4060 (Abrasion Resistance); ASTM D1308 (Chemical Resistance); ASTM D3359 (Adhesion),ASTM D1640; ASTM D7091; ASTM G154; ASTM G155 | DIN EN ISO 12944 series (Protective Coating Systems); DIN EN ISO 4624 (Pull-Off Adhesion); DIN EN ISO 2812 series (Resistance to Liquids); DIN EN ISO 9227 (Salt Spray); DIN EN ISO 2409 (Adhesion) | AMPP: SP 1; AMPP: SP 5/NACE No.1; AMPP: SP 6/NACE No.3; AMPP: SP 10/NACE No.2; REACH: Regulation (EC) No. 1907/2006 (epoxy resins, curing agents, VOC, SVHC) |
| Polyurethane (PU) Paint | IS 101; IS 2074 | ISO 12944 (Protective Coating Systems); ISO 11507 (Weathering); ISO 2813 (Gloss); ISO 4624 (Adhesion),ISO 2409; ISO 2808 | ASTM D4541 (Adhesion); ASTM D4060 (Abrasion Resistance); ASTM D3363 (Hardness); ASTM G154 (UV Weathering); ASTM D1308 (Chemical Resistance),ASTM B117; ASTM D1640; ASTM D7091; ASTM G155 | DIN EN ISO 12944 series; DIN EN ISO 2409; DIN EN ISO 4624; DIN EN ISO 2813; DIN EN ISO 16474 (Weathering) | AMPP: SP 1; AMPP: SP 6/NACE No.3; AMPP: SP 10/NACE No.2; REACH: Regulation (EC) No. 1907/2006 (isocyanates, solvents); REACH Annex XVII (diisocyanates) |
| Acrylic Industrial Paint | IS 101; IS 2074 | ISO 12944 (Protective Coating Systems); ISO 2409 (Adhesion); ISO 2808 (Film Thickness), | ASTM D3359 (Adhesion); ASTM D523 (Gloss); ASTM D4587 (UV Resistance); ASTM D4060 (Abrasion Resistance),ASTM B117; ASTM D1640; ASTM D4541; ASTM D7091; ASTM G154; ASTM G155 | DIN EN ISO 12944 series; DIN EN ISO 2409; DIN EN ISO 2813; DIN EN ISO 16474; DIN EN ISO 9227 | AMPP: SP 1; AMPP: SP 6/NACE No.3; AMPP: SP 10/NACE No.2; REACH: Regulation (EC) No. 1907/2006 |
| Polyester Paint | IS 101; IS 2074 | ISO 12944 (Corrosion Protection); ISO 2813 (Gloss); ISO 11507 (Weathering Resistance),ISO 2409; ISO 2808 | ASTM D3359 (Adhesion); ASTM D523 (Gloss); ASTM D4541 (Pull-Off Adhesion); ASTM D4060 (Abrasion Resistance),ASTM B117; ASTM D1640; ASTM D7091; ASTM G154; ASTM G155 | DIN EN ISO 12944 series; DIN EN ISO 2409; DIN EN ISO 2813; DIN EN ISO 4628 series | AMPP: SP 1; AMPP: SP 6/NACE No.3 where applied on metal; REACH: Regulation (EC) No. 1907/2006 |
| Chlorinated Rubber Paint | IS 101; IS 2074 | ISO 12944 (Corrosion Protection); ISO 9227 (Salt Spray); ISO 4628 Series,ISO 2409; ISO 2808 | ASTM D3359 (Adhesion); ASTM B117 (Salt Spray); ASTM D1308 (Chemical Resistance); ASTM D4060 (Abrasion Resistance),ASTM D1640; ASTM D4541; ASTM D7091; ASTM G154; ASTM G155 | DIN EN ISO 12944 series; DIN EN ISO 2409; DIN EN ISO 2812 (Chemical Resistance); DIN EN ISO 9227 | AMPP: SP 1; AMPP: SP 6/NACE No.3; REACH: Regulation (EC) No. 1907/2006 (chlorinated compounds, solvents) |
| Vinyl Paint | IS 101; IS 2074 | ISO 12944 (Protective Coating Systems); ISO 2409 (Adhesion); ISO 2808 (Film Thickness), | ASTM D3359 (Adhesion); ASTM D523 (Gloss); ASTM D1308 (Chemical Resistance); ASTM D4060 (Abrasion Resistance),ASTM B117; ASTM D1640; ASTM D4541; ASTM D7091; ASTM G154; ASTM G155 | DIN EN ISO 12944 series; DIN EN ISO 2409; DIN EN ISO 2812; DIN EN ISO 16474 | AMPP: SP 1; AMPP: SP 6/NACE No.3; REACH: Regulation (EC) No. 1907/2006 (PVC additives, plasticisers) |
| Silicone Paint | IS 101; IS 2074 | ISO 11507 (Weathering Resistance); ISO 12944 (Protective Coatings); ISO 2813 (Gloss),ISO 2409; ISO 2808 | ASTM D2485 (High Temperature Resistance); ASTM D4587 (Weathering); ASTM D523 (Gloss); ASTM D4541 (Adhesion),ASTM B117; ASTM D1640; ASTM D4060; ASTM D7091; ASTM G154; ASTM G155 | DIN EN ISO 12944; DIN EN ISO 16474; DIN EN ISO 2409; DIN EN ISO 2813 | REACH: Regulation (EC) No. 1907/2006 (siloxanes, additives); AMPP where used in industrial protective systems |
| Zinc Rich Paint | IS 101; IS 2074 | ISO 12944 (Corrosion Protection); ISO 8501 (Surface Preparation); ISO 9227 (Salt Spray | ASTM D520 (Zinc Dust Pigment Specification); ASTM B117 (Salt Spray); ASTM D1654 (Corrosion Evaluation); | DIN EN ISO 12944-5 (Protective Paint Systems); DIN EN ISO 12944-6 (Laboratory Performance | AMPP: SP 5/NACE No.1; AMPP: SP 6/NACE No.3; AMPP: SP 10/NACE No.2; AMPP Paint 20 (Zinc-Rich |

| Product / Application | BIS | ISO | ASTM | DIN | Other Standards(SSPC,AMPP, REACH, FDA) |
|---|---|---|---|---|---|
| | | Resistance),ISO 2409; ISO 2808 | ASTM D7091 (Dry Film Thickness),ASTM D1640; ASTM D4060; ASTM D4541; ASTM G154; ASTM G155 | Testing); DIN EN ISO 9227 (Salt Spray); DIN EN ISO 2808 (Dry Film Thickness) | Primers); REACH: Regulation (EC) No. 1907/2006 (zinc compounds) |
| High Temperature Paint | IS 101; IS 2074 | ISO 12944 (Protective Coating Systems); ISO 2813 (Gloss); ISO 4628 Series,ISO 2409; ISO 2808 | ASTM D2485 (Resistance to Heat of Coatings); ASTM D3359 (Adhesion); ASTM D4541 (Pull-Off Adhesion); ASTM D4060 (Abrasion Resistance),ASTM B117; ASTM D1640; ASTM D7091; ASTM G154; ASTM G155 | DIN EN ISO 12944 (Protective Coatings where applicable); DIN EN ISO 2812 (Resistance to Liquids); DIN EN ISO 2409 (Adhesion); DIN EN ISO 15184 (Hardness) | AMPP: SP 1 (Solvent Cleaning); AMPP: SP 6/NACE No.3 (Commercial Blast Cleaning) where applied on steel; REACH: Regulation (EC) No. 1907/2006 (heat-resistant pigments, binders, solvents, additives) |
| Heat Resistant Paint | IS 101; IS 2074 | ISO 12944 (Protective Coating Systems); ISO 2813 (Gloss); ISO 4628 Series,ISO 2409; ISO 2808 | ASTM D2485 (High Temperature Resistance); ASTM D3359 (Adhesion); ASTM D523 (Gloss); ASTM D1308 (Chemical Resistance),ASTM B117; ASTM D1640; ASTM D4060; ASTM D4541; ASTM D7091; ASTM G154; ASTM G155 | DIN EN ISO 12944; DIN EN ISO 2409; DIN EN ISO 2812; DIN EN ISO 4628 | AMPP: SP 1; AMPP: SP 6/NACE No.3 for metal substrates; REACH: Regulation (EC) No. 1907/2006 (heat-resistant additives, pigments, binders) |
| Chemical Resistant Paint | IS 101; IS 2074 | ISO 2812 Series (Resistance to Liquids); ISO 12944 (Protective Coatings); ISO 4624 (Adhesion),ISO 2409; ISO 2808 | ASTM D1308 (Chemical Resistance); ASTM D543 (Chemical Resistance of Plastics where applicable); ASTM D4541 (Adhesion); ASTM D4060 (Abrasion Resistance),ASTM B117; ASTM D1640; ASTM D7091; ASTM G154; ASTM G155 | DIN EN ISO 2812 series (Resistance to Liquids); DIN EN ISO 2409; DIN EN ISO 4624; DIN EN ISO 12944 | AMPP: SP 1; AMPP: SP 6/NACE No.3; AMPP: SP 10/NACE No.2 for severe-service metal substrates; REACH: Regulation (EC) No. 1907/2006 (resins, curing agents, solvents, additives) |
| Marine Paint | IS 101; IS 2074 | ISO 12944 (Corrosion Protection of Steel Structures by Protective Paint Systems); ISO 20340 (Performance Requirements for Offshore Protective Paint Systems); ISO 9227 (Salt Spray Testing),ISO 2409; ISO 2808 | ASTM D610 (Rust Evaluation); ASTM D714 (Blistering); ASTM B117 (Salt Spray); ASTM D1654 (Corrosion Evaluation); ASTM D4541 (Adhesion),ASTM D1640; ASTM D4060; ASTM D7091; ASTM G154; ASTM G155 | DIN EN ISO 12944 series; DIN EN ISO 9227 (Salt Spray); DIN EN ISO 4628 series; DIN EN ISO 2409; DIN EN ISO 2812 | AMPP: SP 1 (Solvent Cleaning); AMPP: SP 5/NACE No.1 (White Metal Blast Cleaning); AMPP: SP 6/NACE No.3 (Commercial Blast Cleaning); AMPP: SP 10/NACE No.2 (Near White Blast Cleaning); REACH: Regulation (EC) No. 1907/2006 (antifouling agents, biocides, VOC, restricted substances) |
| Offshore Protective Paint | IS 101; IS 2074 | ISO 20340 (Offshore Protective Coating Performance); ISO 12944; ISO 8501 (Surface Preparation),ISO 2409; ISO 2808 | ASTM D5894 (Cyclic Salt Fog/UV Exposure); ASTM B117 (Salt Spray); ASTM D4541 (Pull-Off Adhesion); ASTM D610 (Rust Evaluation),ASTM D1640; ASTM D4060; ASTM D7091; ASTM G154; ASTM G155 | DIN EN ISO 12944-9 (Offshore and Related Structures); DIN EN ISO 9227; DIN EN ISO 4628; DIN EN ISO 2409 | AMPP: SP 5/NACE No.1; AMPP: SP 10/NACE No.2; AMPP: SP 6/NACE No.3; AMPP: offshore protective coating practices; REACH: Regulation (EC) No. 1907/2006 (anticorrosive pigments, solvents, biocides) |
| Automotive Refinish Paint | IS 101; IS 2074 | ISO 2813 (Gloss); ISO 2409 (Adhesion); ISO 11507 (Weathering Resistance),ISO 2808 | ASTM D523 (Gloss); ASTM D3359 (Adhesion); ASTM D3363 (Hardness); ASTM D4587 (Weathering); ASTM D4060 (Abrasion Resistance),ASTM B117; ASTM D1640; ASTM D4541; ASTM D7091; ASTM G154; ASTM G155 | DIN EN ISO 2409; DIN EN ISO 2813; DIN EN ISO 15184; DIN EN ISO 16474; DIN EN ISO 4628 | REACH: Regulation (EC) No. 1907/2006 (VOC, solvents, pigments, isocyanates in PU systems); REACH Annex XVII (diisocyanates where applicable) |
| OEM Automotive Paint | IS 101; IS 2074 | ISO 12944 (Corrosion Protection); ISO 2813 (Gloss); ISO 2409 (Adhesion),ISO 2808 | ASTM D3359 (Adhesion); ASTM D523 (Gloss); ASTM B117 (Corrosion); ASTM D4587 (Weathering); ASTM D3363 (Hardness),ASTM D1640; ASTM D4060; ASTM D4541; ASTM D7091; ASTM G154; ASTM G155 | DIN EN ISO 2409; DIN EN ISO 2813; DIN EN ISO 9227; DIN EN ISO 16474; DIN EN ISO 15184 | REACH: Regulation (EC) No. 1907/2006 (restricted substances, VOC, pigments, coatings additives); REACH Annex XVII restrictions applicable to automotive coatings |
| Coil Coating Paint | IS 101; IS 2074 | ISO 12944 (Corrosion Protection); ISO 2813 (Gloss); ISO 2409 (Adhesion),ISO 2808 | ASTM D2794 (Impact Resistance); ASTM D522 (Flexibility); ASTM D3359 (Adhesion); ASTM B117 (Salt Spray); ASTM D3363 (Hardness),ASTM D1640; ASTM D4060; ASTM D4541; ASTM D7091; ASTM G154; ASTM G155 | DIN EN 10169 (Organic Coated Steel Flat Products); DIN EN ISO 2409 (Cross-Cut Adhesion); DIN EN ISO 2813 (Gloss); DIN EN ISO 6272 (Impact Resistance); DIN EN ISO 1519 (Bend Test); DIN EN ISO 9227 | AMPP: SP 1 (Solvent Cleaning); REACH: Regulation (EC) No. 1907/2006 (chromates, pigments, solvents, additives); FDA: 21 CFR 175.300 only when coated metal is intended for food-contact applications |

| Product / Application | BIS | ISO | ASTM | DIN | Other Standards(SSPC,AMPP, REACH, FDA) |
|---|---|---|---|---|---|
| | | | | (Salt Spray Corrosion Testing); DIN EN ISO 12944 (Corrosion Protection Systems) | |
| Container Coating Paint | IS 101; IS 2074 | ISO 2812 Series (Chemical Resistance); ISO 12944 (Protective Coating); ISO 2409 (Adhesion),ISO 2808 | ASTM D3359 (Adhesion); ASTM D1308 (Chemical Resistance); ASTM B117 (Corrosion); ASTM D4541 (Adhesion Strength),ASTM D1640; ASTM D4060; ASTM D7091; ASTM G154; ASTM G155 | DIN EN ISO 12944 series (Protective Coating Systems); DIN EN ISO 2409 (Adhesion); DIN EN ISO 2812 series (Resistance to Liquids); DIN EN ISO 4628 series (Coating Degradation); DIN EN ISO 9227 (Corrosion Resistance) | AMPP: SP 1; AMPP: SP 10/NACE No.2 where steel substrate preparation is required; REACH: Regulation (EC) No. 1907/2006 (epoxy resins, BPA/BADGE-related substances, solvents); FDA: 21 CFR 175.300 (food-contact container coatings) |
| Machinery Paint | IS 101; IS 2074 | ISO 12944 (Corrosion Protection); ISO 9227 (Salt Spray); ISO 2409 (Adhesion),ISO 2808 | ASTM B117 (Salt Spray); ASTM D3359 (Adhesion); ASTM D4060 (Abrasion); ASTM D1308 (Chemical Resistance),ASTM D1640; ASTM D4541; ASTM D7091; ASTM G154; ASTM G155 | DIN EN ISO 12944 series (Industrial Corrosion Protection); DIN EN ISO 2409 (Adhesion); DIN EN ISO 2813 (Gloss); DIN EN ISO 4628 (Defects Evaluation); DIN EN ISO 9227 (Salt Spray) | AMPP: SP 1; AMPP: SP 2; AMPP: SP 3; AMPP: SP 6/NACE No.3; REACH: Regulation (EC) No. 1907/2006 (VOC, pigments, solvents, additives) |
| Equipment Paint | IS 101; IS 2074 | ISO 12944 (Protective Coating Systems); ISO 4628 Series; ISO 2808 (Thickness),ISO 2409 | ASTM B117 (Corrosion Resistance); ASTM D4541 (Adhesion); ASTM D4060 (Abrasion); ASTM D3359 (Adhesion),ASTM D1640; ASTM D7091; ASTM G154; ASTM G155 | DIN EN ISO 12944 series; DIN EN ISO 2409; DIN EN ISO 4624 (Pull-Off Adhesion); DIN EN ISO 2812 (Chemical Resistance); DIN EN ISO 9227 | AMPP: SP 1; AMPP: SP 6/NACE No.3; AMPP: SP 10/NACE No.2 for high-performance systems; REACH: Regulation (EC) No. 1907/2006 |
| Pipeline Paint | IS 101; IS 2074 | ISO 21809 Series (Pipeline Coatings); ISO 12944; ISO 8501 (Surface Preparation),ISO 2409; ISO 2808 | ASTM G62 (Holiday Detection of Pipeline Coatings); ASTM D4541 (Adhesion); ASTM B117 (Salt Spray); ASTM D7091 (Thickness Measurement),ASTM D1640; ASTM D4060; ASTM G154; ASTM G155 | DIN EN ISO 12944 series (Corrosion Protection); DIN EN ISO 21809 series (Petroleum and Natural Gas Pipeline External Coatings); DIN EN ISO 21809-1 (Polyolefin Coatings); DIN EN ISO 2409 (Adhesion); DIN EN ISO 2808 (Dry Film Thickness); DIN EN ISO 4624 (Pull-Off Adhesion); DIN EN ISO 21809-3 (Field Joint Coatings) | AMPP: SP 1; AMPP: SP 5/NACE No.1; AMPP: SP 10/NACE No.2; AMPP: SP 11 (Power Tool Cleaning to Bare Metal); REACH: Regulation (EC) No. 1907/2006 (epoxy systems, solvents, additives) |
| Tank Lining Paint | IS 101; IS 2074 | ISO 2812 Series (Chemical Resistance); ISO 4624 (Adhesion); ISO 12944,ISO 2409; ISO 2808 | ASTM D1308 (Chemical Resistance); ASTM D4541 (Adhesion); ASTM D5162 (Discontinuity Testing of Protective Coatings); ASTM B117 (Corrosion),ASTM D1640; ASTM D4060; ASTM D7091; ASTM G154; ASTM G155 | DIN EN ISO 12944; DIN EN ISO 2812 series (Resistance to Liquids); DIN EN ISO 4624 (Pull-Off Adhesion); DIN EN ISO 2409 (Adhesion); DIN EN ISO 8501 series (Surface Preparation); DIN EN ISO 8502 series (Surface Cleanliness); DIN EN ISO 8503 (Surface Roughness) | AMPP: SP 1; AMPP: SP 5/NACE No.1; AMPP: SP 10/NACE No.2; AMPP: SP 11; REACH: Regulation (EC) No. 1907/2006 (epoxy resins, curing agents, solvents); FDA: 21 CFR 175.300 where used for food-contact tanks |
| Road Marking Paint | IS 164:2019; IS 101; IS 2074 | ISO 7783 (Water Vapour Transmission); ISO 2813 (Gloss); ISO 2409 (Adhesion),ISO 2808 | ASTM D713 (Road Marking Materials where applicable); ASTM D4061 (Retroreflectance); ASTM D6628 (Color and Appearance of Pavement Markings); ASTM D3359 (Adhesion),ASTM B117; ASTM D1640; ASTM D4060; ASTM D4541; ASTM D7091; ASTM G154; ASTM G155 | DIN EN 1436 (Road Marking Materials — Performance for Road Users); DIN EN 1824 (Road Trial for Road Marking Materials); DIN EN 1871 (Road Marking Materials — Physical Properties); DIN EN ISO 2813 (Gloss); DIN EN ISO 4892 (Weathering); DIN EN ISO 2409 (Adhesion where applicable) | REACH: Regulation (EC) No. 1907/2006 (solvents, pigments, additives, reflective materials); REACH Annex XVII where restricted pigments/chemicals apply |
| Floor Paint | IS 101; IS 2074 | ISO 4624 (Adhesion); ISO 7784 Series (Abrasion Resistance); ISO 2813 (Gloss),ISO 2409; ISO 2808 | ASTM D4060 (Abrasion Resistance); ASTM D4541 (Adhesion); ASTM D2047 (Slip Resistance); ASTM D4259 (Surface Preparation),ASTM B117; ASTM D1640; ASTM D7091; ASTM G154; ASTM G155 | DIN EN 1504-2 (Surface Protection Systems for Concrete); DIN EN ISO 2409 (Adhesion); DIN EN ISO 4624 (Pull-Off Adhesion); DIN EN ISO 2813 (Gloss); DIN EN ISO 7784 | AMPP: SP 13/NACE No.6 (Concrete Surface Preparation); AMPP: SP 3/SP 11 where mechanical preparation is required; REACH: Regulation (EC) No. 1907/2006 (epoxy, PU, VOC, |

| Product / Application | BIS | ISO | ASTM | DIN | Other Standards(SSPC,AMPP, REACH, FDA) |
|---|---|---|---|---|---|
| | | | | (Abrasion Resistance); DIN 51130 (Slip Resistance of Flooring) | additives) |
| Anti-Corrosive Paint | IS 101; IS 2074 | ISO 12944; ISO 8501; ISO 9227; ISO 4628 Series,ISO 2409; ISO 2808 | ASTM B117 (Salt Spray); ASTM D610 (Rust Evaluation); ASTM D714 (Blistering); ASTM D1654 (Corrosion Evaluation); ASTM D7091 (Dry Film Thickness),ASTM D1640; ASTM D4060; ASTM D4541; ASTM G154; ASTM G155 | DIN EN ISO 12944 series (Corrosion Protection by Protective Paint Systems); DIN EN ISO 9227 (Salt Spray); DIN EN ISO 4628 series (Rust, Blistering, Cracking Evaluation); DIN EN ISO 2409 (Adhesion); DIN EN ISO 2808 (Dry Film Thickness); DIN EN ISO 8501-1 (Surface Preparation) | AMPP: SP 1; AMPP: SP 5/NACE No.1; AMPP: SP 6/NACE No.3; AMPP: SP 10/NACE No.2; AMPP coating system practices; REACH: Regulation (EC) No. 1907/2006 (heavy metals, pigments, solvents) |
| Intumescent Fire Protection Paint | IS 101; IS 2074 | ISO 834 (Fire Resistance Tests); ISO 1182 (Non-Combustibility Test); ISO 1716 (Heat Release); ISO 12944 (Protective Coating Systems),ISO 2409; ISO 2808 | ASTM E84 (Surface Burning Characteristics of Building Materials); ASTM E119 (Fire Tests of Building Construction and Materials); ASTM E605 (Thickness and Density of Sprayed Fire-Resistive Material); ASTM E736 (Cohesion/Adhesion of Sprayed Fire-Resistive Materials); ASTM E937 (Corrosion Resistance of Steel Components); ASTM E2924 (Application of Fire-Resistive Materials),ASTM B117; ASTM D1640; ASTM D4060; ASTM D4541; ASTM D7091; ASTM G154; ASTM G155 | DIN 4102 series (Fire Behaviour of Building Materials); DIN EN 13501-1 (Reaction to Fire Classification); DIN EN 13381-8 (Test Methods for Determining Contribution to Fire Resistance — Reactive Protection Applied to Steel Members); DIN EN ISO 11925-2 (Ignitability); DIN EN 13823 (Single Burning Item Test) | AMPP: SP 6/NACE No.3; AMPP: SP 10/NACE No.2 for steel structures; REACH: Regulation (EC) No. 1907/2006 (flame retardants, additives, SVHC substances) |
| Electrostatic Conductive Paint | IS 101; IS 2074 | ISO 2808 (Film Thickness); ISO 2409 (Adhesion); ISO 12944 (Protective Coating Systems); ISO 80079-36 (Explosive Atmosphere Applications where applicable), | ASTM D257 (DC Resistance or Conductance of Insulating Materials); ASTM F390 (Sheet Resistance Measurement); ASTM D3359 (Adhesion); ASTM D4060 (Abrasion Resistance); ASTM D523 (Gloss Measurement),ASTM B117; ASTM D1640; ASTM D4541; ASTM D7091; ASTM G154; ASTM G155 | DIN EN ISO 80079 series (Explosive Atmospheres — Electrostatic Requirements where applicable); DIN EN ISO 60079-0 (Electrical Equipment Requirements); DIN EN ISO 3915 (Electrical Resistivity of Conductive Plastics/Coatings); DIN EN ISO 2409 (Adhesion); DIN EN ISO 2808 (Thickness Measurement) | AMPP: SP 1; AMPP: SP 6/NACE No.3 where metal substrate preparation applies; REACH: Regulation (EC) No. 1907/2006 (conductive fillers, metals, additives) |

*Source field: Dyes and Pigments*