PU Adhesives

Product / Application	BIS	ISO	ASTM	DIN	Other Standards(SSPC,AMPP, REACH, FDA)
One Component PU Adhesive	IS 16481	ISO 4587 (Tensile Shear Strength); ISO 10365 (Failure Classification); ISO 527 (Mechanical Properties),ISO 16396; ISO 604	ASTM D1002 (Lap Shear Strength); ASTM D3165 (Shear Strength of Adhesives); ASTM D1876 (T-Peel Strength); ASTM D903 (Peel Strength); ASTM D1183 (Durability of Adhesive Bonds),ASTM D1184; ASTM D2556; ASTM D4501; ASTM D905	DIN EN 1465 (Adhesives — Tensile Lap-Shear Strength); DIN EN ISO 11339 (Adhesives — T-Peel Test); DIN EN ISO 9142 (Durability of Adhesive Bonds); DIN EN ISO 10365 (Designation of Main Failure Patterns); DIN EN 14257 (WATT 91 Heat Resistance for Wood Applications)	REACH: Regulation (EC) No. 1907/2006 (isocyanates, additives, VOC); REACH Annex XVII (diisocyanate restrictions); FDA: 21 CFR 175.105 where food-contact use exists
Two Component PU Adhesive	IS 16481	ISO 4587 (Bond Strength); ISO 11339 (Peel Strength); ISO 10365 (Failure Classification),ISO 16396; ISO 604	ASTM D1002 (Lap Shear Strength); ASTM D3165 (Adhesive Shear Strength); ASTM D1876 (T-Peel Strength); ASTM D903 (Peel Strength); ASTM D905 (Compression Shear Strength),ASTM D1184; ASTM D2556; ASTM D4501	DIN EN 1465 (Lap Shear Strength); DIN EN ISO 11339 (Peel Strength); DIN EN ISO 9142 (Environmental Durability); DIN EN ISO 10365 (Failure Classification); DIN EN ISO 527 (Mechanical Properties)	REACH: Regulation (EC) No. 1907/2006 (polyisocyanates, polyols, curing agents); REACH Annex XVII (diisocyanates); FDA: 21 CFR 175.105 where applicable
Reactive Polyurethane Adhesive	IS 16481	ISO 4587 (Bond Strength); ISO 11343 (Impact Peel Strength); ISO 10365,ISO 16396; ISO 604	ASTM D1002 (Lap Shear Strength); ASTM D3165 (Shear Strength); ASTM D1876 (T-Peel Strength); ASTM D1183 (Durability of Adhesive Bonds),ASTM D1184; ASTM D2556; ASTM D4501; ASTM D905	DIN EN 1465 (Tensile Lap-Shear Strength); DIN EN ISO 11339 (T-Peel Strength); DIN EN ISO 9142 (Durability); DIN EN ISO 10365 (Failure Modes); DIN EN ISO 527 (Polymer Mechanical Properties)	REACH: Regulation (EC) No. 1907/2006 (reactive isocyanates, curing chemistry); REACH Annex XVII (diisocyanates); FDA: 21 CFR 175.105 where food-contact compliant
Flexible PU Adhesive	IS 16481	ISO 11339 (T-Peel Strength); ISO 4587 (Bond Strength); ISO 10365,ISO 16396; ISO 604	ASTM D1876 (T-Peel Strength); ASTM D903 (Peel Strength); ASTM D1002 (Shear Strength); ASTM D2240 (Hardness where applicable),ASTM D1184; ASTM D2556; ASTM D3165; ASTM D4501; ASTM D905	DIN EN ISO 11339 (Peel Strength); DIN EN 1465 (Lap Shear Strength); DIN EN ISO 9142 (Flexibility and Durability); DIN EN ISO 10365 (Failure Pattern); DIN EN ISO 527 (Tensile Properties)	REACH: Regulation (EC) No. 1907/2006 (isocyanates, plasticisers, additives); REACH Annex XVII (diisocyanates)
Structural PU Adhesive	IS 16481	ISO 4587 (Bond Strength); ISO 11343 (Impact Peel Strength); ISO 10365,ISO 16396; ISO 604	ASTM D3165 (Shear Strength); ASTM D1002 (Lap Shear Strength); ASTM D3762 (Adhesive Bond Strength of Aluminium); ASTM D1876 (Peel Strength); ASTM D1183 (Environmental Durability),ASTM D1184; ASTM D2556; ASTM D4501; ASTM D905	DIN EN 1465 (Lap Shear Strength); DIN EN ISO 11339 (Peel Strength); DIN EN ISO 9142 (Environmental Resistance); DIN EN ISO 10365 (Adhesive Failure Classification); DIN EN ISO 527 (Mechanical Properties)	REACH: Regulation (EC) No. 1907/2006 (polyisocyanates, additives); AMPP: SP 1/SP 6 where used for prepared metal bonding
Wood Flooring PU Adhesive	IS 16481	ISO 17178 (Adhesives for Wood Flooring); ISO 4587 (Bond Strength); ISO 10365,ISO 16396; ISO 604	ASTM D905 (Strength Properties of Adhesive Bonds in Shear by Compression Loading); ASTM D1002 (Shear Strength); ASTM D1876 (Peel Strength); ASTM F710 (Preparation of Concrete Floors for Resilient Flooring),ASTM D1184; ASTM D2556; ASTM D3165; ASTM D4501	DIN EN 14293 (Adhesives for Floor Coverings — Testing Methods); DIN EN 14259 (Adhesives for Floor Coverings — Mechanical and Electrical Performance); DIN EN 205 (Wood Adhesive Shear Strength); DIN EN ISO 9142 (Durability)	REACH: Regulation (EC) No. 1907/2006 (isocyanates, solvents, additives); REACH Annex XVII (diisocyanates); FDA: —
Furniture PU Adhesive	IS 16481	ISO 4587 (Bond Strength); ISO 11339 (Peel Strength); ISO 10365,ISO 16396; ISO 604	ASTM D905 (Wood Adhesive Strength); ASTM D1002 (Lap Shear Strength); ASTM D903 (Peel Strength); ASTM D1876 (T-Peel Strength),ASTM D1184; ASTM D2556; ASTM D3165; ASTM D4501	DIN EN 204 (Classification of Thermoplastic Wood Adhesives); DIN EN 205 (Wood Adhesive Tensile Shear Strength); DIN EN 14257 (WATT 91 Heat Resistance); DIN EN ISO 9142 (Durability)	REACH: Regulation (EC) No. 1907/2006 (isocyanates, VOC, additives); REACH Annex XVII (diisocyanates)
Footwear PU Adhesive	IS 16481	ISO 17707 (Footwear Sole	ASTM D2209 (Strength Properties of	DIN EN 1392 (Adhesives for	REACH: Regulation (EC) No.

Product / Application	BIS	ISO	ASTM	DIN	Other Standards(SSPC,AMPP, REACH, FDA)
		Adhesion); ISO 4587 (Bond Strength); ISO 8510 (Peel Adhesion),ISO 16396; ISO 604	Adhesive Bonds in Footwear Materials); ASTM D903 (Peel Strength); ASTM D1002 (Shear Strength); ASTM D1876 (T-Peel Strength),ASTM D1184; ASTM D2556; ASTM D3165; ASTM D4501; ASTM D905	Leather and Footwear Materials — Test Methods); DIN EN 1465 (Lap Shear Strength); DIN EN ISO 11339 (Peel Strength); DIN EN ISO 9142 (Durability)	1907/2006 (solvents, isocyanates, restricted substances); REACH Annex XVII
Textile Lamination PU Adhesive	IS 16481	ISO 105 Series (Textile Performance where applicable); ISO 4587 (Bond Strength); ISO 11339 (Peel Strength),ISO 16396; ISO 604	ASTM D751 (Coated Fabrics Testing); ASTM D5034 (Breaking Strength of Textile Fabrics); ASTM D903 (Peel Strength); ASTM D1002 (Shear Strength),ASTM D1184; ASTM D2556; ASTM D3165; ASTM D4501; ASTM D905	DIN EN ISO 13934 series (Textile Tensile Properties); DIN EN ISO 11339 (Peel Strength); DIN EN 1465 (Shear Strength); DIN EN ISO 105 series (Colour Fastness after Bonding where applicable)	REACH: Regulation (EC) No. 1907/2006 (isocyanates, residual monomers, additives); REACH Annex XVII; FDA: only food-contact textile applications
Flexible Packaging PU Adhesive	IS 16481	ISO 4587 (Bond Strength); ISO 11339 (Peel Strength); ISO 10365; ISO 1186 Series (Migration Testing where food contact applies),ISO 16396; ISO 604	ASTM F88 (Seal Strength of Flexible Barrier Materials); ASTM D1876 (T-Peel Strength); ASTM D903 (Peel Strength); ASTM D1002 (Shear Strength); ASTM F2029 (Making Heat Seals for Packaging Applications where applicable),ASTM D1184; ASTM D2556; ASTM D3165; ASTM D4501; ASTM D905	DIN EN 1465 (Lap Shear Strength); DIN EN ISO 11339 (Peel Strength); DIN EN 14410 (Determination of Peel Adhesion of Laminated Materials where applicable); DIN EN ISO 9142 (Durability); DIN EN 13999 series (VOC Emission Testing)	FDA: 21 CFR 175.105 (Adhesives for food packaging); REACH: Regulation (EC) No. 1907/2006 (isocyanates, solvents, additives); REACH Annex XVII
Automotive PU Adhesive	IS 16481	ISO 16750 (Road Vehicle Environmental Testing); ISO 4587 (Bond Strength); ISO 11343 (Impact Peel Strength),ISO 16396; ISO 604	ASTM D1002 (Lap Shear Strength); ASTM D3165 (Shear Strength); ASTM D3762 (Metal Bonding Strength); ASTM D1876 (Peel Strength); ASTM D1183 (Durability Testing),ASTM D1184; ASTM D2556; ASTM D4501; ASTM D905	DIN EN ISO 9142 (Durability of Adhesive Bonds); DIN EN 1465 (Lap Shear Strength); DIN EN ISO 11339 (Peel Strength); DIN EN ISO 10365 (Failure Classification); DIN EN ISO 9227 (Corrosion Testing where bonded metal applications apply)	REACH: Regulation (EC) No. 1907/2006 (isocyanates, VOC, additives); REACH Annex XVII (diisocyanates)
Construction PU Adhesive	IS 16481	ISO 4587 (Bond Strength); ISO 10365 (Failure Classification); ISO 11339 (Peel Strength),ISO 16396; ISO 604	ASTM C557 (Adhesives for Installation of Gypsum Wallboard); ASTM D1002 (Lap Shear Strength); ASTM D903 (Peel Strength); ASTM D4541 (Pull-Off Adhesion Strength),ASTM D1184; ASTM D2556; ASTM D3165; ASTM D4501; ASTM D905	DIN EN 15651 series (Sealants for Building Applications); DIN EN ISO 11600 (Classification of Construction Sealants); DIN EN 1465 (Bond Strength); DIN EN ISO 9142 (Durability)	REACH: Regulation (EC) No. 1907/2006 (isocyanates, VOC, additives); REACH Annex XVII
Sandwich Panel PU Adhesive	IS 16481	ISO 4587 (Bond Strength); ISO 527 (Mechanical Properties); ISO 10365,ISO 16396; ISO 604	ASTM C297 (Flatwise Tensile Strength of Sandwich Constructions); ASTM D1002 (Shear Strength); ASTM D903 (Peel Strength); ASTM D3165 (Adhesive Shear Strength),ASTM D1184; ASTM D2556; ASTM D4501; ASTM D905	DIN EN 14509 (Self-Supporting Insulated Sandwich Panels); DIN EN ISO 527 (Mechanical Properties); DIN EN 1465 (Bond Strength); DIN EN ISO 11339 (Peel Strength); DIN EN ISO 9142 (Durability)	REACH: Regulation (EC) No. 1907/2006 (polyurethane systems, isocyanates); REACH Annex XVII
Glass Bonding PU Adhesive	IS 16481	ISO 4587 (Bond Strength); ISO 8510 (Peel Adhesion); ISO 10365,ISO 16396; ISO 604	ASTM D1002 (Lap Shear Strength); ASTM D903 (Peel Strength); ASTM D3165 (Shear Strength); ASTM D3359 (Adhesion),ASTM D1184; ASTM D2556; ASTM D4501; ASTM D905	DIN EN 1465 (Lap Shear Strength); DIN EN ISO 11339 (Peel Strength); DIN EN ISO 9142 (Environmental Durability); DIN EN ISO 10365 (Failure Modes)	REACH: Regulation (EC) No. 1907/2006 (isocyanates, additives); FDA: only food-contact glass applications
Metal Bonding PU Adhesive	IS 16481	ISO 4587 (Bond Strength); ISO 12944 (Corrosion Protection where applicable); ISO 10365,ISO 16396; ISO 604	ASTM D1002 (Lap Shear Strength); ASTM D3762 (Aluminium Adhesive Bond Strength); ASTM D3165 (Shear Strength); ASTM D903 (Peel Strength),ASTM D1184; ASTM D2556; ASTM D4501; ASTM D905	DIN EN 1465 (Lap Shear Strength); DIN EN ISO 11339 (Peel Strength); DIN EN ISO 9142 (Durability); DIN EN ISO 10365 (Failure Classification)	AMPP: SP 1/SP 2/SP 3 where metal preparation is required; REACH: Regulation (EC) No. 1907/2006 (isocyanates, additives)

Product / Application	BIS	ISO	ASTM	DIN	Other Standards(SSPC,AMPP, REACH, FDA)
Plastic Bonding PU Adhesive	IS 16481	ISO 4587 (Bond Strength); ISO 10365 (Failure Classification); ISO 527,ISO 16396; ISO 604	ASTM D3163 (Strength Properties of Adhesively Bonded Plastic Joints); ASTM D1002 (Shear Strength); ASTM D903 (Peel Strength); ASTM D3762 (Bond Strength where applicable),ASTM D1184; ASTM D2556; ASTM D3165; ASTM D4501; ASTM D905	DIN EN ISO 19069 series (Thermoplastic Mechanical Properties where applicable); DIN EN 1465 (Lap Shear Strength); DIN EN ISO 11339 (Peel Strength); DIN EN ISO 9142 (Durability)	REACH: Regulation (EC) No. 1907/2006 (isocyanates, additives, VOC); REACH Annex XVII
Moisture Cure PU Adhesive	IS 16481	ISO 4587 (Bond Strength); ISO 11339 (Peel Strength); ISO 10365,ISO 16396; ISO 604	ASTM D1002 (Lap Shear Strength); ASTM D1876 (T-Peel Strength); ASTM D903 (Peel Strength); ASTM D1183 (Durability),ASTM D1184; ASTM D2556; ASTM D3165; ASTM D4501; ASTM D905	DIN EN ISO 1465 (Shear Strength); DIN EN ISO 11339 (Peel Strength); DIN EN ISO 9142 (Humidity Resistance); DIN EN ISO 10365 (Failure Pattern)	REACH: Regulation (EC) No. 1907/2006 (moisture-reactive isocyanates); REACH Annex XVII (diisocyanates)
Solvent-Free PU Adhesive	IS 16481	ISO 4587 (Bond Strength); ISO 11339 (Peel Strength); ISO 10365,ISO 16396; ISO 604	ASTM D1002 (Lap Shear Strength); ASTM D903 (Peel Strength); ASTM D1876 (T-Peel Strength); ASTM D2369 (VOC Content where low solvent claim applies),ASTM D1184; ASTM D2556; ASTM D3165; ASTM D4501; ASTM D905	DIN EN 13999 series (VOC Emission Testing); DIN EN 1465 (Shear Strength); DIN EN ISO 11339 (Peel Strength); DIN EN ISO 9142 (Durability)	REACH: Regulation (EC) No. 1907/2006 (isocyanates, reactive components); REACH Annex XVII
Low VOC PU Adhesive	IS 16481	ISO 11890-2 (VOC Content); ISO 4587 (Bond Strength); ISO 10365,ISO 16396; ISO 604	ASTM D2369 (Volatile Content); ASTM D3960 (VOC Determination); ASTM D1002 (Shear Strength); ASTM D903 (Peel Strength),ASTM D1184; ASTM D2556; ASTM D3165; ASTM D4501; ASTM D905	DIN EN 13999 series (VOC Emissions from Adhesives); DIN EN ISO 11890-2 (VOC Content Determination); DIN EN 1465 (Bond Strength); DIN EN ISO 9142 (Durability)	REACH: Regulation (EC) No. 1907/2006; EU VOC Directive 2004/42/EC where applicable; REACH Annex XVII
High Strength PU Adhesive	IS 16481	ISO 4587 (Bond Strength); ISO 11343 (Impact Peel Strength); ISO 10365,ISO 16396; ISO 604	ASTM D3165 (Shear Strength); ASTM D1002 (Lap Shear Strength); ASTM D3762 (Bond Strength); ASTM D1183 (Durability),ASTM D1184; ASTM D2556; ASTM D4501; ASTM D905	DIN EN 1465 (Lap Shear Strength); DIN EN ISO 11339 (Peel Strength); DIN EN ISO 9142 (Durability); DIN EN ISO 10365 (Failure Classification)	REACH: Regulation (EC) No. 1907/2006 (polyisocyanates, additives); REACH Annex XVII

Source field: Dyes and Pigments