Surface Coatings

Product / Application	BIS	ISO	ASTM	DIN	Other Standards(SSPC,AMPP, REACH, FDA)
Acrylic Surface Coating	IS 14182	ISO 2409 (Cross-Cut Adhesion); ISO 2813 (Gloss Measurement); ISO 2808 (Film Thickness); ISO 11507 (Artificial Weathering),ISO 15013	ASTM D3359 (Adhesion); ASTM D523 (Gloss); ASTM D4060 (Abrasion Resistance); ASTM D4587 (UV Weathering); ASTM D2244 (Colour Change); ASTM D2369 (VOC Content),ASTM B117; ASTM D4541; ASTM D7091; ASTM G14; ASTM G154; ASTM G155; ASTM G20	DIN EN ISO 2409 (Cross-Cut Adhesion); DIN EN ISO 2813 (Gloss); DIN EN ISO 15184 (Pencil Hardness); DIN EN ISO 6272 (Impact Resistance); DIN EN ISO 16474 (Artificial Weathering); DIN EN ISO 4628 Series (Coating Degradation Evaluation)	REACH: Regulation (EC) No. 1907/2006 (acrylic polymers, residual monomers, VOC, additives); AMPP: SP 1/SP 6 where applied as protective coating on metallic substrates
Epoxy Surface Coating	IS 14182	ISO 12944 (Corrosion Protection of Steel Structures by Protective Paint Systems); ISO 9227 (Salt Spray Testing); ISO 4624 (Pull-Off Adhesion); ISO 2409 (Adhesion),ISO 15013; ISO 2808	ASTM D4541 (Pull-Off Adhesion); ASTM B117 (Salt Spray Corrosion); ASTM D4060 (Abrasion Resistance); ASTM D1308 (Chemical Resistance); ASTM D3359 (Adhesion),ASTM D7091; ASTM G14; ASTM G154; ASTM G155; ASTM G20	DIN EN ISO 12944 series (Corrosion Protection by Protective Paint Systems); DIN EN ISO 4624 (Pull-Off Adhesion); DIN EN ISO 2812 series (Resistance to Liquids); DIN EN ISO 9227 (Salt Spray); DIN EN ISO 2409 (Adhesion)	AMPP: SP 1 (Solvent Cleaning); AMPP: SP 5/NACE No.1 (White Metal Blast Cleaning); AMPP: SP 6/NACE No.3 (Commercial Blast Cleaning); AMPP: SP 10/NACE No.2 (Near White Blast Cleaning); REACH: Regulation (EC) No. 1907/2006 (epoxy resins, curing agents, VOC, SVHC substances)
Polyurethane Surface Coating	IS 14182	ISO 12944 (Protective Coating Systems); ISO 11507 (Artificial Weathering); ISO 2813 (Gloss); ISO 4628 Series (Coating Degradation),ISO 15013; ISO 2808	ASTM D4541 (Pull-Off Adhesion); ASTM D4060 (Abrasion Resistance); ASTM D3363 (Hardness); ASTM G154 (UV Exposure); ASTM D1308 (Chemical Resistance),ASTM B117; ASTM D7091; ASTM G14; ASTM G155; ASTM G20	DIN EN ISO 12944 series; DIN EN ISO 2409; DIN EN ISO 4624; DIN EN ISO 16474 (Weathering); DIN EN ISO 2813 (Gloss); DIN EN ISO 15184 (Hardness)	AMPP: SP 1; AMPP: SP 6/NACE No.3; AMPP: SP 10/NACE No.2 for protective applications; REACH: Regulation (EC) No. 1907/2006 (isocyanates, solvents, additives); REACH Annex XVII (diisocyanates)
Polyester Surface Coating	IS 14182	ISO 12944 (Corrosion Protection); ISO 2813 (Gloss Measurement); ISO 11507 (Weathering Resistance); ISO 2409 (Adhesion),ISO 15013; ISO 2808	ASTM D3359 (Adhesion); ASTM D523 (Gloss); ASTM D2794 (Impact Resistance); ASTM G154 (Weathering); ASTM B117 (Corrosion Resistance),ASTM D4060; ASTM D4541; ASTM D7091; ASTM G14; ASTM G155; ASTM G20	DIN EN ISO 12944 series; DIN EN ISO 2409; DIN EN ISO 6272 (Impact Resistance); DIN EN ISO 16474; DIN EN ISO 2813	AMPP: SP 1; AMPP: SP 6/NACE No.3 where metallic substrate protection is required; REACH: Regulation (EC) No. 1907/2006 (polyester resins, styrene, pigments, additives)
Silicone Surface Coating	IS 14182	ISO 11507 (Artificial Weathering); ISO 16474 Series (Artificial Radiation Exposure); ISO 2813 (Gloss); ISO 12944 (Protective Coating Systems),ISO 15013; ISO 2808	ASTM D2485 (Heat Resistance of Coatings); ASTM D523 (Gloss); ASTM D4541 (Adhesion); ASTM G154 (Weathering Resistance),ASTM B117; ASTM D4060; ASTM D7091; ASTM G14; ASTM G155; ASTM G20	DIN EN ISO 16474 (Weathering); DIN EN ISO 2409 (Adhesion); DIN EN ISO 2813 (Gloss); DIN EN ISO 12944 where protective use applies	AMPP: SP 1 where metallic substrate preparation is required; REACH: Regulation (EC) No. 1907/2006 (siloxanes, additives, restricted substances)
Fluoropolymer Surface Coating	IS 14182	ISO 16474 Series (Artificial Weathering); ISO 11507 (Weather Resistance); ISO 12944 (Protective Coating Systems); ISO 2813 (Gloss),ISO 15013; ISO 2808	ASTM G154 (UV Exposure); ASTM G155 (Xenon Arc Weathering); ASTM D523 (Gloss Retention); ASTM D3359 (Adhesion); ASTM D4060 (Abrasion Resistance),ASTM B117; ASTM D4541; ASTM D7091; ASTM G14; ASTM G20	DIN EN ISO 16474 series (Artificial Weathering); DIN EN ISO 4892 series (UV Exposure); DIN EN ISO 2813 (Gloss Retention); DIN EN ISO 2409 (Adhesion); DIN EN ISO 6272 (Impact Resistance)	AMPP: SP 1; AMPP: SP 6/NACE No.3 for metal substrates; REACH: Regulation (EC) No. 1907/2006 (fluoropolymers, additives); REACH restrictions for applicable PFAS substances
Ceramic Surface Coating	IS 14182	ISO 2409 (Adhesion); ISO 4624 (Pull-Off Adhesion); ISO 2813 (Gloss); ISO 2808 (Film Thickness),ISO 15013	ASTM C633 (Adhesion or Cohesion Strength of Thermal Spray Coatings where applicable); ASTM D3359 (Adhesion); ASTM D4060 (Abrasion Resistance); ASTM D4541 (Pull-Off Strength),ASTM B117; ASTM D7091; ASTM G14; ASTM G154; ASTM G155; ASTM G20	DIN EN ISO 2409 (Adhesion); DIN EN ISO 4624 (Pull-Off Strength); DIN EN ISO 6272 (Impact Resistance); DIN EN ISO 2813 (Gloss); DIN EN ISO 9227 (Corrosion Resistance where metallic substrate applies)	AMPP: SP 1/SP 6 where applied on metallic substrates; REACH: Regulation (EC) No. 1907/2006 (metal oxides, ceramic additives, heavy metal impurities)
Nano Coating	IS 14182	ISO 20566 (Scratch Resistance); ISO	ASTM D3359 (Adhesion); ASTM D4060	DIN EN ISO 2409 (Adhesion); DIN	REACH: Regulation (EC) No.

Product / Application	BIS	ISO	ASTM	DIN	Other Standards(SSPC,AMPP, REACH, FDA)
		2813 (Gloss); ISO 2409 (Adhesion); ISO 16474 (Weathering where applicable),ISO 15013; ISO 2808	(Abrasion Resistance); ASTM D3363 (Hardness); ASTM D523 (Gloss); ASTM D7334 (Surface Wettability where applicable),ASTM B117; ASTM D4541; ASTM D7091; ASTM G14; ASTM G154; ASTM G155; ASTM G20	EN ISO 15184 (Hardness); DIN EN ISO 6272 (Impact Resistance); DIN EN ISO 2813 (Gloss); DIN EN ISO 27448 (Water Repellency where applicable)	1907/2006 (nanomaterials, surface modifiers, SVHC substances); AMPP: SP 1 where applied on industrial metal substrates
Hydrophobic Coating	IS 14182	ISO 27448 (Evaluation of Superhydrophobic Properties where applicable); ISO 2409 (Adhesion); ISO 2813 (Gloss),ISO 15013; ISO 2808	ASTM D7334 (Surface Wettability of Coatings); ASTM D5946 (Contact Angle Measurement); ASTM D3359 (Adhesion); ASTM D523 (Gloss),ASTM B117; ASTM D4060; ASTM D4541; ASTM D7091; ASTM G14; ASTM G154; ASTM G155; ASTM G20	DIN EN ISO 27448 (Water Repellency of Hydrophobic Surfaces); DIN EN ISO 2409 (Adhesion); DIN EN ISO 2813 (Gloss); DIN EN ISO 16474 (Weathering)	REACH: Regulation (EC) No. 1907/2006 (silane/siloxane chemistry, fluorinated compounds where applicable); AMPP: SP 13/NACE No.6 where applied on concrete substrates
Oleophobic Coating	IS 14182	ISO 27448 (Surface Wettability Evaluation where applicable); ISO 2409 (Adhesion); ISO 2813 (Gloss),ISO 15013; ISO 2808	ASTM D7334 (Surface Wettability); ASTM D5946 (Contact Angle); ASTM D3359 (Adhesion); ASTM D4060 (Abrasion Resistance),ASTM B117; ASTM D4541; ASTM D7091; ASTM G14; ASTM G154; ASTM G155; ASTM G20	DIN EN ISO 27448 (Water Repellency/Surface Properties); DIN EN ISO 2409 (Adhesion); DIN EN ISO 6272 (Impact Resistance); DIN EN ISO 2813 (Gloss)	REACH: Regulation (EC) No. 1907/2006 (fluorinated compounds, surface modifiers); REACH restrictions applicable to PFAS substances where relevant
Anti-Graffiti Coating	IS 14182	ISO 2812 Series (Resistance to Liquids); ISO 12944 (Protective Coatings); ISO 2409 (Adhesion),ISO 15013; ISO 2808	ASTM D6578 (Determination of Graffiti Resistance); ASTM D1308 (Chemical Resistance); ASTM D3359 (Adhesion); ASTM D523 (Gloss),ASTM B117; ASTM D4060; ASTM D4541; ASTM D7091; ASTM G14; ASTM G154; ASTM G155; ASTM G20	DIN EN ISO 2409 (Adhesion); DIN EN ISO 2812 (Chemical Resistance); DIN EN ISO 2813 (Gloss); DIN EN ISO 4628 (Coating Damage Evaluation)	AMPP: SP 1; AMPP: SP 6/NACE No.3 where applied on metal/concrete substrates; REACH: Regulation (EC) No. 1907/2006 (solvents, fluorinated additives, polymers)
Anti-Fingerprint Coating	IS 14182	ISO 2813 (Gloss); ISO 2409 (Adhesion); ISO 20566 (Scratch Resistance),ISO 15013; ISO 2808	ASTM D7334 (Wettability); ASTM D3359 (Adhesion); ASTM D4060 (Abrasion Resistance); ASTM D523 (Gloss),ASTM B117; ASTM D4541; ASTM D7091; ASTM G14; ASTM G154; ASTM G155; ASTM G20	DIN EN ISO 2409 (Adhesion); DIN EN ISO 2813 (Gloss); DIN EN ISO 6272 (Scratch/Impact Resistance); DIN EN ISO 27448 (Surface Properties)	REACH: Regulation (EC) No. 1907/2006 (surface modifiers, fluorinated compounds, additives); REACH PFAS restrictions where applicable
Anti-Microbial Coating	IS 14182	ISO 22196 (Antibacterial Activity on Plastics and Non-Porous Surfaces); ISO 21702 (Antiviral Activity); ISO 846 (Microbial Action Evaluation),ISO 15013; ISO 2808	ASTM E2180 (Antimicrobial Activity of Immobilized Agents); ASTM E2149 (Dynamic Contact Antimicrobial Activity); ASTM D5590 (Fungal Resistance),ASTM B117; ASTM D4060; ASTM D4541; ASTM D7091; ASTM G14; ASTM G154; ASTM G155; ASTM G20	DIN EN ISO 22196 (Antibacterial Activity on Plastics and Non-Porous Surfaces); DIN EN ISO 846 (Evaluation of Antimicrobial Activity); DIN EN ISO 2409 (Adhesion)	REACH: Regulation (EC) No. 1907/2006 (biocides, antimicrobial additives); EU Biocidal Products Regulation (EU) No. 528/2012; FDA: only where used on FDA-regulated food-contact surfaces
UV Resistant Coating	IS 14182	ISO 11507 (Artificial Weathering); ISO 16474 Series (Artificial Radiation Exposure); ISO 4628 Series (Coating Degradation),ISO 15013; ISO 2808	ASTM G154 (Fluorescent UV Exposure); ASTM G155 (Xenon Arc Exposure); ASTM D4587 (UV Condensation Weathering); ASTM D2244 (Colour Change); ASTM D523 (Gloss Retention),ASTM B117; ASTM D4060; ASTM D4541; ASTM D7091; ASTM G14; ASTM G20	DIN EN ISO 16474 series (Artificial Weathering); DIN EN ISO 4892 series (UV Exposure); DIN EN ISO 2813 (Gloss Retention); DIN EN ISO 4628 (Degradation Evaluation)	REACH: Regulation (EC) No. 1907/2006 (UV stabilisers, absorbers, additives); AMPP: coating system practices where used for protective exterior applications
Scratch Resistant Coating	IS 14182	ISO 1518 Series (Scratch Resistance); ISO 20566 (Scratch Resistance of Coatings); ISO 2409 (Adhesion),ISO 15013; ISO 2808	ASTM D3363 (Pencil Hardness); ASTM D7027 (Scratch Resistance of Coatings); ASTM D3359 (Adhesion); ASTM D4060 (Abrasion Resistance),ASTM B117; ASTM D4541; ASTM D7091; ASTM G14; ASTM G154; ASTM G155; ASTM G20	DIN EN ISO 1518 series (Scratch Resistance); DIN EN ISO 15184 (Pencil Hardness); DIN EN ISO 2409 (Adhesion); DIN EN ISO 6272 (Impact Resistance)	REACH: Regulation (EC) No. 1907/2006 (hard coatings, additives, nanoparticles where applicable)
Abrasion Resistant Coating	IS 14182	ISO 7784 Series (Abrasion	ASTM D4060 (Abrasion Resistance by	DIN EN ISO 7784 series (Abrasion	AMPP: SP 1; AMPP: SP 6/NACE No.3

Product / Application	BIS	ISO	ASTM	DIN	Other Standards(SSPC,AMPP, REACH, FDA)
		Resistance); ISO 2808 (Film Thickness); ISO 2409 (Adhesion),ISO 15013	Taber Abraser); ASTM D1044 (Abrasion Resistance of Transparent Plastics where applicable); ASTM D3359 (Adhesion),ASTM B117; ASTM D4541; ASTM D7091; ASTM G14; ASTM G154; ASTM G155; ASTM G20	Resistance of Coatings); DIN EN ISO 5470-1 (Rubber/Plastic Abrasion where applicable); DIN EN ISO 2409 (Adhesion)	where applied on industrial substrates; REACH: Regulation (EC) No. 1907/2006 (fillers, resins, additives)
Chemical Resistant Coating	IS 14182	ISO 2812 Series (Resistance to Liquids); ISO 4624 (Adhesion); ISO 12944 (Protective Coating Systems),ISO 15013; ISO 2808	ASTM D1308 (Effect of Household Chemicals on Coatings); ASTM D543 (Chemical Resistance of Plastics where applicable); ASTM D4541 (Adhesion); ASTM D4060 (Abrasion Resistance),ASTM B117; ASTM D7091; ASTM G14; ASTM G154; ASTM G155; ASTM G20	DIN EN ISO 2812 series (Resistance to Liquids); DIN EN ISO 4624 (Adhesion); DIN EN ISO 2409; DIN EN ISO 12944	AMPP: SP 1; AMPP: SP 5/NACE No.1; AMPP: SP 6/NACE No.3; AMPP: SP 10/NACE No.2 for severe chemical environments; REACH: Regulation (EC) No. 1907/2006
Food Contact Coating	IS 14182	ISO 1186 Series (Overall Migration Testing); ISO 2812 Series (Chemical Resistance); ISO 2409 (Adhesion),ISO 15013; ISO 2808	ASTM D543 (Chemical Resistance); ASTM F1249 (Water Vapour Transmission where barrier application applies); ASTM D3359 (Adhesion); ASTM D1308 (Chemical Resistance),ASTM B117; ASTM D4060; ASTM D4541; ASTM D7091; ASTM G14; ASTM G154; ASTM G155; ASTM G20	DIN EN 1186 series (Food Contact Plastics); DIN EN 13130 series (Specific Migration); DIN EN ISO 2409 (Adhesion); DIN EN ISO 2812 (Chemical Resistance)	FDA: 21 CFR 175.300 (Resinous and Polymeric Coatings); FDA 21 CFR 177 series where polymer-specific requirements apply; REACH: Regulation (EC) No. 1907/2006 (SVHC, restricted substances)
Non-Stick Coating	IS 14182	ISO 20566 (Scratch Resistance); ISO 2813 (Gloss); ISO 2409 (Adhesion),ISO 15013; ISO 2808	ASTM D4060 (Abrasion Resistance); ASTM D3359 (Adhesion); ASTM D3363 (Hardness); ASTM D3354 (Adhesion of Fluoropolymer Coatings where applicable),ASTM B117; ASTM D4541; ASTM D7091; ASTM G14; ASTM G154; ASTM G155; ASTM G20	DIN EN ISO 2409 (Adhesion); DIN EN ISO 15184 (Hardness); DIN EN ISO 6272 (Impact Resistance); DIN EN ISO 7784 (Abrasion Resistance)	REACH: Regulation (EC) No. 1907/2006 (fluorinated polymers, additives); REACH restrictions applicable to PFAS substances; FDA: 21 CFR 175.300 where used for food-contact cookware/coatings
Decorative Surface Coating	IS 14182	ISO 2813 (Gloss); ISO 2409 (Adhesion); ISO 2808 (Film Thickness),ISO 15013	ASTM D523 (Gloss); ASTM D2244 (Colour Difference); ASTM D3359 (Adhesion); ASTM D4060 (Abrasion Resistance),ASTM B117; ASTM D4541; ASTM D7091; ASTM G14; ASTM G154; ASTM G155; ASTM G20	DIN EN ISO 2409 (Cross-Cut Adhesion); DIN EN ISO 2813 (Gloss); DIN EN ISO 15184 (Pencil Hardness); DIN EN ISO 11998 (Wet Scrub Resistance); DIN EN ISO 16474 (Artificial Weathering); DIN EN ISO 4628 Series (Coating Defect Evaluation)	REACH: Regulation (EC) No. 1907/2006 (VOC, pigments, additives, preservatives)
Glass Coating	IS 14182	ISO 2409 (Adhesion); ISO 2813 (Gloss); ISO 20566 (Scratch Resistance),ISO 15013; ISO 2808	ASTM C1585 (Rate of Absorption of Water by Concrete-like Materials where applicable); ASTM D3359 (Adhesion); ASTM D523 (Gloss); ASTM D4060 (Scratch/Abrasion Resistance),ASTM B117; ASTM D4541; ASTM D7091; ASTM G14; ASTM G154; ASTM G155; ASTM G20	DIN EN ISO 2409 (Adhesion); DIN EN ISO 2813 (Gloss); DIN EN ISO 15184 (Hardness); DIN EN ISO 6272 (Impact Resistance); DIN EN ISO 16474 (Weathering Resistance); DIN EN ISO 9227 (Corrosion Testing where metallic coatings apply)	REACH: Regulation (EC) No. 1907/2006 (surface modifiers, pigments, additives); FDA: applicable only for food-contact glass coatings
Wood Coating	IS 14182	ISO 2409 (Adhesion); ISO 11507 (Weathering Resistance); ISO 2813 (Gloss),ISO 15013; ISO 2808	ASTM D3023 (Evaluation of Coatings Applied to Wood Products); ASTM D4446 (Water Repellency of Wood); ASTM D3359 (Adhesion); ASTM D523 (Gloss),ASTM B117; ASTM D4060; ASTM D4541; ASTM D7091; ASTM G14; ASTM G154; ASTM G155; ASTM G20	DIN EN 927 Series (Coating Materials and Coating Systems for Exterior Wood); DIN EN ISO 2409 (Adhesion); DIN EN ISO 2813 (Gloss); DIN EN ISO 4628 Series (Coating Degradation); DIN EN ISO 7783 (Water Vapour Transmission); DIN EN ISO 16474 (Weathering)	REACH: Regulation (EC) No. 1907/2006 (biocides, preservatives, VOC, solvents); FDA: only where food-contact wood applications exist
Plastic Coating	IS 14182	ISO 2409 (Adhesion); ISO 4892	ASTM D3359 (Adhesion); ASTM D4060	DIN EN ISO 2409 (Adhesion); DIN	REACH: Regulation (EC) No.

Product / Application	BIS	ISO	ASTM	DIN	Other Standards(SSPC,AMPP, REACH, FDA)
		Series (Weathering of Plastics); ISO 20566 (Scratch Resistance),ISO 15013; ISO 2808	(Abrasion Resistance); ASTM D256 (Impact Resistance where substrate testing applies); ASTM G154 (Weathering),ASTM B117; ASTM D4541; ASTM D7091; ASTM G14; ASTM G155; ASTM G20	EN ISO 15184 (Hardness); DIN EN ISO 6272 (Impact Resistance); DIN EN ISO 4892 Series (Weathering of Plastics); DIN EN ISO 4628 Series (Degradation Evaluation)	1907/2006 (plasticisers, polymers, additives, restricted substances); FDA: 21 CFR 175.300 where food-contact plastic coatings apply
Metal Surface Coating	IS 14182	ISO 12944 (Corrosion Protection); ISO 8501 (Surface Preparation); ISO 9227 (Salt Spray Testing); ISO 2409 (Adhesion),ISO 15013; ISO 2808	ASTM B117 (Salt Spray); ASTM D610 (Rust Evaluation); ASTM D714 (Blister Evaluation); ASTM D1654 (Corrosion Evaluation); ASTM D7091 (Thickness Measurement),ASTM D4060; ASTM D4541; ASTM G14; ASTM G154; ASTM G155; ASTM G20	DIN EN ISO 12944 Series (Corrosion Protection of Steel Structures); DIN EN ISO 9227 (Salt Spray Corrosion Testing); DIN EN ISO 2409 (Adhesion); DIN EN ISO 4624 (Pull-Off Adhesion); DIN EN ISO 2808 (Dry Film Thickness); DIN EN ISO 8501 Series (Surface Preparation)	AMPP: SP 1; AMPP: SP 2; AMPP: SP 3; AMPP: SP 5/NACE No.1; AMPP: SP 6/NACE No.3; AMPP: SP 10/NACE No.2; REACH: Regulation (EC) No. 1907/2006 (corrosion inhibitors, pigments, heavy metals)
Paper Coating	IS 14182	ISO 5637 (Water Absorption of Paper and Board); ISO 8254 Series (Gloss of Paper and Board); ISO 12647 (Printing Applications where applicable),ISO 15013; ISO 2808	ASTM D589 (Opacity of Paper); ASTM D618 (Conditioning of Paper Products); ASTM D523 (Gloss); ASTM E96 (Water Vapour Transmission),ASTM B117; ASTM D4060; ASTM D4541; ASTM D7091; ASTM G14; ASTM G154; ASTM G155; ASTM G20	DIN EN ISO 8254 Series (Specular Gloss of Paper and Board); DIN EN ISO 5631 Series (Colour Measurement of Paper and Board); DIN EN ISO 1924 Series (Paper Mechanical Properties); DIN EN ISO 535 (Water Absorption of Paper and Board); DIN EN ISO 12625 Series (Paper Products Testing)	REACH: Regulation (EC) No. 1907/2006 (coating additives, pigments, preservatives); FDA: 21 CFR 176.170 and 21 CFR 176.180 for food-contact paper and paperboard coatings

Source field: Dyes and Pigments