Water-Based Adhesives

Product / Application	BIS	ISO	ASTM	DIN	Other Standards(SSPC,AMPP, REACH, FDA)
Polyvinyl Acetate (PVA) Adhesive	IS 4835:1979; IS 15057	ISO 4587 (Tensile Shear Strength of Adhesive Bonds); ISO 10365 (Adhesive Failure Classification); ISO 12465 (Wood Adhesive Applications where applicable),ISO 2555; ISO 62	ASTM D4317 (Standard Specification for Polyvinyl Acetate-Based Adhesives); ASTM D905 (Wood Adhesive Bond Strength); ASTM D1002 (Lap Shear Strength); ASTM D1876 (T-Peel Strength),ASTM D1084; ASTM D1151; ASTM D1489; ASTM D1557; ASTM D1993; ASTM D2556; ASTM D3236; ASTM D4498; ASTM D4499; ASTM D897	DIN EN 204 (Classification of Thermoplastic Wood Adhesives); DIN EN 205 (Wood Adhesive Strength); DIN EN 14257 (WATT 91 Heat Resistance); DIN EN ISO 9142 (Durability)	REACH: Regulation (EC) No. 1907/2006 (polymer additives, preservatives, VOC, residual monomers); FDA: 21 CFR 175.105 where used in food-contact adhesive applications
White Glue	IS 4835:1979 (if PVAc wood glue); IS 15057	ISO 4587 (Adhesive Bond Strength); ISO 10365 (Failure Classification),ISO 2555; ISO 62	ASTM D4317 (Polyvinyl Acetate-Based Adhesives); ASTM D905 (Adhesive Strength in Wood); ASTM D1002 (Shear Strength),ASTM D1084; ASTM D1151; ASTM D1489; ASTM D1557; ASTM D1993; ASTM D2556; ASTM D3236; ASTM D4498; ASTM D4499; ASTM D897	DIN EN 204 (Wood Adhesive Classification); DIN EN 205 (Tensile Shear Strength); DIN EN 14256 (Open Assembly Time); DIN EN ISO 9142 (Durability)	REACH: Regulation (EC) No. 1907/2006 (PVA polymers, preservatives, additives); FDA: 21 CFR 175.105 where used in food-contact applications
Wood Glue	IS 4835:1979 (PVAc wood glue) or IS 848:2006 (Phenolic & Aminoplastic resin adhesives for plywood/wood); IS 15057	ISO 12465 (Wood Adhesive Bonding Applications); ISO 4587 (Tensile Shear Strength); ISO 11339 (T-Peel Strength),ISO 2555; ISO 62	ASTM D905 (Strength Properties of Adhesive Bonds in Shear by Compression Loading); ASTM D5751 (Adhesives Used in Wood Products); ASTM D5572 (Adhesives for Finger Joints in Wood Products),ASTM D1002; ASTM D1084; ASTM D1151; ASTM D1489; ASTM D1557; ASTM D1993; ASTM D2556; ASTM D3236; ASTM D4498; ASTM D4499; ASTM D897	DIN EN 204 (Thermoplastic Wood Adhesives); DIN EN 205 (Shear Strength); DIN EN 14257 (Heat Resistance); DIN EN 14256 (Open Assembly Time)	REACH: Regulation (EC) No. 1907/2006 (formaldehyde, preservatives, VOC, additives); FDA: 21 CFR 175.105 where used for food-contact wood applications
Paper Adhesive	IS 2257:1989; IS 15057; IS 4835	ISO 4587 (Adhesive Bond Strength); ISO 10365 (Failure Classification),ISO 2555; ISO 62	ASTM D903 (Peel Strength); ASTM D1002 (Lap Shear Strength); ASTM D3330 (Peel Adhesion where pressure-sensitive application applies),ASTM D1084; ASTM D1151; ASTM D1489; ASTM D1557; ASTM D1993; ASTM D2556; ASTM D3236; ASTM D4498; ASTM D4499; ASTM D897; ASTM D905	DIN EN ISO 1924 series (Paper Mechanical Properties where applicable); DIN EN 1465 (Adhesive Strength); DIN EN ISO 11339 (Peel Strength); DIN EN ISO 9142 (Durability)	REACH: Regulation (EC) No. 1907/2006 (binders, preservatives, additives); FDA: 21 CFR 175.105 and 21 CFR 176.170/176.180 where used in food-contact paper structures
Book Binding Adhesive	IS 15057; IS 4835	ISO 4587 (Bond Strength); ISO 10365 (Adhesive Failure Classification); ISO 12647 (Printing Applications where applicable),ISO 2555; ISO 62	ASTM D903 (Peel Strength); ASTM D1002 (Shear Strength); ASTM D1876 (T-Peel Strength); ASTM D3359 (Adhesion where coated surfaces apply),ASTM D1084; ASTM D1151; ASTM D1489; ASTM D1557; ASTM D1993; ASTM D2556; ASTM D3236; ASTM D4498; ASTM D4499; ASTM D897; ASTM D905	DIN EN 12985 (Bookbinding Adhesive Applications where applicable); DIN EN 1465 (Strength Testing); DIN EN ISO 11339 (Peel Strength); DIN EN ISO 9142 (Durability)	REACH: Regulation (EC) No. 1907/2006 (adhesive polymers, preservatives, VOC); FDA: 21 CFR 175.105 where used for food-contact printed materials
Packaging Adhesive	IS 4643; IS 8542	ISO 4587 (Adhesive Bond Strength); ISO 11339 (Peel Strength); ISO 10365,ISO 10364;	ASTM D903 (Peel Strength); ASTM D1002 (Lap Shear Strength); ASTM F88 (Seal Strength of Flexible Barrier	DIN EN 1895 (Peel Strength of Adhesive Bonds); DIN EN 1465 (Lap Shear Strength); DIN EN ISO	FDA: 21 CFR 175.105 (Adhesives); FDA: 21 CFR 176.170 / 176.180 where used in food-contact

Product / Application	BIS	ISO	ASTM	DIN	Other Standards(SSPC,AMPP, REACH, FDA)
		ISO 3251	Materials); ASTM D1876 (T-Peel Strength),ASTM D1084; ASTM D1151; ASTM D1489; ASTM D1557; ASTM D1993; ASTM D2556; ASTM D3236; ASTM D4498; ASTM D4499; ASTM D897; ASTM D905	9142 (Durability); DIN EN ISO 527 (Film Mechanical Properties where laminated packaging applies)	paper/paperboard structures; REACH: Regulation (EC) No. 1907/2006
Carton Sealing Adhesive	IS 15057; IS 4835	ISO 4587 (Tensile Shear Strength); ISO 11339 (Peel Strength); ISO 10365 (Failure Classification),ISO 2555; ISO 62	ASTM D903 (Peel Strength); ASTM D1002 (Lap Shear Strength); ASTM D1876 (T-Peel Strength),ASTM D1084; ASTM D1151; ASTM D1489; ASTM D1557; ASTM D1993; ASTM D2556; ASTM D3236; ASTM D4498; ASTM D4499; ASTM D897; ASTM D905	DIN EN ISO 1465 (Lap Shear Strength); DIN EN ISO 11339 (Peel Strength); DIN EN ISO 9142 (Durability); DIN EN 15416 series (Adhesives for Load Bearing Timber Structures where applicable)	REACH: Regulation (EC) No. 1907/2006 (polymers, tackifiers, additives); FDA: 21 CFR 175.105 where used for food-contact packaging cartons
Label Adhesive	IS 15057; IS 4835	ISO 29862 (Peel Adhesion of Self-Adhesive Materials); ISO 29863 (Shear Adhesion); ISO 29864 (Tensile Strength),ISO 2555; ISO 62	ASTM D3330 (Peel Adhesion of Pressure Sensitive Tape); ASTM D3654 (Shear Adhesion); ASTM D2979 (Tack of Pressure Sensitive Adhesives); ASTM D6252 (Peel Adhesion of Labels),ASTM D1002; ASTM D1084; ASTM D1151; ASTM D1489; ASTM D1557; ASTM D1993; ASTM D2556; ASTM D3236; ASTM D4498; ASTM D4499; ASTM D897; ASTM D905	DIN EN ISO 29862 (Peel Adhesion of Pressure Sensitive Adhesive Tape); DIN EN ISO 29863 (Shear Adhesion); DIN EN ISO 29864 (Tensile Strength); DIN EN 1939 (Bond Strength)	REACH: Regulation (EC) No. 1907/2006 (adhesive components, tackifiers, preservatives); FDA: 21 CFR 175.105 where used for food-contact labels
Envelope Gum	IS 2257:1989; IS 15057; IS 4835	ISO 4587 (Adhesive Bond Strength); ISO 10365 (Failure Classification),ISO 2555; ISO 62	ASTM D903 (Peel Strength); ASTM D1002 (Lap Shear Strength); ASTM D1876 (T-Peel Strength),ASTM D1084; ASTM D1151; ASTM D1489; ASTM D1557; ASTM D1993; ASTM D2556; ASTM D3236; ASTM D4498; ASTM D4499; ASTM D897; ASTM D905	DIN EN ISO 1465 (Shear Strength); DIN EN ISO 11339 (Peel Strength); DIN EN ISO 9142 (Durability)	REACH: Regulation (EC) No. 1907/2006 (starch/dextrin polymers, preservatives); FDA: 21 CFR 175.105 where food-contact packaging applications exist
Water Based Acrylic Adhesive	IS 15057; IS 4835	ISO 29862 (Peel Adhesion); ISO 29863 (Shear Adhesion); ISO 4587 (Tensile Shear Strength),ISO 2555; ISO 62	ASTM D3330 (Peel Adhesion); ASTM D3654 (Shear Adhesion); ASTM D2979 (Tack); ASTM D1002 (Lap Shear Strength),ASTM D1084; ASTM D1151; ASTM D1489; ASTM D1557; ASTM D1993; ASTM D2556; ASTM D3236; ASTM D4498; ASTM D4499; ASTM D897; ASTM D905	DIN EN ISO 29862 (Peel Adhesion); DIN EN ISO 29863 (Shear Adhesion); DIN EN ISO 9142 (Durability); DIN EN 13999 series (VOC Emissions)	REACH: Regulation (EC) No. 1907/2006 (acrylate polymers, residual monomers, preservatives); FDA: 21 CFR 175.105 where food-contact applications exist
Latex Adhesive	IS 15057; IS 4835	ISO 4587 (Tensile Shear Strength); ISO 10365 (Failure Classification); ISO 1629 (Rubber Classification where applicable),ISO 2555; ISO 62	ASTM D429 (Rubber Adhesion); ASTM D1002 (Lap Shear Strength); ASTM D903 (Peel Strength),ASTM D1084; ASTM D1151; ASTM D1489; ASTM D1557; ASTM D1993; ASTM D2556; ASTM D3236; ASTM D4498; ASTM D4499; ASTM D897; ASTM D905	DIN EN ISO 9142 (Durability); DIN EN 1465 (Shear Strength); DIN EN ISO 11339 (Peel Strength); DIN EN ISO 527 (Polymer Mechanical Properties)	REACH: Regulation (EC) No. 1907/2006 (latex polymers, preservatives, additives); FDA: 21 CFR 175.105 where food-contact applications exist
Dextrin Adhesive	IS 2257:1989; IS 15057; IS 4835	ISO 4587 (Adhesive Bond Strength); ISO 10365 (Failure Classification),ISO 2555; ISO 62	ASTM D1002 (Lap Shear Strength); ASTM D903 (Peel Strength); ASTM D1876 (T-Peel Strength),ASTM D1084; ASTM D1151; ASTM D1489; ASTM D1557; ASTM D1993; ASTM D2556; ASTM D3236; ASTM D4498; ASTM D4499; ASTM D897; ASTM D905	DIN EN ISO 1465 (Lap Shear Strength); DIN EN ISO 11339 (Peel Strength); DIN EN ISO 9142 (Durability)	REACH: Regulation (EC) No. 1907/2006 (starch derivatives, preservatives, additives); FDA: 21 CFR 175.105 and applicable food-contact paper regulations
Starch Based Adhesive	IS 2257:1989; IS	ISO 4587 (Adhesive Bond	ASTM D1002 (Shear Strength); ASTM	DIN EN ISO 1465 (Adhesive	REACH: Regulation (EC) No.

Product / Application	BIS	ISO	ASTM	DIN	Other Standards(SSPC,AMPP, REACH, FDA)
	15057; IS 4835	Strength); ISO 10365 (Failure Classification),ISO 2555; ISO 62	D905 (Wood Adhesive Strength where applicable); ASTM D903 (Peel Strength),ASTM D1084; ASTM D1151; ASTM D1489; ASTM D1557; ASTM D1993; ASTM D2556; ASTM D3236; ASTM D4498; ASTM D4499; ASTM D897	Strength); DIN EN ISO 11339 (Peel Strength); DIN EN ISO 9142 (Durability); DIN EN 13999 series (Emission Testing where required)	1907/2006 (modified starch additives, preservatives); FDA: 21 CFR 175.105; FDA 21 CFR 176.170/176.180 for food-contact paper applications
Wallpaper Adhesive	IS 15057; IS 4835	ISO 4587 (Adhesive Bond Strength); ISO 10365 (Failure Classification),ISO 2555; ISO 62	ASTM C557 (Adhesives for Gypsum Wallboard Applications); ASTM D903 (Peel Strength); ASTM D1002 (Lap Shear Strength),ASTM D1084; ASTM D1151; ASTM D1489; ASTM D1557; ASTM D1993; ASTM D2556; ASTM D3236; ASTM D4498; ASTM D4499; ASTM D897; ASTM D905	DIN EN 12956 (Wallcoverings — Determination of Adhesion where applicable); DIN EN ISO 1465 (Shear Strength); DIN EN ISO 9142 (Durability)	REACH: Regulation (EC) No. 1907/2006 (VOC, preservatives, polymers); REACH Annex XVII restrictions where applicable
Textile Adhesive	IS 15057; IS 4835	ISO 105 Series (Textile Colour/Fastness Evaluation where applicable); ISO 4587 (Bond Strength); ISO 11339 (Peel Strength),ISO 2555; ISO 62	ASTM D751 (Coated Fabrics Testing where applicable); ASTM D903 (Peel Strength); ASTM D1002 (Shear Strength); ASTM D5034 (Textile Fabric Strength where applicable),ASTM D1084; ASTM D1151; ASTM D1489; ASTM D1557; ASTM D1993; ASTM D2556; ASTM D3236; ASTM D4498; ASTM D4499; ASTM D897; ASTM D905	DIN EN ISO 105 series (Textile Fastness where applicable); DIN EN ISO 13934 series (Textile Mechanical Properties); DIN EN 1465 (Adhesive Strength); DIN EN ISO 11339 (Peel Strength)	REACH: Regulation (EC) No. 1907/2006 (restricted substances, residual monomers, additives); REACH Annex XVII (restricted azo compounds where applicable)
Lamination Adhesive	IS 4643; IS 8542	ISO 4587 (Tensile Shear Strength); ISO 11339 (T-Peel Strength); ISO 10365,ISO 10364; ISO 3251	ASTM D1876 (T-Peel Strength); ASTM D903 (Peel Strength); ASTM D1002 (Lap Shear Strength); ASTM F88 (Seal Strength of Flexible Barrier Materials where packaging lamination applies),ASTM D1084; ASTM D1151; ASTM D1489; ASTM D1557; ASTM D1993; ASTM D2556; ASTM D3236; ASTM D4498; ASTM D4499; ASTM D897; ASTM D905	DIN EN 1465 (Lap Shear Strength); DIN EN ISO 11339 (T-Peel Strength); DIN EN ISO 527 (Mechanical Properties of Polymer Films); DIN EN 1939 (Bond Strength of Adhesive Tapes and Laminates where applicable)	REACH: Regulation (EC) No. 1907/2006 (solvents, isocyanates, VOC, additives); FDA: 21 CFR 175.105 where used in food packaging laminates
Pressure Sensitive Water Based Adhesive	IS 15057; IS 4835	ISO 29862 (Peel Adhesion); ISO 29863 (Shear Adhesion); ISO 29864 (Tensile Strength),ISO 2555; ISO 62	ASTM D3330 (Peel Adhesion); ASTM D3654 (Shear Adhesion); ASTM D2979 (Tack); ASTM D6252 (Label Peel Adhesion),ASTM D1002; ASTM D1084; ASTM D1151; ASTM D1489; ASTM D1557; ASTM D1993; ASTM D2556; ASTM D3236; ASTM D4498; ASTM D4499; ASTM D897; ASTM D905	DIN EN ISO 29862 (Peel Adhesion); DIN EN ISO 29863 (Shear Adhesion); DIN EN ISO 29864 (Breaking Strength); DIN EN 13999 (VOC Emissions)	REACH: Regulation (EC) No. 1907/2006 (acrylic/latex polymers, tackifiers, preservatives); FDA: 21 CFR 175.105 for food-contact labels/tapes
Flooring Adhesive	IS 15057; IS 4835	ISO 4587 (Bond Strength); ISO 10365 (Failure Classification); ISO 13007 (Tile Adhesive Applications where applicable),ISO 2555; ISO 62	ASTM F710 (Preparing Concrete Floors to Receive Resilient Flooring); ASTM F2419 (Installation of Resilient Flooring where applicable); ASTM D1002 (Shear Strength); ASTM D903 (Peel Strength),ASTM D1084; ASTM D1151; ASTM D1489; ASTM D1557; ASTM D1993; ASTM D2556; ASTM D3236; ASTM D4498; ASTM D4499; ASTM D897; ASTM D905	DIN EN 14259 (Adhesives for Floor Coverings — Mechanical and Electrical Performance); DIN EN 1372 (Peel Test for Floor Covering Adhesives); DIN EN 13279 where gypsum applications apply; DIN EN ISO 9142 (Durability)	REACH: Regulation (EC) No. 1907/2006 (VOC, solvents, phthalates, polymers); REACH Annex XVII restrictions
Construction Adhesive	IS 4643; IS 8542	ISO 4587 (Tensile Shear Strength);	ASTM C557 (Adhesives for Installation	DIN EN 15651 series (Sealants for	REACH: Regulation (EC) No.

Product / Application	BIS	ISO	ASTM	DIN	Other Standards(SSPC,AMPP, REACH, FDA)
		ISO 11339 (Peel Strength); ISO 10365,ISO 10364; ISO 3251	of Gypsum Wallboard); ASTM D1002 (Lap Shear Strength); ASTM D903 (Peel Strength); ASTM D4541 (Pull-Off Adhesion for Coated Surfaces where applicable),ASTM D1084; ASTM D1151; ASTM D1489; ASTM D1557; ASTM D1993; ASTM D2556; ASTM D3236; ASTM D4498; ASTM D4499; ASTM D897; ASTM D905	Building Construction); DIN EN 1465 (Adhesive Strength); DIN EN ISO 11600 (Classification of Sealants); DIN EN ISO 9142 (Durability)	1907/2006 (VOC, solvents, formaldehyde, additives); REACH Annex XVII restrictions
Eco-Friendly Water Based Adhesive	IS 15057; IS 4835	ISO 4587 (Bond Strength); ISO 10365 (Failure Classification); ISO 11890-2 (VOC Content where low-VOC claim applies),ISO 2555; ISO 62	ASTM D2369 (VOC Content); ASTM D1002 (Shear Strength); ASTM D903 (Peel Strength); ASTM D3330 (Peel Adhesion where pressure-sensitive),ASTM D1084; ASTM D1151; ASTM D1489; ASTM D1557; ASTM D1993; ASTM D2556; ASTM D3236; ASTM D4498; ASTM D4499; ASTM D897; ASTM D905	DIN EN 13999 series (VOC Emissions from Adhesives); DIN EN 1465 (Shear Strength); DIN EN ISO 11339 (Peel Strength); DIN EN ISO 9142 (Durability)	REACH: Regulation (EC) No. 1907/2006 (VOC, preservatives, residual monomers); EU VOC restrictions where applicable; FDA: only food-contact compliant formulations

Source field: Dyes and Pigments