Finished Leather

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
Full Grain Leather	IS 7052,IS 5914; IS 582; IS 3336; IS 2454; IS 15570	ISO 15115 (Leather — Vocabulary); ISO 2418 (Leather — Sampling Location); ISO 3377-1 (Leather — Physical and Mechanical Tests — Tear Load)ISO 2589; ISO 3376; ISO 4045; ISO 5402; ISO 11640; ISO 14087; ISO 17072; ISO 17075; ISO 17229; ISO 17231	ASTM D2209 (Tensile Strength of Leather); ASTM D2210 (Grain Crack and Extension of Leather); ASTM D6182 (Resistance of Leather to Scuffing); ASTM D1813 (Thickness of Leather),ASTM D2099; ASTM D2211; ASTM D2212; ASTM D4704; ASTM D2813; ASTM D1517; ASTM D2341; ASTM D2807	DIN EN ISO 2589 (Leather Thickness); DIN EN ISO 3376 (Tensile Strength and Elongation); DIN EN ISO 3377-1 (Tear Strength); DIN EN ISO 11640 (Leather Colour Fastness to Rubbing)	Leather Working Group (LWG) Performance and Environmental Standards; SATRA Leather Testing Guidelines; IULTCS Testing Methods
Top Grain Leather	IS 7052,IS 5914; IS 582; IS 3336; IS 2454; IS 15570	ISO 15115 (Leather — Vocabulary); ISO 3377-1 (Leather — Tear Load Determination)ISO 2418; ISO 2589; ISO 3376; ISO 4045; ISO 5402; ISO 11640; ISO 14087; ISO 17072; ISO 17075; ISO 17229; ISO 17231	ASTM D2209 (Tensile Strength of Leather); ASTM D2813 (Sampling Leather for Physical and Chemical Tests); ASTM D6182 (Scuff Resistance of Leather); ASTM D4705 (Thickness of Leather),ASTM D2210; ASTM D2099; ASTM D2211; ASTM D2212; ASTM D4704; ASTM D1517; ASTM D2341; ASTM D2807	DIN EN ISO 2589 (Leather Thickness); DIN EN ISO 3376 (Tensile Properties); DIN EN ISO 3377-1 (Tear Strength); DIN EN ISO 11641 (Colour Fastness of Leather to Perspiration)	Leather Working Group (LWG); SATRA Performance Testing Guidelines; OEKO-TEX Leather Standard
Corrected Grain Leather; Split Leather; Suede Leather; Nubuck Leather; Patent Leather	IS 5677 / IS 14898: Covers the structural requirements of chrome-tanned upper leather and structural limits for environmental "ECO" certification,IS 5914; IS 582; IS 3336; IS 2454; IS 15570	ISO 15115 (Leather — Vocabulary); ISO 11640 (Leather — Tests for Colour Fastness — Rubbing)ISO 2418; ISO 2589; ISO 3376; ISO 3377; ISO 4045; ISO 5402; ISO 14087; ISO 17072; ISO 17075; ISO 17229; ISO 17231	ASTM D2209 (Tensile Strength of Leather); ASTM D2211 (Tear Strength of Leather); ASTM D6182 (Resistance to Scuffing); ASTM D1813 (Thickness of Leather),ASTM D2210; ASTM D2099; ASTM D2212; ASTM D4704; ASTM D2813; ASTM D1517; ASTM D2341; ASTM D2807	DIN EN ISO 2589 (Leather Thickness); DIN EN ISO 3376 (Tensile Strength and Elongation); DIN EN ISO 11640 (Colour Fastness to Rubbing); DIN EN ISO 11644 (Adhesion of Finish)	Leather Working Group (LWG); SATRA Leather Testing Guidelines; OEKO-TEX Leather Standard
Upholstery Leather	IS 15006,IS 5914; IS 582; IS 3336; IS 2454; IS 15570	ISO 11640 (Leather — Colour Fastness to Rubbing); ISO 3377-1 (Leather — Tear Load); ISO 2589 (Leather — Physical and Mechanical Tests — Determination of Thickness)ISO 17232; ISO 17233	ASTM D6182 (Resistance of Leather to Scuffing); ASTM D2099 (Dynamic Water Resistance of Shoe Upper Leather, where applicable); ASTM D1610 (Conditioning Leather and Leather Products); ASTM D4705 (Thickness of Leather),ASTM D2097; ASTM D2617; ASTM D3836	DIN EN ISO 3376 (Leather Tensile Properties); DIN EN ISO 3377-1 (Tear Strength); DIN EN ISO 11640 (Colour Fastness to Rubbing); DIN EN ISO 17235 (Leather — Physical and Mechanical Tests — Softness)	Leather Working Group (LWG); California Technical Bulletin 117 (Furniture Flammability, where applicable); GREENGUARD Gold Certification (Indoor Furniture Applications)
Automotive Leather	IS 15006,IS 5914; IS 582; IS 3336; IS 2454; IS 15570	ISO 17235 (Leather — Physical and Mechanical Tests — Determination of Water Resistance of Surface Coated Leather); ISO 11640 (Leather — Colour Fastness to Rubbing); ISO 3377-1 (Leather — Tear Load Determination)ISO 17232; ISO 17233	ASTM D6182 (Leather Resistance to Scuffing); ASTM D2099 (Dynamic Water Resistance of Shoe Upper Leather, where applicable); ASTM D1813 (Thickness of Leather); ASTM D2209 (Tensile Strength of Leather),ASTM D2097; ASTM D2617; ASTM D3836	DIN EN ISO 3376 (Tensile Strength and Elongation); DIN EN ISO 3377-1 (Tear Strength); DIN EN ISO 11640 (Colour Fastness to Rubbing); DIN EN ISO 17235 (Softness)	GMW General Motors Material Specifications (where applicable); VW TL Specifications; Mercedes-Benz DBL Specifications; Leather Working Group (LWG)

Source field: Leather and Leather products