Saddlery

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
Horse Saddle Leather	IS 7487,IS 5914; IS 582; IS 3336; IS 2454; IS 15570	ISO 15115 (Leather — Vocabulary); ISO 3377-1 (Leather — Tear Load Determination); ISO 2589 (Leather — Determination of Thickness)	ASTM D2209 (Tensile Strength of Leather); ASTM D2211 (Tear Strength of Leather); ASTM D6182 (Scuff Resistance of Leather); ASTM D1813 (Thickness of Leather),	DIN EN ISO 3376 (Leather Tensile Properties); DIN EN ISO 3377-1 (Tear Strength); DIN EN ISO 2589 (Thickness); DIN EN ISO 17235 (Leather Softness)	Equestrian Trade Association Guidelines; Leather Working Group (LWG); SATRA Leather Performance Testing
Bridle Leather; Stirrup Strap Leather; Reins	IS 5683 / IS 12450(Critical load-bearing limits, weatherproofing, and strict safety guidelines for equestrian saddlery equipment),IS 5914; IS 582; IS 3336; IS 2454; IS 15570	ISO 15115 (Leather — Vocabulary); ISO 3377-1 (Leather — Tear Load Determination)	ASTM D2209 (Tensile Strength of Leather); ASTM D2211 (Tear Strength of Leather); ASTM D1813 (Thickness of Leather); ASTM D6182 (Scuff Resistance of Leather),	DIN EN ISO 3376 (Leather Tensile Strength); DIN EN ISO 3377-1 (Tear Strength); DIN EN ISO 2589 (Thickness); DIN EN ISO 11640 (Colour Fastness to Rubbing)	Equestrian Trade Association Guidelines; Leather Working Group (LWG); SATRA Leather Testing Guidelines
Harness Leather	IS 7487,IS 5914; IS 582; IS 3336; IS 2454; IS 15570	ISO 15115 (Leather — Vocabulary); ISO 3377-1 (Leather — Tear Load Determination)	ASTM D2209 (Tensile Strength of Leather); ASTM D2211 (Tear Strength of Leather); ASTM D1813 (Thickness of Leather); ASTM D1610 (Conditioning Leather for Testing),	DIN EN ISO 3376 (Leather Tensile Properties); DIN EN ISO 3377-1 (Tear Strength); DIN EN ISO 2589 (Leather Thickness); DIN EN ISO 17235 (Softness)	Leather Working Group (LWG); Equestrian Industry Standards; SATRA Leather Testing Guidelines

Source field: Leather and Leather products