Synthetic Leather

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
PVC Artificial Leather	IS 12592,IS 5914; IS 582; IS 3336; IS 2454; IS 15570	ISO 7617-1 (Plastics — Artificial Leather — Determination of Physical Properties, where applicable); ISO 1421 (Rubber- or Plastics-coated Fabrics — Tensile Strength and Elongation)ISO 2411; ISO 2419; ISO 3011; ISO 5470; ISO 5978; ISO 17076	ASTM D1593 (Nonrigid Vinyl Chloride Plastic Film and Sheeting); ASTM D882 (Tensile Properties of Thin Plastic Sheeting); ASTM D6241 (Static Puncture Strength, where fabric-backed); ASTM D3884 (Abrasion Resistance of Textile Fabrics),ASTM D751; ASTM D2136; ASTM D3393	DIN EN ISO 5470-2 (Coated Fabrics — Abrasion Resistance); DIN EN ISO 1421 (Coated Fabrics — Tensile Strength and Elongation); DIN EN ISO 2411 (Coated Fabrics — Adhesion of Coating); DIN EN ISO 105-B02 (Colour Fastness to Light)	REACH Chemical Compliance (EU); OEKO-TEX Leather Standard; California Proposition 65 Requirements (where applicable); Leather Working Group Guidelines (synthetic leather sustainability applications)
PU Synthetic Leather	IS 17411 (Synthetic Leather),IS 5914; IS 582; IS 3336; IS 2454; IS 15570	ISO 7617-1 (Plastics — Artificial Leather — Determination of Physical Properties); ISO 1421 (Rubber- or Plastics-coated Fabrics — Tensile Strength and Elongation)ISO 2411; ISO 2419; ISO 3011; ISO 5470; ISO 5978; ISO 17076	ASTM D882 (Tensile Properties of Thin Plastic Sheeting); ASTM D751 (Coated Fabrics Testing); ASTM D3884 (Abrasion Resistance of Textile Fabrics); ASTM D624 (Tear Strength of Rubber and Thermoplastic Elastomers),ASTM D2901; ASTM D3690; ASTM D4157	DIN EN ISO 1421 (Rubber or Plastics Coated Fabrics — Tensile Strength); DIN EN ISO 2411 (Coating Adhesion); DIN EN ISO 5470-2 (Abrasion Resistance); DIN EN ISO 105-B02 (Colour Fastness to Light)	REACH Chemical Compliance (EU); OEKO-TEX Leather Standard; SATRA Synthetic Leather Testing Guidelines; California Proposition 65 Requirements
Microfiber Leather	IS 17411 (Synthetic Leather),IS 5914; IS 582; IS 3336; IS 2454; IS 15570	ISO 7617-1 (Artificial Leather — Physical Property Tests); ISO 1421 (Coated Fabrics — Tensile Properties)ISO 32100	ASTM D5034 (Breaking Strength and Elongation of Textile Fabrics); ASTM D3884 (Abrasion Resistance of Textile Fabrics); ASTM D6182 (Scuff Resistance of Leather); ASTM D1813 (Thickness of Leather),ASTM D751; ASTM D2137	DIN EN ISO 1421 (Coated Fabrics — Tensile Strength); DIN EN ISO 3377-1 (Leather Tear Strength, where leather-like applications apply); DIN EN ISO 5470-2 (Abrasion Resistance); DIN EN ISO 11640 (Colour Fastness to Rubbing)	REACH Chemical Compliance; OEKO-TEX Leather Standard; SATRA Material Testing Guidelines; Automotive OEM Material Specifications (where applicable)
Silicone Leather	IS 17411 (Synthetic Leather); IS 14967 (Silicone Applications, where applicable),IS 5914; IS 582; IS 3336; IS 2454; IS 15570	ISO 7617-1 (Artificial Leather — Physical Property Tests); ISO 1421 (Coated Fabrics — Tensile Properties)ISO 32100	ASTM D2000 (Rubber Products Classification System); ASTM D412 (Tensile Properties of Rubber); ASTM D624 (Tear Strength of Rubber); ASTM D2240 (Durometer Hardness of Rubber),ASTM D3884; ASTM D751; ASTM D5034; ASTM D2137	DIN EN ISO 1421 (Coated Fabrics — Tensile Strength); DIN EN ISO 5470-2 (Abrasion Resistance); DIN ISO 37 (Tensile Properties of Silicone Rubber); DIN EN ISO 105-B02 (Colour Fastness to Light)	FDA 21 CFR 177 (Food Contact Silicone Applications, where applicable); OEKO-TEX Leather Standard; UL 94 (Flammability Applications); Medical/Automotive Material Requirements

Source field: Leather and Leather products