Upholstery Leather

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
Sofa Leather	IS 15006,IS 5914; IS 582; IS 3336; IS 2454; IS 15570	ISO 11640 (Leather — Colour Fastness to Rubbing); ISO 3377-1 (Leather — Tear Load); ISO 2419 (Leather — Conditioning of Test Specimens)ISO 17232; ISO 17233	ASTM D6182 (Resistance of Leather to Scuffing); ASTM D2209 (Tensile Strength of Leather); ASTM D3884 (Abrasion Resistance, where textile-backed leather applies); ASTM D1813 (Thickness of Leather),ASTM D2097; ASTM D2617; ASTM D3836	DIN EN ISO 3376 (Leather — Tensile Strength and Elongation); DIN EN ISO 3377-1 (Leather — Tear Load); DIN EN ISO 11640 (Leather — Colour Fastness to Rubbing); DIN EN ISO 17235 (Leather — Physical and Mechanical Tests — Softness)	Leather Working Group (LWG); California TB 117 (Furniture Fire Safety, where applicable); GREENGUARD Gold Certification
Office Chair Leather	IS 15006,IS 5914; IS 582; IS 3336; IS 2454; IS 15570	ISO 11640 (Leather — Colour Fastness to Rubbing); ISO 12947-2 (Textiles — Abrasion Resistance by Martindale Method, where applicable for upholstered surfaces)ISO 17232; ISO 17233	ASTM D6182 (Scuff Resistance of Leather); ASTM D4966 (Abrasion Resistance by Martindale Tester, where applicable); ASTM D2209 (Tensile Strength of Leather); ASTM D1813 (Thickness of Leather),ASTM D2097; ASTM D2617; ASTM D3836	DIN EN ISO 3376 (Leather Tensile Properties); DIN EN ISO 3377-1 (Leather Tear Strength); DIN EN ISO 11640 (Colour Fastness to Rubbing); DIN EN ISO 12947-2 (Abrasion Resistance, where coated/textile composites apply)	BIFMA Standards (Office Furniture Performance); Leather Working Group (LWG); GREENGUARD Gold Certification
Car Seat Leather	IS 15006,IS 5914; IS 582; IS 3336; IS 2454; IS 15570	ISO 17235 (Leather — Water Resistance of Surface Coated Leather); ISO 11640 (Colour Fastness to Rubbing); ISO 3377-1 (Tear Load)ISO 17232; ISO 17233	ASTM D6182 (Resistance of Leather to Scuffing); ASTM D2209 (Tensile Strength of Leather); ASTM D2099 (Dynamic Water Resistance of Shoe Upper Leather, where applicable); ASTM D3884 (Abrasion Resistance),ASTM D2097; ASTM D2617; ASTM D3836	DIN EN ISO 3376 (Leather Tensile Strength and Elongation); DIN EN ISO 3377-1 (Tear Strength); DIN EN ISO 11640 (Colour Fastness to Rubbing); DIN EN ISO 11641 (Colour Fastness to Perspiration)	GMW Material Specifications; VW TL Specifications; Mercedes-Benz DBL Specifications; Leather Working Group (LWG)
Aircraft Seat Leather	IS 577: Regulates durability, colorfastness, and stretching parameters for furniture cushions and heavy-use seating,IS 5914; IS 582; IS 3336; IS 2454; IS 15570	ISO 17235 (Leather — Water Resistance of Surface Coated Leather); ISO 11640 (Colour Fastness to Rubbing)ISO 17232; ISO 17233	ASTM D6182 (Scuff Resistance of Leather); ASTM D2209 (Tensile Strength of Leather); ASTM E1354 (Heat and Visible Smoke Release Rates of Materials, where applicable); ASTM D1813 (Thickness of Leather),ASTM D2097; ASTM D2617; ASTM D3836	DIN EN ISO 3376 (Leather Tensile Properties); DIN EN ISO 3377-1 (Tear Strength); DIN EN ISO 11640 (Colour Fastness to Rubbing); DIN EN ISO 11641 (Colour Fastness to Perspiration)	FAA Aircraft Interior Material Requirements; FAR 25.853 (Aircraft Interior Flammability); SAE Aerospace Material Specifications

Source field: Leather and Leather products