Engineering Plastics

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
PA6 Sheet; PA6 Rod; PA6 Bush	IS 13360;IS 9650; IS 17928; IS 17988; IS 16646; IS 5253; IS 5717; IS 11704; IS 11705; IS 13010; IS 14424; IS 14434; IS 14751; IS 14753; IS 15894	PA6 Rod; PA6 Bush;ISO 1874-1 (Plastics — Polyamide (PA) Moulding and Extrusion Materials — Designation System and Basis for Specifications)	ASTM D4066 (Nylon Injection and Extrusion Materials – material classification); ASTM D638 (Tensile Properties of Plastics); ASTM D790 (Flexural Properties of Plastics); ASTM D256 (Izod Impact Resistance of Plastics); ASTM D648 (Deflection Temperature of Plastics Under Flexural Load – where relevant)	DIN EN ISO 16396-1 (Polyamide Moulding and Extrusion Materials); DIN EN ISO 527 (Tensile Properties of Plastics); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 179-1 (Charpy Impact Strength)	UL 94 (Electrical Applications); FDA 21 CFR 177 (Food Contact Grades); Engineering Plastics Industry Specifications
PA66 Sheet; PA66 Rod; Heat Stabilized PA66	IS 13360;IS 9650; IS 17928; IS 17988; IS 16646; IS 5253; IS 5717; IS 11704; IS 11705; IS 13010; IS 14424; IS 14434; IS 14751; IS 14753; IS 15894	PA66 Rod; Heat Stabilized PA66;ISO 1874-1 (Plastics — Polyamide (PA) Moulding and Extrusion Materials — Designation System and Basis for Specifications)	ASTM D4066 (Nylon Injection and Extrusion Materials – material classification); ASTM D638 (Tensile Properties of Plastics); ASTM D790 (Flexural Properties of Plastics); ASTM D648 (Deflection Temperature of Plastics Under Flexural Load); ASTM D256 (Izod Impact Resistance of Plastics – where relevant)	DIN EN ISO 16396-1 (Polyamide Moulding and Extrusion Materials); DIN EN ISO 527-1 (Tensile Properties of Plastics); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 179-1 (Charpy Impact Strength); DIN EN ISO 2578 (Time-Temperature Limits of Plastics, for heat stabilized grades)	UL 94; UL 746A; Automotive and Electrical Component Material Specifications
Glass Filled PA66	IS 13360;IS 9650; IS 17928; IS 17988; IS 16646; IS 5253; IS 5717; IS 11704; IS 11705; IS 13010; IS 14424; IS 14434; IS 14751; IS 14753; IS 15894	ISO 1874-1 (Plastics — Polyamide (PA) Moulding and Extrusion Materials — Designation System and Basis for Specifications); ISO 527-4 (Plastics — Determination of Tensile Properties — Fibre-reinforced Composites)	ASTM D4066 (Nylon Injection and Extrusion Materials); ASTM D638 (Tensile Properties of Plastics); ASTM D790 (Flexural Properties of Plastics); ASTM D2584 (Ignition Loss of Cured Reinforced Resins)	DIN EN ISO 16396-1 (Polyamide Moulding and Extrusion Materials); DIN EN ISO 527-4 (Tensile Properties of Fibre-Reinforced Plastics); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 179-1 (Impact Strength)	UL 94; UL 746A; Automotive OEM Material Requirements; Electrical Connector Industry Specifications
POM Sheet; POM Rod; POM Bearing Grade	IS 9845 (Overall Migration of Plastics in Contact with Foodstuffs) (Food Contact Applications); IS 13010 (Polyethylene Terephthalate (PET) engineering grade molding compounds);IS 9650; IS 17928; IS 17988; IS 16646; IS 5253; IS 5717; IS 11704; IS 11705; IS 14424; IS 14434; IS 14751; IS 14753; IS 15894	ISO 9988-1 (Plastics — Polyoxymethylene (POM) Moulding and Extrusion Materials — Designation System and Basis for Specifications)	ASTM D6100 (Extruded, Compression Molded and Injection Molded Polyoxymethylene Shapes); ASTM D6778 (Polyoxymethylene Molding and Extrusion Materials – material classification); ASTM D638 (Tensile Properties of Plastics); ASTM D3702 (Wear Rate and Coefficient of Friction of Self-Lubricating Materials – particularly relevant to bearing grade); ASTM D790 (Flexural Properties of Plastics)	DIN EN ISO 9988-1 (Polyoxymethylene Moulding and Extrusion Materials); DIN EN ISO 527 (Tensile Properties); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 179-1 (Charpy Impact Strength)	FDA 21 CFR 177 (Food Contact Applications); NSF/ANSI 61 (Water Applications); UL 94
PTFE Sheet; PTFE Rod	IS 9845 (Overall Migration of Plastics in Contact with Foodstuffs) (Food Contact Applications); IS 11705 (Polytetrafluoroethylene (PTFE / Teflon) raw resins and extruded rods);IS 9650; IS 17928; IS 17988; IS 16646; IS 5253; IS 5717; IS 11704;	ISO 12086-1 (Plastics — Fluoropolymer Dispersions and Moulding and Extrusion Materials — Designation System and Basis for Specifications); ISO 14915 (Thermal and mechanical stability testing for advanced fluoropolymer engineering resins (PTFE))	ASTM D3294 (PTFE Resin Molded Sheet and Molded Basic Shapes); ASTM D1710 (Extruded PTFE Rod, Heavy-Walled Tubing and Basic Shapes – for extruded rod); ASTM D4894 (PTFE Granular Molding and Ram Extrusion Materials – resin); ASTM D4895 (PTFE Resin Produced From Aqueous Dispersion – where applicable); ASTM D638 (Tensile Properties of Plastics); ASTM D3702	DIN EN ISO 13000-1 (Polytetrafluoroethylene (PTFE) Moulding and Extrusion Materials); DIN EN ISO 12086-1 (Fluoropolymer Materials); DIN EN ISO 527-1 (Tensile Properties); DIN EN ISO 178 (Flexural Properties)	FDA 21 CFR 177; USP Class VI (Medical Applications); UL 94

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
	IS 13010; IS 14424; IS 14434; IS 14751; IS 14753; IS 15894		(Wear Rate and Coefficient of Friction of Self-Lubricating Materials – where relevant)		
PTFE Bush; Filled PTFE (Glass Filled); Filled PTFE (Carbon Filled); Filled PTFE (Bronze Filled)	IS 9845 (Overall Migration of Plastics in Contact with Foodstuffs) (Food Contact Applications); IS 11705 (Polytetrafluoroethylene (PTFE / Teflon) raw resins and extruded rods);IS 9650; IS 17928; IS 17988; IS 16646; IS 5253; IS 5717; IS 11704; IS 13010; IS 14424; IS 14434; IS 14751; IS 14753; IS 15894	ISO 12086-1 (Plastics — Fluoropolymer Materials — Designation System and Basis for Specifications); ISO 14915 (Thermal and mechanical stability testing for advanced fluoropolymer engineering resins (PTFE))	ASTM D4894 (PTFE Granular Molding and Ram Extrusion Materials); ASTM D4745 (Filled and Unfilled PTFE Molding and Extrusion Materials); ASTM D3702 (Wear Rate and Coefficient of Friction of Self-Lubricating Materials); ASTM D638 (Tensile Properties of Plastics)	DIN EN ISO 13000-1 (PTFE Materials); DIN EN ISO 12086-1 (Fluoropolymer Materials); DIN EN ISO 527-1 (Tensile Properties); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 1183-1 (Density of Plastics, where filler content evaluation applies)	FDA 21 CFR 177 (Food Contact Applications); USP Class VI (Medical Applications); Aerospace and Mechanical Engineering Material Requirements
UHMWPE Sheet; UHMWPE Rod	IS 10910 (Polyethylene and its Copolymers for Safe Use in Contact with Foodstuffs, Pharmaceuticals and Drinking Water);IS 9650; IS 17928; IS 17988; IS 16646; IS 5253; IS 5717; IS 11704; IS 11705; IS 13010; IS 14424; IS 14434; IS 14751; IS 14753; IS 15894	ISO 11542-1 (Plastics — Ultra-high Molecular Mass Polyethylene (PE-UHMW) Moulding and Extrusion Materials — Designation System and Basis for Specifications)	ASTM D6712 (UHMW-PE Solid Plastic Shapes); ASTM D4020 (UHMW-PE Molding and Extrusion Materials – material classification); ASTM D638 (Tensile Properties of Plastics); ASTM D256 (Izod Impact Resistance of Plastics); ASTM D648 (Deflection Temperature of Plastics Under Flexural Load)	DIN EN ISO 11542-1 (Ultra-High Molecular Weight Polyethylene Moulding Materials); DIN EN ISO 527-1 (Tensile Properties); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 179-1 (Impact Strength)	FDA 21 CFR 177; USP Class VI; Medical Device Material Requirements
UHMWPE Wear Strip	IS 10910 (Polyethylene and its Copolymers for Safe Use in Contact with Foodstuffs, Pharmaceuticals and Drinking Water); IS 14885 (Conveyor/Wear Applications);IS 9650; IS 17928; IS 17988; IS 16646; IS 5253; IS 5717; IS 11704; IS 11705; IS 13010; IS 14424; IS 14434; IS 14751; IS 14753; IS 15894	ISO 11542-1 (Plastics — Ultra-high Molecular Mass Polyethylene (PE-UHMW) Moulding and Extrusion Materials — Designation System and Basis for Specifications)	ASTM D4020 (Standard Specification for Ultra-High-Molecular-Weight Polyethylene Molding and Extrusion Materials); ASTM D3702 (Wear Rate and Coefficient of Friction of Self-Lubricating Materials); ASTM D1894 (Coefficient of Friction of Plastic Film and Sheeting, where applicable)	DIN EN ISO 11542-1 (Ultra-High Molecular Weight Polyethylene Moulding Materials); DIN EN ISO 527 (Tensile Properties); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 179-1 (Impact Strength)	FDA 21 CFR 177; NSF/ANSI 61 (Water Applications); Conveyor Industry Specifications
PC Sheet; PC Rod	IS 14434 (Glass-fiber reinforced Polyamide compounding formulas); IS 16646 (Polycarbonate (PC) molding, extrusion, and optical-grade raw plastics);IS 9650; IS 17928; IS 17988; IS 5253; IS 5717; IS 11704; IS 11705; IS 13010; IS 14424; IS 14751; IS	PC Rod;ISO 21305-1 (Plastics — Polycarbonate (PC) Moulding and Extrusion Materials — Designation System and Basis for Specifications); ISO 7391-1 (Plastics — Polycarbonate (PC) injection/extrusion polymers — Part 1: Designation identification); ISO 7391-2 (Plastics — Polycarbonate (PC) injection/extrusion polymers —	ASTM D6098 (Extruded and Compression Molded Shapes Made From Polycarbonate); ASTM D3935 (Polycarbonate Unfilled and Reinforced Material – material classification); ASTM D638 (Tensile Properties of Plastics); ASTM D256 (Izod Impact Resistance of Plastics); ASTM D1003 (Haze and Luminous Transmittance of Transparent Plastics – where applicable)	DIN EN ISO 21305-1 (Polycarbonate Moulding and Extrusion Materials); DIN EN ISO 527-1 (Tensile Properties); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 179-1 (Charpy Impact Strength)	UL 94; UL 746C; FDA 21 CFR 177 (Food Contact Grades)

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
	14753; IS 15894	Part 2: Standard spec profiles)			
Flame Retardant PC	IS 14434 (Glass-fiber reinforced Polyamide compounding formulas); IS 17048 (Flame Retardant Plastic Applications); IS 16646 (Polycarbonate (PC) molding, extrusion, and optical-grade raw plastics);IS 9650; IS 17928; IS 17988; IS 5253; IS 5717; IS 11704; IS 11705; IS 13010; IS 14424; IS 14751; IS 14753; IS 15894	ISO 21305-1 (Plastics — Polycarbonate (PC) Moulding and Extrusion Materials — Designation System and Basis for Specifications); ISO 4589-1 (Plastics — Determination of Burning Behaviour by Oxygen Index); ISO 7391-1 (Plastics — Polycarbonate (PC) injection/extrusion polymers — Part 1: Designation identification); ISO 7391-2 (Plastics — Polycarbonate (PC) injection/extrusion polymers — Part 2: Standard spec profiles)	ASTM D3935 (Polycarbonate (PC) Molding and Extrusion Materials); ASTM D3801 (Vertical Burning Characteristics of Solid Plastics); ASTM D635 (Horizontal Burning Characteristics of Plastics); ASTM D638 (Tensile Properties of Plastics)	DIN EN ISO 21305-1 (Polycarbonate Moulding and Extrusion Materials); DIN EN ISO 4589-2 (Oxygen Index of Plastics); DIN EN 60695-11-10 (Flammability Testing); DIN EN ISO 527 (Tensile Properties)	UL 94; IEC 60695; Electronics Industry Material Requirements
PMMA Sheet; PMMA Rod	IS 10139 (Acrylic Resins for Safe Use in Contact with Foodstuffs, Pharmaceuticals and Drinking Water); IS 17928 (Polymethyl Methacrylate (PMMA / Acrylic) sheets and raw polymers);IS 9650; IS 17988; IS 16646; IS 5253; IS 5717; IS 11704; IS 11705; IS 13010; IS 14424; IS 14434; IS 14751; IS 14753; IS 15894	ISO 8257-1 (Plastics — Poly(methyl methacrylate) (PMMA) Moulding and Extrusion Materials — Designation System and Basis for Specifications); ISO 24022-1 (Plastics — Polymethyl methacrylate (PMMA) materials — Part 1: Designation configuration structure); ISO 24022-2 (Plastics — Polymethyl methacrylate (PMMA) materials — Part 2: Property tracking profiles)	ASTM D788 (PMMA Molding and Extrusion Materials); ASTM D4802 (Poly(Methyl Methacrylate) Acrylic Plastic Sheet – for sheet); ASTM D638 (Tensile Properties of Plastics); ASTM D1003 (Haze and Luminous Transmittance of Transparent Plastics); ASTM D256 (Izod Impact Resistance of Plastics)	DIN EN ISO 8257-1 (Polymethyl Methacrylate (PMMA) Moulding and Extrusion Materials); DIN EN ISO 527-1 (Tensile Properties); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 179-1 (Impact Strength)	UL 94; UL 746C; Building Material Fire Classification Requirements
ABS Sheet; ABS Rod	IS 17077(ABS molding and extrusion materials); IS 9650; IS 17928; IS 17988; IS 16646; IS 5253; IS 5717; IS 11704; IS 11705; IS 13010; IS 14424; IS 14434; IS 14751; IS 14753; IS 15894	ISO 2580-1 (Plastics — Acrylonitrile-butadiene-styrene (ABS) Moulding and Extrusion Materials — Designation System and Basis for Specifications)	ASTM D4673 (ABS Plastics and Alloys Molding and Extrusion Materials); ASTM D638 (Tensile Properties of Plastics); ASTM D256 (Izod Impact Resistance of Plastics); ASTM D648 (Deflection Temperature of Plastics Under Flexural Load)	DIN EN ISO 2580-1 (Acrylonitrile-Butadiene-Styrene (ABS) Moulding and Extrusion Materials); DIN EN ISO 527-1 (Tensile Properties); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 179-1 (Impact Strength)	UL 94; UL 746A; UL 746C
Flame Retardant ABS	IS 17077(ABS molding and extrusion materials); IS 9650; IS 17928; IS 17988; IS 16646; IS 5253; IS 5717; IS 11704; IS 11705; IS 13010; IS 14424; IS 14434; IS 14751; IS 14753; IS 15894	ISO 2580-1 (Plastics — Acrylonitrile-butadiene-styrene (ABS) Moulding and Extrusion Materials — Designation System and Basis for Specifications); ISO 4589-1 (Plastics — Determination of Burning Behaviour by Oxygen Index)	ASTM D4673 (ABS Molding and Extrusion Materials); ASTM D3801 (Vertical Burning Characteristics of Solid Plastics); ASTM D635 (Horizontal Burning Characteristics of Plastics); ASTM D638 (Tensile Properties of Plastics)	DIN EN ISO 2580-1 (ABS Moulding and Extrusion Materials); DIN EN ISO 4589-2 (Oxygen Index); DIN EN 60695-11-10 (Flammability Testing); DIN EN ISO 527 (Tensile Properties)	UL 94; IEC 60695; Electronics Industry Safety Requirements
PVDF Sheet; PVDF Rod	IS 9845 (Overall Migration of Plastics in Contact with Foodstuffs) (Food Contact Applications); IS 11705 (Polytetrafluoroethylene	ISO 12086-1 (Plastics — Fluoropolymer Dispersions and Moulding and Extrusion Materials — Designation System and Basis for Specifications); ISO 14915 (Thermal and mechanical stability	ASTM D6713 (Extruded and Compression Molded Shapes Made From PVDF); ASTM D3222 (Unmodified PVDF Molding, Extrusion and Coating Materials – material classification); ASTM D638 (Tensile	DIN EN ISO 12086-1 (Fluoropolymer Materials); DIN EN ISO 527-1 (Tensile Properties); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 179-1 (Impact Strength)	FDA 21 CFR 177; NSF/ANSI 61; Semiconductor Industry Material Specifications

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
	(PTFE / Teflon) raw resins and extruded rods);IS 9650; IS 17928; IS 17988; IS 16646; IS 5253; IS 5717; IS 11704; IS 13010; IS 14424; IS 14434; IS 14751; IS 14753; IS 15894	testing for advanced fluoropolymer engineering resins (PTFE))	Properties of Plastics); ASTM D256 (Izod Impact Resistance of Plastics); ASTM D543 (Resistance of Plastics to Chemical Reagents – where chemical resistance is relevant)		
PEEK Sheet	IS 9845 (Overall Migration of Plastics in Contact with Foodstuffs) (Food Contact Applications); IS 9650; IS 17928; IS 17988; IS 16646; IS 5253; IS 5717; IS 11704; IS 11705; IS 13010; IS 14424; IS 14434; IS 14751; IS 14753; IS 15894	ISO 16354 (Plastics — Polyetheretherketone (PEEK) Moulding and Extrusion Materials — Designation System and Basis for Specifications)	ASTM D6262 (Polyetheretherketone (PEEK) Molding and Extrusion Materials); ASTM D638 (Tensile Properties of Plastics); ASTM D790 (Flexural Properties of Plastics); ASTM D648 (Deflection Temperature of Plastics Under Flexural Load)	DIN EN ISO 21318-1 (Polyetheretherketone Moulding and Extrusion Materials); DIN EN ISO 527 (Tensile Properties); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 179-1 (Impact Strength)	FDA 21 CFR 177; USP Class VI; Aerospace Material Specifications
PEEK Rod	IS 9845 (Migration Limits for Plastics in Contact with Foodstuffs) (Food Contact Applications); IS 14193; IS 14434; IS 11297; IS 1998; IS 13360	ISO 16354 (Plastics — Polyetheretherketone (PEEK) Moulding and Extrusion Materials — Designation System and Basis for Specifications); ISO 604 (General test method for determining compressive properties of plastic rod elements)	ASTM D6262 (Extruded, Compression Molded, and Injection Molded Basic Shapes of PAEK); ASTM D8033 (PEEK Molding and Extrusion Materials – material classification); ASTM D638 (Tensile Properties of Plastics); ASTM D790 (Flexural Properties of Unreinforced and Reinforced Plastics); ASTM D648 (Deflection Temperature of Plastics Under Flexural Load – where relevant)	DIN EN ISO 21318-1 (Polyetheretherketone Moulding and Extrusion Materials); DIN EN ISO 527 (Tensile Properties); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 179-1 (Impact Strength)	FDA 21 CFR 177; USP Class VI; UL 94
Glass Filled PEEK; Carbon Filled PEEK; Bearing Grade PEEK	IS 9845 (Overall Migration of Plastics in Contact with Foodstuffs) (Food Contact Applications); IS 13010 (Polyethylene Terephthalate (PET) engineering grade molding compounds);IS 9650; IS 17928; IS 17988; IS 16646; IS 5253; IS 5717; IS 11704; IS 11705; IS 14424; IS 14434; IS 14751; IS 14753; IS 15894	ISO 16354 (Plastics — Polyetheretherketone (PEEK) Moulding and Extrusion Materials — Designation System and Basis for Specifications); ISO 527-4 (Plastics — Determination of Tensile Properties — Fibre-reinforced Composites)	ASTM D6262 (Polyetheretherketone (PEEK) Molding and Extrusion Materials); ASTM D638 (Tensile Properties of Plastics); ASTM D790 (Flexural Properties of Plastics); ASTM D2584 (Ignition Loss of Cured Reinforced Resins); ASTM D3702 (Wear Rate and Coefficient of Friction of Self-Lubricating Materials)	DIN EN ISO 21318-1 (Polyetheretherketone Moulding and Extrusion Materials); DIN EN ISO 527-4 (Tensile Properties of Fibre-Reinforced Plastics); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 179-1 (Impact Strength); DIN EN ISO 1183-1 (Density of Plastics)	FDA 21 CFR 177; USP Class VI; Aerospace and High Performance Engineering Material Requirements
PPS Sheet; PPS Rod	IS 9845 (Overall Migration of Plastics in Contact with Foodstuffs) (Food Contact Applications); IS 9650; IS 17928; IS 17988; IS 16646; IS 5253; IS 5717; IS 11704; IS 11705; IS 13010; IS 14424; IS 14434; IS 14751; IS	ISO 20558-1 (Plastics — Polyphenylene Sulfide (PPS) Moulding and Extrusion Materials — Designation System and Basis for Specifications)	ASTM D4067 (Reinforced and Filled PPS Injection Molding and Extrusion Materials Using ASTM Methods); ASTM D638 (Tensile Properties of Plastics); ASTM D790 (Flexural Properties of Plastics); ASTM D648 (Deflection Temperature of Plastics Under Flexural Load)	DIN EN ISO 28078-1 (Polyphenylene Sulfide Moulding and Extrusion Materials); DIN EN ISO 527 (Tensile Properties); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 179-1 (Impact Strength)	UL 94; UL 746A; Electrical/Electronic Component Material Requirements

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
	14753; IS 15894				
PSU Sheet	IS 9845 (Overall Migration of Plastics in Contact with Foodstuffs) (Food Contact Applications); IS 9650; IS 17928; IS 17988; IS 16646; IS 5253; IS 5717; IS 11704; IS 11705; IS 13010; IS 14424; IS 14434; IS 14751; IS 14753; IS 15894	ISO 21304-1 (Plastics — Polyarylsulfone (PSU) Moulding and Extrusion Materials — Designation System and Basis for Specifications)	ASTM D6394 (Polyphenylene Ether (PPE) Molding and Extrusion Materials, where applicable); ASTM D638 (Tensile Properties of Plastics); ASTM D790 (Flexural Properties of Plastics); ASTM D648 (Deflection Temperature of Plastics Under Flexural Load)	DIN EN ISO 21305-1 (Polycarbonate Materials, where applicable); DIN EN ISO 527 (Tensile Properties); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 179-1 (Impact Strength)	FDA 21 CFR 177; USP Class VI; UL 94
PEI Sheet	IS 9845 (Overall Migration of Plastics in Contact with Foodstuffs) (Food Contact Applications); IS 9650; IS 17928; IS 17988; IS 16646; IS 5253; IS 5717; IS 11704; IS 11705; IS 13010; IS 14424; IS 14434; IS 14751; IS 14753; IS 15894	ISO 21304-2 (Plastics — Polyetherimide (PEI) Moulding and Extrusion Materials — Designation System and Basis for Specifications)	ASTM D5205 (Polyetherimide (PEI) Molding and Extrusion Materials); ASTM D638 (Tensile Properties of Plastics); ASTM D790 (Flexural Properties of Plastics); ASTM D648 (Deflection Temperature of Plastics Under Flexural Load)	DIN EN ISO 527 (Tensile Properties); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 179-1 (Impact Strength); DIN EN ISO 11357 (Thermal Properties by DSC)	UL 94; Aerospace Material Requirements; Electrical Component Specifications
PET Sheet (Engineering Grade); PET Rod (Engineering Grade)	IS 12252 (Polyethylene Terephthalate (PET) for Safe Use in Contact with Foodstuffs, Pharmaceuticals and Drinking Water); IS 11704 (Polyurethane (PU) engineering resins for casting and structures); IS 13010 (Polyethylene Terephthalate (PET) engineering grade molding compounds); IS 14424 (Polybutylene Terephthalate (PBT) engineering raw materials); IS 14751 (Polyphenylene Ether (PPE) technical engineering plastic resins);IS 9650; IS 17928; IS 17988; IS 16646; IS 5253; IS 5717; IS 11705; IS 14434; IS 14753; IS 15894	ISO 7792-1 (Plastics — Thermoplastic Polyester (TP) Moulding and Extrusion Materials — Designation System and Basis for Specifications)	ASTM D6261 (Extruded and Compression Molded Basic Shapes Made From Thermoplastic Polyester); ASTM D4603 (Inherent Viscosity of PET); ASTM D638 (Tensile Properties of Plastics); ASTM D790 (Flexural Properties of Plastics); ASTM D648 (Deflection Temperature of Plastics Under Flexural Load)	DIN EN ISO 7792-1 (Thermoplastic Polyester Moulding Materials); DIN EN ISO 527-1 (Tensile Properties); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 179-1 (Impact Strength)	FDA 21 CFR 177; UL 94; Engineering Plastics Industry Specifications
PBT Sheet; PBT Rod	IS 9845 (Overall Migration of Plastics in Contact with Foodstuffs) (Food Contact Applications); IS 13010 (Polyethylene	ISO 7792-1 (Plastics — Thermoplastic Polyester (TP) Moulding and Extrusion Materials — Designation System and Basis for Specifications)	ASTM D6261 (Extruded and Compression Molded Basic Shapes Made From Thermoplastic Polyester – applicable to PBT shapes); ASTM D5927 (Thermoplastic Polyester Molding and Extrusion Materials	DIN EN ISO 7792-1 (Thermoplastic Polyester Moulding Materials); DIN EN ISO 527-1 (Tensile Properties); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 179-1 (Impact Strength)	UL 94; UL 746A; Electrical Connector Industry Specifications

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
	Terephthalate (PET) engineering grade molding compounds); IS 14424 (Polybutylene Terephthalate (PBT) engineering raw materials);IS 9650; IS 17928; IS 17988; IS 16646; IS 5253; IS 5717; IS 11704; IS 11705; IS 14434; IS 14751; IS 14753; IS 15894		Based on ISO Test Methods – material classification); ASTM D638 (Tensile Properties of Plastics); ASTM D790 (Flexural Properties of Plastics); ASTM D648 (Deflection Temperature of Plastics Under Flexural Load)		
ESD Engineering Plastic	IS 11704 (Polyurethane (PU) engineering resins for casting and structures); IS 13010 (Polyethylene Terephthalate (PET) engineering grade molding compounds); IS 14424 (Polybutylene Terephthalate (PBT) engineering raw materials); IS 14751 (Polyphenylene Ether (PPE) technical engineering plastic resins);IS 9650; IS 17928; IS 17988; IS 16646; IS 5253; IS 5717; IS 11705; IS 14434; IS 14753; IS 15894	ISO 11469 (Plastics — Generic Identification and Marking of Plastics Products); IEC 61340-5-1 (Electrostatics — Protection of Electronic Devices from Electrostatic Phenomena); ISO 14915 (Thermal and mechanical stability testing for advanced fluoropolymer engineering resins (PTFE))	ASTM D257 (DC Resistance or Conductance of Insulating Materials); ASTM E595 (Total Mass Loss and Collected Volatile Condensable Materials from Outgassing in Vacuum Environment, where electronic applications apply); ASTM D991 (Volume Resistivity of Electrically Conductive and Antistatic Products); ASTM D638 (Tensile Properties of Plastics)	DIN EN 61340-2-3 (Methods for Determining Resistance and Resistivity of Flat Materials); DIN EN 61340-5-1 (Protection of Electronic Devices from Electrostatic Phenomena); DIN EN ISO 527 (Tensile Properties); DIN EN ISO 178 (Flexural Properties)	IEC 61340 Series; ANSI/ESD S20.20; UL 94
Medical Grade Engineering Plastic	IS 17387 (Packaging Materials for Terminally Sterilized Medical Devices); IS 9845 (Medical/Food Contact Applications); IS 11704 (Polyurethane (PU) engineering resins for casting and structures); IS 13010 (Polyethylene Terephthalate (PET) engineering grade molding compounds); IS 14424 (Polybutylene Terephthalate (PBT) engineering raw materials); IS 14751 (Polyphenylene Ether (PPE) technical engineering plastic resins);IS 9650; IS 17928; IS 17988; IS 16646; IS 5253; IS 5717;	ISO 10993-1 (Biological Evaluation of Medical Devices — Evaluation and Testing); ISO 13485 (Medical Devices — Quality Management Systems); ISO 14915 (Thermal and mechanical stability testing for advanced fluoropolymer engineering resins (PTFE))	ASTM F2026 (Polyetheretherketone (PEEK) for Surgical Implant Applications, where applicable); ASTM F748 (Standard Practice for Selecting Generic Biological Test Methods for Materials and Devices); ASTM D638 (Tensile Properties of Plastics); ASTM D543 (Resistance of Plastics to Chemical Reagents)	DIN EN ISO 10993-5 (Biological Evaluation of Medical Devices — Cytotoxicity); DIN EN ISO 10993-10 (Skin Sensitization and Irritation); DIN EN ISO 527 (Tensile Properties); DIN EN ISO 10993-18 (Chemical Characterization of Medical Device Materials)	USP Class VI; FDA 21 CFR 177; Medical Device Material Requirements

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
	IS 11705; IS 14434; IS 14753; IS 15894				
Food Contact Engineering Plastic	IS 9845 (Overall Migration of Plastics in Contact with Foodstuffs); IS 16738 (Positive List of Constituents for Polypropylene, Polyethylene and their Copolymers for Safe Use in Contact with Foodstuffs and Pharmaceuticals); IS 11704 (Polyurethane (PU) engineering resins for casting and structures); IS 13010 (Polyethylene Terephthalate (PET) engineering grade molding compounds); IS 14424 (Polybutylene Terephthalate (PBT) engineering raw materials); IS 14751 (Polyphenylene Ether (PPE) technical engineering plastic resins);IS 9650; IS 17928; IS 17988; IS 16646; IS 5253; IS 5717; IS 11705; IS 14434; IS 14753; IS 15894	ISO 22000 (Food Safety Management Systems); ISO 1186 (Materials and Articles in Contact with Foodstuffs — Plastics); ISO 14915 (Thermal and mechanical stability testing for advanced fluoropolymer engineering resins (PTFE))	ASTM D6400 (Compostable Plastics, where applicable); ASTM D1894 (Coefficient of Friction of Plastic Film and Sheeting, where applicable); ASTM D792 (Density and Specific Gravity of Plastics); ASTM D638 (Tensile Properties of Plastics)	DIN EN 1186 (Materials and Articles in Contact with Foodstuffs); DIN EN ISO 527 (Tensile Properties); DIN EN ISO 175 (Chemical Resistance); DIN EN ISO 1183-1 (Density of Plastics)	FDA 21 CFR 177; EU 10/2011; NSF/ANSI 51

Source field: Plastic and Plastic Products