Extruded Profiles

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
PVC Window Profile; PVC Door Profile	IS 4020 (PVC Door and Window Profiles); IS 12818 (Unplasticized PVC (uPVC) Extruded Screen and Casing Pipes for Wells); IS 14925 (Extruded PVC Profiles for Architectural Doors and Windows); IS 13592 (Extruded uPVC Pipes for Soil and Waste Discharge Systems in buildings); IS 15265 (Extruded flexible PVC strip curtains for industrial doorways); IS 15778 (Chlorinated Polyvinyl Chloride (CPVC) extruded pipes for hot/cold water);IS 4984; IS 14885; IS 4985; IS 7834; IS 9537; IS 12231; IS 14182; IS 14333; IS 15328; IS 16088	PVC Door Profile;ISO 1163-1 (Plastics — Unplasticized Poly(vinyl chloride) (PVC-U) Moulding and Extrusion Materials — Designation System and Basis for Specifications); ISO 12608-1 (Thermoplastics Profiles for Windows and Doors — PVC-U Profiles)	ASTM D4726 (Rigid Poly(Vinyl Chloride) (PVC) Exterior-Profile Extrusions); ASTM D648 (Heat Deflection Temperature of Plastics); ASTM D638 (Tensile Properties of Plastics); ASTM D256 (Izod Impact Resistance of Plastics); ASTM D3678S (Standard Specification for Rigid Poly(Vinyl Chloride) (PVC) Interior-Profile Extrusions); ASTM D4099S (Standard Specification for Poly(Vinyl Chloride) (PVC) Prime Windows/Sliding Glass Doors and Profile Extrusions); ASTM D5260S (Standard Classification for Chemical Resistance of Poly(Vinyl Chloride) (PVC) Homopolymer and Copolymer Compounds and Profile Extrusions); ASTM D1042S (Standard Test Method for Linear Dimensional Changes of Plastics Caused by Exposure to Heat and Moisture (Profile Stability)); ASTM D256S (Standard Test Methods for Determining the Izod Pendulum Impact Resistance of Plastics (Applicable to profile section testing)); ASTM D4216S (Standard Specification for Rigid Poly(Vinyl Chloride) (PVC) and Related PVC and Chlorinated Poly(Vinyl Chloride) (CPVC) Building Products Compounds)	DIN EN 12608-1 (PVC-U Profiles for the Fabrication of Windows and Doors); DIN EN ISO 527 (Tensile Properties); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 179-1 (Impact Strength)	AAMA Fenestration Standards; NFRC Window Performance Standards; ENERGY STAR Fenestration Requirements (where applicable)
PVC Electrical Trunking Profile	IS 14927 (PVC Cable Trunking and Ducting Systems); IS 12818 (Unplasticized PVC (uPVC) Extruded Screen and Casing Pipes for Wells); IS 14925 (Extruded PVC Profiles for Architectural Doors and Windows); IS 9537 (Part 3) (Extruded rigid insulating PVC conduits for electrical wiring); IS 13592 (Extruded uPVC Pipes for Soil and Waste Discharge Systems in buildings); IS 15265	ISO 9001 (Quality Management Systems, where applicable); ISO 1163-1 (PVC-U Materials Designation)	ASTM D1784 (Rigid PVC and CPVC Compounds); ASTM D635 (Rate of Burning and/or Extent and Time of Burning of Plastics in a Horizontal Position); ASTM D638 (Tensile Properties of Plastics); ASTM D3678S (Standard Specification for Rigid Poly(Vinyl Chloride) (PVC) Interior-Profile Extrusions); ASTM D4099S (Standard Specification for Poly(Vinyl Chloride) (PVC) Prime Windows/Sliding Glass Doors and Profile Extrusions); ASTM D5260S (Standard Classification for Chemical Resistance of Poly(Vinyl Chloride) (PVC) Homopolymer and Copolymer Compounds and Profile Extrusions); ASTM D1042S (Standard Test Method for Linear Dimensional Changes of Plastics Caused by Exposure to Heat and Moisture (Profile Stability)); ASTM	DIN EN 50085-1 (Cable Trunking Systems and Cable Ducting Systems for Electrical Installations); DIN EN 60695-11-10 (Fire Hazard Testing — Flame Test Methods); DIN EN ISO 527 (Tensile Properties); DIN EN ISO 178 (Flexural Properties)	UL 94; UL 2239 (Electrical Raceways and Fittings); NFPA 70 (Electrical Installations)

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
	(Extruded flexible PVC strip curtains for industrial doorways); IS 15778 (Chlorinated Polyvinyl Chloride (CPVC) extruded pipes for hot/cold water);IS 4984; IS 14885; IS 4985; IS 7834; IS 12231; IS 14182; IS 14333; IS 15328; IS 16088		D256S (Standard Test Methods for Determining the Izod Pendulum Impact Resistance of Plastics (Applicable to profile section testing)); ASTM D4216S (Standard Specification for Rigid Poly(Vinyl Chloride) (PVC) and Related PVC and Chlorinated Poly(Vinyl Chloride) (CPVC) Building Products Compounds)		
PVC Cable Duct Profile	IS 14927 (PVC Cable Trunking and Ducting Systems); IS 12818 (Unplasticized PVC (uPVC) Extruded Screen and Casing Pipes for Wells); IS 14925 (Extruded PVC Profiles for Architectural Doors and Windows); IS 9537 (Part 3) (Extruded rigid insulating PVC conduits for electrical wiring); IS 13592 (Extruded uPVC Pipes for Soil and Waste Discharge Systems in buildings); IS 15265 (Extruded flexible PVC strip curtains for industrial doorways); IS 15778 (Chlorinated Polyvinyl Chloride (CPVC) extruded pipes for hot/cold water);IS 4984; IS 14885; IS 4985; IS 7834; IS 12231; IS 14182; IS 14333; IS 15328; IS 16088	ISO 161-1 (Thermoplastics Pipes for the Conveyance of Fluids — Nominal Outside Diameters and Nominal Pressures); ISO 1163-1 (PVC-U Materials)	ASTM D1784 (Rigid PVC and CPVC Compounds); ASTM D635 (Flammability of Plastics); ASTM D256 (Impact Resistance of Plastics); ASTM D3678S (Standard Specification for Rigid Poly(Vinyl Chloride) (PVC) Interior-Profile Extrusions); ASTM D4099S (Standard Specification for Poly(Vinyl Chloride) (PVC) Prime Windows/Sliding Glass Doors and Profile Extrusions); ASTM D5260S (Standard Classification for Chemical Resistance of Poly(Vinyl Chloride) (PVC) Homopolymer and Copolymer Compounds and Profile Extrusions); ASTM D1042S (Standard Test Method for Linear Dimensional Changes of Plastics Caused by Exposure to Heat and Moisture (Profile Stability)); ASTM D256S (Standard Test Methods for Determining the Izod Pendulum Impact Resistance of Plastics (Applicable to profile section testing)); ASTM D4216S (Standard Specification for Rigid Poly(Vinyl Chloride) (PVC) and Related PVC and Chlorinated Poly(Vinyl Chloride) (CPVC) Building Products Compounds)	DIN EN 61386-1 (Conduit Systems for Cable Management); DIN EN 61386-24 (Conduit Systems Buried Underground); DIN EN ISO 527 (Tensile Properties); DIN EN ISO 178 (Flexural Properties)	UL 94; NFPA 70; Telcordia/Telecom Utility Specifications
PVC Wall Panel Profile; PVC Ceiling Panel Profile	IS 10151 (Polyvinyl Chloride (PVC) and its Copolymers) (PVC Material); IS 4020 (PVC Building Profiles); IS 12818 (Unplasticized PVC (uPVC) Extruded	PVC Ceiling Panel Profile;ISO 1163-1 (PVC-U Moulding and Extrusion Materials — Designation System)	ASTM D4726 (Rigid PVC Exterior-Profile Extrusions); ASTM D635 (Flammability of Plastics); ASTM D638 (Tensile Properties of Plastics); ASTM D3678S (Standard Specification for Rigid Poly(Vinyl Chloride) (PVC) Interior-Profile Extrusions); ASTM D4099S (Standard Specification for	DIN EN 13245-1 (Plastics — PVC Profiles for Building Applications); DIN EN 13501-1 (Reaction to Fire Classification); DIN EN ISO 527 (Tensile Properties); DIN EN ISO 178 (Flexural Properties)	GREENGUARD Certification (Indoor Air Quality); UL 94 (Fire Classification, where applicable); Building Material Authority Requirements

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
	Screen and Casing Pipes for Wells); IS 14925 (Extruded PVC Profiles for Architectural Doors and Windows); IS 13592 (Extruded uPVC Pipes for Soil and Waste Discharge Systems in buildings); IS 15265 (Extruded flexible PVC strip curtains for industrial doorways); IS 15778 (Chlorinated Polyvinyl Chloride (CPVC) extruded pipes for hot/cold water);IS 4984; IS 14885; IS 4985; IS 7834; IS 9537; IS 12231; IS 14182; IS 14333; IS 15328; IS 16088		Poly(Vinyl Chloride) (PVC) Prime Windows/Sliding Glass Doors and Profile Extrusions); ASTM D5260S (Standard Classification for Chemical Resistance of Poly(Vinyl Chloride) (PVC) Homopolymer and Copolymer Compounds and Profile Extrusions); ASTM D1042S (Standard Test Method for Linear Dimensional Changes of Plastics Caused by Exposure to Heat and Moisture (Profile Stability)); ASTM D256S (Standard Test Methods for Determining the Izod Pendulum Impact Resistance of Plastics (Applicable to profile section testing)); ASTM D4216S (Standard Specification for Rigid Poly(Vinyl Chloride) (PVC) and Related PVC and Chlorinated Poly(Vinyl Chloride) (CPVC) Building Products Compounds)		
WPC Decking Profile	IS 17334 (Wood Polymer Composite Products for Building Applications); IS 4984; IS 12818; IS 14885; IS 14925; IS 4985; IS 7834; IS 9537; IS 12231; IS 13592; IS 14182; IS 14333; IS 15265; IS 15328; IS 15778; IS 16088	ISO 16616 (Wood-Plastic Composites — Test Methods for Deck Boards); ISO 20819 (Wood-Plastic Composites — Specifications)	ASTM D7031 (Standard Guide for Evaluating Mechanical and Physical Properties of Wood-Plastic Composite Products); ASTM D7032 (Establishing Performance Ratings for Wood-Plastic Composite Deck Boards and Guardrail Systems); ASTM D790 (Flexural Properties of Plastics); ASTM D4099S (Standard Specification for Poly(Vinyl Chloride) (PVC) Prime Windows/Sliding Glass Doors and Profile Extrusions); ASTM D5260S (Standard Classification for Chemical Resistance of Poly(Vinyl Chloride) (PVC) Homopolymer and Copolymer Compounds and Profile Extrusions); ASTM D1042S (Standard Test Method for Linear Dimensional Changes of Plastics Caused by Exposure to Heat and Moisture (Profile Stability)); ASTM D256S (Standard Test Methods for Determining the Izod Pendulum Impact Resistance of Plastics (Applicable to profile section testing))	DIN EN 15534-1 (Wood-Plastic Composites — Characteristics of WPC Materials); DIN EN 15534-4 (Decking Profiles and Tiles); DIN EN ISO 527 (Tensile Properties); DIN EN ISO 178 (Flexural Properties)	ICC-ES Evaluation Criteria for Composite Decking; GREENGUARD Gold Certification (Indoor/Low Emission Applications); Building Code Approval Requirements
WPC Fence Profile	IS 17334 (Wood Polymer Composite Products for Building Applications); IS 4984; IS 12818; IS 14885; IS 14925; IS	ISO 16616 (Wood-Plastic Composites — Test Methods); ISO 20819 (Wood-Plastic Composites — Specifications)	ASTM D7031 (Mechanical and Physical Properties of Wood-Plastic Composite Products); ASTM D7032 (Performance Ratings for Wood-Plastic Composite Deck Boards and Guardrail Systems); ASTM D790 (Flexural Properties of	DIN EN 15534-1 (Wood-Plastic Composites — Characteristics); DIN EN ISO 527 (Tensile Properties); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 4892-3 (Artificial Weathering)	ICC-ES Evaluation Criteria for Composite Building Products; GREENGUARD Certification; Local Building Authority Specifications

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
	4985; IS 7834; IS 9537; IS 12231; IS 13592; IS 14182; IS 14333; IS 15265; IS 15328; IS 15778; IS 16088		Plastics); ASTM D4099S (Standard Specification for Poly(Vinyl Chloride) (PVC) Prime Windows/Sliding Glass Doors and Profile Extrusions); ASTM D5260S (Standard Classification for Chemical Resistance of Poly(Vinyl Chloride) (PVC) Homopolymer and Copolymer Compounds and Profile Extrusions); ASTM D1042S (Standard Test Method for Linear Dimensional Changes of Plastics Caused by Exposure to Heat and Moisture (Profile Stability)); ASTM D256S (Standard Test Methods for Determining the Izod Pendulum Impact Resistance of Plastics (Applicable to profile section testing))		
Plastic Handrail Profile	IS 17334 (Building Applications); IS 10151 / IS 10910 (Depending on Material); IS 4984; IS 12818; IS 14885; IS 14925; IS 4985; IS 7834; IS 9537; IS 12231; IS 13592; IS 14182; IS 14333; IS 15265; IS 15328; IS 15778; IS 16088	ISO 14122-3 (Safety of Machinery — Permanent Means of Access — Stairs, Stepladders and Guard-rails)	ASTM D7032 (Performance Ratings for Wood-Plastic Composite Deck Boards and Guardrail Systems, where WPC-based); ASTM D638 (Tensile Properties of Plastics); ASTM D790 (Flexural Properties of Plastics); ASTM D4099S (Standard Specification for Poly(Vinyl Chloride) (PVC) Prime Windows/Sliding Glass Doors and Profile Extrusions); ASTM D5260S (Standard Classification for Chemical Resistance of Poly(Vinyl Chloride) (PVC) Homopolymer and Copolymer Compounds and Profile Extrusions); ASTM D1042S (Standard Test Method for Linear Dimensional Changes of Plastics Caused by Exposure to Heat and Moisture (Profile Stability)); ASTM D256S (Standard Test Methods for Determining the Izod Pendulum Impact Resistance of Plastics (Applicable to profile section testing))	DIN EN ISO 527-1 (Tensile Properties of Plastics); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 179-1 (Impact Strength); DIN EN ISO 4892-3 (Artificial Weathering, where outdoor application applies)	OSHA Walking-Working Surface Requirements; ADA Accessibility Guidelines; Building Code Requirements
FRP Pultruded Profile	IS 6746 (FRP Structural Profiles for Building/Industrial Applications);IS 4984; IS 12818; IS 14885; IS 14925; IS 4985; IS 7834; IS 9537; IS 12231; IS 13592; IS 14182; IS 14333; IS 15265; IS 15328; IS 15778; IS 16088	ISO 14125 (Fibre-reinforced Plastic Composites — Determination of Flexural Properties); ISO 527-5 (Plastics — Determination of Tensile Properties — Unidirectional Fibre-reinforced Plastic Composites)	ASTM D3917 (Dimensional Tolerances of Thermosetting Glass-Reinforced Plastic Pultruded Shapes); ASTM D638 (Tensile Properties of Plastics); ASTM D790 (Flexural Properties of Plastics); ASTM D2584 (Ignition Loss of Cured Reinforced Resins); ASTM D4099S (Standard Specification for Poly(Vinyl Chloride) (PVC) Prime Windows/Sliding Glass Doors and Profile Extrusions); ASTM D5260S (Standard Classification for Chemical Resistance of Poly(Vinyl Chloride) (PVC) Homopolymer and Copolymer Compounds and Profile Extrusions); ASTM D1042S (Standard Test Method for Linear Dimensional Changes of	DIN EN 13706-1 (Reinforced Plastics Composites — Pultruded Profiles); DIN EN 13706-2 (General Specifications); DIN EN ISO 527-4 (Tensile Properties of Fibre-Reinforced Plastics); DIN EN ISO 14125 (Flexural Properties of Fibre-Reinforced Composite Materials)	ANSI/ACMA FRP Standards; OSHA Structural Safety Requirements; NEMA FG Standards (Electrical Applications)

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
			Plastics Caused by Exposure to Heat and Moisture (Profile Stability)); ASTM D256S (Standard Test Methods for Determining the Izod Pendulum Impact Resistance of Plastics (Applicable to profile section testing))		

Source field: Plastic and Plastic Products