Plastic Compounds

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
Glass Filled PP Compound (Automotive)	IS 10910 (Polypropylene for its Safe Use in Contact with Foodstuffs, Pharmaceuticals and Drinking Water); (Automotive Plastic Components, where applicable);IS 2530; IS 15225; IS 16087; IS 10146; IS 10151; IS 12252; IS 13360	ISO 1873-1 (Plastics — Polypropylene (PP) Moulding and Extrusion Materials — Designation System and Basis for Specifications); ISO 527-4 (Plastics — Determination of Tensile Properties — Isotropic and Orthotropic Fibre-reinforced Composites); ISO 3451-1 (Standardized protocols for general ash content verification in raw compound bases)	ASTM D4101 (Polypropylene Injection and Extrusion Materials); ASTM D638 (Tensile Properties of Plastics); ASTM D790 (Flexural Properties of Plastics); ASTM D2584 (Ignition Loss of Cured Reinforced Resins); ASTM D256 (Izod Impact Resistance of Plastics); ASTM D4101S (Standard Classification System for Polypropylene Injection and Extrusion Materials); ASTM D2584S (Standard Test Method for Ignition Loss of Cured Reinforced Resins (Determining glass fiber or mineral filler content in plastic compounds))	DIN EN ISO 1873-1 (Polypropylene Moulding and Extrusion Materials); DIN EN ISO 527 (Tensile Properties of Plastics); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 179-1 (Charpy Impact Strength); DIN EN ISO 3451-1 (Determination of Ash Content of Plastics)	UL 94 (Flammability Classification); OEM Automotive Material Specifications (GM/Ford/VW); SAE Automotive Material Requirements
Talc Filled PP Compound; Mineral Filled PP Compound; Long Glass Fibre PP Compound; UV Stabilized PP Compound	IS 10910 (Polypropylene for its Safe Use in Contact with Foodstuffs, Pharmaceuticals and Drinking Water);IS 2530; IS 15225; IS 16087; IS 10146; IS 10151; IS 12252; IS 13360	Mineral Filled PP Compound; Long Glass Fibre PP Compound; UV Stabilized PP Compound;ISO 1873-1 (Polypropylene (PP) Moulding and Extrusion Materials — Designation System and Basis for Specifications); ISO 527-4 (Fibre-reinforced Composite Tensile Properties); ISO 3451-1 (Standardized protocols for general ash content verification in raw compound bases)	ASTM D4101 (Polypropylene Injection and Extrusion Materials); ASTM D638 (Tensile Properties of Plastics); ASTM D790 (Flexural Properties of Plastics); ASTM D256 (Izod Impact Resistance of Plastics); ASTM D4329 (Fluorescent UV Exposure of Plastics, where UV stabilized application applies); ASTM D4101S (Standard Classification System for Polypropylene Injection and Extrusion Materials); ASTM D2584S (Standard Test Method for Ignition Loss of Cured Reinforced Resins (Determining glass fiber or mineral filler content in plastic compounds))	DIN EN ISO 1873-1 (Polypropylene Moulding and Extrusion Materials); DIN EN ISO 527-1 (Tensile Properties); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 3451-1 (Determination of Ash Content of Plastics); DIN EN ISO 4892-3 (Artificial Weathering, where UV stabilization applies)	UL 94 (where electrical applications apply); Automotive OEM Material Specifications; SAE Weathering Requirements (UV Stabilized Grades)
Flame Retardant PP Compound	IS 10910 (Polypropylene for its Safe Use in Contact with Foodstuffs, Pharmaceuticals and Drinking Water); IS 17048 (Flame Retardant Plastic Applications);IS 2530; IS 15225; IS 16087; IS 10146; IS 10151; IS 12252; IS 13360	ISO 1873-1 (Plastics — Polypropylene (PP) Moulding and Extrusion Materials — Designation System and Basis for Specifications); ISO 4589-1 (Plastics — Determination of Burning Behaviour by Oxygen Index — General Requirements); ISO 3451-1 (Standardized protocols for general ash content verification in raw compound bases)	ASTM D4101 (Polypropylene Injection and Extrusion Materials); ASTM D635 (Rate of Burning and/or Extent and Time of Burning of Plastics in a Horizontal Position); ASTM D3801 (Flammability of Solid Plastics in Vertical Position); ASTM D638 (Tensile Properties of Plastics); ASTM D4101S (Standard Classification System for Polypropylene Injection and Extrusion Materials)	DIN EN ISO 4589-2 (Oxygen Index of Plastics); DIN EN 60695-11-10 (Fire Hazard Testing — Flame Test); DIN EN ISO 527 (Tensile Properties); DIN EN ISO 178 (Flexural Properties)	UL 94; IEC 60695 (Fire Hazard Testing for Electrical Equipment); NFPA Fire Safety Requirements (where applicable)
Conductive PP Compound; Antistatic PP Compound	IS 10910 (Polypropylene for its Safe Use in Contact with Foodstuffs, Pharmaceuticals and Drinking Water);IS 4985; IS 13592; IS	Antistatic PP Compound;ISO 1873-1 (Polypropylene (PP) Moulding and Extrusion Materials — Designation System and Basis for Specifications); IEC 61340-5-1 (Electrostatics — Protection of Electronic Devices from Electrostatic Phenomena); ISO 3451-1 (Standardized protocols for	ASTM D257 (DC Resistance or Conductance of Insulating Materials); ASTM D991 (Rubber Property — Volume Resistivity of Electrically Conductive and Antistatic Products); ASTM D638 (Tensile Properties of Plastics); ASTM D4101 (Polypropylene Materials); ASTM D4101S (Standard	DIN EN 61340-2-3 (Methods for Determining Resistance and Resistivity of Flat Materials); DIN EN ISO 1873-1 (Polypropylene Materials); DIN EN ISO 527-1 (Tensile Properties); DIN EN ISO 178 (Flexural Properties)	IEC 61340 Series (Electrostatic Control); ANSI/ESD S20.20 (ESD Control Programme); UL 94

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
	15778; IS 12231; IS 12818; IS 14182; IS 16087; IS 4984; IS 14333; IS 14885; IS 16088; IS 15225; IS 15265; IS 15801; IS 16098; IS 14402; IS 7834; IS 14735; IS 17546; IS 10124; IS 13593; IS 8008; IS 17424; IS 12235; IS 7634; IS 5382	general ash content verification in raw compound bases)	Classification System for Polypropylene Injection and Extrusion Materials)		
Food Contact PP Compound	IS 10910 (Polypropylene and its Copolymers for Safe Use in Contact with Foodstuffs, Pharmaceuticals and Drinking Water); IS 10146:1982 (Polyethylene for its Safe Use in Contact with Foodstuffs, Pharmaceuticals and Drinking Water); IS 10151:2019 (Polyvinyl Chloride (PVC) for its Safe Use in Contact with Foodstuffs, Pharmaceuticals and Drinking Water); IS 12252:2017 (Polyalkylene Terephthalates (PET & PBT) for their Safe Use in Contact with Foodstuffs, Pharmaceuticals and Drinking Water);IS 2530; IS 15225; IS 16087; IS 13360	ISO 1873-1 (Polypropylene (PP) Moulding and Extrusion Materials — Designation System and Basis for Specifications); ISO 22000 (Food Safety Management Systems); ISO 3451-1 (Standardized protocols for general ash content verification in raw compound bases)	ASTM D4101 (Polypropylene Injection and Extrusion Materials); ASTM D6400 (Compostable Plastics, where applicable); ASTM D1238 (Melt Flow Rates of Thermoplastics); ASTM D792 (Density and Specific Gravity of Plastics); ASTM D4101S (Standard Classification System for Polypropylene Injection and Extrusion Materials)	DIN EN 1186 (Materials and Articles in Contact with Foodstuffs); DIN EN ISO 1873-1 (Polypropylene Materials); DIN EN ISO 527 (Tensile Properties); DIN EN ISO 1183-1 (Density of Plastics)	FDA 21 CFR 177 (Food Contact Plastics); EU 10/2011 (Food Contact Materials); NSF/ANSI 51 (Food Equipment Materials)
Medical Grade PP Compound	IS 10910 (Polypropylene for its Safe Use in Contact with Foodstuffs, Pharmaceuticals and Drinking Water); IS 17387 (Medical Device Packaging Applications);IS 2530; IS 15225; IS 16087; IS 10146; IS 10151; IS 12252; IS	ISO 1873-1 (Polypropylene (PP) Moulding and Extrusion Materials — Designation System and Basis for Specifications); ISO 10993-1 (Biological Evaluation of Medical Devices); ISO 3451-1 (Standardized protocols for general ash content verification in raw compound bases)	ASTM D4101 (Polypropylene Injection and Extrusion Materials); ASTM D638 (Tensile Properties of Plastics); ASTM D543 (Resistance of Plastics to Chemical Reagents); ASTM F2026 (Polyetheretherketone (PEEK) Materials, where applicable to medical polymer applications); ASTM D4101S (Standard Classification System for Polypropylene Injection and Extrusion Materials)	DIN EN ISO 10993-5 (Biological Evaluation of Medical Devices — Cytotoxicity); DIN EN ISO 10993-10 (Skin Sensitization); DIN EN ISO 1873-1 (Polypropylene Materials); DIN EN ISO 527 (Tensile Properties)	USP Class VI (Biocompatibility); FDA 21 CFR 177; FDA Medical Device Material Requirements

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
	13360				
Glass Filled Nylon 6 Compound	IS 13464;IS 2530; IS 15225; IS 16087; IS 10146; IS 10910; IS 10151; IS 12252; IS 13360	ISO 1874-1 (Plastics — Polyamide (PA) Moulding and Extrusion Materials — Designation System and Basis for Specifications); ISO 527-4 (Plastics — Determination of Tensile Properties — Fibre-reinforced Composites); ISO 16396-1 (Designation and engineering compilation matrix for Polyamide (PA) compounding [2.1]); ISO 3451-1 (Standardized protocols for general ash content verification in raw compound bases)	ASTM D4066 (Nylon Injection and Extrusion Materials); ASTM D638 (Tensile Properties of Plastics); ASTM D790 (Flexural Properties of Plastics); ASTM D2584 (Ignition Loss of Cured Reinforced Resins); ASTM D4066S (Standard Classification System for Nylon Injection and Extrusion Materials (PA)); ASTM D2584S (Standard Test Method for Ignition Loss of Cured Reinforced Resins (Determining glass fiber or mineral filler content in plastic compounds)); ASTM D789S (Standard Test Methods for Determination of Solution Viscosity of Polyamide (PA))	DIN EN ISO 16396-1 (Polyamide Moulding and Extrusion Materials); DIN EN ISO 527-4 (Tensile Properties of Fibre-Reinforced Plastics); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 179-1 (Impact Strength)	UL 94; UL 746A (Polymeric Material Evaluation); Automotive and Electrical Component Material Specifications
Glass Filled Nylon 66 Compound	IS 13464;IS 2530; IS 15225; IS 16087; IS 10146; IS 10910; IS 10151; IS 12252; IS 13360	ISO 1874-1 (Plastics — Polyamide (PA) Moulding and Extrusion Materials — Designation System and Basis for Specifications); ISO 527-4 (Fibre-reinforced Composite Tensile Properties); ISO 16396-1 (Designation and engineering compilation matrix for Polyamide (PA) compounding [2.1]); ISO 3451-1 (Standardized protocols for general ash content verification in raw compound bases)	ASTM D4066 (Nylon Injection and Extrusion Materials); ASTM D638 (Tensile Properties of Plastics); ASTM D790 (Flexural Properties of Plastics); ASTM D256 (Izod Impact Resistance of Plastics); ASTM D4066S (Standard Classification System for Nylon Injection and Extrusion Materials (PA)); ASTM D2584S (Standard Test Method for Ignition Loss of Cured Reinforced Resins (Determining glass fiber or mineral filler content in plastic compounds)); ASTM D789S (Standard Test Methods for Determination of Solution Viscosity of Polyamide (PA))	DIN EN ISO 16396-1 (Polyamide Materials); DIN EN ISO 527-4 (Tensile Properties of Reinforced Plastics); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 179-1 (Impact Strength)	UL 94; UL 746A; UL 746C (End Product Applications); Electrical Connector Industry Specifications
Flame Retardant Nylon Compound	IS 13464;IS 2530; IS 15225; IS 16087; IS 10146; IS 10910; IS 10151; IS 12252; IS 13360	ISO 1874-1 (Polyamide (PA) Moulding and Extrusion Materials — Designation System and Basis for Specifications); ISO 4589-1 (Determination of Burning Behaviour by Oxygen Index); ISO 16396-1 (Designation and engineering compilation matrix for Polyamide (PA) compounding [2.1]); ISO 3451-1 (Standardized protocols for general ash content verification in raw compound bases)	ASTM D4066 (Nylon Injection and Extrusion Materials); ASTM D635 (Flammability of Plastics); ASTM D3801 (Vertical Flammability of Solid Plastics); ASTM D638 (Tensile Properties of Plastics); ASTM D4066S (Standard Classification System for Nylon Injection and Extrusion Materials (PA)); ASTM D789S (Standard Test Methods for Determination of Solution Viscosity of Polyamide (PA))	DIN EN ISO 4589-2 (Oxygen Index); DIN EN 60695-11-10 (Flammability Testing); DIN EN ISO 527 (Tensile Properties); DIN EN ISO 178 (Flexural Properties)	UL 94; IEC 60695; Electrical/Electronic Component Material Requirements
Heat Stabilized Nylon Compound; Oil Resistant Nylon Compound	IS 13464;IS 2530; IS 15225; IS 16087; IS 10146; IS 10910; IS 10151; IS 12252; IS 13360	Oil Resistant Nylon Compound;ISO 1874-1 (Polyamide (PA) Moulding and Extrusion Materials — Designation System and Basis for Specifications); ISO 16396-1 (Designation and engineering compilation matrix for Polyamide (PA) compounding [2.1]); ISO 3451-1 (Standardized protocols for general ash content verification in raw compound bases)	ASTM D4066 (Nylon Injection and Extrusion Materials); ASTM D638 (Tensile Properties of Plastics); ASTM D648 (Deflection Temperature of Plastics Under Flexural Load); ASTM D543 (Resistance of Plastics to Chemical Reagents); ASTM D4066S (Standard Classification System for Nylon Injection and Extrusion Materials (PA)); ASTM D789S (Standard Test Methods for Determination of Solution Viscosity of Polyamide (PA))	DIN EN ISO 16396-1 (Polyamide Moulding and Extrusion Materials); DIN EN ISO 527-1 (Tensile Properties); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 175 (Resistance of Plastics to Liquid Chemicals); DIN EN ISO 2578 (Time-Temperature Limits of Plastics, where heat stabilization applies)	UL 94; Automotive OEM Material Specifications; Engine Compartment Material Requirements

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
Glass Filled PBT Compound	IS 9845 (Overall Migration of Plastics in Contact with Foodstuffs) (Food Contact Applications); IS 2530; IS 15225; IS 16087; IS 10146; IS 10910; IS 10151; IS 12252; IS 13360	ISO 7792-1 (Plastics — Thermoplastic Polyester (TP) Moulding and Extrusion Materials — Designation System and Basis for Specifications); ISO 527-4 (Fibre-reinforced Composite Tensile Properties); ISO 3451-1 (Standardized protocols for general ash content verification in raw compound bases)	ASTM D7291 (Polybutylene Terephthalate (PBT) Molding and Extrusion Materials); ASTM D638 (Tensile Properties of Plastics); ASTM D790 (Flexural Properties of Plastics); ASTM D2584 (Ignition Loss of Cured Reinforced Resins); ASTM D2584S (Standard Test Method for Ignition Loss of Cured Reinforced Resins (Determining glass fiber or mineral filler content in plastic compounds))	DIN EN ISO 7792-1 (Thermoplastic Polyester Moulding Materials); DIN EN ISO 527-4 (Fibre-Reinforced Plastics Tensile Properties); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 179-1 (Impact Strength)	UL 94; UL 746A; UL 746C; Electrical Connector Industry Specifications
Flame Retardant PBT Compound	IS 9845 (Overall Migration of Plastics in Contact with Foodstuffs) (Food Contact Applications); IS 17048 (Flame Retardant Plastic Applications); IS 2530; IS 15225; IS 16087; IS 10146; IS 10910; IS 10151; IS 12252; IS 13360	ISO 7792-1 (Thermoplastic Polyester (TP) Moulding and Extrusion Materials — Designation System and Basis for Specifications); ISO 4589-1 (Oxygen Index Determination); ISO 3451-1 (Standardized protocols for general ash content verification in raw compound bases)	ASTM D7291 (Polybutylene Terephthalate (PBT) Materials); ASTM D635 (Horizontal Burning Characteristics of Plastics); ASTM D3801 (Vertical Burning Characteristics of Solid Plastics); ASTM D638 (Tensile Properties of Plastics)	DIN EN ISO 4589-2 (Oxygen Index); DIN EN 60695-11-10 (Flammability Testing); DIN EN ISO 7792-1 (PBT Materials); DIN EN ISO 527 (Tensile Properties)	UL 94 V-rating Requirements; IEC 60695; Electrical and Electronics Industry Material Specifications
Glass Filled PC Compound	IS 14434 (Polycarbonate Applications); IS 2530; IS 15225; IS 16087; IS 10146; IS 10910; IS 10151; IS 12252; IS 13360	ISO 21305-1 (Plastics — Polycarbonate (PC) Moulding and Extrusion Materials — Designation System and Basis for Specifications); ISO 527-4 (Plastics — Determination of Tensile Properties — Fibre-reinforced Composites); ISO 3451-1 (Standardized protocols for general ash content verification in raw compound bases)	ASTM D3935 (Polycarbonate (PC) Molding and Extrusion Materials); ASTM D638 (Tensile Properties of Plastics); ASTM D790 (Flexural Properties of Plastics); ASTM D256 (Izod Impact Resistance of Plastics); ASTM D2584S (Standard Test Method for Ignition Loss of Cured Reinforced Resins (Determining glass fiber or mineral filler content in plastic compounds))	DIN EN ISO 21305-1 (Polycarbonate Moulding Materials); DIN EN ISO 527-4 (Fibre-Reinforced Plastics); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 179-1 (Impact Strength)	UL 94; UL 746A; Electrical Component Material Specifications
Flame Retardant PC Compound	IS 14434 (Polycarbonate Applications); IS 17048 (Flame Retardant Plastic Applications); IS 2530; IS 15225; IS 16087; IS 10146; IS 10910; IS 10151; IS 12252; IS 13360	ISO 21305-1 (Polycarbonate (PC) Moulding and Extrusion Materials — Designation System and Basis for Specifications); ISO 4589-1 (Plastics — Determination of Burning Behaviour by Oxygen Index); ISO 3451-1 (Standardized protocols for general ash content verification in raw compound bases)	ASTM D3935 (Polycarbonate (PC) Molding and Extrusion Materials); ASTM D3801 (Vertical Burning Characteristics of Solid Plastics); ASTM D635 (Horizontal Burning Characteristics of Plastics); ASTM D638 (Tensile Properties of Plastics)	DIN EN ISO 4589-2 (Oxygen Index); DIN EN 60695-11-10 (Flammability); DIN EN ISO 21305-1 (Polycarbonate Materials); DIN EN ISO 527 (Tensile Properties)	UL 94; IEC 60695; Electrical/Electronics Industry Requirements
PC/ABS Compound; ABS Flame Retardant Compound	IS 17077(ABS molding and extrusion materials); IS 2530; IS 15225; IS 16087; IS 10146; IS 10910; IS 10151; IS 12252; IS 13360	ABS Flame Retardant Compound;ISO 2580-1 (Plastics — Acrylonitrile-butadiene-styrene (ABS) Moulding and Extrusion Materials — Designation System and Basis for Specifications); ISO 21305-1 (Polycarbonate Materials); ISO 3451-1 (Standardized protocols for general ash content verification in raw compound bases)	ASTM D4673 (ABS Molding and Extrusion Materials); ASTM D3935 (Polycarbonate Materials); ASTM D638 (Tensile Properties of Plastics); ASTM D256 (Izod Impact Resistance of Plastics); ASTM D3801 (Vertical Flammability of Solid Plastics)	DIN EN ISO 2580-1 (ABS Moulding and Extrusion Materials); DIN EN ISO 21305-1 (Polycarbonate Materials, where applicable); DIN EN ISO 527-1 (Tensile Properties); DIN EN ISO 179-1 (Impact Strength); DIN EN ISO 4589-2 (Oxygen Index, for flame retardant grades)	UL 94; UL 746A; UL 746C; Electronics Housing Material Requirements

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
Glass Filled POM Compound; PTFE Filled POM Compound	IS 9845 (Overall Migration of Plastics in Contact with Foodstuffs) (Food Contact Applications); IS 2530; IS 15225; IS 16087; IS 10146; IS 10910; IS 10151; IS 12252; IS 13360	PTFE Filled POM Compound;ISO 9988-1 (Plastics — Polyoxymethylene (POM) Moulding and Extrusion Materials — Designation System and Basis for Specifications); ISO 527-4 (Fibre-reinforced Composite Tensile Properties, where applicable); ISO 3451-1 (Standardized protocols for general ash content verification in raw compound bases)	ASTM D6778 (Polyoxymethylene (Acetal) Molding and Extrusion Materials); ASTM D638 (Tensile Properties of Plastics); ASTM D790 (Flexural Properties of Plastics); ASTM D256 (Izod Impact Resistance of Plastics); ASTM D2584S (Standard Test Method for Ignition Loss of Cured Reinforced Resins (Determining glass fiber or mineral filler content in plastic compounds))	DIN EN ISO 9988-1 (Polyoxymethylene Moulding and Extrusion Materials); DIN EN ISO 527-4 (Tensile Properties of Fibre-Reinforced Plastics, for filled grades); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 179-1 (Impact Strength)	FDA 21 CFR 177 (Food Contact Applications); UL 94; Engineering Plastics Industry Specifications
Carbon Filled PEEK Compound; Glass Filled PEEK Compound	IS 9845 (Overall Migration of Plastics in Contact with Foodstuffs) (Food Contact Applications); IS 2530; IS 15225; IS 16087; IS 10146; IS 10910; IS 10151; IS 12252; IS 13360	Glass Filled PEEK Compound;ISO 16354 (Plastics — Polyetheretherketone (PEEK) Moulding and Extrusion Materials — Designation System and Basis for Specifications); ISO 527-4 (Fibre-reinforced Composite Tensile Properties); ISO 18553 (Assessment method for carbon black or organic pigment dispersion uniformity in polyolefin compounds [2.1]); ISO 3451-1 (Standardized protocols for general ash content verification in raw compound bases)	ASTM D6262 (Polyetheretherketone (PEEK) Molding and Extrusion Materials); ASTM D638 (Tensile Properties of Plastics); ASTM D790 (Flexural Properties of Plastics); ASTM D2584 (Ignition Loss of Cured Reinforced Resins); ASTM D2584S (Standard Test Method for Ignition Loss of Cured Reinforced Resins (Determining glass fiber or mineral filler content in plastic compounds))	DIN EN ISO 21318-1 (Polyetheretherketone Moulding and Extrusion Materials); DIN EN ISO 527-4 (Fibre-Reinforced Plastics Tensile Properties); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 179-1 (Impact Strength)	FDA 21 CFR 177; USP Class VI; Aerospace and Medical Device Material Requirements
Bearing Grade PEEK Compound	IS 9845 (Overall Migration of Plastics in Contact with Foodstuffs) (Food Contact Applications); IS 2530; IS 15225; IS 16087; IS 10146; IS 10910; IS 10151; IS 12252; IS 13360	ISO 16354 (Polyetheretherketone (PEEK) Moulding and Extrusion Materials — Designation System and Basis for Specifications); ISO 3451-1 (Standardized protocols for general ash content verification in raw compound bases)	ASTM D6262 (Polyetheretherketone (PEEK) Molding and Extrusion Materials); ASTM D3702 (Wear Rate and Coefficient of Friction of Self-Lubricating Materials); ASTM D638 (Tensile Properties of Plastics)	DIN EN ISO 21318-1 (PEEK Materials); DIN EN ISO 527 (Tensile Properties); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 2813 (Wear/Surface Characteristics, where applicable)	FDA 21 CFR 177; USP Class VI; Aerospace/High Performance Tribology Material Specifications
Conductive PEEK Compound	IS 9845 (Overall Migration of Plastics in Contact with Foodstuffs) (Food Contact Applications); IS 4985; IS 13592; IS 15778; IS 12231; IS 12818; IS 14182; IS 16087; IS 4984; IS 14333; IS 14885; IS 16088; IS 15225; IS 15265; IS 15801; IS 16098; IS 14402; IS 7834; IS 14735; IS 17546; IS 10124; IS 13593; IS 8008; IS 17424; IS 12235; IS 7634; IS 5382	ISO 16354 (Polyetheretherketone (PEEK) Moulding and Extrusion Materials — Designation System and Basis for Specifications); IEC 61340-5-1 (Electrostatics — Protection of Electronic Devices from Electrostatic Phenomena); ISO 3451-1 (Standardized protocols for general ash content verification in raw compound bases)	ASTM D257 (DC Resistance or Conductance of Insulating Materials); ASTM D6262 (PEEK Molding and Extrusion Materials); ASTM D638 (Tensile Properties of Plastics)	DIN EN 61340-2-3 (Determination of Resistance and Resistivity of Flat Materials); DIN EN ISO 21318-1 (PEEK Materials); DIN EN ISO 527 (Tensile Properties); DIN EN ISO 178 (Flexural Properties)	IEC 61340 Series (ESD Applications); ANSI/ESD S20.20; UL 94
Glass Filled PPS Compound	IS 9845 (Overall	ISO 20558-1 (Plastics —	ASTM D4067 (Reinforced and Filled	DIN EN ISO 28078-1 (Polyphenylene	UL 94; UL 746A;

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
	Migration of Plastics in Contact with Foodstuffs) (Food Contact Applications); IS 2530; IS 15225; IS 16087; IS 10146; IS 10910; IS 10151; IS 12252; IS 13360	Polyphenylene Sulfide (PPS) Moulding and Extrusion Materials — Designation System and Basis for Specifications); ISO 527-4 (Fibre-reinforced Composite Tensile Properties); ISO 3451-1 (Standardized protocols for general ash content verification in raw compound bases)	Polyphenylene Sulfide (PPS) Molding and Extrusion Materials); ASTM D638 (Tensile Properties of Plastics); ASTM D790 (Flexural Properties of Plastics); ASTM D2584 (Ignition Loss of Cured Reinforced Resins); ASTM D2584S (Standard Test Method for Ignition Loss of Cured Reinforced Resins (Determining glass fiber or mineral filler content in plastic compounds))	Sulfide (PPS) Moulding Materials); DIN EN ISO 527-4 (Fibre-Reinforced Plastics Tensile Properties); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 179-1 (Impact Strength)	Electrical/Electronic Component Material Requirements
Flame Retardant PPS Compound	IS 9845 (Overall Migration of Plastics in Contact with Foodstuffs) (Food Contact Applications); IS 17048 (Flame Retardant Plastic Applications); IS 2530; IS 15225; IS 16087; IS 10146; IS 10910; IS 10151; IS 12252; IS 13360	ISO 20558-1 (Polyphenylene Sulfide (PPS) Moulding and Extrusion Materials — Designation System and Basis for Specifications); ISO 4589-1 (Determination of Burning Behaviour by Oxygen Index); ISO 3451-1 (Standardized protocols for general ash content verification in raw compound bases)	ASTM D4067 (Polyphenylene Sulfide (PPS) Molding and Extrusion Materials); ASTM D3801 (Vertical Burning Characteristics of Solid Plastics); ASTM D635 (Horizontal Burning Characteristics of Plastics); ASTM D638 (Tensile Properties of Plastics)	DIN EN ISO 4589-2 (Oxygen Index of Plastics); DIN EN 60695-11-10 (Flammability Testing); DIN EN ISO 28078-1 (PPS Materials); DIN EN ISO 527 (Tensile Properties)	UL 94; IEC 60695; Electrical Industry Safety Requirements
Glass Filled PVDF Compound	IS 9845 (Overall Migration of Plastics in Contact with Foodstuffs) (Food Contact Applications); IS 2530; IS 15225; IS 16087; IS 10146; IS 10910; IS 10151; IS 12252; IS 13360	ISO 12086-1 (Plastics — Fluoropolymer Dispersions and Moulding and Extrusion Materials — Designation System and Basis for Specifications); ISO 527-4 (Fibre-reinforced Composite Tensile Properties); ISO 3451-1 (Standardized protocols for general ash content verification in raw compound bases)	ASTM D3222 (Unmodified Poly(Vinylidene Fluoride) (PVDF) Molding and Extrusion Materials); ASTM D638 (Tensile Properties of Plastics); ASTM D790 (Flexural Properties of Plastics); ASTM D2584 (Ignition Loss of Cured Reinforced Resins); ASTM D2584S (Standard Test Method for Ignition Loss of Cured Reinforced Resins (Determining glass fiber or mineral filler content in plastic compounds))	DIN EN ISO 12086-1 (Fluoropolymer Materials); DIN EN ISO 527-4 (Fibre-Reinforced Plastics Tensile Properties); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 179-1 (Impact Strength)	FDA 21 CFR 177; NSF/ANSI 61 (where water applications apply); Chemical Processing Industry Specifications
Flame Retardant PVC Compound (Wire & Cable)	IS 5831 (PVC Insulation and Sheathing Compounds for Electric Cables); IS 694 (PVC Insulated Cables); IS 16087:2016 (Polyvinyl Chloride (PVC) Compounds for Rigid and Flexible Applications — Specification);IS 2530; IS 15225; IS 10146; IS 10910; IS 10151; IS 12252; IS 13360	ISO 1163-1 (Plastics — Unplasticized Poly(vinyl chloride) (PVC-U) Moulding and Extrusion Materials — Designation System and Basis for Specifications); IEC 60332-1-2 (Tests on Electric and Optical Fibre Cables Under Fire Conditions — Vertical Flame...); ISO 3451-1 (Standardized protocols for general ash content verification in raw compound bases)	ASTM D1784 (Rigid PVC and CPVC Compounds); ASTM D635 (Rate of Burning and/or Extent and Time of Burning of Plastics); ASTM D2863 (Measuring the Minimum Oxygen Concentration to Support Candle-like Combustion of Plastics); ASTM D638 (Tensile Properties of Plastics); ASTM D1784S (Standard Classification System and Basis for Specification for Rigid Poly(Vinyl Chloride) (PVC) Compounds and Chlorinated Poly(Vinyl Chloride) (CPVC) Compounds); ASTM D5260S (Standard Classification for Chemical Resistance of Poly(Vinyl Chloride) (PVC) Homopolymer and Copolymer Compounds and Profile Extrusions); ASTM D4396S (Standard Specification for Rigid Poly(Vinyl Chloride) (PVC) and Chlorinated	DIN EN IEC 60227-1 (Polyvinyl Chloride Insulated Cables — General Requirements); DIN EN IEC 60811-501 (Mechanical Tests for Insulation and Sheathing Materials); DIN EN IEC 60332-1-2 (Tests on Electric Cables Under Fire Conditions — Vertical Flame Propagation); DIN EN ISO 4589-2 (Oxygen Index of Plastics)	UL 94; UL 1581 (Wire and Cable Testing); NFPA 70 (Electrical Installations); NEMA Cable Requirements

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
			Poly(Vinyl Chloride) (CPVC) Compounds for Plastic Pipe and Fittings); ASTM D4216S (Standard Specification for Rigid Poly(Vinyl Chloride) (PVC) and Related PVC and Chlorinated Poly(Vinyl Chloride) (CPVC) Building Products Compounds)		
XLPE Cable Compound	IS 7098 (Cross-linked Polyethylene Insulated PVC Sheathed Cables); IS 14255 (XLPE Insulation Compounds); IS 2530; IS 15225; IS 16087; IS 10146; IS 10910; IS 10151; IS 12252; IS 13360	ISO 1872-2 (Plastics — Polyethylene (PE) Moulding and Extrusion Materials — Preparation of Test Specimens and Determination of Properties); IEC 60502-1 (Power Cables with Extruded Insulation); ISO 3451-1 (Standardized protocols for general ash content verification in raw compound bases)	ASTM D1248 (Polyethylene Plastics Extrusion Materials for Wire and Cable); ASTM D2655 (Polyethylene Insulation and Jacket Materials for Wire and Cable); ASTM D638 (Tensile Properties of Plastics); ASTM D257 (DC Resistance or Conductance of Insulating Materials)	DIN EN 60811-501 (Mechanical Tests for Insulation and Sheathing Materials); DIN EN IEC 60502-1 (Power Cables with Extruded Insulation); DIN EN ISO 527 (Tensile Properties); DIN EN ISO 11357 (Thermal Properties of Plastics)	UL 44 (Thermoset-Insulated Wires and Cables); UL 1581; IEEE Cable Industry Requirements
LSZH Cable Compound	IS 17048 (Low Smoke Halogen Free Cable Applications); IS 17091 (LSZH Cable Compounds, where applicable); IS 2530; IS 15225; IS 16087; IS 10146; IS 10910; IS 10151; IS 12252; IS 13360	ISO 3451-1 (Standardized protocols for general ash content verification in raw compound bases)	ASTM D2863 (Minimum Oxygen Concentration to Support Combustion of Plastics); ASTM D635 (Burning Characteristics of Plastics); ASTM D257 (Electrical Resistance of Insulating Materials); ASTM D638 (Tensile Properties of Plastics)	DIN EN 60754-1 (Test on Gases Evolved During Combustion of Cable Materials — Halogen Acid Gas); DIN EN 60754-2 (Acidity and Conductivity of Gases); DIN EN 61034-2 (Smoke Density of Cables); DIN EN 50399 (Heat Release and Smoke Production During Flame Propagation)	IEC 60754 (Halogen Acid Gas Emission); IEC 61034 (Smoke Density); UL Cable Safety Requirements
TPU Compound (Medical Grade)	IS 17387 (Medical Device Packaging/Medical Polymer Applications); IS 9845 (Food/Medical Contact Applications); IS 2530; IS 15225; IS 16087; IS 10146; IS 10910; IS 10151; IS 12252; IS 13360	ISO 16365-1 (Plastics — Thermoplastic Polyurethane (TPU) Moulding and Extrusion Materials — Designation System and Basis for Specifications); ISO 10993-1 (Biological Evaluation of Medical Devices); ISO 3451-1 (Standardized protocols for general ash content verification in raw compound bases)	ASTM D412 (Vulcanized Rubber and Thermoplastic Elastomers — Tensile Properties); ASTM D2240 (Rubber Property — Durometer Hardness); ASTM D624 (Tear Strength of Conventional Vulcanized Rubber and Thermoplastic Elastomers); ASTM F2026 (Polyetheretherketone Materials for Surgical Implant Applications, where applicable)	DIN EN ISO 18064 (Thermoplastic Elastomers — Nomenclature and Classification); DIN EN ISO 10993-5 (Biological Evaluation of Medical Devices — Cytotoxicity); DIN EN ISO 10993-18 (Chemical Characterization of Medical Device Materials); DIN EN ISO 527-1 (Tensile Properties of Plastics)	USP Class VI; FDA 21 CFR 177; Medical Device Material Requirements
TPU Compound (Industrial Grade)	IS 9845 (Food Contact Applications, where applicable); IS 2530; IS 15225; IS 16087; IS 10146; IS 10910; IS 10151; IS 12252; IS 13360	ISO 16365-1 (Plastics — Thermoplastic Polyurethane (TPU) Moulding and Extrusion Materials — Designation System and Basis for Specifications); ISO 3451-1 (Standardized protocols for general ash content verification in raw compound bases)	ASTM D412 (Tensile Properties of Rubber and Thermoplastic Elastomers); ASTM D2240 (Durometer Hardness); ASTM D624 (Tear Strength of Rubber and Thermoplastic Elastomers); ASTM D471 (Rubber Property — Effect of Liquids)	DIN EN ISO 18064 (Thermoplastic Elastomers Classification); DIN EN ISO 527-1 (Tensile Properties); DIN EN ISO 868 (Hardness of Plastics and Ebonite by Durometer); DIN EN ISO 34-1 (Tear Strength of Rubber and Thermoplastic Elastomers)	UL 94; Automotive OEM Material Specifications; Industrial Elastomer Industry Requirements
TPE Compound; TPV Compound	IS 9845 (Overall Migration of Plastics in Contact with Foodstuffs) (Food Contact Applications); IS 2530; IS 15225; IS	TPV Compound;ISO 18064 (Thermoplastic Elastomers — Nomenclature and Abbreviated Terms); ISO 37 (Rubber, Vulcanized or Thermoplastic — Determination of Tensile Stress-Strain Properties); ISO 3451-1 (Standardized protocols	ASTM D412 (Tensile Properties of Rubber and Thermoplastic Elastomers); ASTM D2240 (Durometer Hardness); ASTM D624 (Tear Strength of Rubber and Thermoplastic Elastomers); ASTM D395 (Rubber Property — Compression Set)	DIN EN ISO 18064 (Thermoplastic Elastomers — Classification); DIN EN ISO 527-1 (Tensile Properties); DIN EN ISO 868 (Hardness by Durometer); DIN ISO 188 (Accelerated Ageing of Rubber, where elastomer phase applies)	UL 94; FDA 21 CFR 177 (Food Contact Grades); Automotive OEM Material Specifications

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
	16087; IS 10146; IS 10910; IS 10151; IS 12252; IS 13360	for general ash content verification in raw compound bases)			
SEBS Compound	IS 9845 (Overall Migration of Plastics in Contact with Foodstuffs) (Food Contact Applications); IS 2530; IS 15225; IS 16087; IS 10146; IS 10910; IS 10151; IS 12252; IS 13360	ISO 18064 (Thermoplastic Elastomers — Nomenclature and Abbreviated Terms); ISO 3451-1 (Standardized protocols for general ash content verification in raw compound bases)	ASTM D412 (Tensile Properties of Rubber and Thermoplastic Elastomers); ASTM D2240 (Durometer Hardness); ASTM D624 (Tear Strength of Rubber and Thermoplastic Elastomers); ASTM D395 (Compression Set of Rubber)	DIN EN ISO 18064 (Thermoplastic Elastomers Classification); DIN EN ISO 527 (Tensile Properties); DIN EN ISO 868 (Hardness); DIN EN ISO 34-1 (Tear Strength of Rubber and Thermoplastic Elastomers)	FDA 21 CFR 177 (food-contact grades); UL 94; Consumer Product Material Requirements

Source field: Plastic and Plastic Products