Plastic Laminates

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
High Pressure Decorative Laminate (HPL)	IS 2046 (Parts 1 to 8):2025 (Decorative Thermosetting Synthetic Resin-Bonded Laminated Sheets — Specification)	ISO 4586-1 (High-pressure Decorative Laminates – Classification & Specifications); ISO 4586-2 (Determination of Properties); ISO 19712-1 (Decorative solid surfacing materials); ISO 4586-7 (Test methods for decorative laminates)	ASTM E84 (Surface Burning Characteristics of Building Materials); ASTM D1037 (Evaluating Properties of Wood-Base Fiber and Particle Panel Materials, where applicable); ASTM D256 (Impact Resistance of Plastics); ASTM D4060 (Abrasion Resistance of Organic Coatings); ASTM D790 (flexural properties — notably absent despite being core to laminate qualification)	DIN EN 438-1 (High Pressure Decorative Laminates — Classification and Specifications); DIN EN 438-2 (Test Methods); DIN EN 438-6 (Exterior Grade Decorative Laminates); DIN EN ISO 2813 (Gloss Measurement)	EN 438 (High Pressure Decorative Laminates); NEMA LD 3 (Decorative Laminates); NSF/ANSI 35 (Laminate Food Service Applications, where applicable)
Compact Decorative Laminate	IS 2046 (Parts 1 to 8):2025 (Decorative Thermosetting Synthetic Resin-Bonded Laminated Sheets — Specification)	ISO 4586-1 (High-pressure decorative laminates (HPL)); ISO 4586-7 (Compact Laminate Classification & Requirements); ISO 19712-1 (Decorative solid surfacing materials)	ASTM E84 (Surface Burning Characteristics of Building Materials); ASTM D4060 (Abrasion Resistance of Organic Coatings); ASTM D790 (Standard Test Methods for Flexural Properties of Unreinforced and Reinforced Plastics and Electrical Insulating Materials); ASTM D5420 (Impact Resistance of Flat Rigid Plastic Specimens)	DIN EN 438-4 (Compact Decorative Laminates); DIN EN 438-2 (Test Methods for Decorative Laminates); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 4586 (Decorative Laminates — Specifications)	EN 438 (High Pressure Decorative Laminates); NEMA LD 3; GREENGUARD Certification Requirements (Indoor Applications, where applicable)
Postforming Decorative Laminate	IS 2046 (Parts 1 to 8):2025 (Decorative Thermosetting Synthetic Resin-Bonded Laminated Sheets — Specification)	ISO 4586-5 (Postforming Grade Decorative Laminates); ISO 19712-1 (Decorative solid surfacing materials); ISO 4586-1 (High-pressure decorative laminates (HPL)); ISO 4586-7 (Test methods for decorative laminates)	ASTM D790 (Standard Test Methods for Flexural Properties of Unreinforced and Reinforced Plastics and Electrical Insulating Materials); ASTM D4060 (Abrasion Resistance of Organic Coatings); ASTM D3359 (Adhesion by Tape Test, where coatings apply); ASTM E84 (Surface Burning Characteristics of Building Materials)	DIN EN 438-1 (Decorative Laminates); DIN EN 438-2 (Test Methods); DIN EN ISO 527 (Tensile Properties); DIN EN ISO 178 (Flexural Properties)	EN 438; NEMA LD 3; NSF/ANSI 35 (Food Service Applications, where applicable)
Fire Retardant Decorative Laminate	IS 2046 (Parts 1 to 8):2025 (Decorative Thermosetting Synthetic Resin-Bonded Laminated Sheets — Specification)	ISO 4586-6 (Fire-retardant Decorative Laminates); ISO 19712-1 (Decorative solid surfacing materials); ISO 4586-1 (High-pressure decorative laminates (HPL)); ISO 4586-7 (Test methods for decorative laminates)	ASTM E84 (Surface Burning Characteristics of Building Materials); ASTM D635 (Flammability of Plastics); ASTM D3801 (Vertical Burning Characteristics of Solid Plastics); ASTM D2863 (Minimum Oxygen Concentration to Support Combustion); ASTM D790; ASTM D570 (water absorption — relevant since fire-retardant fillers can affect moisture uptake)	DIN EN 438-3 (Decorative Laminates with Flame Retardant Properties); DIN EN 13501-1 (Fire Classification of Construction Products and Building Elements); DIN EN ISO 11925-2 (Ignitability of Building Products); DIN EN ISO 4586 (Decorative Laminates)	EN 438; NEMA LD 3; EN 13501-1 (Reaction to Fire Classification); NFPA 286 (Fire Propagation Testing, where applicable)
Chemical Resistant Laminate	IS 2046 (Parts 1 to 8):2025 (Decorative Thermosetting Synthetic Resin-Bonded Laminated Sheets — Specification)	ISO 19712-1; ISO 4586-1; ISO 4586-7;	ASTM D543 (Resistance of Plastics to Chemical Reagents); ASTM D1308 (Effect of Household Chemicals on Clear and Pigmented Organic Finishes); ASTM D4060 (Abrasion Resistance of Organic Coatings); ASTM D638 (Tensile Properties of Plastics); ASTM D790; ASTM D570 (water absorption is a standard chemical/moisture-resistance companion test)	DIN EN 438-2 (Resistance to Chemicals and Test Methods); DIN EN ISO 175 (Effect of Liquid Chemicals on Plastics); DIN EN ISO 2812-1 (Resistance to Liquids of Coatings); DIN EN 438-1 (Classification of Decorative Laminates)	EN 438; NEMA LD 3; SEFA Standards (Scientific Equipment and Furniture Association — Laboratory Surfaces)
Exterior Grade Compact Laminate	IS 2046 (Parts 1 to 8):2025	ISO 4586-6 (Exterior Grade Decorative Laminates);ISO 19712-	ASTM G154 (Fluorescent UV Exposure of Nonmetallic Materials); ASTM D256	DIN EN 438-6 (Exterior Grade Compact Decorative Laminates);	EN 438; NEMA LD 3; EN 13501-1 (Fire Classification); GREENGUARD

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
	(Decorative Thermosetting Synthetic Resin-Bonded Laminated Sheets — Specification)	1; ISO 4586-1	(Impact Resistance of Plastics); ASTM D4060 (Abrasion Resistance of Organic Coatings); ASTM E84 (Surface Burning Characteristics of Building Materials); ASTM D790; ASTM D570 (moisture absorption is critical for exterior-grade qualification — notable gap)	DIN EN ISO 4892-3 (Artificial Weathering); DIN EN ISO 4586 (Decorative Laminates); DIN EN 13501-1 (Reaction to Fire Classification)	Certification (where applicable)
Self-supporting Compact Laminate	IS 2046 (Parts 1 to 8):2025 (Decorative Thermosetting Synthetic Resin-Bonded Laminated Sheets — Specification)	ISO 4586-7 (Compact Laminates – Self-supporting Grade);ISO 19712-1; ISO 4586-1;	ASTM D790 (Standard Test Methods for Flexural Properties of Unreinforced and Reinforced Plastics and Electrical Insulating Materials); ASTM D638 (Tensile Properties of Plastics); ASTM D256 (Izod Impact Resistance of Plastics); ASTM E84 (Surface Burning Characteristics of Building Materials);ASTM D570	DIN EN 438-4 (Compact Decorative Laminates); DIN EN 438-2 (Test Methods); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 527 (Tensile Properties)	EN 438 (High Pressure Decorative Laminates); NEMA LD 3 (Decorative Laminates); GREENGUARD Certification Requirements (Indoor Air Quality, where applicable)
Decorative Wall Cladding Laminate	IS 2046	ISO 4586-1 (High-pressure decorative laminates (HPL)); ISO 4586-7 (Test methods for decorative laminates); ISO 19712-1 (Decorative solid surfacing materials)	ASTM E84 (Surface Burning Characteristics of Building Materials); ASTM D4060 (Abrasion Resistance of Organic Coatings); ASTM D543 (Resistance of Plastics to Chemical Reagents); ASTM G154 (Fluorescent UV Exposure of Nonmetallic Materials); ASTM D790; ASTM D570	DIN EN 438-6 (Exterior Grade Decorative Laminates); DIN EN 438-2 (Test Methods for Decorative Laminates); DIN EN 13501-1 (Reaction to Fire Classification); DIN EN ISO 4892-3 (Artificial Weathering)	EN 438 (Decorative Laminates); NEMA LD 3; EN 13501-1 (Reaction to Fire Classification, where applicable)
Decorative Door Laminate	IS 2046	ISO 4586-1 (High-pressure decorative laminates (HPL)); ISO 4586-7 (Test methods for decorative laminates); ISO 19712-1 (Decorative solid surfacing materials)	ASTM D4060 (Abrasion Resistance of Organic Coatings); ASTM D256 (Izod Impact Resistance of Plastics); ASTM D638 (Tensile Properties of Plastics); ASTM E84 (Surface Burning Characteristics of Building Materials); ASTM D790; ASTM D570	DIN EN 438-1 (High Pressure Decorative Laminates — Classification); DIN EN 438-2 (Test Methods); DIN EN ISO 2813 (Gloss Measurement); DIN EN ISO 178 (Flexural Properties)	EN 438; NEMA LD 3; EN 1121 (Doors — Behaviour Between Different Climates, where applicable)
Furniture Grade Laminate	IS 2046 (Parts 1-8):2025	ISO 4586-1 (High-pressure decorative laminates (HPL)); ISO 4586-2 (Furniture Surface Application);ISO 19712-1; ISO 4586-7;	ASTM D4060 (Abrasion Resistance of Organic Coatings); ASTM D3363 (Film Hardness by Pencil Test); ASTM D3359 (Adhesion by Tape Test); ASTM D638 (Tensile Properties of Plastics); ASTM D790	DIN EN 438-3 (Decorative Laminates for Interior Applications); DIN EN 438-2 (Test Methods); DIN EN ISO 4586 (Decorative Laminates — Specifications); DIN EN ISO 2813 (Gloss Measurement)	EN 438; NEMA LD 3; GREENGUARD Gold Certification (Indoor Furniture Applications, where applicable)
Flooring Laminate	IS 2046 (Parts 1-8):2025	ISO 24336 (Laminate Floor Coverings — Specifications, Requirements and Test Methods);ISO 19712-1; ISO 4586-1; ISO 4586-7;	ASTM D4060 (Abrasion Resistance of Organic Coatings); ASTM D2047 (Slip Resistance of Floor Surfaces); ASTM E648 (Critical Radiant Flux of Floor-Covering Systems Using a Radiant Heat Energy Source); ASTM D1037 (Evaluating Properties of Wood-Base Fiber and Particle Panel Materials); ASTM D790; ASTM D570 (moisture absorption highly relevant for flooring)	DIN EN 13329 (Laminate Floor Coverings — Elements with Surface Layer Based on Aminoplastic Thermosetting Resins); DIN EN 438-2 (Decorative Laminate Test Methods); DIN EN ISO 24343-1 (Determination of Indentation and Residual Indentation); DIN EN ISO 10874 (Classification of Floor Coverings)	EN 13329 (Laminate Floor Coverings — Requirements and Test Methods); EN 14041 (Floor Coverings — CE Marking Requirements); AC Rating System (Laminate Flooring Abrasion Classification)
Electrical Grade Paper Phenolic Laminate	IS 2036; IS 11297 (Part 3/Sec 1):1988 (Specification for Plastic Laminates for Electrical Purposes — Industrial Rigid	IEC 60893-3-4 (Electrical Insulating Laminated Sheets – Paper Phenolic)	ASTM D709 (Laminated Thermosetting Materials); ASTM D149 (Dielectric Breakdown Voltage and Dielectric Strength of Solid Electrical Insulating Materials); ASTM D257 (DC Resistance or Conductance of Insulating Materials); ASTM D2303 (Liquid-Contaminant,	DIN EN 60893-1 (Industrial Rigid Laminated Sheets Based on Thermosetting Resins); DIN EN 60893-2 (Methods of Test for Industrial Rigid Laminated Sheets); DIN EN 60243-1 (Electrical Strength of Insulating	NEMA LI 1 (Industrial Laminates); UL 94 (Flammability Classification); IEC 60243 (Electrical Strength of Insulating Materials); IEC 60664 (Insulation Coordination)

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
	Laminated Sheets Based on Thermosetting Resins); IS 10192:1982 (Synthetic Resin Bonded Laminated Paper Sheets for Electrical Purposes — Specification)		Inclined-Plane Tracking and Erosion of Insulating Materials); ASTM D790 (Standard Test Methods for Flexural Properties of Unreinforced and Reinforced Plastics and Electrical Insulating Materials)	Materials); DIN EN 60250 (Permittivity and Dissipation Factor)	
Cotton Fabric Phenolic Laminate	IS 2036;IS 1998:1962 (test methods); IS 11297 (Part 3/Sec 1)	IEC 60893-3-2 (Electrical Insulating Laminated Sheets – Cotton Fabric Phenolic)	ASTM D709 (Laminated Thermosetting Materials); ASTM D638 (Tensile Properties of Plastics); ASTM D790 (Standard Test Methods for Flexural Properties of Unreinforced and Reinforced Plastics and Electrical Insulating Materials); ASTM D149 (Dielectric Breakdown Voltage and Dielectric Strength);ASTM D570 (moisture absorption affects electrical-grade phenolic performance)	DIN EN 60893-1 (Industrial Rigid Laminated Sheets Based on Thermosetting Resins); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 527 (Tensile Properties); DIN EN 60243-1 (Dielectric Strength)	NEMA LI 1 (Industrial Laminates); UL 94 (Flammability Classification); IEC 60664 (Insulation Coordination); UL 746A (Polymeric Materials Evaluation)
Glass Epoxy Laminate (FR-4)	IS 2036;IS 1998:1962 (test methods); IS 11297 (Part 3/Sec 1)	IEC 60893-3-2 (Glass Epoxy Laminated Sheets – FR-4)	ASTM D709 (Laminated Thermosetting Materials); ASTM D149 (Dielectric Breakdown Voltage and Dielectric Strength); ASTM D257 (DC Resistance or Conductance of Insulating Materials); ASTM D229 (Rigid Sheet and Plate Materials Used for Electrical Insulation); ASTM D790; ASTM D2344 (interlaminar shear — standard FR-4 qualification test); ASTM D3039; ASTM D3846; ASTM D570	DIN EN 60893-1 (Industrial Rigid Laminated Sheets); DIN EN 60893-2 (Test Methods); DIN EN 60243-1 (Electrical Strength); DIN EN 60250 (Dielectric Properties)	IPC-4101 (Specification for Base Materials for Rigid and Multilayer Printed Boards); UL 94 V-0 (Flammability Classification); IEC 60249 (Base Materials for Printed Circuits); NEMA LI 1 (Industrial Laminates)
Glass Epoxy Laminate (FR-5)	IS 2036;IS 1998:1962 (test methods); IS 11297 (Part 3/Sec 1)	IEC 60893-3-2 (Glass Epoxy Laminated Sheets – FR-5)	ASTM D709 (Laminated Thermosetting Materials); ASTM D149 (Dielectric Breakdown Voltage and Dielectric Strength); ASTM D790 (Standard Test Methods for Flexural Properties of Unreinforced and Reinforced Plastics and Electrical Insulating Materials); ASTM D638 (Tensile Properties of Plastics); ASTM D2344 (interlaminar shear — standard FR-4 qualification test); ASTM D3039; ASTM D3846; ASTM D570	DIN EN 60893-1 (Industrial Rigid Laminated Sheets); DIN EN ISO 178 (Flexural Properties); DIN EN 60243-1 (Dielectric Strength); DIN EN 60250 (Electrical Properties)	IPC-4101 (Rigid Printed Board Base Materials); UL 94 V-0 (Flammability Classification); IEC 60249; NEMA LI 1
Copper Clad Laminate (PCB)	IS 1998 (Methods of Test for Thermosetting Synthetic Resin Bonded Laminated Sheets)	IEC 61249-2-7 (Copper-clad Laminates for Printed Boards)	ASTM D349 (Copper-Clad Laminates for Printed Wiring Boards); ASTM D229 (Rigid Sheet and Plate Materials Used for Electrical Insulation); ASTM D149 (Dielectric Breakdown Voltage); ASTM D257 (Electrical Resistance of Insulating Materials); ASTM D790; ASTM D2344; ASTM D3039; ASTM D3846; ASTM D570	DIN EN 61249-2-7 (Materials for Printed Boards — Reinforced Base Materials); DIN EN 61189-2 (Test Methods for Electrical Materials); DIN EN 60243-1 (Electrical Strength); DIN EN 60250 (Dielectric Properties)	IPC-4101 (Base Materials for Printed Boards); IPC-6012 (Qualification and Performance Specification for Rigid Printed Boards); UL 746E (Laminated Plastics); IEC 60249
Flexible Copper Clad Laminate	IS 1998 (Copper Clad Laminated Sheets for Printed	IEC 61249-2-21 (Flexible Copper-clad Laminates)	ASTM D2148 (Testing Flexible Copper-Clad Laminates); ASTM D149 (Dielectric Breakdown Voltage); ASTM D257	DIN EN 61249-9-1 (Flexible Base Materials for Printed Boards); DIN EN 61189-2 (Test Methods for	IPC-4204 (Flexible Base Dielectrics for Printed Boards); IPC-4203 (Flexible Metal-Clad Dielectric

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
	Wiring Boards) (PCB Applications)		(Electrical Resistance of Insulating Materials); ASTM D638 (Tensile Properties of Plastics); ASTM D2344; ASTM D3846; ASTM D570	Electrical Materials); DIN EN 60243-1 (Electrical Strength); DIN EN 60250 (Dielectric Properties)	Materials); UL 746E; IEC 60249
Flexible Packaging Laminate (PET/PE)	IS 14636 (Flexible Packaging for Food Products); IS 15609 (Multilayer Plastic Pouches for Packaged Drinking Water); IS 14218:1994 (Sealed Plastic Laminates for Water-Resistant Packaging — Specification); IS 8970:1991 (Aluminium Foil Laminates for Packaging — Specification);IS 13583 (Flexible Laminates for packaging Edible Oils, Fats, and Vanaspati)	ISO 18602 (Packaging and the Environment – Packaging System Optimization); ISO 11607-1 (Sterile Barrier Systems, where applicable)	ASTM F88 (Seal Strength of Flexible Barrier Materials); ASTM D882 (Tensile Properties of Thin Plastic Sheeting); ASTM F1249 (Water Vapour Transmission Rate Through Plastic Film and Sheeting); ASTM D3985 (Oxygen Gas Transmission Rate Through Plastic Film and Sheeting)	DIN EN 868-5 (Packaging Materials for Terminally Sterilized Medical Devices, where medical use applies); DIN EN ISO 527 (Tensile Properties); DIN EN ISO 15106 (Water Vapour Transmission Rate); DIN EN ISO 15105 (Gas Transmission Rate)	FDA 21 CFR 177 (Food Contact Plastics); EU 10/2011 (Food Contact Plastics); JIS Z 1707 (Plastic Films for Packaging)
Flexible Packaging Laminate (PET/Al Foil/PE)	IS 14636 (Flexible Packaging for Food Products); IS 15609 (Multilayer Plastic Pouches for Packaged Drinking Water); IS 14218:1994 (Sealed Plastic Laminates for Water-Resistant Packaging — Specification); IS 8970:1991 (Aluminium Foil Laminates for Packaging — Specification);IS 13583 (Flexible Laminates for packaging Edible Oils, Fats, and Vanaspati)	ISO 18602 (Flexible Packaging); ISO 11607-1 (Medical Sterile Packaging, where applicable)	ASTM F88 (Seal Strength of Flexible Barrier Materials); ASTM F1249 (Water Vapour Transmission Rate Through Plastic Film and Sheeting); ASTM D3985 (Oxygen Gas Transmission Rate Through Plastic Film and Sheeting); ASTM D882 (Tensile Properties of Thin Plastic Sheeting)	DIN EN ISO 15105 (Gas Transmission Rate Through Plastic Films); DIN EN ISO 15106 (Water Vapour Transmission Rate); DIN EN ISO 527 (Tensile Properties); DIN EN 1186 (Food Contact Materials)	FDA 21 CFR 177; EU 10/2011; Aluminium Association Standards (Aluminium Foil Packaging Applications); JIS Z 1707
Flexible Packaging Laminate (BOPP/CPP); Retort Packaging Laminate	IS 14636 (Flexible Packaging for Food Products); IS 15609 (Multilayer Plastic Pouches for	ISO 18602 (Flexible Packaging); ISO 17480 (Retort Packaging)	ASTM F88 (Seal Strength of Flexible Barrier Materials); ASTM F2029 (Heat Sealability of Flexible Webs); ASTM F1921 (Hot Tack of Flexible Webs and Laminates); ASTM D882 (Tensile	DIN EN ISO 527 (Tensile Properties); DIN EN ISO 15105 (Gas Transmission Rate); DIN EN ISO 15106 (Water Vapour Transmission Rate); DIN EN ISO	FDA 21 CFR 177; EU 10/2011; JIS Z 1707; Retort Packaging Alliance Guidelines (Retort Packaging Applications)

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
	Packaged Drinking Water); IS 14218:1994 (Sealed Plastic Laminates for Water-Resistant Packaging — Specification); IS 8970:1991 (Aluminium Foil Laminates for Packaging — Specification)		Properties of Thin Plastic Sheeting)	8295 (Coefficient of Friction of Plastic Films)	
Pharmaceutical Blister Laminate	IS 14636 (Flexible Packaging for Food Products) (Pharmaceutical Packaging); IS 10146 (PVC/PVDC Materials for Safe Contact Applications, where applicable); IS 14218:1994; IS 8970:1991	ISO 15378 (Primary Packaging Materials for Medicinal Products); ISO 11607-1 (Sterile Barrier Systems, where applicable)	ASTM F88 (Seal Strength of Flexible Barrier Materials); ASTM F2029 (Heat Sealability of Flexible Webs); ASTM D1003 (Haze and Luminous Transmittance of Transparent Plastics); ASTM D3985 (Oxygen Gas Transmission Rate Through Plastic Film and Sheeting)	DIN EN 868-5 (Packaging for Terminally Sterilized Medical Devices); DIN EN ISO 11607-1 (Packaging for Terminally Sterilized Medical Devices); DIN EN ISO 527 (Tensile Properties); DIN EN ISO 15106 (Water Vapour Transmission Rate)	USP <661> (Plastic Packaging Systems and Materials); USP Class VI (Biocompatibility, where applicable); FDA 21 CFR 177; EU 10/2011
Medical Sterile Packaging Laminate	IS 17387 (Packaging Materials for Terminally Sterilized Medical Devices); IS 14636 (Flexible Packaging for Medical Packaging Applications); IS 14218:1994 (Sealed Plastic Laminates for Water-Resistant Packaging — Specification); IS 8970:1991 (Aluminium Foil Laminates for Packaging — Specification)	ISO 11607-1 (Packaging for Terminally Sterilized Medical Devices – Requirements for Materials, Sterile Barrier Systems and Packaging Systems); ISO 11607-2 (Validation Requirements for Forming, Sealing and Assembly Processes)	ASTM F88 (Seal Strength of Flexible Barrier Materials); ASTM F1929 (Detecting Seal Leaks in Porous Medical Packaging by Dye Penetration); ASTM F1306 (Slow Rate Penetration Resistance of Flexible Barrier Films and Laminates); ASTM D882 (Tensile Properties of Thin Plastic Sheeting)	DIN EN ISO 11607-1 (Packaging for Terminally Sterilized Medical Devices); DIN EN ISO 11607-2 (Validation of Forming, Sealing and Assembly Processes); DIN EN 868-5 (Sealable Pouches and Reels); DIN EN ISO 527 (Tensile Properties)	USP <661>; USP Class VI; FDA 21 CFR 177; EN 868 (Packaging Materials for Sterilization, where applicable)
Aluminium Composite Panel (ACP)	IS 17633; IS 8970:1991 (Aluminium Foil Laminates for Packaging — Specification)	ISO 12543-1 (Laminated Composite Panels – General Requirements); ISO 16936-1 (Building Façade Application, where applicable)	ASTM E84 (Surface Burning Characteristics of Building Materials); ASTM D1781 (Climbing Drum Peel Test for Sandwich Panels); ASTM D3359 (Adhesion by Tape Test); ASTM D790 (Standard Test Methods for Flexural Properties of Unreinforced and Reinforced Plastics and Electrical Insulating Materials); ASTM D2344	DIN EN 13501-1 (Fire Classification of Construction Products); DIN EN 1396 (Aluminium and Aluminium Alloy Coil Coated Sheet for General Applications); DIN EN ISO 178 (Flexural Properties); DIN EN ISO 527 (Tensile Properties)	EN 13501-1 (Reaction to Fire Classification); NFPA 285 (Fire Propagation Test for Exterior Wall Assemblies); AAMA 2605 (High Performance Organic Coatings on Aluminium); UL 94 (Plastic Core Fire Classification, where applicable)

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
			(Standard Short-Beam Test Method for Relation Strength of Polymer Matrix Composite Materials and Their Laminates); ASTM D3039 (Standard Test Method for Tensile Properties of Polymer Matrix Composite Materials);ASTM D3846; ASTM D570		

Source field: Plastic and Plastic Products