Gaskets

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
NBR Gasket; Neoprene Gasket	IS 9992 (Rubber Gaskets); IS 5382; IS 7466; IS 11149; IS 10188; IS 13137; IS 3400	ISO 7483 (Dimensions of Gaskets for Use with Flanges to ISO 7005); ISO 1817 (Rubber, Vulcanized or Thermoplastic — Determination of Effect of Liquids),ISO 3601-1; ISO 3601-3; ISO 3601-5; ISO 4633; ISO 6447; ISO 9631	ASTM F36 (Compressibility and Recovery of Gasket Materials); ASTM F37 (Sealability of Gasket Materials); ASTM D2000 (Rubber Products Classification System); ASTM D471 (Effect of Liquids on Rubber); ASTM C1115; ASTM C361; ASTM C443; ASTM C564; ASTM C864; ASTM D1414; ASTM D1869; ASTM D5193; ASTM F104; ASTM F112; ASTM F1276; ASTM F146; ASTM F152; ASTM F2524; ASTM F38; ASTM F433; ASTM F495; ASTM F607; ASTM F806	DIN EN 13555 (Flanges and Their Joints — Gasket Parameters); DIN ISO 37 (Tensile Properties); DIN ISO 1817 (Resistance to Liquids); DIN ISO 815-1 (Compression Set)	SAE J200 (Rubber Material Classification); NSF/ANSI 61 (Potable Water Applications); API 6A (Oilfield Equipment Sealing Applications, where applicable)
EPDM Gasket	IS 11149:2024; IS 5382; IS 7466; IS 10188; IS 13137; IS 3400	ISO 7483 (Dimensions of Gaskets for Flanges); ISO 1817 (Rubber — Determination of Effect of Liquids),ISO 3601-1; ISO 3601-3; ISO 3601-5; ISO 4633; ISO 6447; ISO 9631	ASTM F36 (Compressibility and Recovery of Gasket Materials); ASTM F37 (Sealability of Gasket Materials); ASTM D2000 (Rubber Products Classification System); ASTM D471 (Effect of Liquids on Rubber); ASTM C1115; ASTM C361; ASTM C443; ASTM C564; ASTM C864; ASTM D1414; ASTM D1869; ASTM D5193; ASTM F104; ASTM F112; ASTM F1276; ASTM F146; ASTM F152; ASTM F2524; ASTM F38; ASTM F433; ASTM F495; ASTM F607; ASTM F806	DIN EN 13555 (Flanges and Their Joints — Gasket Parameters); DIN ISO 1817 (Resistance to Liquids); DIN ISO 815-1 (Compression Set); DIN ISO 188 (Ageing Resistance)	NSF/ANSI 61 (Drinking Water System Components); FDA 21 CFR 177 (Food Contact Applications); SAE J200 (Rubber Classification)
Silicone Gasket	IS 11149:2024; IS 5382; IS 7466; IS 10188; IS 13137; IS 3400	ISO 3601-1 (Fluid Power Systems — O-rings, where applicable); ISO 3302-1 (Rubber — Dimensional Tolerances for Products),ISO 3601-3; ISO 3601-5; ISO 4633; ISO 6447; ISO 9631	ASTM F36 (Compressibility and Recovery of Gasket Materials); ASTM F37 (Sealability of Gasket Materials); ASTM D2000 (Rubber Products Classification System); ASTM D471 (Effect of Liquids on Rubber); ASTM C1115; ASTM C361; ASTM C443; ASTM C564; ASTM C864; ASTM D1414; ASTM D1869; ASTM D5193; ASTM F104; ASTM F112; ASTM F1276; ASTM F146; ASTM F152; ASTM F2524; ASTM F38; ASTM F433; ASTM F495; ASTM F607; ASTM F806	DIN EN 13555 (Flanges and Their Joints — Gasket Parameters); DIN ISO 37 (Tensile Properties); DIN ISO 1817 (Resistance to Fluids); DIN ISO 188 (Ageing Resistance)	FDA 21 CFR 177 (Food Contact Silicone); USP Class VI (Medical Applications); NSF/ANSI 51 (Food Equipment Materials)
FKM Gasket	IS 11149:2024; IS 5382; IS 7466; IS 10188; IS 13137; IS 3400	ISO 1817 (Rubber — Determination of Effect of Liquids); ISO 37 (Rubber — Tensile Stress-Strain Properties),ISO 3601-1; ISO 3601-3; ISO 3601-5; ISO 4633; ISO 6447; ISO 9631	ASTM F36 (Compressibility and Recovery of Gasket Materials); ASTM F37 (Sealability of Gasket Materials); ASTM D2000 (Rubber Products Classification System); ASTM D471 (Effect of Liquids on Rubber); ASTM C1115; ASTM C361; ASTM C443; ASTM C564; ASTM C864; ASTM D1414; ASTM D1869; ASTM D5193; ASTM F104; ASTM F112; ASTM F1276; ASTM F146; ASTM F152; ASTM F2524; ASTM F38; ASTM F433; ASTM F495; ASTM F607;	DIN EN 13555 (Flanges and Their Joints — Gasket Parameters); DIN ISO 1817 (Resistance to Chemicals and Fluids); DIN ISO 815-1 (Compression Set); DIN ISO 188 (Heat Ageing)	SAE J200 (Rubber Classification); API 6A (Oilfield Sealing Applications); NORSOK M-710 (Oil & Gas Applications)

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
			ASTM F806		
Food Grade Gasket	IS 11149:2024; IS 5382; IS 7466; IS 10188; IS 13137; IS 3400	ISO 22000 (Food Safety Management Systems); ISO 1817 (Rubber — Determination of Effect of Liquids),ISO 3601-1; ISO 3601-3; ISO 3601-5; ISO 4633; ISO 6447; ISO 9631	ASTM F36 (Compressibility and Recovery of Gasket Materials); ASTM F37 (Sealability of Gasket Materials); ASTM D543 (Resistance of Plastics and Rubber to Chemical Reagents); ASTM D471 (Effect of Liquids on Rubber); ASTM C1115; ASTM C361; ASTM C443; ASTM C564; ASTM C864; ASTM D1414; ASTM D1869; ASTM D5193; ASTM F104; ASTM F112; ASTM F1276; ASTM F146; ASTM F152; ASTM F2524; ASTM F38; ASTM F433; ASTM F495; ASTM F607; ASTM F806	DIN EN 1935 (Materials and Articles Intended to Come into Contact with Foodstuffs, where applicable); DIN EN 1186 (Food Contact Materials); DIN ISO 1817 (Resistance to Liquids); DIN ISO 37 (Tensile Properties)	FDA 21 CFR 177 (Food Contact Materials); NSF/ANSI 51 (Food Equipment Materials); 3-A Sanitary Standards
Steam Gasket	IS 11149:2024; IS 5414:2024 (where gland packing is used); IS 5382; IS 7466; IS 10188; IS 13137; IS 3400	ISO 23936-1 (Petroleum, Petrochemical and Natural Gas Industries — Non-metallic Materials in Contact with Media Related to Oil and Gas Production); ISO 1817 (Rubber — Effect of Liquids),ISO 3601-1; ISO 3601-3; ISO 3601-5; ISO 4633; ISO 6447; ISO 9631	ASTM F36 (Compressibility and Recovery of Gasket Materials); ASTM F37 (Sealability of Gasket Materials); ASTM D471 (Effect of Liquids on Rubber); ASTM D573 (Heat Aging of Rubber); ASTM C1115; ASTM C361; ASTM C443; ASTM C564; ASTM C864; ASTM D1414; ASTM D1869; ASTM D5193; ASTM F104; ASTM F112; ASTM F1276; ASTM F146; ASTM F152; ASTM F2524; ASTM F38; ASTM F433; ASTM F495; ASTM F607; ASTM F806	DIN EN 13555 (Gasket Parameters for Flange Connections); DIN ISO 1817 (Resistance to Liquids); DIN ISO 188 (Heat Ageing Resistance); DIN ISO 815-1 (Compression Set)	ASME B16.20 (Metallic Gaskets for Pipe Flanges, where applicable); API 601 (Pressure Equipment Gaskets, where applicable); FDA 21 CFR 177 (Food Steam Applications)
Pipe Flange Gasket	IS 11149:2024; IS 17796:2023 (for CNAF gaskets); IS 5382; IS 7466; IS 10188; IS 13137; IS 3400	ISO 7483 (Dimensions of Gaskets for Use with Flanges to ISO 7005); ISO 16047 (Fasteners — Torque/clamp Force Testing, where applicable),ISO 3601-1; ISO 3601-3; ISO 3601-5; ISO 4633; ISO 6447; ISO 9631	ASTM F36 (Compressibility and Recovery of Gasket Materials); ASTM F37 (Sealability of Gasket Materials); ASTM F38 (Sealability of Gasket Materials Under Compressive Load); ASTM D2000 (Rubber Products Classification System); ASTM C1115; ASTM C361; ASTM C443; ASTM C564; ASTM C864; ASTM D1414; ASTM D1869; ASTM D5193; ASTM F104; ASTM F112; ASTM F1276; ASTM F146; ASTM F152; ASTM F2524; ASTM F433; ASTM F495; ASTM F607; ASTM F806	DIN EN 1514-1 (Flanges and Their Joints — Dimensions of Gaskets); DIN EN 13555 (Gasket Parameters); DIN ISO 37 (Tensile Properties); DIN ISO 815-1 (Compression Set)	ASME B16.20 (Metallic Gaskets for Pipe Flanges); ASME B16.21 (Nonmetallic Flat Gaskets); API 6A (Oilfield Flange Sealing Applications)

Source field: Rubber and Rubber products