Reclaimed Rubber

Product / Application	BIS (IS)	ISO	ASTM	DIN	Other Standards
Whole Tyre Reclaim; Butyl Reclaim	IS 6208 (Reclaimed Rubber); IS 5192; IS 10130; IS 15078; IS 1685; IS 3400	ISO 247 (Rubber — Determination of Ash), where applicable,ISO 23529; ISO 289-1; ISO 6502-1; ISO 6502-3; ISO 7663; ISO 11235	ASTM D297 (Chemical Analysis of Rubber Products); ASTM D6814 (Determination of Percent Reclaimed Rubber in Vulcanized Rubber); ASTM D1646 (Mooney Viscosity of Raw Rubber); ASTM D412 (Tensile Properties of Rubber); ASTM D1052; ASTM D1056; ASTM D1149; ASTM D1329; ASTM D1765; ASTM D1993; ASTM D2084; ASTM D2137; ASTM D2231; ASTM D2240; ASTM D2663; ASTM D3182; ASTM D395; ASTM D413; ASTM D429; ASTM D430; ASTM D4482; ASTM D454; ASTM D471; ASTM D5099; ASTM D5289; ASTM D573; ASTM D5964; ASTM D6204; ASTM D624; ASTM D813; ASTM D925	DIN ISO 247 (Carbon Black and Ash Content of Rubber); DIN ISO 37 (Tensile Properties of Rubber); DIN ISO 188 (Accelerated Ageing Resistance); DIN ISO 4649 (Abrasion Resistance)	RMA Rubber Material Classification; ARPM Rubber Industry Guidelines; EPA Rubber Recycling Guidelines (where environmental applications apply)
EPDM Reclaim	IS 5798; IS 5192; IS 10130; IS 15078; IS 1685; IS 3400	ISO 247 (Rubber — Determination of Ash), where applicable,ISO 23529; ISO 289-1; ISO 6502-1; ISO 6502-3; ISO 7663; ISO 11235	ASTM D297 (Chemical Analysis of Rubber Products); ASTM D6814 (Determination of Reclaimed Rubber Content); ASTM D471 (Effect of Liquids on Rubber); ASTM D412 (Tensile Properties of Rubber); ASTM D1052; ASTM D1056; ASTM D1149; ASTM D1329; ASTM D1646; ASTM D1765; ASTM D1993; ASTM D2084; ASTM D2137; ASTM D2231; ASTM D2240; ASTM D2663; ASTM D3182; ASTM D395; ASTM D413; ASTM D429; ASTM D430; ASTM D4482; ASTM D454; ASTM D5099; ASTM D5289; ASTM D573; ASTM D5964; ASTM D6204; ASTM D624; ASTM D813; ASTM D925	DIN ISO 37 (Tensile Properties of Rubber); DIN ISO 188 (Ageing Resistance); DIN ISO 1817 (Resistance to Liquids); DIN ISO 48-1 (Hardness of Rubber)	RMA Rubber Material Classification; SAE J200 (Rubber Classification); UL 94 (Flammability Applications, where applicable)
Crumb Rubber	IS 17028 (recycled rubber applications); IS 5192; IS 10130; IS 15078; IS 1685; IS 3400	ISO 2007 (Rubber, Unvulcanized — Determination of Plasticity and Plasticity Retention Index), where applicable,ISO 23529; ISO 289-1; ISO 6502-1; ISO 6502-3; ISO 7663; ISO 11235	ASTM D297 (Chemical Analysis of Rubber Products); ASTM D5644 (Rubber Composition Analysis by Thermogravimetric Analysis); ASTM D6814 (Reclaimed Rubber Content); ASTM D5603 (Rubber from Recycled Tires); ASTM D1052; ASTM D1056; ASTM D1149; ASTM D1329; ASTM D1646; ASTM D1765; ASTM D1993; ASTM D2084; ASTM D2137; ASTM D2231; ASTM D2240; ASTM D2663; ASTM D3182; ASTM D395; ASTM D412; ASTM D413; ASTM D429; ASTM D430; ASTM D4482; ASTM D454; ASTM D471; ASTM D5099; ASTM D5289; ASTM D573; ASTM D5964; ASTM D6204; ASTM D624; ASTM D813; ASTM D925	DIN ISO 37 (Tensile Properties); DIN ISO 7619-1 (Hardness); DIN ISO 4649 (Abrasion Resistance); DIN ISO 247 (Ash and Carbon Black Content)	GRI Standards for Rubber Modified Materials (where geotechnical applications apply); EPA Rubber Recycling Guidelines; Rubber Manufacturers Association (RMA) Specifications

Source field: Rubber and Rubber products